



CII Short Form Reference Guide

High Performance Electromechanical Relays

1	Amp
	Rated














MGA. HC





. 10.000
CII Series
Relay Type
Contacts
Contact Rating
Coil Voltages
Mil Spec
Qualifications













1 Amp

5 to 48 Vdc

M28776/7

1-2 Amp Rated









HMB







CII Series				
Relay Type				
Contacts				
Contact Rating				
Coil Voltages				
Mil Spec				
Qualifications				



SIVIGA, SHC	SIVIGS, SITUS
Std. SMT Grid	Sens. SMT Grid
DPDT	DPDT
1 Amp	1 Amp
5 to 26.5 Vdc	5 to 48 Vdc
Designed to meet	Designed to meet
M39016	M39016









2 Amp

5 to 26.5 Vdc

M39016/40

2 Amp Rated



3SBC

Standard 1/5 Size **DPDT**

2 Amp

5 to 36 Vdc



3SBH

4 Pole 1/5 Size

4PDT

2 Amp

6 to 36 Vdc

M39016/13,37,38 M39016/14,53,54 M39016/31,35,36



3SBM

4PDT

2 Amp

6 to 26.5 Vdc



3SAM

DPDT

2 Amp

6 to 24 Vdc

M39016/32

Latching 1/5 Size Latching Full Size Sensitive Full Size



3SAT

DPDT

2 Amp

2 to 45 Vdc

M5757/13



RD, 02, 03

Multi-Pole

2.4 & 6PDT

2 Amp

6 to 26.5 Vdc

M5757/1, 7, 8

CII Series				
Relay Type				
Contacts				
Contact Rating				
Coil Voltages				
Mil Spec				
Qualifications				







Standard Tall

DPDT

2 & 5 Amp

1.8 to 40 Vdc

Designed to meet

M5757







CII Series Relay Type Contacts **Contact Rating** Coil Voltages Mil Spec Qualifications

2-10 Amp

Rated



DPDT

2, 4 & 5 Amp

5 to 48 Vdc

M39016/6



DPDT

3 & 5 Amp

6 to 110 Vdc

M5757/10

Standard 1/2 Size Standard Full Size



2253
FCB-205

Std. Midrange

DPDT

5 Amp

6 to 48 Vdc

M83536/1, 2

A COLOR
FCB-405
Std. Midrange

4PDT

5 Amp

6 to 48 Vdc

M83536/5. 6

С			
Standard 1/2 Size			
SPDT			
10 Amp			

6 to 26.5 Vdc

Designed to meet

10-50 Amp Rateo















Salar.			
FCA-210, 21	5		
Std. Midrange	9		





disting
FCA-325
Std. Midrange
3PDT
0F A



CII Series	07	FCA-210, 215	FCA-410, 415	FCA-125	FCA-325	FCA-150
Relay Type	Std. Full Size	Std. Midrange				
Contacts	DPDT	DPDT	4PDT	SPDT	3PDT	SPDT
Contact Rating	10 Amp	10 & 15 Amp	10 & 15 Amp	25 Amp	25 Amp	50 Amp
Coil Voltages	6-120Vdc, 115Vac	6-48Vdc, 115Vac	6-48Vdc, 115Vac	6-48Vdc, 115Vac	6-48Vdc, 115Vac	6 to 28 Vdc
Mil Spec	M5757/23, MS-	M83536/9, 10	M83536/15, 16	M83536/36, 37	M83536/32, 33	Designed to meet
Qualifications	27245 & 27247			M6106/19		M6106
Contact ratings shown are 28 V/de Posistive ratings CIL TE /Logo) and Typo Electronics are trademarks of the Typo Electronics group of companies and its licensors						