



DUAL FLUSH JACK

Can be flushed mounted in wall to eliminate external wires. Two modular jacks permit use of two telephones at same location or one telephone and answering machine or other related equipment. Two solderless jacks can be connected independently or in series, utilizing one or two lines. UL listed, CSA approved.

Cat. No.	Description	Net Price
30-8447-00BU	4-conductor ivory	\$1.52
30-8449-00BU	4-conductor white	1.52
30-8667-00BU	6-conductor ivory	2.28
30-8669-00BU	6-conductor white	2.28
30-8807-00BU	8-conductor ivory	2.49
30-8809-00BU	8-conductor white	2.49



MODULAR SURFACE JACK

Modular Surface Jack mounts to baseboard or wall. Screw terminals for easy installation. UL listed, CSA approved.

Cat. No.	Description	Net Price
30-8607-00BU	4-conductor ivory	\$1.02
30-8609-00BU	4-conductor white	1.02
30-8627-00BU	6-conductor ivory	1.44
30-8629-00BU	6-conductor white	1.44
30-8687-00BU	8-conductor ivory	1.86
30-8689-00BU	8-conductor white	1.86



5-OUTLET MODULAR JUNCTION BOX WITH CORD

Permits up to five telephone related devices to be used from single modular jack. 6 ft. Ivory.

Cat. No.	Net Price
30-9802-0000	\$7.87



MODULAR "T" ADAPTER

"T" adapter enables two modular plugs to be used in a single modular jack.

Cat. No.	Description	Net Price
30-9654-0000	4-conductor ivory	\$1.98
30-9647-0000	6-conductor ivory	2.30
30-9649-0000	8-conductor ivory	4.16



DB9 (M)



DB9 (F)

DB-9 CABLE ASSEMBLIES

DB-9 connectors. Fully molded assemblies. All nine lines are wired straight through. Fully shielded with both Mylar foil over-layer plus 100% braid. PVC insulation, pure copper stranded wire. Gold plated contacts. Male to female 5 ft.

Cat. No.	Net Price
45-0314-0000	\$4.91



DB25 (F)



DB25 (M)

RS-232 DB-25 LINE CABLES

All 25 Lines wired straight through. Standard 25-pin (DB-25) subminiature connectors each end. Shielded 100% (Copper Braid over Mylar foil) precious metal contacts. PVC insulation throughout. Molded ends. Fully shielded.

Cat. No.	Description	Net Price
45-0379-0000	Male to Female 5 ft.	\$4.16
45-0374-0000	Male to Female 10 ft.	5.22
45-0375-0000	Male to Female 25 ft.	9.79
45-4363-0000	Male to Male 5 ft.	12.43
45-4364-0000	Male to Male 10 ft.	20.88



DB25 (M)



CEN36 (M)




90° CEN36 (M)

STANDARD PARALLEL PRINTER CABLES

All cables fully wired with 25 conductors. All high quality computer cables have a 5 year warranty.

Cat. No.	Description	Net Price
45-0201-0000	Parallel printer cables DB25(M)/CEN36(M) 6'	\$4.49
45-0202-0000	Parallel printer cables DB25(M)/CEN36(M) 2'	4.16
45-0204-0000	Parallel printer cables DB25(M)/CEN36(M) 10'	5.22
45-0210-0000	90° Parallel printer cables DB25(M)/90° CEN36(M) 6'	6.27



DB25 (M)



CEN36 (M)

HIGH SPEED BI-DIRECTIONAL PRINTER CABLES

Low noise bi-directional printer cables. May be used on most printers. Fully compliant with H.P.® IEEE 1284 standards. 18 twisted pair cable with a minimum of 35 twists/meter. Double shielded, heavy duty mylar foil and braided shield. Uses 28 AWG cable.

Cat. No.	Description	Net Price
45-1806-0000	6' DB25 (M)/CEN36 (M)	\$13.57
45-1810-0000	10' DB25 (M)/CEN36 (M)	19.84



USB (A)




USB (B)

USB TO USB CABLES

USB (Universal Serial Bus) cable consists of (1) pair 28 AWG twisted wire for signal and (1) 24 AWG wire for cables up to 3 metres. All are double shielded with mylar foil and braided shields.

Cat. No.	Description	Net Price
45-1413-0000	1m (3.3'), USB (A)/USB (B)	\$4.70
45-1416-0000	2m (6.5'), USB (A)/USB (B)	5.41
45-1403-0000	3m (9.9'), USB (A)/USB (B)	6.58



USB MOTHERBOARD ADAPTER

Adds USB capability to your PC. (2) USB (A) to (2) IDC10 (F) with a Port Bracket.

Cat. No.	Net Price
45-1422-0000	\$15.64




DB9 (F)



DB25 (M)

IBM-AT, PS/2, AND COMPATIBLE ADAPTOR CABLES

Cat. No.	Description	Net Price
45-0391-0000	IBM-AT to serial printers cable 6'	\$4.70
45-0320-0000	RS-232 DB-9 Female to DB-25 Male 6'	4.38
45-0321-0000	RS-232 DB-9 Female to DB-25 Male 10'	4.16



HD15 (M)



HD15 (F)

VGA MONITOR CABLES

These cables use 28 AWG 14 conductor wire. Heavy duty mylar foil shield. Molded connectors with thumb screws.

Cat. No.	Length	Description	Net Price
45-0476-0000	6'	HD15 (M)/HD15 (M)	\$4.18
45-0435-0000	6'	HD15 (M)/HD15 (F)	3.97

SUPER VGA HIGH QUALITY CABLE

45-1839-0000	10'	HD15 (M)/HD15 (M)	20.88
45-1838-0000	10'	HD15 (M)/HD15 (F)	20.88



DB25 (M)



DB25 (F)



DB9 (M)



DB9 (F)

RS232 STANDARD COMPUTER CABLES

All computer cables are made to comply with industry standards. Cables are made with U/L listed cable with is tested at 80°C @ 300V. The connectors have molded cover, and thumbscrews. Premium quality cables carry a limited lifetime warranty, and are made with 24 AWG stranded cable. High quality cables are made with 28 AWG cable and heavy duty mylar foil shield.

Cat. No.	Description	Net Price
----------	-------------	-----------

PREMIUM QUALITY CABLES

45-0376-0000	6' DB25 (M)/DB25 (M)	\$4.18
45-0377-0000	10' DB25 (M)/DB25 (M)	5.01
45-0358-0000	2' DB25 (M)/DB25 (F)	3.97
45-0379-0000	6' DB25 (M)/DB25 (F)	4.16
45-0374-0000	10' DB25 (M)/DB25 (F)	5.22

HIGH QUALITY CABLES

45-0308-0000	6' D89 (M)/D89 (F)	3.95
45-0306-0000	25' D89 (M)/D89 (F)	10.23



MD6 (F)



MD6 (M)

IBM PS2® STYLE KEYBOARD CABLES

6 pin mini DIN for use with notebooks and PS2 keyboards. Keyboard cable MD6 (M)/MD6 (F) 6'.

Cat. No.	Net Price
45-0431-0000	\$4.62



HD15 (M)



HD15 (F)

VGA MONITOR CABLES

These cables use 28 AWG 14 conductor wire. Heavy duty mylar foil shield. Molded connectors with thumb screws. VGA cable HD15 (M)/HD15 (F) 6'.

Cat. No.	Net Price
45-0435-0000	\$3.97



45-0578-0000



45-0579-0000

MOUSE ADAPTERS

These adapters make it possible to connect a serial mouse to your IBM PS/2® computer.

Cat. No.	Description	Net Price
45-0578-0000	Serial mouse to PS/2, DB9 (M)/MD6 (M)	\$3.53
45-0579-0000	PS/2 Mouse to IBM® AT, DB9 (F)/MD6 (F)	3.53



45-0400-0000



45-0401-0000

POWER CORDS AND ADAPTER CABLES

These cables are used as replacements for computer, printers, and other small office/home office devices with a current draw of less than 7A @ 125 VAC. Cords are made with 18 AWG stranded U/L listed cable, and molded ends.

Cat. No.	Description	Net Price
45-0400-0000	Computer power cord, AC (M)/molded (F) 6'	\$3.40
45-0401-0000	Power adapter shrouded (M)/AC (F) 1'	3.09



45-0570-0000



45-0571-0000



45-0573-0000

KEYBOARD ADAPTERS

Cat. No.	Description	Net Price
45-0570-0000	Keyboard adapter D5 (F)/MD6 (M) 6"	\$2.90
45-0573-0000	Keyboard adapter D5 (F)/MD6 (M)	3.95
45-0571-0000	Keyboard adapter D5 (F)/MD6 (F) 6"	2.90



45-2510-0000



45-2511-0000

LOW PROFILE PORT ADAPTERS

These connectors are used to change the I/O (input/output) ports from one type of connector to another. They are most commonly used when hooking up peripheral devices such as a monitor or printer to your PC.

Cat. No.	Description	Net Price
45-2510-0000	Low profile serial adapter, DB9 (M) / DB25 (F)	\$3.45
45-2511-0000	Low profile serial adapter, DB9 (F) / DB25 (M)	3.24
45-2509-0000	Low profile serial adapter, DB9 (F) / DB25 (F)	3.45
45-2512-0000	Low profile serial adapter, DB9 (M) / DB25 (M)	3.45



IBM COMPATIBLE PORT ADAPTOR

Eliminates need for special printer cable. Adaptor plugs into "Centronics-Type" 36-Pin connector on most parallel printers and converts the connector to a standard female 25-Pin "D".

Cat. No.	Net Price
45-0598-0000	\$4.70



NULL MODEM CABLES

The cables allow you to connect two DCE or DTE devices in order to communicate between them. Null modem cable DB9 (F)/DB9 (F) 6'.

Cat. No.	Net Price
45-0389-0000	\$4.91



DB-9 GENDER CHANGERS & ADAPTORS

Cat. No.	Description	Net Price
45-0510-0000	DB-9, Male/Male	\$3.13
45-0515-0000	DB-9, Female/Female	2.61



45-0560-0000



45-0561-0000

DB-15 GENDER CHANGERS

Cat. No.	Description	Net Price
45-0560-0000	High Density DB-15 Male/Male	\$5.62
45-0561-0000	High Density DB-15 Female/Female	9.35