

SINGLE BELDSOL SOLDERABLE

Description	AWG	Cat. No.	Approximate Length		Std. Unit Lbs. ea.	Turns per Linear inch	Turns per Square inch
			ft.	m			
	18	8049	100	30.5	.5	23.9	571
	20	8050	160	48.8	.5	29.9	894
	22	8051	254	77.4	.5	37.5	1406
	24	8052	404	123.1	.5	46.9	2200
	26	8053	645	196.6	.5	59.0	3481
	28	8054	1020	310.9	.5	73.8	5446
	30	8055	1615	492.3	.5	91.7	8409
	32	8056	2515	766.6	.5	114.0	12996
	34	8057	4060	1237.5	.5	144.0	20736
	36	8058	6400	1950.7	.5	180.0	32400

Portable Cordage

Description	Cat. No.	Standard Lengths		Std. Unit Lbs. ea.	AWG (strand-ing)	Insulation Thickness		Jacket Thickness		Nominal O.D.	
		ft.	m			Inch	mm	Inch	mm	Inch	mm
SPT-1 2-Conductor PVC Parallel Lamp Cord 300V 60°C (One conductor polarity ribbed)											
	19122	250 Black	76.2	5.4	18 (41×34) bare	.032	.81	—	—	.110 × .207	2.79 × 5.26
	8888	100 Brown	30.5	2.3	18 (41×34) bare	.031	.79	—	—	.110 × .207	2.79 × 5.26
		250 Brown	76.2	5.4							
		1000 Brown	304.8	20.1							







• Regular SJT cords are U.L. Listed and C.S.A. certified. C.S.A. does not recognize SJT low-leakage cordage. NA North American Colour Coding.

Description	Cat. No.	Standard Lengths		Std. Unit Lbs. ea.	AWG (strand-ing)	Insulation Thickness		Jacket Thickness		Nominal O.D.	
		ft.	m			Inch	mm	Inch	mm	Inch	mm
SV-2-Conductor—Rubber Jacket 300V 60°C Colour code: Black, White.											
Cotton Serve Separator	8452	100 Black	30.5	3.8	18 (41×34) bare	.017	.43	.037	.94	.245	6.22
		250 Black	76.2	8.6							
		500 Black	152.4	16.7							
		1000 Black	304.8	32.3							
SJ-2-Conductor—Rubber Jacket 300V 60°C Colour code: Black, White.											
Paper Tape Separator	8478	250 Black	76.2	11.4	18 (41×34) bare	0.32	.81	.039	.99	.298	7.57
		1000 Black	304.8	44.1							
	8472	250 Black	76.2	15.0	16 (65×34) bare	0.31	.79	.040	1.02	3.25	8.26
SVT-3-Conductor—Rubber Jacket 300V 60°C Colour code: Black, White, Green.											
Paper Tape Separator	19350	250 Grey	76.2	10.5	18 (41×34) bare	.018	.46	.034	.86	.253	6.43
SJ-3-Conductor—Rubber Jacket 300V 60°C Colour code: Black, White, Green.											
Paper Tape Separator	19125	250 Black	76.2	15.2	18 (41×34) bare	.032	.81	.044	1.12	.328	8.33
	19124	250 Black	76.2	19.3	16 (65×34) bare	.031	.79	.044	1.12	.353	8.97
	8479	250 Black	76.2	24.7	14 (41×30) bare	.031	.79	.035	.89	.380	9.65
SV-3-Conductor—Rubber Jacket 300V 60°C Colour code: Black, White, Green.											
Cotton Serve	8453	100 Black	30.5	4.6	18 (41×34) tinned	.018	.46	.034	.86	.256	.650
		500 Black	152.4	21.0							

Continued on next page....







For complete product selection please contact your Electro Sonic sales representative.

3-CONDUCTOR DETACHABLE POWER SUPPLY CORDS—UNSHIELDED

Description	Cat. No.		Length of Cord		Packaging	Colour Coding	AWG stranding [Dia. in mm]	Nominal O.D.		Rating	Type of Cordage	Jacket Colour
	Plug	Conn.	ft.	m				Inch	mm			
 Molded PVC 3-Contact Connector PH-163 Contact View 17280  Type SVT	17280		7-1/2'	2.29	B-50	CEE	18 (41 x 34) [1.19]	.246	6.25	875 Watts 7A-125V	SVT	Black Grey
	290B	163	60°C									
 Contact View 17280  NEMA 5-15P	17952		8'	2.44	B-50	NA	18 (41 x 34) [1.19]	.246	6.25	875 Watts 7A-125V	SVT	Grey
	290B	163	60°C									
 												



CEE European Colour Coding. NA North American Colour Coding N.S.N. National Stock Number

EXTENSION CORDS

Description	Cat. No.		Length of Cord		Packaging	Colour Coding	AWG stranding [Dia. in mm]	Nominal O.D.		Rating	Type of Cordage	Jacket Colour
	Plug	Conn.	ft.	m				Inch	mm			
NEMA 5-15P  Add-A-Line Plug PH-745  Molded PVC Grounding Connector PH-108 Contact View NEMA 5-15R These 8' and 15' detachable power supply cords have the added convenience of an outlet in the plug so you can add a line. Type SJT Add-A-Line, PVC Jacketed	17462		8'	2.44	S-10	NA	16 (26 x 30) [1.52]	.340	8.64	1625 Watts 13A-125V	SJT	Black
	745	108	60°C									
NEMA 5-15P  Add-A-Line Plug PH-185  Molded PVC Grounding Connector PH-108 Contact View NEMA 5-15R Detachable power supply cord for business, mailing machines, and electrical equipment that have a built-in receptacle with blades and grounding pin for cord attachment. Type SJ	17463		15'	4.57	S-10	NA	16 (26 x 30) [1.52]	.340	8.64	1625 Watts 13A-125V	SJT	Black
	745	108	60°C									
NEMA 5-15P  Add-A-Line Plug PH-185  Molded PVC Grounding Connector PH-108 Contact View NEMA 5-15R Detachable power supply cord for business, mailing machines, and electrical equipment that have a built-in receptacle with blades and grounding pin for cord attachment. Type SJ	17461		10'	3.05	S-15	NA	16 (26 x 30) [1.52]	.340	8.64	1625 Watts 13A-125V	SJ	Black
	185	108	60°C									

NA North American Colour Coding. N.S.N. National Stock Number.



Description	Cat. No.		Length of Cord		Packaging	Colour Coding	AWG stranding [Dia. in mm]	Nominal O.D.		Rating	Type of Cordage	Jacket Colour
	Plug	Conn.	ft.	m				Inch	mm			
NEMA 5-15P  Molded PVC Grounding Plug PH-185 or PH-173  Molded PVC Heavy-Duty Grounding Duplex Connector PH-117 Contact View NEMA 5-15R These three-conductor extension cords are for use with power tools and other appliances requiring grounding. Type SJO Neoprene and SJT PVC Jacketed.	17475		25'	7.62	S-1	NA	16 (26 x 30) [1.52]	.340	8.64	1625 Watts 13A-125V	SJO	Black
	185	117	60°C									

POWER ADAPTERS

PLUG-IN POWER ADAPTERS

These AC/DC and AC/AC plug-in adapters are designed for use with products requiring low supply voltages. They can be used as original equipment replacements for many consumer products or can be included with manufactured goods as low cost power supply. All models plug directly into standard AC wall outlets and include a built-in output cable with strain relief terminated with the specified plug. Custom models featuring different input and output voltages, output current, and plug terminations are also available. **APPLICATIONS INCLUDE:** Battery chargers, consumer products, data communications, telephone products, and computer peripherals.



RP-9500



RP-1201

AC/DC POWER ADAPTERS—LINEAR: 120 VAC INPUT

Cat. No.	Output Voltage	Output Current	Tip Diameter	Centre Polarity	Net Price
RP-0530R-P	5 VDC	300mA Regulated	2.1 x 5.5 mm	+	\$18.60
RP-6500	6 VDC	500mA	2.1 x 5.5 mm	-	6.08
RP-6500-P	6 VDC	500mA	2.1 x 5.5 mm	+	6.08
RP-061A	6 VDC	1000mA	2.1 x 5.5 mm	-	15.66
RP-061A5	6 VDC	1500mA	2.1 x 5.5 mm	-	22.06
RP-9200-P	9 VDC	200mA	2.1 x 5.5 mm	+	5.31
RP-9500	9 VDC	500mA	2.1 x 5.5 mm	-	6.31
RP-9500-P	9 VDC	500mA	2.1 x 5.5 mm	+	6.31
RP-9500R	9 VDC	500mA Regulated	2.1 x 5.5 mm	-	15.80
RP-9500R-P	9 VDC	500mA Regulated	2.1 x 5.5 mm	+	15.80
RP-091A	9 VDC	1000mA	2.1 x 5.5 mm	-	8.77
RP-091A-P	9 VDC	1000mA	2.1 x 5.5 mm	+	8.77
RP-091A5	9 VDC	1500mA	2.1 x 5.5 mm	-	25.35
RP-1220	12 VDC	200mA	2.1 x 5.5 mm	-	6.23
RP-1240R-P	12 VDC	400mA Regulated	2.1 x 5.5 mm	+	16.80
RP-1250	12 VDC	500mA	2.1 x 5.5 mm	-	6.62
RP-1250-P	12 VDC	500mA	2.1 x 5.5 mm	+	6.62
RP-1280	12 VDC	800mA	2.1 x 5.5 mm	-	8.23
RP-1280-P	12 VDC	800mA	2.1 x 5.5 mm	+	8.23
RP-1201	12 VDC	1000mA	2.1 x 5.5 mm	-	9.08
RP-1201-P	12 VDC	1000mA	2.1 x 5.5 mm	+	9.08
RP-1201A2	12 VDC	1200mA	2.1 x 5.5 mm	-	10.85
RP-1201A2-P	12 VDC	1200mA	2.1 x 5.5 mm	+	10.85
RP-1540	15 VDC	400mA	2.1 x 5.5 mm	-	7.08
RP-1501A-P	15 VDC	1000mA	2.5 x 5.5 mm	+	21.95
RP-1850-P	18 VDC	500mA	2.1 x 5.5 mm	+	11.65
RP-1880-P	18 VDC	800mA	2.1 x 5.5 mm	+	21.54
RP-1801A2-P	18 VDC	1200mA	2.1 x 5.5 mm	+	22.57
RP-2440	24 VDC	400mA	2.1 x 5.5 mm	-	8.38
RP-2440-P	24 VDC	400mA	2.1 x 5.5 mm	+	8.38
RP-2460-P	24 VDC	350mA	2.1 x 5.5 mm	+	13.82
RP-2401A-P	24 VDC	1000mA	2.1 x 5.5 mm	+	18.38
RP-2401A5-P	24 VDC	1500mA	2.1 x 5.5 mm	+	41.14

AC/DC MULTIPOWER ADAPTERS—LINEAR: 120 VAC INPUT

Cat. No.	Output Voltage (VDC)	Output Current	Tip Diameter	Centre Polarity	Net Price
M300R	1.5,3,4.5,6,7.5,9,12	300mA	Universal	Reversible	\$7.58
M500R	3,4.5,6,7.5,9,12	500mA	Universal	Reversible	8.28
M800	3,4.5,6,7.5,9,12	800mA	Universal	Reversible	12.80



RPR-092A-P5



RPT-1203A3-P6

AC/DC POWER ADAPTERS—SWITCHING: 100-240 VAC INPUT

Cat. No.	Output Voltage	Output Current	Tip Diameter	Centre Polarity	Net Price
RPR-052A6-P5	5 VDC	2600mA Reg	2.1 x 5.5 mm	+	\$20.00
RPR-092A-P5	9 VDC	2000mA Reg	2.1 x 5.5 mm	+	20.00
RPR-1201A5-P5	12 VDC	1500mA Reg	2.1 x 5.5 mm	+	20.00
RPR-1501A2-P5	15 VDC	1200mA Reg	2.1 x 5.5 mm	+	20.00
RPR-1801A-P5	18 VDC	1000mA Reg	2.1 x 5.5 mm	+	20.00
RPR-24750-P5	24 VDC	750mA Reg	2.1 x 5.5 mm	+	20.00
RPT-1202A5-P5*	12 VDC	2500mA Red	2.1 x 5.5 mm	+	35.00
RPT-1202A5-P5-2**	12 VDC	2500mA Reg	2.1 x 5.5 mm	+	30.00
RPT-1203A3-P6***	12 VDC	3330mA Reg	2.5 x 5.0 mm	+	43.00
RPT-1502A6-P5***	15 VDC	2670mA Reg	2.1 x 5.5 mm	+	43.00
RPT-1802A7-P5***	18 VDC	2780mA Reg	2.1 x 5.5 mm	+	43.00
RPT-2402A0-P5***	24 VDC	2100mA Reg	2.1 x 5.5 mm	+	43.00

*Desktop style IEC cord sold separately. **138-330, ***138-201 or ***138-406.

AC/DC MULTIPOWER ADAPTERS—SWITCHING: 100-140 VAC INPUT

Cat. No.	Output Voltage (VDC)	Output Current	Tip Diameter	Centre Polarity	Net Price
MWS1088UC	3,4.5,6,7.5,9,12	1000mA Reg	Universal	Reversible	\$23.80
MWS1189UC	3,4.5,6,7.5,9,12	1700mA Reg	Universal	Reversible	27.28



RP-1283

AC/AC POWER ADAPTERS: 120VAC INPUT

Cat. No.	Output Voltage	Output Current	Tip Diameter	Net Price
RP-091AA	9 VAC	1000mA	2.1 x 5.5 mm	\$6.08
RP-091AA5	9 VAC	1500mA	2.1 x 5.5 mm	16.91
RP-1283	12 VAC	830mA	2.1 x 5.5 mm	6.46
RP-1630A	16 VAC	300mA	2.1 x 5.5 mm	6.00
RP-1601AA1	16 VAC	1100mA	2.1 x 5.5 mm	10.42



POWER ADAPTER EXTENSION CORDS, COAXIAL PLUG TO JACK

Cat. No.	Plug Diameter	Length	Gauge	Net Price
310-803	2.1 x 5.5 x 11 mm	3ft	22 AWG	\$2.22
310-806	2.1 x 5.5 x 11 mm	6ft	22 AWG	2.58
310-812	2.1 x 5.5 x 11 mm	12ft	22 AWG	2.86
310-825	2.1 x 5.5 x 11 mm	25ft	22 AWG	3.92
310-848	2.5 x 5.5 x 11 mm	25ft	22 AWG	3.60



310-900



310-910

COAXIAL PLUG TO TINNED WIRE LEAD CABLES

Cat. No.	Plug Diameter	Length	Gauge	Net Price
310-900	2.1 x 5.5 x 11 mm	6ft	22 AWG	\$1.94
310-905	2.5 x 5.5 x 11 mm	6ft	22 AWG	1.94
310-910	2.5 x 5.5 x 11 mm R/A	6ft	22 AWG	1.94
310-920	2.1 x 5.5 x 11 mm	6ft	18 AWG	2.68
310-925	2.5 x 5.5 x 11 mm	6ft	18 AWG	2.68
310-937	1.7 x 4.5 x 11 mm R/A	6ft	18 AWG	3.14