



MS-10C/MS-10CE

Most Popular Floor Stand for budget conscious users. MS-10C includes chrome finished tube and circular cast iron base. MS-10CE is supplied with ebony finished tube and circular cast base. Height: 35"-63". Base: 10" dia. Weight: 10 lbs. MS-10CE: Height 34"-61".

Cat. No.	Description	Net Price
MS-10C	Chrome	\$36.54
MS-10CE	Ebony	36.54



**INDUSTRY STANDARD OMNI-PURPOSE
TRANSFORMER-EQUIPPED LOUDSPEAKERS**

Patented environment-resistant, double re-entrant loudspeakers are available in 15 watt and 30 watt versions for medium and high-powered sound distribution. Those 25/70.7/100 volt loudspeakers have a screwdriver-adjust power tap selection for a variety of sound and signaling applications. Loudspeakers include the Omni-Purpose® bracket for vertical/horizontal positioning and have provisions for surface/strap mounting to pillars and I-beams. Colours: grey or beige with baked epoxy finish. Impedance: 8 ohms.

Cat. No.	Power Rating	Nominal Frequency	Dimensions WxHxD	Net Price
AP-15T	15 watts	400Hz-14kHz	7-7/8" x 8-3/4" x 9-5/16"	\$99.56
AP-30T	30 watts	300Hz-12kHz	10" x 10" x 10-1/2"	120.93



**PROFESSIONAL CONSTANT-DIRECTIVITY
TRANSFORMER-EQUIPPED LOUDSPEAKER**

Model APX40TN a conservatively rated 40 watt, constant-directivity paging loudspeaker for use in public address or paging applications. Environment-resistant units feature a 60° x 40° (±10 degrees) constant-dispersion pattern across the controlled frequency band of 1.25-10 kHz. APX models are equipped with an internal 25/70.7/100 volt transformer with screw terminal connections made beneath the rear cap. Rear cap will facilitate armoured cable. Loudspeaker mounts to die-cast zinc base. Finish in natural "X"-TRA VALUE FEATURES: The rotating bell pivots in precise 15° increments for exact on-site positioning of projection angles. A triple lock security mounting method saves installation time and provides long-term stability. Power stripe code around the driver assembly provides identification of power rating from a distance. 40 watt model includes 30 watt tap @ 70V. Quality materials. "X"-TRA EASY INSTALLATION: Pre-mount the base to a standard 1-gang, 2-gang, or 4" square E.O. box. If replacing AP Series speakers, simply remove the APX base and mount to the Omni-purpose® bracket. "X"-TRA PREDICTABILITY: Clear messaging and music. Consistent beamwidth control. Fewer speakers to provide quality communications. Impedance: 40 watt Xfmr. Power taps: 25V: .63, 1.25, 2.5, 3.75, 5, 10, 20, 40; 70.7V: 2.5, 10, 20, 30, 40; 100V: 5, 10, 20, 40.

Cat. No.	Power rating	Nominal Frequency*	Dimensions WxHxD	Net Price
APX40TN	40 watts	400-700Hz	14-1/2" x 10-1/4" x 13-1/4"	\$119.71

*±6dB.

electro sonic

Electro Sonic
appreciates your business

1-800-56-SONIC

www.e-sonic.com

info@e-sonic.com



KÖNIG & MEYER MICROPHONE STANDS

Microphone stand, folding legs with boom, zinc die-cast base.

Cat. No.	Description	Net Price
210/6	Height: 925/1630 mm. Boom arm length: 805 mm-nickel	\$73.50
210/6-BLACK	Height: 925/1630 mm. Boom arm length: 805 mm-black	73.50



KÖNIG & MEYER TABLE MICROPHONE STANDS

Small, lightweight stand, plastic base with folding nickel plated legs, 3/8" thread. Height: 60 mm.

Cat. No.	Net Price
231/1	\$11.75



KÖNIG & MEYER TABLE MICROPHONE STAND WITH SCREW-IN ROD

Sound-absorbing cast-iron base with nickel plated screw-in rod, 3/8" thread. Height: 175 mm. Base diameter: 130 mm.

Cat. No.	Net Price
232	\$39.25



LITTLITE HIGH INTENSITY GOOSENECK LAMP

Littlite comes complete with bulb, chassis, 6 foot cord, and adjustable dimmer.

Cat. No.	Description	Net Price
L-3/12	12 inch gooseneck	\$83.00
L-3/18	18 inch gooseneck	83.00

ACCESSORIES

WB	Weighted base	20.00
Q5	5W halogen replacement bulb	12.00