




KAHNETICS® ECONOMY SHOT METER

FEATURES: Digital timer control (CMOS 8-bit micro processor) for reproducibility. Time duration from .01 to 99.99 seconds. Adjustable four-position push button timer switch. Vacuum feature to prevent dripping. Timer duration indicator light (LED). Electrical foot pedal actuation for excellent ergonomics (optimal finger switch available). 0-100 PSI regulator and gauge with locking ring. Slide switch for easy change from 110-220 volts. Benchtop unit for easy reading of dials and adjustment of air pressure and vacuum. Low voltage unit. Order syringe adapters, kits and other accessories separately. **SPECIFICATIONS:** Power: 110-230 VAC switchable 50/60 Hz. Internal voltage: 24 volt transformer. Repeat accuracy: .5ms (.0005 sec.). Recycle time: 12ms (.012 sec.). Setting accuracy: ±2%. Size: 6.25" x 7.75" x 5" (W x D x H). Weight: 5 lbs. 10 oz.

Cat. No.	Description	Net Price
KDS834A	Economy Shot Meter	\$980.15
KDS834AD	Economy Shot Meter with Deluxe Kit	1210.77
KDS808	Shot Meter with Vacuum Only (no timer)	749.52



KAHNETICS® FOOT VALVE

FEATURES: Basic ON-OFF function. "Eyeball" accuracy Foot actuated for excellent ergonomics. No electrical. 0-100 PSI regulator and gauge. Easy to set up and operate. Sits on floor, thus using no table space. Drip-free vacuum accessory (on the KDS806V only). Order syringe adapters, kits and other accessories separately. **SPECIFICATIONS: KDS806**—Size: 3.75" x 7.25" x 3.75" (W x D x H). Weight: 3 lbs. 5 oz. **KDS806V**—Vacuum: 0–18" of mercury. Size: 3.75" x 8.50" x 3.75" (W x D x H). Weight: 3 lbs. 5 oz.

Cat. No.	Description	Net Price
KDS806	Foot Valve	\$322.88
KDS806V	Foot Valve with Vacuum	449.72



KAHNETICS® DELUXE SHOT METER

FEATURES: Digital timer control (CMOS 8-bit micro processor) for reproducibility. Time duration from .01 to 99.99 seconds. Adjustable four-position push button timer switch. Vacuum feature to prevent dripping. Timer duration indicator light (LED). Electrical foot pedal actuation for excellent ergonomics (optimal finger switch available). Accessory port for a vacuum pickup wand or for pressurizing an external cartridge or tank. Two 0-100 PSI regulator and gauge with locking ring. Slide switch for easy change from 110-220 volts. Benchtop unit for easy reading of dials and adjustment of air pressure and vacuum. Low voltage unit. Order syringe adapters, kits and other accessories separately. **SPECIFICATIONS:** Power: 110-230 VAC switchable 50/60 Hz. Internal voltage: 24 volt transformer. Repeat accuracy: .5ms (.0005 sec.). Recycle time: 12ms (.012 sec.). Setting accuracy: ±2%. Size 9.5" x 7.75" x 5" (W x D x H). Weight: 7 lbs. 7 oz.

Cat. No.	Description	Net Price
KDS824A	Deluxe Shot Meter	\$1268.43



KAHNETICS® UNIVERSAL SYRINGE ADAPTERS

Adapter is offered with both metal or plastic grippers. **The adapters work with all manufacturer's syringes.** You can use Luer Lok™, Luer Slim™ or tapered syringes from 1cc to 35cc. The adapter comes with a 360° swivel for ease of motion. An air operated syringe system handles most types of material (i.e.: single component, 2-part materials, self-leveling, and non-self-leveling materials). These systems produce repeatable amounts and minimal cleanup or maintenance. "Gasket" seal (rather than "O" ring) allows for the universal feature and prevents air leakage between the adapter and the syringe. Plastic Adapter Features: Light weight, lower cost. Metal Adapter Features: Fits many odd size syringes best. Syringe adapter assemblies include: 6-foot hose and male fittings.

SYRINGE ADAPTER ASSEMBLIES

Cat. No.	Description	Net Price
METAL ADAPTER ASSEMBLIES		
KDS803S6	Fits all 2-1/2 & 3cc Syringes	\$32.28
KDS805S6	Fits all 5 & 6cc Syringes	32.28
KDS810S6	Fits all 10 & 12cc Syringes	34.59
KDS830S6	Fits all 30 & 35cc Syringes	34.59
PLASTIC ADAPTER ASSEMBLIES		
KDS501S6	Fits all 1cc Syringes	29.97
KDS503S6	Fits all 2-1/2 & 3cc Syringes	26.52
KDS505S6	Fits all 5 & 6cc Syringes	26.52
KDS510S6	Fits all 10 & 12cc Syringes	28.82
KDS530S6	Fits all 30 & 35cc Syringes	27.68



KAHNETICS STAINLESS STEEL NEEDLES

Blunt. Plastic hub, stainless steel shaft, non-sterile. Available in various lengths, from 14 to 27 gauges. Prepackaged: 50 needles to a box.

Cat. No.	Description	Net Price
KDS1412P	14 Ga. Needle 1/2"	\$19.60
KDS1512P	15 Ga. Needle 1-1/2"	19.60
KDS1612P	16 Ga. Needle 1/2"	19.60
KDS1812P	18 Ga. Needle 1/2"	11.62
KDS2012P	20 Ga. Needle 1/2"	11.62
KDS2112P	21 Ga. Needle 1/2"	11.62
KDS2212P	22 Ga. Needle 1/2"	11.62
KDS221P	22 Ga. Needle 1"	11.62



KAHNETICS® MANUAL AND AIR OPERATED SYRINGES

Kahnetics has a complete line of industrial syringes for manual use and micro-air dispensing. Accessory items such as tip caps, flange caps and syringe adapters are available, as well as black barrels for UV materials.

Cat. No.	Description	Net Price Per Pkg.
MANUAL SYRINGES		
M3LL	3 c, 20/Pkg	\$8.07
M5LL	5 c, 20/Pkg	14.52
M10LL	10cc, 15/Pkg	12.92
AIR OPERATED SYRINGES		
A3LL	3cc, 20/Pkg	5.99
A5LL	5cc, 20/Pkg	9.68
A10LL	10cc, 15/Pkg	10.14
A30LL	30cc, 10/Pkg	10.37

GIVING YOU WHAT YOU WANT!



- SPEED
- PRODUCTS
- INFORMATION
- PROCUREMENT
- LINKS

IT'S ALL HERE... www.e-sonic.com