



SUPER GLUE LIQUID

This super cyanoacrylate adhesive has been formulated to quickly bond rubber, plastics, metal, and ceramics. It offers excellent strength characteristics.

Cat. No.	Description	Net Price
8333-3G	3 grams (0.1 oz) liquid	\$2.95
8333-20G	20 grams (0.7 oz) liquid	10.95



SUPER GLUE GEL

The hybrid cyanoacrylate adhesive has been formulated to quickly bond rubber, plastics, metal, and ceramics. It offers excellent strength characteristics. Choose gel when bonding uneven or vertical surfaces.

Cat. No.	Description	Net Price
8334-3ML	3 ml (0.1 oz) gel	\$3.45



SUPER GLUE DISPLAY PACK

The super glue display pack offers a point of sale solution for MG chemicals super glue products. Contains 12 units of Cat. No. 8333 super glue liquid and 12 units of Cat. No. 8334 super glue gel.

Cat. No.	Description	Net Price
8335	Display Pack (12xGel, 12xliquid)	\$79.04



SUPER CONTACT CEMENT

Quick drying, water proof, clear, and vibration-resistant bond with minimal shrinkage. For shop, industry, home and hobby use. Ideal for speaker repair.

Cat. No.	Description	Net Price
8336-55ML	55 ml (2 oz) Bottle	\$7.45



SPEAKER SERVICE CEMENT

A quick drying adhesive that is specially designed for speaker repair. It forms a hard, durable and vibration resistant bond with minimal shrinkage. Use for repairing Cones, foam surrounds, and more.

Cat. No.	Description	Net Price
8337-55ML	55 ml (2 oz) Bottle	\$8.95



THREADLOCKERS

The solution to vibrational loosening. Loosening of fasteners creates warranty problems, reliability issues and unscheduled shutdown of equipment. Threadlockers completely fills in thread paths to eliminate the movements that cause parts to shake and vibrate loose. **Four strengths. Display pack with 20 bottles available.**

Cat. No.	Description	Net Price
8701-10ML	10 ml liquid, removable, up to 1/4"	\$8.45
8701-50ML	50 ml liquid, removable, up to 1/4"	29.95
8702-10ML	10 ml liquid, removable, up to 3/4"	8.45
8702-50ML	50 ml liquid, removable, up to 3/4"	29.95
8703-10ML	10 ml liquid, permanent, up to 1"	8.45
8703-50ML	50 ml liquid, permanent, up to 1"	29.95
8704-10ML	10 ml liquid, wicking grade	8.45
8704-50ML	50 ml liquid, wicking grade	29.95
8700	Display pack	161.71

Swabs



CHAMOIS SWAB

For cleaning sensitive tape heads. Lint free synthetic suede bonded to a bendable handle allowing access to hard to reach areas. Use with M.G. Chemicals' Cat. No. 407C Audio/Video Head Cleaner.

Cat. No.	Description	Net Price
SINGLE HEAD		
810-15	15 swabs	\$7.95
810-50	50 swabs	24.95
810-500	500 swabs	180.00
DOUBLE HEAD		
810D-15	15 swabs	8.95
810D-50	50 swabs	27.95
810D-500	500 swabs	225.33



811



8112

COTTON SWABS (DOUBLE ENDED)

Pharmaceutical grade. Extra absorbent on a 6" birch shaft. Compatible with most solvents. Available in standard or tapered head.

Cat. No.	Description	Net Price
811-100	100 standard head	\$3.65
8112-100	100 tapered head	3.65



FOAM OVER COTTON SWAB

Absorbent precision cleaning applicator. Shred resistant, 100% urethane foam heads with 100 PPI porosity over extra absorbent U.S.P. pharmaceutical grade purified cotton. Bonded securely to a 6" birch shaft. Compatible with most solvents.

Cat. No.	Description	Net Price
812-10	10 swabs	\$5.95
812-50	50 swabs	16.75
812-250	250 swabs	79.45
812-1000	1000 swabs	245.00



THREAD SEALANTS

Henkel Loctite® thread sealants seal and secure plastic and metal pipes and fittings. By filling the space between threaded metal parts, thread sealants harden to prevent leaking. Designed for low and high pressure applications, thread sealants seal instantly for low pressure testing. When fully cured they seal to the burst strength of most piping systems. For repairs, parts may be disassembled with basic hand tools.

545 HYDRAULIC/PNEUMATIC THREAD SEALANT

Designed for both hydraulic and pneumatic systems, 545 contains no fillers or particles which could contaminate system fluids, foul valves, or clog fine filters and screens. Suitable for fittings up to 2" (50 mm) in diameter. Excellent solvent resistance.

565 THREAD SEALANT

Formulated specifically for metal, tapered, pipe thread fittings, 565 cures rapidly to provide immediate low pressure sealing.

567 THREAD SEALANT

A high performance sealant that locks and seals metal, tapered pipe threads, and fittings. Ideal for stainless steel, aluminum, and galvanized metal.

H.V.A.C. BLUE PIPE JOINT COMPOUND

Tough, pliable sealant specially formulated for heating, air conditioning, and refrigeration applications. Seals oils, refrigerants, butane, propane, natural gas, and more. Easy cleanup.

NO MORE LEAKS

Seals plastic pipes and allows easy disassembly. Specially formulated without the added lubricity of Teflon® to avoid cracked fittings caused by over-tightened plastic joints.

Cat. No.	Description	Net Price
545 HYDRAULIC/PNEUMATIC THREAD SEALANT		
54531	50 ml tube	\$41.00
54541	250 ml tube	140.85
565 THREAD SEALANT		
56507	6 ml tube	8.02
56531	50 ml tube	18.40
56541	250 ml tube	67.66
56571	300 ml cartridge	77.34
567 THREAD SEALANT		
56707	6 ml tube	8.02
56747	50 ml tube	18.40
56765	250 ml tube	67.66
H.V.A.C. BLUE PIPE JOINT COMPOUND		
82480	0.25 pt. brush-top	12.24
82481	1 pt. brush can	22.17
NO MORE LEAKS		
80725	2 fl. oz. tube	7.62
80724	7 fl. oz. tube	19.33
80726	1 pt. brush can	32.43



LUBRICANTS

A variety of penetrants, greases, and oils are available for lasting, general-purpose lubrication or specific applications. ViperLube™ Synthetic-Based Lubricants provide superior protection for equipment exposed to a wide range of operating temperatures and environments and are NSF H1 rated for incidental food contact. Formulated in partnership, Loctite® DuPont® Krytox® RFE Lubricants are, quite simply, the most advanced lubricants in the world. Featuring astonishing lubricity, extreme temperature resistance, nonflammability, and chemical inertness; Krytox® RFE Lubricants are the cost-effective solution to a broad range of challenging lubrications problems in a variety of industries.

VIPERLUBE™ HIGH PERFORMANCE SYNTHETIC GREASE

NLGI Grade 2/Severe Duty GC-LB Grease provides superior protection against equipment exposed to a wide range of operating temperatures and environments. Use as a lubricant and protective anti-rust film on bearings, machine parts, equipment, or as a release agent on gaskets and seals. NSF H1 rated for incidental food contact.

VIPERLUBE™ HIGH PERFORMANCE SYNTHETIC GEAR OIL

90W gear oil extends equipment life and reduces oil changes and energy costs. Recommended for use on gear sets, bearings, circulating oil systems, chains, and worn gear units. NSF H1 rated for incidental food contact.

VIPERLUBE™ HIGH PERFORMANCE SYNTHETIC LIGHTWEIGHT OIL

10W oil reduces varnish and deposits, minimizing the need for replacement parts and maintenance. Recommended for use on hydraulic systems, rotary screw compressors, food processing machinery, bearings, chains, and valves. NSF H1 rated for incidental food contact.

KRYTOX® RFE PFPE LUBRICANT

PFPE Lubricant has excellent lubrication properties over a broad temperature range, will not cause cracking or swelling, and protects against undue wear. It eliminates sticking, and aids in disassembly.

KRYTOX® RFE SYNTHETIC PFPE LUBRICATING OIL

A high performance, synthetic oil specifically designed to provide long-lasting lubrication for all maintenance activities. Provides long-lasting protection against friction and wear over a broad temperature range. Does not dry out.

KRYTOX® RFE PFPE HIGH PERFORMANCE LUBRICANT

Specially-formulated, synthetic grease designed to provide long-lasting lubrication for all types of moving and/or sliding parts. Corrosion protection.

KRYTOX® RFE ADVANCE PTFE DRY LUBRICANT

A high performance, synthetic lubricant designed to provide long-lasting lubrication for parts that require a dry, thin lubrication film. Dries to the touch in 60 seconds.

Cat. No.	Description	Net Price
VIPERLUBE™ HIGH PERFORMANCE SYNTHETIC GREASE		
36780	1 cc tube	\$1.04
36781	3 oz. tube	7.79
36782	14 oz. cartridge	13.66
36783	400 gm can	17.16
36784	0.42 oz. tube	3.22
36786	10.1 oz. aerosol can	9.19
37061	30 lb. pail	407.80
VIPERLUBE™ HIGH PERFORMANCE SYNTHETIC GEAR OIL (90 W)		
36787	1 gal. container	84.00
VIPERLUBE™ HIGH PERFORMANCE SYNTHETIC LIGHTWEIGHT OIL (10 W)		
36788	1 gal. container	82.80
KRYTOX® RFE PFPE LUBRICANT		
29710	2 oz. tube	66.18
31361	16 oz. cartridge	426.31
31360	16 lb. pail	5721.41
KRYTOX® RFE SYNTHETIC PFPE LUBRICATING OIL		
30394	8 oz. aerosol	88.56
KRYTOX® RFE PFPE HIGH PERFORMANCE LUBRICANT		
29711	2 oz. tube	66.18
29709	16 oz. cartridge	369.17
KRYTOX® RFE ADVANCE PTFE DRY LUBRICANT		
30138	8 oz. aerosol	40.64