


Half-Size Computers



PCA-6359

PENTIUM®MMX™ SBC WITH VGA/LCD/LAN/SCSI

CPU: On-board Pentium® MMX™. **CHIPSET:** Intel® 430TX. **MAX. RAM:** 256 MB. **IO:** RS232 × 2, USB × 2, SCSI, LAN × 1. **DISPLAY:** VGA/LCD. **REMARK:** Support Doc® 2000.

Cat. No.	Description
PCA-6359L	VGA/LCD
PCA-6359V	VGA/LCD
PCA-6359VE	VGA/LCD/LAN
PCA-6359F	VGA/LCD/LAN/SCSI

PCA-6771

SOCKET 370 HALF-SIZE SBC WITH VGA/LCD AND ETHERNET

CPU: Socket 370 Intel® Pentium®III. **CHIPSET:** Intel® 440BX. **MAX. RAM:** 256 MB. **IO:** RS232 × 2, USB × 2, LAN × 1. **DISPLAY:** VGA/LCD. **REMARK:** Support CFC.

Cat. No.
PCI-6771F-00B3

PCA-6770

SOCKET 370 HALF-SIZE SBC WITH VGA/LCD AND ETHERNET

CPU: Socket 370 Intel® Celeron™. **CHIPSET:** Intel® 440BX. **MAX. RAM:** 256 MB. **IO:** RS232 × 2, USB × 2, LAN × 1. **DISPLAY:** VGA/LCD. **REMARK:** Support CFC.

Cat. No.
PCA-6770F-00B3

Ethernet Data Gateway



ADAM-4570

2-PORT ETHERNET TO RS-232/422/485 DATA GATEWAY

FEATURES: 2 independent RS-232/422/485 ports. Support 10/100 Mbps Base-T standard. Supports an advanced security mechanism to avoid unauthorized access. Network broken handling. Loopback test: Easy-to-diagnose. Remote download firmware: Easy to maintain.

Cat. No.
ADAM-4570

Backplane




PCA-6114 BACKPLANE

SEGMENTS: 1. **SLOTS:** 14 ISA slot. **SIZE:** 315 × 175mm (12.4" × 6.9"). **COMPATIBLE ADVANTECH CHASSIS:** IPC-610.

Cat. No.
PCA-6114

Multifunction




PCI-1710/L/HG/HGL

100 KS/S, 12-BIT, 16-CH MULTIFUNCTION CARD

FEATURES: 12-bit resolution, 100 kS/s sampling rate. 16 S.E. or 8 Diff. AI, or a combination. Unipolar/Bipolar input range. High Gain for PCI-1710HG/HGL. 4K samples FIFO for AI. 2-ch AO for PCI-1710/1710HG. 16 DI/16 DO/1 CTR.

Cat. No.	Description
PCI-1710	100 kS/s Multifunction Card
PCI-1710L	100 kS/s Multifunction Card w/o AO
PCI-1710HG	100 kS/s High-Gain Multifunction Card
PCI-1710HGL	100 kS/s High-Gain Multifunction Card w/o AO

PC/104 Module



CE

PCM-3610

ISOLATED RS-232/422/485 CARD

FEATURES: Speed up to 115.2 Kbps. Automatic RS-485 data flow control. Jumper selectable interrupt level.

Cat. No.
PCM-3610-A

NOTE: PLEASE CONTACT YOUR ELECTRO SONIC SALES REPRESENTATIVE FOR PRICING AND AVAILABILITY