

Panduit Spiral Wrapping

MANU
356
CODE

Cat. No.	Material	Colour	A In. (mm)	B In. (mm)	T In. (mm)	Bundle Size In. (mm)	Length	Net Price	
∅ T12N-C	Nylon (Black Nylon is weather resistant)	Natural	0.125" (3.2)	0.218" (5.5)	0.015" (.38)	1/16" (1.6) - 1/2" (12.7)	100' (30.5M)	\$89.17	
∅ T12N-C0		Black	0.125" (3.2)	0.218" (5.5)	0.015" (.38)	1/16" (1.6) - 1/2" (12.7)	100' (30.5M)	112.33	
∅ T19N-C		Natural	0.188" (4.8)	0.250" (6.4)	0.020" (0.51)	1/8" (3.2) - 1" (25.4)	100' (30.5M)	163.23	
∅ T19N-C0		Black	0.188" (4.8)	0.250" (6.4)	0.020" (0.51)	1/8" (3.2) - 1" (25.4)	100' (30.5M)	163.23	
∅ T25N-C		Natural	0.25" (6.4)	0.375" (9.5)	0.023" (.58)	3/16" (4.8) - 2" (50.8)	100' (30.5M)	162.12	
∅ T25N-C0		Black	0.25" (6.4)	0.375" (9.5)	0.023" (.58)	3/16" (4.8) - 2" (50.8)	100' (30.5M)	202.65	
∅ T38N-C		Natural	0.375" (9.5)	0.437" (11.1)	0.03" (.76)	5/16" (7.9) - 3" (76.2)	100' (30.5M)	275.18	
∅ T38N-C0		Black	0.375" (9.5)	0.437" (11.1)	0.03" (.76)	5/16" (7.9) - 3" (76.2)	100' (30.5M)	302.72	
∅ T50N-C		Natural	0.5" (12.7)	0.5" (12.7)	0.032" (.81)	3/8" (9.5) - 4" (101.6)	100' (30.5M)	477.99	
∅ T50N-C0		Black	0.5" (12.7)	0.5" (12.7)	0.032" (.81)	3/8" (9.5) - 4" (101.6)	100' (30.5M)	597.46	
∅ T62N-C	TEFLON†	Natural	0.625" (15.9)	0.625" (15.9)	0.035" (.89)	1/2" (12.7) - 4 1/2" (114.3)	100' (30.5M)	671.62	
∅ T62N-C0		Black	0.625" (15.9)	0.625" (15.9)	0.035" (.89)	1/2" (12.7) - 4 1/2" (114.3)	100' (30.5M)	899.99	
∅ T75N-C		Natural	0.75" (19.1)	0.875" (22.2)	0.4" (1.01)	5/8" (15.9) - 5" (127)	100' (30.5M)	835.96	
∅ T75N-C0		Black	0.75" (19.1)	0.875" (22.2)	0.4" (1.01)	5/8" (15.9) - 5" (127)	100' (30.5M)	1180.15	
∅ T100N-C		Natural	1" (25.4)	1.125" (28.6)	0.045" (1.0)	7/8" (22.2) - 6" (152.4)	100' (30.5M)	1170.31	
∅ T100N-C0		Black	1" (25.4)	1.125" (28.6)	0.045" (1.0)	7/8" (22.2) - 6" (152.4)	100' (30.5M)	1462.92	
∅ T12T-C		TEFLON†	Natural	0.125" (3.2)	0.218" (5.5)	0.02" (.5)	1/16" (1.6) - 1/2" (12.7)	100' (30.5M)	532.67
∅ T19T-C			Natural	0.188" (4.8)	0.250" (6.4)	0.03" (.76)	1/8" (3.2) - 1" (25.4)	100' (30.5M)	764.73
∅ T25T-L			Natural	0.25" (6.4)	0.375" (9.5)	0.03" (.76)	3/16" (4.8) - 2" (50.8)	50' (15.2M)	486.79
∅ T50T-Q			Natural	0.5" (12.7)	0.5" (12.7)	0.03" (.76)	3/8" (9.5) - 4" (101.6)	25' (7.6M)	506.89
∅ T62T-Q	Natural		0.625" (15.9)	0.625" (15.9)	0.03" (.76)	1/2" (12.7) - 4 1/2" (114.3)	25' (7.6M)	632.88	
∅ T75T-X	Natural		0.75" (19.1)	0.875" (22.2)	0.03" (.76)	5/8" (15.9) - 5" (127)	10' (3.0M)	353.89	
∅ T100T-X	Natural		1" (25.4)	1.125" (28.6)	0.04" (1.01)	7/8" (22.2) - 6" (152.4)	10' (3.0M)	547.02	

†TEFLON or equivalent fluorocarbon PTFE material is used. TEFLON is a registered trademark of E.I. DuPont Co.







PANDUIT PAN-WRAP™ SPLIT HARNESS WRAP

Pan-Wrap Split Harness Wrap is an innovative addition to the Panduit Abrasion Protection Line. Engineered for wire harness protection. Pan-Wrap bundles and protects wire, cable, and hoses. The Pan-Wrap design provides full 360° coverage with pre-cut slots for break-outs to maximize reliability and reduce installation time. **FEATURES:** Flexible design allows maneuverability and protects wire and cables during movement. Installation tool reduces installation time and lowers installed cost.

Cat. No.	Size I.D. In. (mm)	Maximum Bundle Diameter In. (mm)	Material	Colour	Length Ft. (M)	Net Price
∅ PW50F-T	0.50 (12.7)	0.55 (13.97)	Polyethylene	Natural	200 (61.05)	\$263.03
∅ PW75F-C	0.75 (19.05)	0.80 (20.32)	Polyethylene	Natural	100 (30.48)	189.73
∅ PW50F-T20	0.50 (12.7)	0.55 (13.97)	Polyethylene	Black	200 (61.05)	288.90
∅ PW75F-C20	0.75 (19.05)	0.80 (20.32)	Polyethylene	Black	100 (30.48)	204.82

INSTALLATION TOOL

Cat. No.	Material	Colour	Size (In.)	Net Price
∅ PWT50	ABS	White	0.50	\$8.72
∅ PWT75	ABS	White	0.75	9.11



PANDUIT GROMMET EDGING

Protects and insulates wires and cables from chafing against sharp edges. Choose from five materials—**Nylon:** Self extinguishing. For indoor use up to 149°F (65°C). **Polyethylene:** General purpose material for indoor use up to 122°F (50°C). Style GEE and GES provided in .030" (0.88mm) thick material, making them highly flexible. Available with slotted or solid wall construction. **Weather Resistant Polyethylene:** For outdoor use to 122°F (50°C). Excellent resistance to acid rain and ultra-violet light. **Flame Retardant Polyethylene:** UL94-0 rated material. Will not support a flame. Available in slotted or solid wall construction. **Adhesive Lined Polyethylene:** Base is lined with a pressure sensitive adhesive. Available in natural and weather resistant Adhesive ensures that the product will stay where it is installed.

Continued on next page....