






## PANDUIT FOAM MOUNTING TAPE

Used to hold, join, or bond a wide variety of surfaces—rubber for indoor applications and acrylic for outdoor and high temperature applications.

Cat. No.	Width (In.)	Length Per Roll (Yards)	Net Price Per Roll
<b>1/32" THICK, WHITE, RUBBER</b>			
⊕ P32W2R1-50-72	1/2	72	\$99.20
⊕ P32W2R1-75-72	3/4	72	132.02
⊕ P32W2R1-100-72	1	72	164.72
<b>1/32" THICK, WHITE, ACRYLIC</b>			
⊕ P32W2A2-50-72	1/2	72	97.78
⊕ P32W2A2-75-72	3/4	72	130.18
⊕ P32W2A2-100-72	1	72	160.82



## PANDUIT PLASTIC WIRING DUCT

**Reduce your total installed costs with restricted slot design:** Holds breakout wires captive while providing complete accessibility for adding or removing wires—even with terminations attached. Results: Your total cost is reduced during initial installation, wire tracing, trouble shooting and circuit revisions. Non-slip cover prevents vibration, yet is easy to install or remove. **Three material choices for Type D Duct:** PVC for indoor general purpose use. NORYL special purpose thermoplastic resin; temperature use to 95°C (203°F), chlorine-free. Polycarbonate special purpose material for temperature use up to 125°C (257°F); low chlorine, low smoke generation. **Type F snap-in slot design:** Offers more slots and narrow fingers than traditional Type E duct. Designed with a flush base and cover for improved aesthetics. More mounting holes for even greater design flexibility.

Cat. No.	Duct Width (Inches)	Height (Inches)	Net Price Per Foot
<b>TYPE G WIRING DUCT, PVC MATERIAL, LIGHT GREY, 6 FOOT LENGTH</b>			
⊕ G.5X.5LG6	1/2	1/2	\$3.04
⊕ G.5X1LG6	1/2	1	3.58
⊕ G.75X.75LG6	3/4	3/4	3.94
⊕ G.75X1LG6	3/4	1	3.89
⊕ G.75X1.5LG6	3/4	1-1/2	4.65
⊕ G.75X2LG6	3/4	2	5.66

Cat. No.	Duct Width (Inches)	Height (Inches)	Net Price Per Foot
<b>TYPE G WIRING DUCT, PVC MATERIAL, LIGHT GREY, 6 FOOT LENGTH</b>			
⊕ G1X1LG6	1	1	\$3.89
⊕ G1X1.5LG6	1	1-1/2	4.87
⊕ G1X2LG6	1	2	5.26
⊕ G1X3LG6	1	3	6.86
⊕ G1X4LG6	1	4	8.43
⊕ G1.5X1LG6	1-1/2	1	4.43
⊕ G1.5X1.5LG6	1-1/2	1-1/2	5.26
⊕ G1.5X2LG6	1-1/2	2	5.73
⊕ G1.5X3LG6	1-1/2	3	7.27
⊕ G1.5X4LG6	1-1/2	4	8.64
⊕ G2X1LG6	2	1	5.10
⊕ G2X1.5LG6	2	1-1/2	5.59
⊕ G2X2LG6	2	2	5.78
⊕ G2X3LG6	2	3	7.49
⊕ G2X4LG6	2	4	9.09
⊕ G2X5LG6	2	5	12.22
⊕ G2.5X3LG6	2-1/2	3	8.33
⊕ G3X1LG6	3	1	5.73
⊕ G3X2LG6	3	2	7.03
⊕ G3X3LG6	3	3	8.64
⊕ G3X4LG6	3	4	10.39
⊕ G3X5LG6	3	5	13.74
⊕ G4X1.5LG6	4	1-1/2	7.15
⊕ G4X2LG6	4	2	8.01
⊕ G4X3LG6	4	3	9.53
⊕ G4X4LG6	4	4	11.63
⊕ G4X5LG6	4	5	16.29
⊕ G6X4LG6	6	4	18.03

Cat. No.	Duct Width (Inches)	Height (Inches)	Net Price Per Foot
<b>TYPE F WIRING DUCT, PVC MATERIAL, LIGHT GREY, 6 FOOT LENGTH</b>			
⊕ F.5X.5LG6	1/2	1/2	3.17
⊕ F.5X1LG6	1/2	1	3.73
⊕ F.75X.75LG6	3/4	3/4	4.10
⊕ F1X1LG6	1	1	3.89
⊕ F1X1.5LG6	1	1-1/2	4.87
⊕ F1X2LG6	1	2	5.26
⊕ F1X3LG6	1	3	6.86
⊕ F1X4LG6	1	4	8.43
⊕ F1.5X1LG6	1-1/2	1	4.61
⊕ F1.5X1.5LG6	1-1/2	1-1/2	5.26
⊕ F1.5X2LG6	1-1/2	2	5.73
⊕ F1.5X3LG6	1-1/2	3	7.27
⊕ F1.5X4LG6	1-1/2	4	8.99
⊕ F2X1LG6	2	1	5.32
⊕ F2X1.5LG6	2	1-1/2	5.83
⊕ F2X2LG6	2	2	5.78
⊕ F2X3LG6	2	3	7.49
⊕ F2X4LG6	2	4	9.09
⊕ F2X5LG6	2	5	12.72
⊕ F3X1LG6	3	1	5.97
⊕ F3X2LG6	3	2	7.03
⊕ F3X3LG6	3	3	8.64
⊕ F3X4LG6	3	4	10.39
⊕ F3X5LG6	3	5	14.31
⊕ F4X2LG6	4	2	8.34
⊕ F4X3LG6	4	3	9.93
⊕ F4X4LG6	4	4	11.63
⊕ F4X5LG6	4	5	16.29

Cat. No.	Duct Width (Inches)	Height (Inches)	Net Price Per Foot
<b>TYPE D WIRING DUCT, PVC MATERIAL, LIGHT GREY, 6 FOOT LENGTH</b>			
⊕ D1X1LG6	1	1	00.00
⊕ D1X1.5LG6	1	1-1/2	5.35
⊕ D1X2LG6	1	2	5.88
⊕ D1X3LG6	1	3	7.62
⊕ D1X4LG6	1	4	9.31
⊕ D1.5X2LG6	1-1/2	2	6.30
⊕ D1.5X3LG6	1-1/2	3	7.97
⊕ D1.5X4LG6	1-1/2	4	9.49
⊕ D2X2LG6	2	2	6.39
⊕ D2X3LG6	2	3	8.27
⊕ D2X4LG6	2	4	9.94
⊕ D2.5X3LG6	2-1/2	3	8.62
⊕ D3X2LG6	3	2	7.74
⊕ D3X3LG6	3	3	9.47
⊕ D3X4LG6	3	4	11.46
⊕ D4X2LG6	4	2	8.89
⊕ D4X3LG6	4	3	10.54
⊕ D4X4LG6	4	4	12.78

Continued on next page....