



AC MOTOR RUN CAPACITORS AC METALLIZED POLYPROPYLENE CAPACITORS

Metallized polypropylene film dielectric capacitors offer a new alternative for alternating current applications. All devices have metal cases and 4-prong quick disconnect terminal. These capacitors pack the same capacitance and voltage capabilities of a conventional paper capacitor into a smaller case of considerably lighter weight. In addition these capacitors have extremely low dissipation factors, offer high reliability and long life. Allow 1/2 inch clearance above the terminals on fluid-filled capacitors for interrupter operation. Use OC1 neoprene rubber boots for terminal insulators. Mount with OB Mtg. Brackets.

- HIGHLIGHTS:**
Capacitance Range: 1µF to 80µF
Capacitance Tolerance: ±10% (standard)
Voltage: 330, 370 and 440 VAC
Operating Frequency: 50 to 60 Hz
Dissipation Factor: 0.1% Max. @ 60 Hz.
Operating Temperature: -40°C to +70°C

OUTLINE DIMENSIONS (INCHES)

Style	A	B	H	D	Industry Type
ROUND CONTAINERS					
21	1 3/4	1 7/8	*	1 3/16	1 3/4" Round
23	2	2 1/8	*	1 3/16	2" Round
24	2 1/2	2 5/8	*	1 3/16	2 1/2" Round
FLAT OVAL CONTAINERS					
32	1 5/16	2 5/32	*	1 3/16	1 1/4" F.O.
37	1 29/32	2 29/32	*	1 3/16	1 3/4" F.O.
38	1 31/32	3 21/32	*	1 3/16	2" F.O.

*See rating table for "H" dimension.

ROUND TYPE

Cat. No.	Cap. µF	VAC	Base Style	Height Inches	Net Price
23FD3308	8	330	23	2.63"	\$22.00
21FD3715	15	370	21	2 5/8"	17.73
21FD37175	17.5	370	21	2 7/8"	18.97
21FD3720	20	370	21	2 7/8"	20.37
23FD3725	25	370	23	3.00"	24.33
23FD3730	30	370	23	3.00"	25.57
23FD3735	35	370	23	3.00"	26.80
23FD3740	40	370	23	3.00"	27.63
24FD3750	50	370	24	3.00"	39.19
24FD3760	60	370	24	3.00"	35.02
21FB4415	15	440	21	2 7/8"	24.74
23FB4425	25	440	23	3.00"	32.45
24FB4430	30	440	24	3.00"	39.61
24FB4440	40	440	24	3 3/4"	35.05

NOTE: Add suffix "F" to Cat. No. for RoHS Compliant.

FLAT OVAL (SINGLE) TYPE

Cat. No.	Cap. µF	VAC	Base Style	Height Inches	Net Price
32FD3701	1	370	32	2.13	\$13.69
32FD3702	2	370	32	2.13	13.69
32FD3703	3	370	32	2.13	13.69
32FD3704	4	370	32	2.13	14.20
32FD3705	5	370	32	2.38	12.38
32FD3706	6	370	32	2.38	12.79
32FD37075	7.5	370	32	2 1/8"	13.21
32FD3710	10.0	370	32	2.63"	14.85
37FD37125	12.5	370	37	2 5/8"	18.56
37FD3715	15.0	370	37	2 3/4"	19.38
37FD37175	17.5	370	37	2 7/8"	26.94
37FD3720	20.0	370	37	2 7/8"	21.04
37FD3725	25.0	370	37	2.63"	22.52
38FD3730	30.0	370	38	3.00"	31.76
38FD3735	35.0	370	38	3.00"	33.00
38FD3740	40.0	370	38	3.00"	39.19
38FD3745	45.0	370	38	3.00"	45.79
38FD3750	50.0	370	38	3.00"	36.74
32FB4401	1	440	32	2.13	18.93
32FB4402	2	440	32	2.13	14.20
32FB4405	5	440	32	2.38	13.52
32FB4406	6	440	32	2.38	14.03
37FB44075	7.5	440	37	2 5/8"	17.32
37FB4410	10.0	440	37	2 5/8"	17.73
37FB44125	12.5	440	37	2 1/8"	26.39
37FB4415	15.0	440	37	2 1/8"	28.06
38FB4420	20.0	440	38	3.00"	39.06
38FB4425	25.0	440	38	3 3/4"	33.00
38FB4430	30.0	440	38	3.75"	46.74
38FB4440	40.0	440	38	3.75"	46.24

NOTE: Add suffix "F" to Cat. No. for RoHS Compliant.



TH



VR

BASIC HARDWARE FOR VR SERIES AND TH SERIES

VR Series: Clamps fit all can types.

Cat. No.	Size		Net Price
	In.	mm.	
VR1	1	25.4	\$2.08
VR3	1-3/8	35	1.57
VR4	1-1/2	38.1	2.44
VR6	1-3/4	44.5	2.55
VR8	2	50.8	2.33
VR10	2-1/2	63.5	2.58
VR12	3	76.2	2.82