



MULTIMETER ACCESSORY CROSS-REFERENCE GUIDE

Cat. No.	Description	XR Series DMM's	Heavy Duty Series DMM's	XP Series DMM's	DM73B	LCR55	CR50	DM7, DM9	AM8, DM2	Net Price
CARRYING CASES										
VC11	Vinyl				X					\$8.33
VC20	Padded Vinyl								X	20.00
VC30	Padded Vinyl			X			X	X		23.75
VC221A	Padded Vinyl	X	X			X				26.67
DC205B	Deluxe case	X	X							50.77
DC207B	Deluxe case with clamp pocket	X	X							61.54
TEST LEADS AND PROBE TIPS										
RTL25	Replacement test leads, non-shrouded plugs								DM2	10.00
TL35A	Standard leads with alligator clips, 0.6" jaw	X	X	X		X	X			26.67
TL36	Standard leads with alligator clips, 0.4" jaw	A	X	X		A	A			20.00
TL244	Heavy duty leads, 48" long, Ever Sharp™ tips	X	X	X		X	X			21.67
AL244	Screw on alligator clips for TL244	X	X	X		X	X			6.67
TL245	Standard leads, shrouded 90° banana plugs		A	A		X	X			18.33
TL246B	Silicone leads with large alligator clips	X	X	X		X	X			30.00
DL243C	Basic Test Lead Kit	X	X	X		X	X			53.85
DL248C	Deluxe Test Lead Kit	X	X	X		X	X			90.77
ELECTRONIC AND SPECIALITY PROBES										
LP10A	FEATURES: Good value for most common circuits. Pen-size logic probe. Troubleshoot and analyze digital logic circuits. Detects pulses > 30 ns up to 17 MHz, TTL, CMOS levels and dual LEDs indicate Hi/Lo state.									33.33
LP25A	FEATURES: Better unit test more. Pen-size logic probe. Troubleshoot and analyze digital logic circuits. Detects pulses > 30 ns up to 25 MHz, TTL, CMOS, DTL, RTL, NMOS. MOS logic dual LEDs indicate Hi/Lo state.									66.67
HV231-10	FEATURES: High voltage probe. Extended voltage measuring to 40 kV. Use with standard multimeters with 10 MΩ input impedance.									176.67
TC253A	FEATURES: Adds thermometer function to DMM. °C/°F switchable. Uses type K thermocouple sensor. Included TP255 bead probe. Range: -50°C to 1000°C. Range: -58°F to 1832°F. Output: 1 mV/°.									110.00
OTHER ACCESSORIES										
TC253A	Temperature Converter	B	B	B						110.00
XR-TA	Temperature Adapter	C								15.00
38-SW	RS232 optical cable and software	D								31.00

NOTE: A: Originally supplied with instrument. B: TC253A not required for HD110T, 33XR, 34XR, 38XR, 35XP. C: Models 35XP, 33XR, 34XR, 38XR. D: Model 38XR only.