



SILVER PRINT

Resistivity: 0.2 ohm mil. Excellent for repairing and modifying printed circuits. Quick drying. Durable acrylic base pigmented with high purity silver flakes. EMI/RFTI shielding applications.

Cat. No.	Description	Net Price
842-20G	20 grams (0.7 oz) liquid	\$34.95
842-250G	250 grams (8.8 oz) liquid	278.57



SILVER PRINT PEN

Resistivity: 0.2 Ohm-mil. Excellent for repairing and modifying printed circuits. Quick drying. Durable acrylic base pigmented with high purity silver flakes. EMI/RFTI shielding applications. Convenient microtip pen format allows precision dispensing.

Cat. No.	Description	Net Price
8420-P	8.5 grams (0.3oz) Microtip Pen	\$16.95

Lubricants



NU-TROL CONTROL CLEANER

Use when cleaning and lubricating controls. Contains a light, electronic grade, mineral oil lubricant. Cleans and lubricates controls, locks, hinges, selector switches, office equipment, power tools, clock mechanisms, and delicate mechanical equipment. Nor for use directly on electronic circuits. **Fast dry, static free, safe on plastics and elastomers, mineral oil lubrication.**

Cat. No.	Description	Net Price
401B-140G	140 grams (5 oz) aerosol	\$5.95
401B-340G	340 grams (12 oz) aerosol	10.95



SILVER CONDUCTIVE GREASE

This Silver Grease provides maximum electrical and thermal conductivity between sliding surfaces, while providing protection from moisture and corrosion. Typical applications include lubrication of substation switches or circuit breakers, heat dissipation from transformers, or static grounding on seals or O-rings.

Cat. No.	Description	Net Price
8463-7G	7 grams (0.25 oz)	\$14.95



CARBON CONDUCTIVE GREASE

Lubricates and improves electrical and thermal connections between sliding surfaces, while providing protection from moisture & corrosion. Excellent for use on switches and EMI shielding applications. Prevents normally closed switches

from corroding in place, reduces make-break arcing and pitting of switch contact surfaces, improves the connection between irregular or pitted contact surfaces, and reduces EMI noise by maintaining a continuous path between conductive surfaces. Thermally stable over a large temperature range.

Cat. No.	Description	Net Price
846-80G	80 grams (2.8 oz) tube	\$12.95
846-1P	473 ml (1 pint)	47.45



WHITE LITHIUM GREASE

Provides superior lubrication and protection against corrosion and oxidation. Reduces friction and wear. Retains consistency over a wide range of temperatures.

Cat. No.	Description	Net Price
8461-140G	140 grams (5 oz) aerosol	\$10.95
8461-85ML	85 ml (2.9 oz) tube	8.95
8461-1P	473 ml (1 pint)	37.45



TRANSLUCENT SILICONE GREASE

Provides superior corrosion protection. Lubricates and protects against moisture. Compatible with most plastics and elastomers. Conforms to the requirement of 21 CFR section 178.3570, "Lubricants for incidental food contact". **Meet MIL S-8660. Broad temperature range (-70°F to 400°F). Excellent dielectric properties. Prevents high voltage arcing.**

Cat. No.	Description	Net Price
8462-85ML	85 ml (2.9 oz) tube	\$12.95
8462-1P	473 ml (1 pint)	62.25



PEN OILER WITH TEFLON

Convenient needle tip applicator allows drop-at-a-time dispensing for precision work. Contains a long lasting super lubricant with Teflon that penetrates and prevents rust and corrosion. Hundreds of uses. Lubricates everything from appliances to vending machines. Can be used in temperatures from -60°F to +500°F.

Cat. No.	Description	Net Price
8471-7ML	7ml (0.2 oz) Pen	\$6.95



SUPER PENETRATING LUBRICANT

Use when you need a lubricant that cleans, protects, and lubricates. Protects against rusting and corrosion. Penetrates rusted nuts and bolts for easy removal. Drives out moisture and safe on plastics and metals. Contains contact and vapor phase inhibitors that prevent corrosion in both operating and idle conditions, even in very humid atmosphere.

Cat. No.	Description	Net Price
8472-125G	125 grams (4.4 oz)	\$4.95