




THE CLEAR CHOICE



### DUPLEX ALIGNMENT SCREWDRIVER

Material: Delrin. Shaft: Long end  $\frac{7}{32}$ " (5.5 mm) dia., 6" (15.2 cm) long; short end  $\frac{5}{32}$ " (4 mm) dia., 1" (2.5 cm) long. Ends:  $\frac{1}{32}$ " thick screwdriver tip (Both Ends). Total Length: 7" (17.7 cm).


Cat. No.	Net Price
00-2520-0000	\$2.53



### ANTI-STATIC ALIGNMENT TOOL KIT

Kit contains all nine anti-static alignment tools. The wide range of tip styles and sizes assures that the user will have a tool for adjusting or aligning any conventional component. Supplied with pocket storage case. **KIT CONTAINS 1 EACH:** AS-5004-0000 adjustment screwdriver, AS-8275-0000 combination aligner, AS-76-0000 steel tip duplex aligner, AS-8605-0000 small hex and screwdriver, AS-06-0000 hex and tip tool, AS-8608-0000 mini potentiometer and trimmer tool, AS-9300-0000 double ended hex tool, AS-9302-0000 3-in-1 hex core tool, AS-9400-0000 square and hex tool.


Cat. No.	Net Price
AS-5007-0000	\$12.70



### ADJUSTMENT SCREWDRIVER

Material: Conductive Nylon. Shaft:  $\frac{1}{4}$ " (6.3mm) dia., 7" (17.7 cm) long. Ends:  $\frac{1}{32}$ " thick screwdriver tip (Both ends). Total Length: 7" (17.7 cm).

Cat. No.	Net Price
AS-5004-0000	\$2.57




### SMALL ENDS HEX & SCREWDRIVER

Hex: 0.050" (1.25 mm).

Material: Conductive Nylon. Ends: hex (allen) steel 0.050" (1.25 mm),  $\frac{3}{32}$ " (2.4 mm) long;  $\frac{3}{32}$ " (2.4 mm) wide steel screwdriver tip with  $\frac{3}{32}$ " (2.4 mm) shank,  $\frac{1}{4}$ " (4.4 cm) long shank. Total Length:  $5\frac{3}{16}$ " (13.2 cm).

Cat. No.	Net Price
AS-8605-0000	\$3.61




### DOUBLE ENDED HEX TOOL

Hex:  $\frac{5}{64}$ " (0.078" -2 mm).

Material: Conductive Nylon. Ends:  $\frac{1}{4}$ " long hex, 0.096" dia. shaft,  $\frac{3}{8}$ " long hex, undercut (0.068" dia.) shaft to reach bottom slugs in coils. Total Length: 5" (12.7 cm).


Cat. No.	Net Price
AS-9300-0000	\$2.82



### COMBINATION ALIGNER

Material: Conductive Nylon. Shaft: long end  $\frac{1}{8}$ " (3.2 mm) dia.,  $2\frac{1}{2}$ " (6.3 cm) long; short end  $\frac{7}{32}$ " (5.5 mm) dia.,  $2\frac{1}{16}$ " (6.2 cm) long. Ends:  $\frac{1}{32}$ " thick screwdriver tip (long end);  $\frac{1}{8}$ " (3.2 mm) wide steel tip, recessed  $\frac{1}{16}$ " (short end). Total Length:  $4\frac{15}{16}$ " (12.5 cm).

Cat. No.	Net Price
AS-8275-0000	\$3.15




### HEX & SPECIAL TIP TOOL

Hex: 0.100" (2.5 mm).

Material: Conductive Nylon. Ends: Flat screwdriver tip (0.027" thick-.095" wide), followed by 0.100" hex; 0.100" hex,  $\frac{7}{32}$ " long, undercut shaft to reach bottom slugs in coils. Total Length:  $5\frac{3}{32}$ " (12.9 cm).

Cat. No.	Net Price
AS-8606-0000	\$2.55




### 3-IN-1 HEX CORE TOOL

Hex  $\frac{5}{64}$ " (0.078" -2 mm) and 0.100" (2.5 mm)

Material: Conductive Nylon. Ends: small (0.078") hex followed by 0.100 hex; 0.100" hex ( $\frac{3}{8}$ " long), undercut shaft to reach bottom slugs in coils. Total Length:  $5\frac{3}{8}$ " (13.7 cm).


Cat. No.	Net Price
AS-9302-0000	\$2.82



### STEEL TIPPED DUPLEX ALIGNER

Material: Conductive Nylon. Shaft:  $\frac{7}{32}$ " (5.5 mm) dia.,  $6\frac{1}{8}$ " (15.5 cm) long. Ends:  $\frac{1}{8}$ " (3.2 mm) wide steel tip;  $\frac{1}{8}$ " (3.2 mm) wide steel tip, recessed  $\frac{1}{16}$ ". Fits no. 6 slotted stud. Total Length:  $6\frac{1}{8}$ " (15.5 cm).

Cat. No.	Net Price
AS-8276-0000	\$2.99



### MINIATURE POTENTIOMETER-TRIMMER ADJUSTMENT TOOL

Material: Conductive Nylon. Shaft:  $\frac{1}{4}$ " (6.3 mm) dia.  $4\frac{15}{16}$ " (12.5 cm) long. Ends: .085" (2.2 mm) wide steel tip; .085" (2.2 mm) wide steel tip, recessed .040". Total Length:  $4\frac{15}{16}$ " (12.5 cm).

Cat. No.	Net Price
AS-8608-0000	\$3.24