



OK SOCKET-WRAP I.D.™

Used to identify pin numbers on wire wrapping sockets. These unique items greatly simplify both initial wire wrapping and subsequent trouble shooting or repair.

Cat. No.	Pins	Row Spacing In. (mm)	Qty/Pkg	Net Price Per Pkg
ID-8-100	8	.3 (7.5)	100	\$23.69
ID-14-100	14	.3 (7.5)	100	23.69
ID-16-100	16	.3 (7.5)	100	23.69
ID-18-50	18	.3 (7.5)	50	23.69
ID-20-50	20	.3 (7.5)	50	23.69
ID-22-50	22	.4 (10)	50	23.69
ID-24-50	24	.6 (15)	50	23.69
ID-28-50	28	.6 (15)	50	23.69
ID-40-25	40	.6 (15)	25	23.69
ID-96-25	96	.3 (7.5)	25	23.69



JONARD GD TENSION GAUGES

Tension gauges are produced in two sizes and a total of 11 different ranges. Just place point of gauge arm perpendicular to the force to be measured. Reading can be taken in both directions—clockwise and counterclockwise. All gauges come equipped with maximum reading point. Maximum reading point moves with indicator when testing. It will remain at maximum force measured, enabling user to take reading afterward. No need to look at dial hand while measuring, thus avoiding reading errors. Gauges offer extreme precision and durability. The measuring springs are made of hard tempered annealed beryllium copper. This alloy provides outstanding flexibility with minimum effort. Dial is protected by unbreakable glass. Packaged in rigid, fitted plastic case to protect instrument. Tolerance $\pm .01$ (reading + maximum scale reading).

Cat. No.	Range in Grams	Graduation in Grams	Net Price
SMALL GAUGES (FLAT TIP, DIAL DIAMETER 1-1/2")			
GD-1	0-10	.25	\$220.98
GD-3	4-35	1.00	204.63
GD-5	5-50	1.00	204.63
GD-10	10-100	2.00	204.63
GD-15	15-150	5.00	204.63
GD-25	30-250	10.00	204.63
GD-30	40-350	10.00	436.26
LARGE GAUGES (ROUND TIP, DIAL DIAMETER 2-1/2")			
GD-50	60-500	20.00	457.46
GD-100	100-1000	25.00	436.26
GD-200	200-2000	50.00	204.63
GD-400	400-4000	100.00	436.26

GIVING YOU WHAT YOU WANT!



- SPEED
- PRODUCTS
- INFORMATION
- PROCUREMENT
- LINKS

IT'S ALL HERE... www.e-sonic.com