



### XENON FLASH TUBE

**Anode to cathode voltage:** 300V (200 min.-400 max.). **Maximum energy/flash:** 4WS (watt seconds). **Flash rate:** 1/second minimum. **Nominal life:** 1,000,000 flashes (@ max. energy). **Trigger voltage:** 4KV. **Tube length:** 32mm. **Lead length:** 40mm. **Lead spacing:** 10mm (overall) 5mm between leads.

Cat. No.	Net Price
90-152-0	\$4.17



### CDS PHOTOCELLS

Peak response (nm): 550.


Cat. No.	Min. Resistance (10 lux)	Max. Resistance (10 lux)	Min. Dark Resistance	Peak AC Voltage	Net Price
90-154-0	5K	10K	500K	100	\$4.3
90-155-0	11K	20K	650K	100	.43
90-156-0	16K	30K	700K	150	.43
90-157-0	30K	60K	2.5M	150	.43



### ANALOG MULTIMETER

**FEATURES:** Audible continuity checker, db output. hFE test. Mirror scale. Comes with: Test leads and battery. **SPECIFICATIONS:** DC volts: .1, .5, 10, 50, 250, 1KV (3% 20KΩ/V). AC volts: 10, 50, 250, 1KV (4% 9KΩ/V). DC current: 50μA, 2.5mA, 25mA, 250mA (3%). Resistance: x1, x10, x100, x1K, x10K. Size: 150mm x 100mm x 36mm. Warranty: 3 years.

Cat. No.	Net Price
81-011-1	\$17.92



### POCKET DIGITAL MULTIMETER

**FEATURES:** 3-1/2 digits. Diode test. Transistor test. Protective holster. Comes with: Test leads and battery. **SPECIFICATIONS:** DC volts: 200mV, 2, 20, 200, 600V (.5%). AC volts: 200, 600V (1.2%). DC current: 200μA, 2mA, 20mA, 200mA, 10A (1%). Resistance: 200, 2K, 20K, 200K, 2MΩ (.8%). Size: 70mm x 126mm x 24mm. Warranty: 3 years.


Cat. No.	Net Price
81-020-1	\$12.08



### DIGITAL MULTIMETER

**FEATURES:** 3-1/2 digits. Audible continuity test. Transistor test. Diode test. Comes with: test leads and battery. **SPECIFICATIONS:** DC volts: 200mV, 2, 20, 200, 600V (.5%). AC volts: 200mV, 2, 20, 200, 700V (.8%). DC current: 20μA, 200μA, 2mA, 20mA, 200mA, 2A, 10A (.8%). AC current: 20μA, 200μA, 2mA, 20mA, 200mA, 2A, 10A (1%). Resistance: 200, 2K, 20K, 200K, 2MΩ (.5%). Size: 88mm x 172mm x 36mm. Warranty: 3 years.

Cat. No.	Net Price
81-022-1	\$29.58



### DIGITAL MULTIMETER

**FEATURES:** 3-1/2 digits. Flip-up display. Audible continuity test. Capacitance. Transistor test. Diode test. Protective holster. Comes with: Test leads and battery. **SPECIFICATIONS:** DC volts: 200mV, 2, 20, 200, 1000V (.5%). AC volts: 200mV, 2, 20, 200, 700V (.8%). AC current: 20mA, 200mA, 2A, 20A (1%). Resistance: 200, 2K, 20K, 200K, 2M, 20M, 200MΩ (.8%). Capacitance: 2n, 20n, 200n, 2φA, 20μF (4%). Size: 91mm x 192mm x 42mm. Warranty: 3 years.

Cat. No.	Net Price
81-023-1	\$52.50



### DIGITAL MULTIMETER

**FEATURES:** 3-3/4 digits. Data hold. Bar graph. Audible continuity test. Frequency. Capacitance. Transistor test. Diode test. Protective holster. Comes with: Test leads and battery. **SPECIFICATIONS:** DC volts: 326mV, 3.26, 32.6, 326, 1000V (.5%). AC volts: 3.26, 32.6, 326, 750V (.8%). DC current: 326μA, 3.26mA, 32.6mA, 326A, 10A (1.2%). AC current: 326μA, 3.26mA, 32.6mA, 326mA, 10A (1.5%). Resistance: 326, 3.26K, 32.6K, 326K, 3.26M, 32M (.8%). Capacitance: 326nF—32.6φF (4%).

Cat. No.	Net Price
81-024-1	\$56.67