




MICRO-GATOR



MICRO-GATOR  
WITH INSULATOR

### MUELLER MICRO-GATOR CLIP

Smooth jawed clip with a "Microscopic Tip". Lock-eared construction provides maximum hinge strength. For No. 20 wire or smaller, solder connections.  $\frac{7}{32}$ " jaw opening. Length  $1\frac{3}{32}$ ".

Cat. No.	Description	Net Price
BU-34	Plated Steel	\$ .46
BU-34C	Solid Copper	.54

### NO. 36 VINYL INSULATOR FOR 34 AND 34-C

Cat. No.	Colour	Net Price
BU-36-0	Black	\$ .19
BU-36-2	Red	.19
BU-36-6	Blue	.21
BU-36-5	Green	.21
BU-36-9	White	.21
BU-36-4	Yellow	.21



MINI-GATOR



MINI-GATOR  
WITH INSULATOR


### MUELLER MINI-GATOR CLIP

Full-meshing teeth grip finest wires. Designed with rivet hinge for greater strength. For No. 20 wire or smaller. Strong spring action for penetrating protective coatings. Solder connections.  $\frac{3}{16}$ " jaw opening. Length  $1\frac{3}{32}$ ".

Cat. No.	Description	Net Price
BU-30	Plated Steel	\$ .26
BU-30C	Solid Copper	.34

### NO. 32 VINYL INSULATOR FOR 30 AND 30-C

Cat. No.	Colour	Net Price
BU-32-0	Black	\$ .19
BU-32-2	Red	.19
BU-32-6	Blue	.21
BU-32-5	Green	.21
BU-32-9	White	.21
BU-32-4	Yellow	.21



### NO. 30-BL ROLLER BARREL TAIL SECTION

Improved design offers greater utility and value. Full meshed teeth, rivet hinge, and roller barrel tail section. Solder or crimp connection.  $\frac{3}{16}$ " jaw opening.  $\frac{1}{8}$ " I.D. Length  $1\frac{1}{4}$ ".

Cat. No.	Description	Net Price
BU-30BL	Plated Steel	\$ .25



### NO. 30-TBO THREADED BARREL

This design offers great utility and value. Using a standard No. 30BL, a threaded steel barrel is added. This allows connection to any 6-32 threaded male test prod.  $\frac{3}{16}$ " jaw opening. Length  $1\frac{1}{2}$ ".

Cat. No.	Description	Net Price
BU-30TBO	Plated Steel	\$ .56



### NO. 60 ALLIGATOR CLIP

Standard alligator clip in plated steel or solid copper. Outstanding for a wide range of test work. Convenient knurled thumb grip, barrel connection for banana plug. Has small lip for soldering, or wire may be staked in barrel. Strong hinge prevents jaw offset. Standard barrel diameter .161" I.D.,  $\frac{5}{16}$ " jaw opening. Length  $1\text{-}\frac{31}{32}$ ".

Cat. No.	Description	Net Price
BU-60	Plated Steel	\$ .31
BU-60C	Solid Copper	.61



### NO. 60-S SCREW CONNECTION

The most popular configuration. A 6-40 set screw eliminates soldering or crimping. Same as No. 60 except for screw.  $\frac{5}{16}$ " jaw opening. Length  $1\text{-}\frac{31}{32}$ ".

Cat. No.	Description	Net Price
BU-60S	Plated Steel	\$ .43
BU-60CS	Solid Copper	.67



### NO. 60PR-2 SPECIAL BARREL FOR TEST PROD OR PHONE TIP

Like No. 60 except the barrel is formed to accept standard phone tip or test prod tip. .080" I.D.,  $\frac{5}{16}$ " jaw opening. Length  $1\text{-}\frac{31}{32}$ ".

Cat. No.	Description	Net Price
BU-60PR2	Plated Steel	\$ .54



### NO. 60-HS INSULATED HANDLE

An alligator clip in plated steel or solid copper equipped with red or black insulating sleeve. Very convenient for distinguishing leads. 6-40 set screw.  $\frac{5}{16}$ " jaw opening. Length  $2\text{-}\frac{1}{32}$ ".

Cat. No.	Colour	Description	Net Price
BU-60HS-0	Black	Steel	\$ .67
BU-60HS-2	Red	Steel	.67
BU-60CHS-0	Black	Copper	.87
BU-60CHS-2	Red	Copper	.87