

Cat. No.	Size	Sensing	Overall Length	Termination	Net Price
<b>DC 3-WIRE, 10-30 VDC SUPPLY, NPN N.O.</b>					
NBB2-8GM50-E0	M8	2mm	50mm	2m PVC Cable	<b>\$99.00</b>
NBB2-8GM40-E0-V1			65mm	4-Pin Micro DC Connector	<b>99.00</b>
NBB4-12GM50-E0	M12	4mm	50mm	2m PVC Cable	<b>89.00</b>
NBB4-12GM50-E0-V1			65mm	4-Pin Micro DC Connector	<b>89.00</b>
NBB8-18GM50-E0	M18	8mm	50mm	2m PVC Cable	<b>105.00</b>
NBB8-18GM50-E0-V1			65mm	4-Pin Micro DC Connector	<b>105.00</b>
NBB15-30GM50-E0	M30	15mm	50mm	2m PVC Cable	<b>125.00</b>
NBB15-30GM50-E0-V1			65mm	4-Pin Micro DC Connector	<b>125.00</b>
<b>DC 3-WIRE, 10-30 VDC SUPPLY, PNP N.O.</b>					
NBB2-8GM30-E2	M8	2mm	30mm*	2m PVC Cable	<b>102.00</b>
NBB2-8GM50-E2			50mm		<b>99.00</b>
NBB2-8GM30-E2-V1			55mm*	4-Pin Micro DC Connector	<b>102.00</b>
NBB2-8GM40-E2-V1			65mm		<b>99.00</b>
NBB4-12GM30-E2	M12	4mm	30mm*	2m PVC Cable	<b>91.00</b>
NBB4-12GM50-E2			50mm		<b>89.00</b>
NBB4-12GM30-E2-V1			45mm*	4-Pin Micro DC Connector	<b>91.00</b>
NBB4-12GM50-E2-V1			65mm		<b>89.00</b>
NBB8-18GM30-E2	M18	8mm	30mm*	2m PVC Cable	<b>107.00</b>
NBB8-18GM50-E2			50mm		<b>105.00</b>
NBB8-18GM30-E2-V1			45mm*	4-Pin Micro DC Connector	<b>107.00</b>
NBB8-18GM50-E2-V1			65mm		<b>105.00</b>
NBB15-30GM30-E2	M30	15mm	30mm*	2m PVC Cable	<b>127.00</b>
NBB15-30GM50-E2			50mm		<b>125.00</b>
NBB15-30GM30-E2-V1			45mm*	4-Pin Micro DC Connector	<b>127.00</b>
NBB15-30GM50-E2-V1			65mm		<b>125.00</b>

\* 1/2 pint short housing style

**EXTENDED RANGE VERSIONS:** All types shown are shielded (embeddable) with normally open output. Additional units available contact your Electro Sonic sales representative

## PILE DRIVER



### PILE DRIVER ALL STAINLESS STEEL INDUCTIVE SENSORS

Pile Drivers 1-piece housing is machined from stainless steel stock and is designed for applications involving impact or abrasion. Able to withstand 1200 psi washdown and 150G of shock, Pile Driver outlasts traditional "plastic face" inductive sensors by a factor of 20 times. **FEATURES:** All stainless steel construction. Output LED indicators. 100% shielded and fully embeddable. Fully shielded and embeddable. **SPECIFICATIONS:** Housing material: 303 stainless steel. Operating temperature: -25°C to +70°C. Sealing: IP67/IP68

Cat. No.	Size	Sensing	Overall Length	Output	Net Price
<b>DC 3-WIRE, 10-30 VDC SUPPLY, 4 PIN MICRO DC CONNECTOR</b>					
NMB1.5-8GM50-E0-FE-V1	M8	1.5mm	50mm	NPN N.O.	<b>\$139.00</b>
NMB1.5-8GM50-E2-FE-V1				PNP N.O.	<b>139.00</b>
NMB2-12GM75-E0-FE-V1	M12	2mm	75mm	NPN N.O.	<b>112.00</b>
NMB2-12GM75-E2-FE-V1				PNP N.O.	<b>112.00</b>
NMB5-18GM65-E0-FE-V1	M18	5mm	65mm	NPN N.O.	<b>124.00</b>
NMB5-18GM65-E2-FE-V1				PNP N.O.	<b>124.00</b>
NMB8-30GM65-E0-FE-V1	M30	8mm	65mm	NPN N.O.	<b>135.00</b>
NMB8-30GM65-E2-FE-V1				PNP N.O.	<b>135.00</b>
<b>AC/DC 2 WIRE, 20-140 VAC OR 20-200 VDC SUPPLY, DUAL KEY MICRO AC CONNECTOR</b>					
NMB2-12GM85-US-FE-V12	M12	2mm	85mm	N.O.	<b>194.00</b>
NMB5-18GM85-US-FE-V12	M18	5mm	90mm		<b>196.00</b>
NMB8-30GM85-US-FE-V12	M30	8mm	90mm		<b>198.00</b>

**NOTE:** These are ferrous sensing models only, for non-ferrous, models replace "FE" in Cat. No. with "NFE". Also available in heavy-duty polyurethane pre-leaded and Mini connector versions. For more information contact your Electro Sonic sales representative.