


## BUSS®

### 5mm × 20mm FUSES



#### GMA TYPE FUSES FAST ACTING

Glass tube visual indicating. Designed for protection of miniaturized circuits or equipment. UL & CSA certified.

Cat. No.	Volts	Net Price
GMA-63-R	250	\$2.60
GMA-100-R	250	1.22
GMA-125-R	250	1.22
GMA-200-R	250	1.22
GMA-250-R	250	1.22
GMA-300-R	250	1.22
GMA-500-R	250	.66
GMA-600-R	250	.66
GMA-750-R	250	.66
GMA-800-R	250	.66
GMA-1-R	250	.54
GMA-1.5-R	250	.54
GMA-1.6-R	250	.54
GMA-2-R	250	.54
GMA-2.5-R	250	.54
GMA-3-R	250	.54
GMA-3.5-R	125	.54
GMA-4-R	125	.54
GMA-5-R	125	.54
GMA-6-R	125	.54
GMA-7-R	125	.54
GMA-8-R	125	.54
GMA-10-R	125	.54
GMA-15-R	125	.54



#### S501 HIGH BREAKING TYPE FUSES 250 VOLT FUSES, FAST ACTING

S501 are fast acting 250 Volt ceramic tube miniature fuses for foreign equipment, with a 1500 Amp interrupting rating at 250 Volts. These fuses meet IEC specification 127 sheet 1 and are covered by SEMKO 104 approval and CEE certification.

Cat. No.	Volts	Net Price
S501-50-R	250	\$3.86
S501-63-R	250	3.86
S501-80-R	250	3.86
S501-100-R	250	3.60
S501-125-R	250	3.60
S501-160-R	250	3.60
S501-200-R	250	3.60
S501-250-R	250	3.60
S501-315-R	250	3.60
S501-400-R	250	3.60
S501-500-R	250	3.39
S501-630-R	250	3.39
S501-800-R	250	3.39
GDA-1.25-R	250	2.16
GDA-1.6-R	250	2.16
GDA-2-R	250	2.16
GDA-2.5-R	250	4.48
GDA-3.15-R	250	2.16
GDA-4-R	250	2.16
GDA-5-R	250	2.16
GDA-6.3-R	250	2.16

### 5mm × 20mm FUSES



#### S500 LOW BREAKING TYPE FUSES 250 VOLT FUSES, FAST ACTING

S500 are fast acting 250 Volt miniature glass fuses, for foreign equipment, with a 35 Amp or 10 times current rating of fuse (whichever is larger) interrupting rating at 250 Volts. These fuses meet IEC specifications 127 sheet 2 and are covered by SEMKO 104 approval and CEE certification.

Cat. No.	Volts	Net Price
S500-32-R	250	\$4.28
S500-40-R	250	4.28
S500-50-R	250	4.28
S500-63-R	250	4.28
S500-80-R	250	4.28
S500-100-R	250	4.28
S500-125-R	250	2.97
S500-160-R	250	2.97
S500-200-R	250	2.97
S500-250-R	250	2.97
S500-315-R	250	2.97
S500-400-R	250	2.97
S500-500-R	250	2.42
S500-630-R	250	2.42
S500-800-R	250	2.42
S500-1A-R	250	2.42
S500-1.25-R	250	2.42
S500-1.6-R	250	2.42
S500-2-R	250	2.42
S500-2.5-R	250	2.42
S500-3.15-R	250	2.42
S500-4-R	250	2.42
S500-5-R	250	2.42
S500-6.3-R	250	2.42



#### S506 LOW BREAKING TYPE FUSES 250 VOLT FUSES, TIME DELAY

S506 time delay (for circuits with large surge currents) 250 Volt miniature glass fuses for foreign equipment. Meet IEC specification 127 sheet 3 and are covered by SEMKO 104 approval and CEE 4 certification. The interrupting rating is 35 Amps, 10 times current rating of fuse whichever is larger at 250 Volts.

Cat. No.	Volts	Net Price
S506-32-R	250	\$6.83
S506-40-R	250	6.83
S506-50-R	250	3.38
S506-63-R	250	3.38
S506-80-R	250	6.83
S506-100-R	250	1.97
S506-125-R	250	1.97
S506-160-R	250	1.97
S506-200-R	250	5.93
S506-250-R	250	1.97
S506-315-R	250	5.93
S506-400-R	250	1.97
S506-500-R	250	1.42
S506-630-R	250	1.42
S506-800-R	250	1.42
S506-1-R	250	1.42
S506-1.25-R	250	3.03
S506-1.6-R	250	3.03
S506-2-R	250	3.03
S506-2.5-R	250	3.03
S506-3.15-R	250	3.03
S506-4-R	250	3.03
S506-5-R	250	3.03
S506-6.3-R	250	3.03