

RFID Reader Antenna



ARRKP7059-S915B

Request Samples



Check Inventory



70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1


Features

- 902 ~ 928 MHz frequency range
- Gain of 3.5 dBi
- $VSWR \leq 2.0$
- Easy to install
- RF Cable and Connector
- RoHS Compliant

Applications

- Industrial automation
- Smart Cards
- Asset Management
- Manufacturing
- Field Mobility
- Transportation

Product Image



RFID Reader Antenna



ARRKP7059-S915B

Request Samples



Check Inventory



70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

Electrical Specification

Parameter	Specification	Unit	Note
Center Frequency	915	MHz	
Operating Frequency Range	902-928	MHz	
VSWR	< 2	:1	
Polarization	RHCP	-	
Peak Gain	3.5	dBi	Based on 70×70mm ground plane
Axial Ratio	< 3	dB	
Impedance	50	Ω	
Band width @ -10dB	≥20	MHz	

Note: All measurements were performed using the evaluation board in a free-space environment. Actual performance may vary depending on factors such as the ground plane, specific application, and surrounding environment.

Mechanical Specification

Parameter	Specification
Antenna	60 x 60 x 5.0 mm
Evaluation board Dimension	70 x 70 mm
PCB	FR4
RF Cable	RG-178, L1=90±2.5mm
RF Connector	MMCX-JW
Material(s)	Dielectric Ceramics

Environmental Specification

Parameter	Specification
Operating Temperature	-40°C ~ +85°C
Storage Temperature	-45°C ~ +85°C
Relative Humidity	10% ~ 95% RH
MSL	1



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION I.R: 04-03-25

ABRACON IS
ISO9001-2015
CERTIFIED

RFID Reader Antenna



ARRKP7059-S915B

Request Samples




Check Inventory



70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

Product Dimensions



Unit: mm



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION I.R: 04-03-25

ABRACON IS
ISO9001-2015
CERTIFIED

RFID Reader Antenna



ARRKP7059-S915B

Request Samples




Check Inventory



70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

Measurement Setup photo



RFID Reader Antenna



ARRKP7059-S915B

Request Samples




Check Inventory



70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

Smith Chart



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION I.R: 04-03-25

ABRACON IS
ISO9001-2015
CERTIFIED

RFID Reader Antenna



ARRKP7059-S915B

Request Samples



Check Inventory




70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

Radiation Pattern

2D Pattern @ 915MHz

Plane	XZ	YZ	XY
Measurement Angle(deg)	94.37	110.06	0-360
Peak Gain (dBi)	3.10	2.80	3.20

XZ - Plane



RFID Reader Antenna



ARRKP7059-S915B

Request Samples




Check Inventory



70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

YZ- Plane



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION I.R: 04-03-25

ABRACON IS
ISO9001-2015
CERTIFIED

RFID Reader Antenna



ARRKP7059-S915B

Request Samples




Check Inventory



70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

XY -Plane



RFID Reader Antenna



ARRKP7059-S915B

Request Samples



Check Inventory




70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

2D Pattern @ 917MHz

Measurement Frequency: 917 MHz
Polarization Mode: Right-Handed
Comparison Error: 2.90

XZ -Plane



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION I.R: 04-03-25

ABRACON IS
ISO9001-2015
CERTIFIED

RFID Reader Antenna



ARRKP7059-S915B

Request Samples



Check Inventory




70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

2D Pattern @ 918MHz

Measurement Frequency: 918 MHz
Polarization Mode: Right-Handed
Comparison Error: 2.98

XZ -Plane



RFID Reader Antenna



ARRKP7059-S915B

Request Samples



Check Inventory




70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

2D Pattern @ 919MHz

Measurement Frequency: 919 MHz
Polarization Mode: Right-Handed
Comparison Error: 2.98

XZ -Plane



RFID Reader Antenna



ARRKP7059-S915B

Request Samples



Check Inventory




70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

2D Pattern @ 920MHz

Measurement Frequency: 920 MHz
Polarization Mode: Right-Handed
Comparison Error: 2.97

XZ -Plane



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION I.R: 04-03-25

ABRACON IS
ISO9001-2015
CERTIFIED

RFID Reader Antenna



ARRKP7059-S915B

Request Samples



Check Inventory




70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

2D Pattern @ 921MHz

Measurement Frequency: 921 MHz
Polarization Mode: Right-Handed
Comparison Error: 2.90

XZ -Plane



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION I.R: 04-03-25

ABRACON IS
ISO9001-2015
CERTIFIED

RFID Reader Antenna



ARRKP7059-S915B

Request Samples



Check Inventory




70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

2D Pattern @ 922MHz

Measurement Frequency: 922 MHz
Polarization Mode: Right-Handed
Comparison Error: 2.78

XZ -Plane



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION I.R: 04-03-25

ABRACON IS
ISO9001-2015
CERTIFIED

RFID Reader Antenna



ARRKP7059-S915B

Request Samples



Check Inventory



70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1


2D Pattern @ 923MHz

Measurement Frequency: 923 MHz

Polarization Mode: Right-Handed

Comparison Error: 2.61

XZ -Plane



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION I.R: 04-03-25

ABRACON IS
ISO9001-2015
CERTIFIED



ARRKP7059-S915B

Request Samples



Check Inventory



70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

Reflow Profile [JEDEC J-STD-020]

Solder paste: Sn/3.0Ag/0.5Cu




Table 1

SnPb Eutectic Process

Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥ 350
<2.5mm	235°C	220°C
≥ 2.5mm	220°C	220°C

Table 2

Pb-Free Process

Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ >2000
<1.6mm	260°C	260°C	260°C
1.6mm - 2.5mm	260°C	250°C	245°C
>2.5mm	250°C	245°C	245°C

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat / soak		
Temperature minimum (T_{smin})	100°C	150°C
Temperature maximum (T_{smax})	150°C	200°C
Time (T_{smin} to T_{smax}) (t_s)	60 – 120 sec.	60 – 90 sec.
Average ramp-up rate (T_{smax} to T_p)	3°C/sec. max	3°C/sec. max
Liquidous temperature (T_L)	183°C	217°C
Time at Liquidous (T_L)	60 – 150 sec.	60 – 150 sec.
Peak package body temperature (T_p)*	See Table 1	See Table 2
Time (T_p)** within 5°C of the specified classification temperature (T_c)	20 sec.	10 sec.
Ramp-down rate (T_p to T_{smax})	6°C/sec. max	6°C/sec. max
Time 25°C to peak temperature	6 min. max	8 min. max
Reflow cycles	2 max	2 max

*Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

**Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

RFID Reader Antenna



ARRKP7059-S915B

Request Samples



Check Inventory



70.0 x 70.0 x 5.9 mm
RoHS/RoHS II Compliant
MSL Level = 1

Packaging

The carton contains 2 inner boxes each with 18 pcs inside, and the size of each carton is 38 x 30 x 24cm.

Package Type	Quantity
Inner Box	18
Boxes per carton	2
Total qty per carton	36
Carton Gross weight	4Kg
Carton dimensions	38*30*24cm

Caution

- (1) Do not apply excess mechanical stress to the component body or terminations. Do not attempt to re-form or bend the components as this will cause damage to the component.
- (2) Do not expose the component to open flame.
- (3) This specification applies to the functionality of the component as a single unit. Please ensure the component is thoroughly evaluated in the application circuit.

ATTENTION: Abracon LLC's products are Commercial-Off-The-Shelf ('COTS'), which are designed, intended, and validated for use in commercial, industrial, and automotive applications. The customer is responsible for testing and verifying the performance of an Abracon solution to meet their system-level requirements.



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION I.R: 04-03-25

ABRACON IS
ISO9001-2015
CERTIFIED