

4		3		2		1			
THIS DRAWING IS UNPUBLISHED.				RELEASED FOR PUBLICATION					
© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION.				ALL INTERNATIONAL RIGHTS RESERVED.					
LOC		DIST		REVISIONS					
G		86		P	LTR	DESCRIPTION	DATE	DWN	APVD
					A	DRAWN	29OCT09	JR	TM

1 WIRE RANGE IS FOR #4 AWG STANDARD.
WIRE CROSS SECTION OF AREA RANGE:
33,100-52,600 CMA, STRANDED WIRE

2 THE TONGUE THK IS .070±.003

3 RECOMMENDED OPERATING TEMP -55°C TO
+200°C FOR HEAT SHRINK TUBING

1	1958321-1	HIGH AND LOW TEMPERTURE CROSS LINKED FLOUROPOLYMER HEAT SHRINK TUBING .500 MIN ID X 38mm±1.5mm, RT-555
1	33115-2	TERMINAL BODY: COPPER PER ASTM B-152 ANNEALED FINISH: NICKEL PLATE .000300 MIN THK PER SAE AMS QQ-N-290
-1	PART NO	DESCRIPTION

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
INCHES

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± -

4 PLC ± -

ANGLES ± 1°

MATERIAL -

FINISH -

DWN JR RUTH 29OCT09

CHK TOM MICHIELUTTI 29OCT09

APVD TOM MICHIELUTTI 29OCT09

PRODUCT SPEC -

APPLICATION SPEC -

WEIGHT -

Tyco Electronics Corporation
Harrisburg, PA 17105-3608

NAME HEAT RESISTANT TERMINAL KIT

SIZE A3 CAGE CODE 00779 DRAWING NO C-696641

RESTRICTED TO -

CUSTOMER DRAWINGSCALE 4:1SHEET 1 OF 1REV A

1470-19 (1/08)