



Industrial grade manual motor controllers

Product description

2-pole & 3-pole
30A, 600V/AC

Two-position, maintained contact, single throw, 2-pole, single-phase

Rating A	V/AC	Description	Termination style	Max. AWG wire size	Catalog no.		
30	600	Switch only	Front wired screw	#10 AWG	☐ AH6810U	•	•
		Switch in NEMA Type 1 enclosure	Front wired screw	#10 AWG	☐ AH6810G	•	•
		Switch in NEMA Type 3R enclosure	Front wired screw	#10 AWG	☐ AH6810W*	•	•
		Switch in NEMA Type 3, 7 & 9 enclosure for hazardous enclosures. Class I, Div. 1 & 2, Groups C, D; Class II, Groups E, F, G	Front wired screw	#10 AWG	☐ AH6810E	•	•

*For Canada, order Cat. no. AH6810WR
type 3, 7, 9 enclosure: iron back box with galvanized
and acrylic paint finish copperless aluminum

Horsepower rated for motor loads per UL508

	120 V/AC	240 V/AC	480 V/AC	600 V/AC
HP	2	5	7.5	7.5

Two-position, maintained contact, single throw, 3-pole, 3-phase

Rating A	V/AC	Description	Termination style	Max. AWG wire size	Catalog no.		
30	600	Switch only	Front wired screw & clamp	#10 AWG	☐ AH7810UD	•	•
		Switch with cover plate for flush mounting	Front wired screw & clamp	#10 AWG	☐ AH7810FD	•	•
		Switch in NEMA Type 1 single-gang enclosure	Front wired screw & clamp	#10 AWG	☐ AH7810GD	•	•
		Switch in NEMA Type 1 double-gang enclosure	Front wired screw & clamp	#10 AWG	☐ AH7810GDB	•	•
		Switch in NEMA Type 3R enclosure	Front wired screw & clamp	#10 AWG	☐ AH7810WD	•	•
		Switch in NEMA Type 3, 7 & 9 Enclosure for hazardous enclosures. Class I, Div. 1 & 2, Groups C, D; Class II, groups E, F, G	Front wired screw & clamp	#10 AWG	☐ AH7810ED	•	•

Type 3, 7, 9 enclosure: iron back box with galvanized steel
and acrylic paint finish copperless aluminum
Also available in Type 4X enclosure (see page E-23)

Horsepower rated for motor loads per UL508

	120 V/AC	240 V/AC	480 V/AC	600 V/AC
HP	3	7.5	15	15

Accessories for 30A manual motor controllers

Description	Catalog no.		
Empty enclosure, NEMA type 1 single-gang	☐ AHN1GD	•	•
Empty enclosure, NEMA type 3R	☐ AHN3WD	•	•
Wet-location plastic 1-gang weather protective flush mount toggle switch cover	☐ S2983	•	•
Cast aluminum single gang 3-hole powder coated back box	☐ 1113	•	•
1-Gang, standards size 302/304 stainless steel wallplate	☐ 93071	•	•



AHN1GD



AHN3WD



S2983



1113



93071

Specification information: AH6800 & AH7800 series: E-45

Compliances, specifications and availability are subject to change without notice.

 Indicates NAFTA compliant - Page Q-30

 RoHS compliant - Page Q-30