



Product: 8500 ☑

Lead Wire, #16 Str TC, PVC Ins, TYPE B MIL-W-16878/1

Request Sample

Product Description

Low Temp Plastic Lead Wire, 16AWG (19x29) Tinned Copper, PVC Insulation, TYPE B MIL-W-16878/1 600V 105C

Technical Specifications

Product Overview

Suitable Applications: inter-connection circuits, internal wiring of computer and electronic equipments, (Type B) MIL-W-16878/1-Low Temp applications

Construction Details

Conductor

| Element | Element No. of Elements | | Stranding | Material | |
|--------------|-------------------------|--------|-----------|--------------------|--|
| Conductor(s) | 1 | 16 AWG | 19x29 | TC - Tinned Copper | |

Insulation

| Material | Nom. Thickness | Nom. Insulation Diameter |
|---------------------------|--------------------|--------------------------|
| PVC - Polyvinyl Chloride | 0.01 in (0.25 mm) | 0.079 in (2.0 mm) |
| Overall Cable Diameter (I | Nominal): 0.079 in | (2.0 mm) |

Electrical Characteristics

Electricals

| Nom. Conductor DCR | Max. Current | | | |
|--------------------|---|--|--|--|
| 6.5 Ohm/1000ft | Single conductor in free air @ 30°C: 14.0 A | | | |

Voltage

UL Voltage Rating 600 V RMS

Mechanical Characteristics

Temperature

| UL Temperature | Operating |
|-----------------------|-----------------|
| 105°C | -40°C To +105°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-------------------|-------------------|
| 0.79 in (20 mm) | 0.79 in (20 mm) |
| Max. Pull Tension | n: |

| Max. Pull Tension: | 27 lbs (12 kg) |
|--------------------|----------------|
| Bulk Cable Weight: | 10 lbs/1000ft |

Standards and Compliance

| Environmental Suitability: | Outdoor |
|--------------------------------|---|
| Sustainability: | CA Prop 65 |
| Military Compliance: | MIL-W-16878/1 |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |

History

Update and Revision:

Revision Number: 0.450 Revision Date: 07-03-2024

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC | Footnote |
|--------------|----------------------|------------|----------|--------------|----------|
| 8500 010100 | Black | Reel | 100 ft | 612825209058 | |
| 8500 0101000 | Black | Reel | 1,000 ft | 612825209065 | Р |
| 8500 006100 | Blue, Light | Reel | 100 ft | 612825208969 | |
| 8500 0061000 | Blue, Light | Reel | 1,000 ft | 612825208976 | Р |
| 8500 0011000 | Brown | Reel | 1,000 ft | 612825208839 | Р |
| 8500 0081000 | Gray | Reel | 1,000 ft | 612825208990 | Р |
| 8500 005100 | Green, Dark | Reel | 100 ft | 612825208945 | |
| 8500 0051000 | Green, Dark | Reel | 1,000 ft | 612825208952 | Р |
| 8500 0031000 | Orange | Reel | 1,000 ft | 612825208907 | Р |
| 8500 002100 | Red | Reel | 100 ft | 612825208860 | |
| 8500 0021000 | Red | Reel | 1,000 ft | 612825208877 | Р |
| 8500 0071000 | Violet | Reel | 1,000 ft | 612825208983 | Р |
| 8500 009100 | White | Reel | 100 ft | 612825209010 | |
| 8500 0091000 | White | Reel | 1,000 ft | 612825209027 | Р |
| 8500 0141000 | White, Black Stripe | Reel | 1,000 ft | 612825209089 | |
| 8500 0181000 | White, Blue Stripe | Reel | 1,000 ft | 612825209126 | А |
| 8500 0191000 | White, Brown Stripe | Reel | 1,000 ft | 612825209133 | Α |
| 8500 0161000 | White, Green Stripe | Reel | 1,000 ft | 612825209102 | Α |
| 8500 0201000 | White, Orange Stripe | Reel | 1,000 ft | 612825209140 | Α |
| 8500 0151000 | White, Red Stripe | Reel | 1,000 ft | 612825209096 | Α |
| 8500 0171000 | White, Yellow Stripe | Reel | 1,000 ft | 612825209119 | Α |
| 8500 004100 | Yellow | Reel | 100 ft | 612825208914 | |
| 8500 0041000 | Yellow | Reel | 1,000 ft | 612825208921 | Р |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.