Specifications



Photo is representative

Eaton XTSC012BBMA

Eaton IEC motor control, Combined with a 45 mm B-frame, 7 to 15A IEC contactor, Short circuit release: 168A, Factory-assembled, B-frame, 110V/50 Hz, 120V/60 Hz coil, 1NO-1NC, Three-phase, 12A

General specifications		
PRODUCT NAME	Eaton XT IEC motor control	
CATALOG NUMBER	XTSC012BBMA	
UPC	786680186851	
PRODUCT LENGTH/DEPTH	1.77 in	
PRODUCT HEIGHT	7.03 in	
PRODUCT WIDTH	3.77 in	
PRODUCT WEIGHT	4 lb	
CERTIFICATIONS	UL Listed CSA Certified	
GLOBAL CATALOG	XTSC012BBMA	



Product specifications		
AMPERAGE RATING	12A	
HP RATING - MAX	3 Hp at 200 and 240V, 7- 1/2 Hp at 480V, 7.5 Hp at 600V	
ТҮРЕ	Factory-assembled	
FRAME SIZE	45 mm, 0.1 to 32 A	
AUXILIARY CONTACTS	1 NO, 1 NC	
COIL VOLTAGE	110-120 Vac, 50/60 Hz	
FRAME	В	
FULL LOAD CURRENT RANGE	8-12 A	
SPECIAL FEATURES	Combined with a 45 mm B-frame, 7 to 15A IEC contactor, Short circuit release: 168A	
PHASE	Three-phase	
CLASS	Class 10	
TRIP TYPE	Class 10	

Resources	
CATALOGS	Original Equipment Manufacturer, Motor Control and Protection, Volume 9, Tab 2
SPECIFICATIONS AND DATASHEETS	<u>Eaton Specification Sheet -</u> <u>XTSC012BBMA</u>

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









