

Specifications

Photo is representative

Eaton BK/SC-40

Eaton Bussmann series SC fuse, Current-limiting time-delay fuse, Rejection style, 40 A, Class G, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 100 kAIC at 480 Vac, 10 kAIC at 300 Vdc, Bulk, 480 V, 300 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series SC fuse
CATALOG NUMBER	BK/SC-40
UPC	051712750639
EAN	5027590454940
PRODUCT LENGTH/DEPTH	0.41 in
PRODUCT HEIGHT	2.25 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.35 lb
WARRANTY	Not Applicable
COMPLIANCES	Not Applicable RoHS Compliant
CATALOG NOTES	Bulk

Electrical rating

AMPERAGE RATING	40 A
INTERRUPT RATING	100 kAIC at 480 Vac 10 kAIC at 300 Vdc
RESPONSE TIME	12 sec at 200%
VOLTAGE RATING	480 Vac, 300 Vdc

General information

CLASS	Class G
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Rejection style

Physical details

PACKAGING TYPE	Standard Bulk
-----------------------	------------------

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007 BK/SC-40~BK-SC-40~BUSS SC FUSE CLASS G
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - BK/SC-40

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

