

# Specifications

## Eaton BSPMA2240S3GR

Eaton Bussmann series BSPM series surge arrestor, Technology type MOV, 230/400 Wye (4W+G), Surge arrestor, Thermoplastic, UL94V14, 50/60 Hz, 200 Kilo Ampere, Thermoplastic, Remote Contact

### General specifications

|                                 |                                                        |
|---------------------------------|--------------------------------------------------------|
| <b>PRODUCT NAME</b>             | Eaton Bussmann series<br>BSPM series surge<br>arrestor |
| <b>CATALOG NUMBER</b>           | BSPMA2240S3GR                                          |
| <b>UPC</b>                      | 051712709040                                           |
| <b>PRODUCT<br/>LENGTH/DEPTH</b> | 1.42 in                                                |
| <b>PRODUCT HEIGHT</b>           | 3.54 in                                                |
| <b>PRODUCT WIDTH</b>            | 2.56 in                                                |
| <b>PRODUCT WEIGHT</b>           | 0.52 lb                                                |
| <b>WARRANTY</b>                 | Five year limited warranty                             |
| <b>COMPLIANCES</b>              | Contact factory<br>RoHS Compliant                      |
| <b>CERTIFICATIONS</b>           | UL 94V0<br>UL Listed                                   |

## Product specifications

|                                  |                        |
|----------------------------------|------------------------|
| <b>FREQUENCY RATING</b>          | 50/60 Hz               |
| <b>NOMINAL DISCHARGE CURRENT</b> | 20 kA                  |
| <b>OPERATING VOLTAGE</b>         | 600/1200               |
| <b>VOLTAGE RATING</b>            | 230/400 Wye (4W+G)     |
| <b>ENCLOSURE</b>                 | Thermoplastic, UL94V14 |
| <b>SURGE CURRENT</b>             | 200 kA                 |
| <b>INDICATOR TYPE</b>            | Remote contact         |
| <b>SHORT-CIRCUIT RATING</b>      | 200 kA                 |
| <b>OPERATING TEMPERATURE</b>     | -35 to 85 °C           |
| <b>MOUNTING METHOD</b>           | 35 mm DIN rail         |
| <b>DEGREE OF PROTECTION</b>      | IP20                   |
| <b>MATERIAL</b>                  | Thermoplastic          |
| <b>TYPE</b>                      | Surge arrestor         |
| <b>SPECIAL FEATURES</b>          | Technology type MOV    |
| <b>APPLICATION</b>               | Surge Protection       |

## Resources

### CATALOGS

[BSPMA2240S3GR~240V  
Corner Grnd Delta, 2P](#)

[Bussmann series complete  
full line catalog no. 1007](#)

### SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet -  
BSPMA2240S3GR](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

