

# Specifications

## Eaton FNQ-R-1-1/2

Eaton Bussmann Series Class CC fuse, FNQ, time-delay, dual-element current limiting fuse, 1.5 A, rejection style fuse, interrupting rating of 200kA at 600Vac

### General specifications

|                                 |                                             |
|---------------------------------|---------------------------------------------|
| <b>PRODUCT NAME</b>             | Eaton Bussmann series<br>FNQ-R fuse         |
| <b>CATALOG NUMBER</b>           | FNQ-R-1-1/2                                 |
| <b>UPC</b>                      | 051712147057                                |
| <b>EAN</b>                      | 5027590449625                               |
| <b>PRODUCT<br/>LENGTH/DEPTH</b> | 1.5 in                                      |
| <b>PRODUCT HEIGHT</b>           | 0.41 in                                     |
| <b>PRODUCT WIDTH</b>            | 0.41 in                                     |
| <b>PRODUCT WEIGHT</b>           | 0.015 lb                                    |
| <b>WARRANTY</b>                 | Not Applicable                              |
| <b>COMPLIANCES</b>              | CE Marked<br><a href="#">RoHS Compliant</a> |

## Product specifications

|                  |                                                                                  |
|------------------|----------------------------------------------------------------------------------|
| AMPERAGE RATING  | 1.5 A                                                                            |
| CLASS            | Class CC                                                                         |
| INTERRUPT RATING | 200 kAIC                                                                         |
| FUSE INDICATOR   | Non-indicating                                                                   |
| CONNECTION       | Ferrule end x ferrule end                                                        |
| RESPONSE TIME    | 12 sec at 200%                                                                   |
| MATERIAL         | Melamine tube                                                                    |
| PACKAGING TYPE   | Standard                                                                         |
| VOLTAGE RATING   | 600 V                                                                            |
| TYPE             | Current-limiting high inrush time-delay fuse                                     |
| SPECIAL FEATURES | Rejection style                                                                  |
| APPLICATION      | Line protection, small control transformers, industrial control, branch circuits |

## Resources

|                        |                                                                                                       |
|------------------------|-------------------------------------------------------------------------------------------------------|
| CATALOGS               | <a href="#">Low Voltage Branch Circuit Fuse Chapter</a><br><a href="#">Bussmann Full Line Catalog</a> |
| CERTIFICATION REPORTS  | <a href="#">Eaton Bussmann EU Declaration of conformity 93-68-EEC2000</a>                             |
| COMPLIANCE INFORMATION | <a href="#">RoHS Search Tool</a>                                                                      |
| MULTIMEDIA             | <a href="#">Bussmann series Fuseology</a>                                                             |
| TECHNICAL DATA SHEETS  | <a href="#">Bussmann series FNQ-R Class CC Fuse Data Sheet No. 1014</a>                               |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

