

Specifications

Eaton LP-CC-3

Eaton Bussmann Series Class CC fuse, LP-CC, time-delay, dual-element current limiting fuse, 3 A, rejection style fuse, interrupting rating of 200 kA at 600 Vac and 20 kA at 150 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series LP-CC fuse
CATALOG NUMBER	LP-CC-3
UPC	051712180290
EAN	5027590446990
PRODUCT LENGTH/DEPTH	1.5 in
PRODUCT HEIGHT	0.41 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.015 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified

Product specifications

AMPERAGE RATING	3 A
NUMBER OF ELEMENTS	Dual
CLASS	Class CC
INTERRUPT RATING	200 kAIC at 600 Vac 20 kAIC at 150 Vdc
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end
RESPONSE TIME	12 sec at 200%
MATERIAL	Melamine tube
PACKAGING TYPE	Standard
QUANTITY	10
VOLTAGE RATING	600 Vac, 150 Vdc
TYPE	Current-limiting time-delay fuse
SPECIAL FEATURES	Rejection style
APPLICATION	Specialized circuits and industrial control

Resources

	Bussmann Full Line Catalog
CATALOGS	Low Voltage Branch Circuit Fuse Chapter
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2000
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	LP-CC Spec Sheet

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

