


RoHS COMPLIANT 515-1001F

Part Numbers with the "F" suffix ending are RoHS Compliant.
Packaging is marked with "RoHS Compliant" label or equivalent markings.

719


[18,26]




.118±.005

 $[3\pm 0, 12]$

REV	ECN NO	REVISIONS		CKD	APP	DATE
Α		NEW RELEASE		KLJ	NO	7-22-10
В	103221	RECOMMENDED HOLE WAS .113±.002	LD	CS	NO	4-25-23





NOTES:

.095

[2,41]

- I. DIALIGHT PART NUMBER: 515-1001F.
- 2. COMPONENTS DESIGNED TO BE PRESSED INTO PC BOARD.
- 3. MATERIAL TO BE CLEAR, TRANSMISSIVE POLYCARBONATE (UL-94V-0 FLAMMABILITY).

[12,17]

[16,31]

- 4. STORAGE AND OPERATING TEMPERATURE: -30 TO +100°C.
- 5. RECOMMENDED SURFACE MOUNT LEDS DIALIGHT PART NUMBERS: 597-3XXI-2XXF (SINGLE COLOR) 597-77XI-2XXF (BI-COLOR)
- 6. 45° CHAMFER AROUND INSIDE OF PANEL CUT OUT (OPTIONAL).

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT CORP. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT CORP.

SCALE 2.000

SCALE: 4.000 ALL DIM'S: INCH (mm) TOLERANCES:	drawing number C - 7855	rev B			
UNLESS OTHERWISE SPECIFIED FRACTIONS: ±1/64 DECIMALS (.XX): ±.02 DECIMALS (.XXX): ±.010	TITLE SINGLE ELEMENT LIGHTPIPE				
ANGLES: ±3°	MATERIAL SEE NOTES				
	FARMINGDAL (732)	E 34 SOUT E, NJ 077 919-3119 Light.com			
FSCM 83330	SHEET I OF I FAMILY TABLE:				