







| ▲ SWITCH FUNCTION |        |        |
|-------------------|--------|--------|
| POS. 1            | POS. 2 | POS. 3 |
|                   |        |        |
| ON                | NONE   | ON     |
| 2-3               | N/A    | 2-1    |



## NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. CONTACT MATERIAL: GOLD
5. RATING: 0.4 VOLT-AMPS (VA) MAX. @ 20V MAX. (AC OR DC) EPOXY SEAL
6. ELECTRIC LIFE: 6,000 MAKE-AND-BREAK CYCLES AT FULL LOAD.
7. INSULATION RESISTANCE: 1,000 MEGA-OHM MIN.
8. DIELECTRIC STRENGTH: 1,000 V RMS @SEA LEVEL.
9. OPERATING TEMP.: -40°C TO 85°C
10. ▲ DENOTES CRITICAL PARAMETER.
11. HARDWARE INCLUDED  
T100011 - LOCK WASHER - QTY 1  
T100015 - LOCK RING - QTY 1  
T100000 - HEX NUT - QTY 2

| REV | ECO NO     | DESCRIPTION       | DATE     | BY | E-SWITCH®             |           |    |          | OBJECT ID |
|-----|------------|-------------------|----------|----|-----------------------|-----------|----|----------|-----------|
| C   | ECO-102794 | 100 SERIES UPDATE | 08/19/24 | MR | TITLE 100DP1T2B3M2REH |           |    |          | 000023125 |
|     |            |                   |          |    | SCALE                 | DATE      | DR | DWG      | REV       |
|     |            |                   |          |    | 2:1                   | 2/23/2005 | AR | ST121068 | C         |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED