

e

1		2		3		4		5		6	
PRODUCT NO.		NO OF POS		DIM L		DIM J		DIM K		DIM D	
65817-001LF		2 x 8		.700/17.78		1.05/26.7		1.30/33.0		.805/20.45	
65817-002LF		2 x 10		.900/22.86		1.25/31.8		1.50/38.1		1.005/25.53	
65817-003LF		2 x 13		1.200/30.48		1.55/39.4		1.80/45.7		1.305/33.15	
65817-004LF		2 x 16		1.500/38.10		1.85/47.0		2.10/53.3		1.605/40.77	
65817-005LF		2 x 20		1.900/48.26		2.25/57.2		2.50/63.5		2.005/50.93	
65817-006LF		2 x 22		2.100/53.34		2.45/62.2		2.70/68.6		2.205/56.01	
65817-007LF		2 x 2		.100/2.54		.45/11.4		.70/17.8		.205/5.21	
65817-008LF		2 x 3		.200/5.08		.55/14.0		.80/20.3		.305/7.75	
65817-009LF		2 x 4		.300/7.62		.65/16.5		.90/22.9		.405/10.29	
65817-010LF		2 x 5		.400/10.16		.75/19.1		1.00/25.4		.505/12.83	
65817-011LF		2 x 6		.500/12.70		.85/21.6		1.10/27.9		.605/15.37	
65817-012LF		2 x 7		.600/15.24		.95/24.1		1.20/30.5		.705/17.91	
65817-013LF		2 x 9		.800/20.32		1.15/29.2		1.40/35.6		.905/22.99	
65817-014LF		2 x 11		1.000/25.40		1.35/34.3		1.60/40.6		1.105/28.07	
65817-015LF		2 x 12		1.100/27.94		1.45/36.8		1.70/43.2		1.205/30.61	
65817-016LF		2 x 14		1.300/33.02		1.65/41.9		1.90/48.3		1.405/35.69	
65817-017LF		2 x 15		1.400/35.56		1.75/44.5		2.00/50.8		1.505/38.23	
65817-018LF		2 x 17		1.600/40.64		1.95/49.5		2.20/55.9		1.705/43.31	
65817-019LF		2 x 18		1.700/43.18		2.05/52.1		2.30/58.4		1.805/45.85	
65817-020LF		2 x 19		1.800/45.72		2.15/54.6		2.40/61.0		1.905/48.39	
65817-021LF		2 x 21		2.000/50.80		2.35/59.7		2.60/66.0		2.105/53.47	
65817-022LF		2 x 23		2.200/55.88		2.55/64.8		2.80/71.1		2.305/58.55	
65817-023LF		2 x 24		2.300/58.42		2.65/67.3		2.90/73.7		2.405/61.09	
65817-024LF		2 x 25		2.400/60.96		2.75/69.9		3.00/76.2		2.505/63.63	
65817-025LF		2 x 26		2.500/63.50		2.85/72.4		3.10/78.7		2.605/66.17	
65817-026LF		2 x 27		2.600/66.04		2.95/74.9		3.20/81.3		2.705/68.71	
65817-027LF		2 x 28		2.700/68.58		3.05/77.5		3.30/83.8		2.805/71.25	
65817-028LF		2 x 29		2.800/71.12		3.15/80.01		3.40/86.36		2.905/73.79	
NOTES:											
1. MOLDING MATERIAL: MODIFIED POLYPHENYLENE ETHER, COLOR: BLACK, UL 94V-0.											
2. PIN LENGTH TO BE .210/5.33 MIN. RECOMMENDED PIN LENGTH IS .225±.015/5.72±0.38.											
3. TO REMOVE TERM PUSH TERM FORWARD, LIFT LATCH WITH HAND TOOL AS SHOWN IN FIGURES 2 & 3 ON TA-531. DAMAGE TO LATCH CAN OCCUR IF LIFTED MORE THAN A 25° ANGLE TO TOP OF HOUSING.											
4. TERMINAL MUST BE CRIMPED PROPERLY FOR SATISFACTORY LATCHING. SEE TA-75 FOR CRIMPING INSTRUCTIONS. PRODUCT SECIFICATION: BUS-12-067.											
5. THE HOUSING IS INTENDED FOR USE WITH MINI PV™ TERMINALS WITH 22-32 GAUGE WIRE.											
6. MOLD CORING HOLES (FOR MANUFACTURING PURPOSES ONLY.)											
7. ALL MARKINGS FOR MILITARY PART NUMBERS ARE TO BE PER MIL-STD-1285. SEE TABULATION.											
8. PLACE DESC P/N AND CAGE NO. ON PACKAGING LABEL. PRODUCT LENGTH IS TO SMALL TO MARK PART.											
9. PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.											
10. THE PRODUCT IS NOT INTENDED TO BE EXPOSED TO MANUFACTURING SOLDER PROCESS.											
11. THIS PART SERIES IS NOT INITIALLY INTENDED FOR AUTOMOTIVE APPLICATIONS. ADDITIONAL FEES ARE CHARGEABLE FOR ANY ADDITIONAL QUALIFICATION AND TEST REPORTS PERFORMED OUTSIDE THE SCOPE OF THE STANDARD PRODUCT SPECIFICATIONS.											
12. UNLESS OTHERWISE APPROVED BY AMPHENOL, ALL PARTS AND COMPONENTS ARE DESIGNED & BUILT ACCORDING TO AMPHENOL'S SPECIFICATIONS WHICH ARE SUBJECT TO CHANGE WITHOUT NOTICE.											
mat'l. code SEE NOTES surface ISO 1302 ✓ tolerance ISO 406 ISO 1101 projection product family PV HOUSING											
ltr ecn no dr date tolerances unless otherwise specified angles linear .XX±.01/.X±.3 .XXX±.005/.X±.13 .XXX±.002/.XXX±.13 scale2.5:1 title MINI LATCH HOUSING DR BULKHEAD .100 [2.54] CC											
R V07-0510 HTB 07.08.03 S F-55268 DDE 25.04.03 dr A.RAISTRICK 91.02.14 engr C.TREXLER 91.02.14 chr C.TREXLER 91.02.14 appd C.TREXLER 91.02.14 dwg no sheet 2 of 2 size A3											
sheet revision index sheet type CUSTOMER Drawing											
form: A3 1 2 PDS: Rev: S STATUS:Released Printed: Apr 07, 2025 5 6											