

HD36-24-35SN-059

✓ ACTIVE

DEUTSCH | DEUTSCH HD, DEUTSCH HD30

TE Internal #: HD36-24-35SN-059

35 Position Housing, Housing for Female Terminals, Wire-to-Wire, Sealable, Wire & Cable, Power, Panel Mount, -55 – 125 °C [-67 – 257 °F], Hybrid

[View on TE.com >](#)



Automotive Parts > Automotive Connectors > Automotive Housings > DEUTSCH HD30 Housings



Connector & Housing Type: **Housing for Female Terminals**

Number of Positions: **35**

Sealable: **Yes**

Operating Temperature Range: **-55 – 125 °C [-67 – 257 °F]**

Connector Position Assurance Capable: **No**

[All DEUTSCH HD30 Housings \(358\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	Yes
Connector Shape	Circular
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Primary Locking Feature	Contact Retainer
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Blank Cavity Position	0
Connector Modification	Cable Clamp
Connector Seal Code	N Seal
Number of Positions	35



Electrical Characteristics

Operating Voltage	250 VDC
Nominal Voltage Architecture	12 V, 24 V

Body Features

Cable Exit Angle	180°
------------------	------

Contact Features

Contact Size	Size 16, Size 20
Contact Type	Socket
Mating Pin Diameter	1 mm, 1.6 mm[.04 in][.063 in]
Contact Current Rating (Max)	7.5 A, 13 A

Mechanical Attachment

Strain Relief	With
Terminal Position Assurance	No
Mating Alignment Type	Guide Slot
Mating Alignment	With
Connector Mounting Type	Panel Mount

Housing Features

Housing Material	Aluminum Alloy
------------------	----------------

Dimensions

Compatible Insulation Diameter Range	1.4 – 3.8 mm, 1.9 – 3.2 mm[.055 – .15 in][.075 – .125 in]
Product Width	49.3 mm[1.94 in]
Product Length	49.3 mm[1.94 in]
Connector Height	81 mm[3.19 in]

Usage Conditions

Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operating Temperature (Max)	125 °C[257 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

IP Rating	IP67
-----------	------

Packaging Features



Packaging Quantity	1
Packaging Method	Package

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Octamethylcyclotetrasiloxane (D4) (.4% in 8676549007) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1062-14-0177
SOC, SF, SIZE 16, 14-18, SN/SN

TE Part # 1062-16-1422
SOC, SF, SIZE 16, 12-16, SLVLES, NI/NI

TE Part # CAT-H3930-PC8382
Plug Protective Caps - DEUTSCH HD30

TE Part # CAT-D48-ST273
DEUTSCH Solid Contacts

TE Part # CAT-D48-SFT273
DEUTSCH Stamped and Formed Contacts

TE Part # 114017-ZZ
SEALING PLUG, SIZE 12/16, WHT

TE Part # CAT-H3930-CH8172
DEUTSCH HD30 Housings

Also in the Series | **DEUTSCH HD**

Automotive Housings(453)

Automotive Seals & Cavity Plugs(11)

Connector Strain Relief(6)

Other Automotive Connector Accessories(12)

Also in the Series | **DEUTSCH HD30**

Automotive Housings(453)

Automotive Seals & Cavity Plugs(11)

Connector Strain Relief(6)

Other Automotive Connector Accessories(12)

Customers Also Bought



TE Part #HD16-9-96S-C016
PLG, 9P, GRY, HJ BLK, THRD, 16

TE Part #207486-5
SIZE 23-16 RECEPT,CPC,W/SEAL

TE Part #554084-1
PLUG ASSY,36 POS,BAIL LOCK,LPF

TE Part #749108-6
68 50SR CBL CONN TERM COVER

TE Part #1579028-5
EXTRACTION TOOL

TE Part #9-1768032-1
LEB-0415P-4

TE Part #6-2176416-5
9W STD M/OX 5% 24K

TE Part #1-1105001-2
HD.M-C-BU.AU.0,3

TE Part #1977907-1
CAT5e In-Line Shielded Coupler

TE Part #174928-5
070 MLC W-W CAP HSG 3P BLUE

Documents

Product Drawings

PLG,35P,AL,N, CBLCLMPBT,DRAIN,16/20,S,MC

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_HD36-24-35SN-059_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_HD36-24-35SN-059_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_HD36-24-35SN-059_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



DEUTSCH HD30 & HDP20 CONNECTOR SERIES

English

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English