





UPC Code: 07847780947

L5-30R

2610

Brand Features

Leviton's Industrial Grade Locking Devices are built to provide unparalleled quality and superior performance in the most severe industrial settings. Leviton combines the best materials available with superior production standards to produce a broad selection of Locking Devices of unmatched flexibility and dependability.

Item Description

30 Amp, 125 Volt, NEMA L5-30R, 2P, 3W, Flush Mtg Locking Receptacle, Industrial Grade, Grounding, V-0-MAX - BLACK

Technical InformationAC Horsepower Ratings

At Rated Voltage: 2 HP

Electrical Specifications

Grounding: Grounding

Amperage: 30 Amp

Voltage: 125 Volt

Pole: 2 Wire: 3

Dielectric Voltage: Withstands 2000V

per UL498

Current Limiting: Full Rated Current Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications
Flammability: Rated V-0 per UL94
Operating Temperature: -40C to 60C

Material Specifications
Face Material: Ultramid
Base Material: Valox
Line Contacts: Brass

Environment: Corrosive

Terminal Screws: Chromated Brass **Grounding Screw:** Chromated Brass

Body Material: Nylon **Cover Material:** Valox 357

Strap Material: Nickel-Plated Brass

Color: Black

Terminal Clamps: Nickel-Plated Brass

Ground Contacts: Brass

Mechanical Specifications
Terminal ID: Marked on Device
Terminal Accom.: 14-8 AWG
Product ID: Ratings and NEMA I.D.
permanently marked on device
Termination: Back & Side

Product Features
Face Material: Ultramid

NEMA: L5-30R Base Material: Valox

Color: Black

Warranty: Lifetime Limited

Device Type: Locking Receptacle

Brand: V-0-Max

Standards and Certifications


NEMA: WD-1 & WD-6

ANSI: C-73 NOM: 057 UL: 498


CSA: C22.2 No. 42 UL Fed Spec: W-C-596

Warranty

Warranty: Lifetime Limited



Wiring Diagram



SPECIFICATION SUBMITTAL

	OF EGILLOWING GODINITIVE	
I	JOB NAME:	CATALOG NUMBERS:
ı		
ı	JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:temperature} \textbf{Teléfono: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

