



LED ELEMENT, STEADY LIGHT, BASE MOUNT ON LPZ CONTROL STATIONS Ø22MM PLATINUM SERIES, 12...30VAC/DC. BLUE

Product designation  Product type designation		LED elements steady light base mount on LPZ control station LPXLPB
General characteristics		
Colour		Blue
Electrical characteristics		
Rated frequency	Hz	50-60
Supply voltage (AC)	V	1230
Operations		
Electrical life	hours	100000
Mechanical features		
Conductor section		
AWG/kcmil conductor section		
max		14
IEC		
max	mm²	1 or 2 / 2.5
Mounting adapter		LPXAU120
Weight	g	16
Ambient conditions	9	
Temperature		
Operating temperature		
min	°C	-25
max	°C	+70
Storage temperature		170
otorage temperature min	°C	-40
max	°C	+85
Dimensions	U	+05
Wiring diagrams		
Certifications and compliance		
Compliance		
CSA C22.2 n° 14		
IEC/EN/BS 60947-1		_
IEC/EN/BS 60947-5-1		
UL508		
Certificates		
CCC		
cULus		
EAC		_
RINA		
UL		
ETIM classification		
ETHIN Glassification		EC000204 -
ETIM 8.0		Lamp holder block for control circuit devices