

1		2		3		4		5		6		7		8			
△B MI2T-XXBMMB-SL7002 XX: No. Of Pin				REV.	ECN NO.	DATE	SIGN	DESCRIPTION									
				C	C210025	2021/01/20	Vicky	△C X1									
				D	C210561	2021/04/19	Vicky	△D X2									
				E	C221890	2022/12/29	Vicky	△E X1									
Connector Clamp Ring Seal Sealing Nut																	
4P Pin Assignments Front View				58.5(Ref.) △B △D Note: * RoHS Compliant * Important Dimension △E * Waterproof rate: IP67, mated * Connector Housing: Thermoplastic, Black Pin: Copper alloy, Gold plated Extension Nut: Thermoplastic, Black △C Nut: Metal O-Ring: Rubber, Gray * Clamp Ring: Thermoplastic, Black * Sealing Nut: Thermoplastic, Black * Seal: Rubber, Gray, OD:Ø8.0mm~Ø10.0mm * One set unassembled in one pe bag													
UNIT:mm				TITLE				ITEM NO		DRAWN BY		DATE					
TOLERANCE				N SEN, MI2 T, SCREW				DWC NO		Cary		2015-03-26					
.X ±0.25				CABLE W/O SR, M, M, FI SCREW IN				△B MI2T-XXBMMB-SL7002		CHECKED BY		Lu Di					
.XX ±0.1				SCALE 1:1				SIZE A4		SHEET 1 OF 1		DATE		2015-03-26			
.XXX ±0.05				REV. E				WC-REV. A.1		QC:Inspection item		APPROVED BY		Jerry			
ANGLES ±1°										CUSTOMER ALTW		DATE		2015-03-26			
														W10814-03-0001A2			

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.