






THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

Recommended open dimensions of case.

Tolerance: $\pm 0.03\text{mm}$



Matting area with sealing



Assembly Way
組裝方式，左右方向裝配


Note:

- * IP: IP67
- * Connector: Thermoplastic
- * Pin: Copper Alloy, 30u" Gold
- * Shield: Stainless (Inner)
Stainless & Nickel Plating (Out)
- * Operating Temperature: -40°C To $+85^{\circ}\text{C}$
- * All specifications are in compliance with the USB Association's specifications.



After Assembled View
組裝面板後公母頭對差示意圖

UNIT:mm



TOLERANCE

.X ± 0.3
.XX ± 0.2
.XXX ± 0.1
ANGLES $\pm 3^{\circ}$

TITLE

USB, C TYPE, FRONT FASTENED
F, F, SMT+DIP, QUICK

SCALE

4:1

SIZE

A4

SHEET

2

OF

3

REV.

F

WC-REV.

A.3

QC: Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO

UC-00PFFH-QF7001

DWG NO

UC-00PFFH-QF7001

CUSTOMER

ALTW

DRAWN BY

Hubert

CHECKED BY

Aric

APPROVED BY

Fred

DATE


2024/08/28

DATE

2024/08/28


DATE

2024/08/28



* 1K PCS (Connector) In A Tape&Reel
5 PCS Tape&Reel In A Carton
(5K PCS/Carton)

UNIT:mm



TOLERANCE
.X ±0.3
.XX ±0.2
.XXX ±0.1
ANGLES ±3°

TITLE
USB, C TYPE, FRONT FASTENED
F, F, SMT+DIP, QUICK

SCALE 4:1 SIZE A4 SHEET 3 OF 3

REV. F WC-REV. A.3 QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO
UC-00PFFH-QF7001

DWG NO
UC-00PFFH-QF7001

CUSTOMER
ALTW

DRAWN BY
Hubert

CHECKED BY
Aric

APPROVED BY
Fred

DATE
2024/08/28

DATE
2024/08/28

DATE
2024/08/28

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.