




Technical data

Current	10 A (A.C. and D.C.)
Voltage	400 V
Rated impulse withstand voltage	6kV
Pollution degree	3
Wire cross-section	0,14 mm ² - 2,50 mm ²
AWG size	26 - 14
Operating temperature range (min, max)	(-40°C ... +125°C)
Contact type	silver plated
Mating cycles	≥ 500
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure
PE wire cross-section	0,50 - 4 mm ² ; AWG 20 - 12
Insulation resistance	≥ 10 GΩ
Weight	127,67 g

Description:			
female insert, 27 poles (28 - 54) + ground, Spring connection contacts SQUICH, 10A, 400V, silver			
Approvals / Standards			
Reference standard		EN 61984:2009-06	
Quality mark		EAC	
Conformity		CQC, CE	
UNLESS OTHERWISE SPECIFIED:		DRAWN BY DCG	
DIMENSIONS ARE IN MM TOLERANCES: FRACTIONAL ±1/64 ANGULAR: MACH±3° BEND ±5° ONE PLACE DECIMAL ±.2 TWO PLACE DECIMAL ±.1		DRAWN DATE 08/24/2021	
		CHECKED BY JJH	
		CHECK DATE 08/24/2021	
MATERIAL		COMMENTS:	
FINISH			
DO NOT SCALE DRAWING		SIZE DWG. NO. REV	
		B CDSHF-27N A	
		SCALE: 3:2 WEIGHT: SHEET 1 OF 1	

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.