



MAC (1/2"-20) Series Cordsets

2 & 3 Conductor MAC Series Cordsets, 18/20/22AWG







Double Ended Cordsets | 300 Volt, 4 amps | IP69 Rating



G


Micro-AC Series (1/2"-20) Cordsets

Male Faceview	Part Number	Cables	Features	Color Code	Female Faceview
 1/2"-20	MAC-2MFP-**	Yellow PVC AWM 2 X 20 AWG 300V, 4A -40°C to +105°C 5mm OD	Industry Standard PVC	1. Brown 2. Blue	 1/2"-20
	MACB-2MFP-**	Yellow PVC AWM With Braided Shield 2 X 22 AWG 300V, 4A -40°C to +105°C 5.8mm OD	Industry Standard PVC Braided Shield		
 1/2"-20	MAC-3MFPX-**	Yellow PVC AWM 3 X 18 AWG 300V, 4A -40°C to +105°C 7.4mm OD	Industry Standard PVC	1. Green/Yellow 2. Red/Black 3. Red/White	 1/2"-20
	MAC-3MFP-**	Yellow PVC AWM 3 X 22 AWG 300V, 4A -40°C to +105°C 5mm OD	Industry Standard PVC		
	MACB-3MFP-**	Yellow PVC AWM With Braided Shield 3 X 22 AWG 300V, 4A -40°C to +105°C 5.8mm OD	Industry Standard PVC Braided Shield		
	MACP-3MFP-**	Yellow PUR AWM 3 X 22 AWG 300V, 4A -40°C to +80°C 5.1mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR		

** Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

For extension cables with right angle male and/or female ends, please consult the factory.

Standard coupling nut is Nickel Plated Brass, for stainless steel coupling nut add a "-SS" suffix. (e.g. MAC-2MFP-1M becomes MAC-2MFP-1M-SS)



Male - Female Extension