



MDC (M12) Series Receptacles

2, 3, 4 & 5 Conductor MDC Series Receptacles, 18/22AWG




Front Mount Receptacles | PG Threads | 300 Volt, 4 amps | IP69 Rating



# of Poles	Male Face-view	Color Code	Rating	Wire AWG	Male Receptacles				Female Receptacles
					PG 7	PG 9	PG 11	PG 13.5	PG 9
2	 M12 x 1	3. Brown 4. Blue	300V 4A	18	MDC-2MR-PG7-18	MDC-2MR-PG9-18	MDC-2MR-PG11-18	MDC-2MR-PG13.5-18	MDC-2FR-PG9-18
				22	MDC-2MR-PG7	MDC-2MR-PG9	MDC-2MR-PG11	MDC-2MR-PG13.5	MDC-2FR-PG9
3	 M12x1	1. Brown 3. Blue 4. Black	300V 4A	18	MDC-3MR-PG7-18	MDC-3MR-PG9-18	MDC-3MR-PG11-18	MDC-3MR-PG13.5-18	MDC-3FR-PG9-18
				22	MDC-3MR-PG7	MDC-3MR-PG9	MDC-3MR-PG11	MDC-3MR-PG13.5	MDC-3FR-PG9
4	 M12 x 1	1. Brown 2. White 3. Blue 4. Black	300V 4A	18	MDC-4MR-PG7-18	MDC-4MR-PG9-18	MDC-4MR-PG11-18	MDC-4MR-PG13.5-18	MDC-4FR-PG9-18
				22	MDC-4MR-PG7	MDC-4MR-PG9	MDC-4MR-PG11	MDC-4MR-PG13.5	MDC-4FR-PG9
5	 M12 x 1	1. Brown 2. White 3. Blue 4. Black 5. Gray	300V 4A	18	MDC-5MR-PG7-18	MDC-5MR-PG9-18	MDC-5MR-PG11-18	MDC-5MR-PG13.5-18	MDC-5FR-PG9-18
				22	MDC-5MR-PG7	MDC-5MR-PG9	MDC-5MR-PG11	MDC-5MR-PG13.5	MDC-5FR-PG9


12" leads are standard. Longer lead lengths are available, please consult the factory for part numbers.
Stainless Steel is available, add a "SS" suffix (e.g. MDC-5MR-PG11 becomes MDC-5MR-PG11-SS).

PG7




Male Receptacle

PG9




Male Receptacle

PG11




Male Receptacle

PG13.5



Male Receptacle



Female Receptacle

Specifications:

Shell: PG7, PG9 & PG11: Nickel Plated Brass
PG13.5: Clear Anodized Aluminum
Insulator: Polyamide
Wire: 18, 22 AWG: 300V, UL Style 1007/1569

Contacts: Copper Alloy with Gold Plating
Jam Nut: Nickel Plated Brass
O-Ring: NBR
Temperature: -40°C to 105°C (-40°F to +221°F)