





Ethernet (M12) Series Etherplug Field Wireable Plugs

4 Conductor Ethernet Series Field Wireable Plugs, 18-24AWG



Field Wireable Plugs | 4 Pole D-Coded | 8 Pole A-Coded | IP67 Rating




# of Poles	Male Faceview	Wire AWG Rating	Cable O.D. Range	Male plugs		Female Plugs	
				Straight	Right Angle	Straight	Right Angle
4	 M12 x 1	18-24 AWG 250V 4A	3-6.5 mm	MDE45-4MP-FW07	MDE45-4MP-FW07-R	MDE45-4FP-FW07	MDE45-4FP-FW07-R
			4-8 mm	MDE45-4MP-FW09	MDE45-4MP-FW09-R	MDE45-4FP-FW09	MDE45-4FP-FW09-R
8	 M12 x 1	18-24 AWG 250V 4A	3-6.5 mm	MDC-8MP-FW07	MDC-8MP-FW07-R	MDC-8FP-FW07	MDC-8FP-FW07-R
			4-8 mm	MDC-8MP-FW09	MDC-8MP-FW09-R	MDC-8FP-FW09	MDC-8FP-FW09-R

These connectors are easily wired by inserting the individual wires into the screw terminal contacts.
The Connectors are water tight to IP67 and are fully mateable with other D-Coded M12 connectors.

Straight Field Wireable Plugs


Right Angle Field Wireable Plugs




Male Plugs



Female Plugs



Male Plugs



Female Plugs

Specifications:

- Body: Black Polyamide
- Insulator: Black Polyamide
- Contacts: Copper Alloy with Gold Plating
- Coupling Nut: Nickel Plated Brass
- Seal: NBR
- Temperature: -25°C to +85°C (-13°F to +185°F)