L-21



Ethernet (M12) Series Etherplug Field Wireable Plugs

4 & 8 Conductor Ethernet Series Field Wireable Plugs, 18-24/20-24AWG



Straight Field Wireable Plugs

Shielded

4 Pole D-Coded

8 Pole A-Coded

IP67 Rating



# of Poles	Male Faceview	Rating	Wire AWG	Cable 0.D. Range	Part Number	
					Male Plugs	Female Plugs
4	M12 x 1	250V 4A	18-24 AWG	3-9 mm	MDE45M-4MP-FW	MDE45M-4FP-FW
8	0 8 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	50V 4A	20-24AWG	6-8 mm	MDCM-8MP-FW	MDCM-8FP-FW


These connectors are easily wired by inserting the individual wires into the screw terminal contacts. The Connectors are water tight to IP 67 and are fully mateable with other D-Coded M12 connectors.

4 Pole Version

[66] 2.6 [21] M12x1

Male Straight Female Straight

8 Pole Version



[20] Ø.8 M12x1

Male Straight

Female Straight

[55] 2.2



Specifications:

Body: Nickel Plated Brass Coupling Nut: Nickel Plated Brass Insulator: Black Polyamide Seal: NBR

Contacts: Copper Alloy with Gold Plating Temperature: -25°C to +85°C (-13°F to +185°F)

Mencom Corporation | 1-770-534-4585 | www.mencom.com