

according to WHMIS 2023 and HCS 2024

Date of issue 07/02/2025 Version number 6.02 Revision: 07/02/2025

#### 1 Identification

- · Product identifier
  - · Trade name: 832FX-B
    - · Other Means of Identification: Black Flexible Epoxy Encapsulating and Potting Compound (Part B)
    - · Related Part Number:
    - 832FX-Part B, 832FX-450ML (B), 832FX-1.7L (B), 832FX-7.4L (B), 832FX-40L (B), 832FX-360L (B)
  - · Application of the substance / the mixture Epoxy Hardener
  - · Uses advised against Not applicable
- · Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

MG Chemicals (Head Office) 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA +(1) 800-340-0772

+(1) 905-331-1396

info@mgchemicals.com

#### Distributor:

Masline 511 Clinton Ave S Rochester, New York 14620 **United States** +(1) 586-546-5373

- · Information department: sds@mgchemicals.com
- · Emergency telephone number:

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA-Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA-Call CANUTEC collect at +1-613-996-6666 or \*666 on cellular phones

#### 2 Hazard identification

#### · Classification of the substance or mixture

Acute Toxicity (Oral) - Category 4 Skin Corrosion - Category 1B

Eye damage/irritation - Category 1

Sensitization - skin - Category 1

Specific target organ toxicity (repeated exposure) -Category 2

Aquatic Acute 1 Aquatic Chronic 1 H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H373 May cause damage to the liver, the immune system and the gastro-intestinal tract through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. (Contd. on page 2)

CA -

Page 1/13



according to WHMIS 2023 and HCS 2024

Date of issue 07/02/2025 Version number 6.02 Revision: 07/02/2025

Trade name: 832FX-B

(Contd. of page 1)

Page 2/13

#### · Label elements

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

#### · Hazard pictograms









GHS05 GHS07 GHS08 GHS09

#### · Signal word Danger

#### · Hazard-determining components of labeling:

polyoxypropylene diamine

Amines, coco alkyl

trimethylhexane-1,6-diamine

#### Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H373 May cause damage to the liver, the immune system and the gastro-intestinal tract through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

#### Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe fumes, mist or vapours.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves, protective clothing, and eye protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES; Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice.

P363 Wash contaminated clothing before reuse.
P391 Collect spillage.
P405 Store locked up.

P501 Dispose of contents and container in accordance with local, regional, and national

regulations.

#### · Other hazards Not available

- CA ---



according to WHMIS 2023 and HCS 2024

Date of issue 07/02/2025 Version number 6.02 Revision: 07/02/2025

Trade name: 832FX-B

(Contd. of page 2)

Page 3/13

### 3 Composition/Information on ingredients

#### · Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
9046-10-0	polyoxypropylene diamine	59% w/w
61788-44-1	phenol, styrenated	20% w/w
25620-58-0	trimethylhexane-1,6-diamine	9% w/w
61788-46-3	Amines, coco alkyl	9% w/w
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	2% w/w

#### 4 First-aid measures

#### Description of first aid measures

#### · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Seek immediate medical advice.

Remove person to fresh air and keep comfortable for breathing.

If feeling unwell: Call a POISON CENTRE or doctor.

#### After skin contact:

Take off immediately all contaminated clothing. Wash with plenty of water or shower.

Immediately call a POISON CENTRE or doctor.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice or attention.

#### · After eye contact:

Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

#### · After swallowing:

Rinse mouth.

Do NOT induce vomiting.

If symptoms persist consult doctor.

#### Information for doctor:

In case of exposure to nitrogen oxides (NOx) combustion products vapors during a fire, the symptoms may be delayed. For significant exposures, the exposed person should be kept under medical surveillance for 48 hours.

#### · Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)



according to WHMIS 2023 and HCS 2024

Date of issue 07/02/2025 Version number 6.02 Revision: 07/02/2025

Trade name: 832FX-B

(Contd. of page 3)

Page 4/13

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
  - Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires. Prevent fire-fighting wash from entering waterway or sewer system.

· Hazardous combustion products:

Carbon Oxides (COx) Nitrogen Oxides (NOx)

- Advice for firefighters
  - · Protective equipment: Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

### 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Do not breathe fumes, mist or vapors.

· Environmental precautions:

Avoid release to the environment.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Use neutralizing agent.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect liquid in a sealable, chemical-resistant container.

Wash residue with a paper towel and place dirty towels in container.

Use soap and water to remove the last traces of residue.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)



## Safety Data Sheet according to WHMIS 2023 and HCS 2024

Date of issue 07/02/2025 Version number 6.02 Revision: 07/02/2025

Trade name: 832FX-B

(Contd. of page 4)

Page 5/13

Prevent formation of aerosols.

Wear protective gloves and eye protection.

Wash hands and exposed skin thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

Collect spillage.

Contaminated work clothing should not be allowed out of the workplace.

Do not breathe mist, vapours, spray.

#### Information about protection against explosions and fires:

Keep respiratory protective device available.

### · Conditions for safe storage, including any incompatibilities

- · Storage:
  - Requirements to be met by storerooms and receptacles:

Keep in a dry and clean area, away from incompatible substances

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store locked up.

Specific end use(s) See section 1.2

### 8 Exposure controls/ Personal protection

#### · Control parameters

#### · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

#### Additional information:

The lists that were valid during the creation were used as basis.

Refer to the national or regional occupational exposure limit regulation for abbreviations and acronyms.

#### · Exposure controls

- · Appropriate engineering controls No further data; see section 7.
- · Personal protective equipment:

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Advice should be sought from respiratory protection specialists.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

(Contd. on page 6)



according to WHMIS 2023 and HCS 2024

Date of issue 07/02/2025 Version number 6.02 Revision: 07/02/2025

Trade name: 832FX-B

(Contd. of page 5)

Page 6/13

#### · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses or tightly sealed goggles: EN 166

### 9 Physical and chemical properties

· Information on basic physical and chemical properties

· Physical state

· Form:

· Color:

· Odor:

Odor threshold:

· Melting point/Melting range:

· Boiling point/Boiling range:

· Flammability:

**Explosion limits:** 

Lower:

· Upper:

· Flash point:

· Auto igniting:

· Decomposition temperature:

· pH-value:

· Viscosity:

Kinematic:

Liquid

Viscous

Amber colored

Ammonia-like

Not determined.

Undetermined.

>230 °C (>446 °F)

Non flammable

Not applicable

Not applicable

>104 °C (>219.2 °F)

Not determined

Not determined.

Not determined.

Not determined.

(Contd. on page 7)



according to WHMIS 2023 and HCS 2024

Date of issue 07/02/2025 Version number 6.02 Revision: 07/02/2025

Trade name: 832FX-B

(Contd. of page 6)

Page 7/13

· Solubility in / Miscibility with

· Water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water):

Not determined. Not determined.

· Vapor pressure:

0.98

· Relative density at 25 °C (77 °F):

Not determined.

Vapor density (air=1):
Particle characteristics

Not applicable.

· Other information

· Important information on protection of health and environment, and on safety.

Ignition temperature:

Product is not selfigniting.

Danger of explosion:

Product does not present an explosion hazard.

· Solvent content:

Not available 0.000 %

· Organic solvents: · VOC content:

0.0 g/l / 0.00 lb/gal

· Solids content:

1.0 %

· Evaporation rate

Not determined.

### 10 Stability and reactivity

· Reactivity Reacts exothermically with epoxide groups.

· Chemical stability Chemically stable at normal temperatures and pressures.

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

\* Conditions to avoid Avoid open flames, excessive heat, sparks, ignition sources, and incompatible substances.

· Incompatible materials:

Strong oxidizing agents

Strong acids

· Hazardous decomposition products:

No dangerous decomposition products known.

Hazardous combustion products: see section 5.

### 11 Toxicological information

- Information on toxicological effects
  - · Acute toxicity:

· LD/LC50 values that are relevant for classification:

**ATE (Acute Toxicity Estimate)** 

Oral LD50 667 mg/kg

(Contd. on page 8)



according to WHMIS 2023 and HCS 2024

Date of issue 07/02/2025 Version number 6.02 Revision: 07/02/2025

Trade name: 832FX-B

(Contd. of page 7)

Page 8/13

9046-	9046-10-0 polyoxypropylene diamine			
Oral	LD50	500 mg/kg (ATE)		
25620-58-0 trimethylhexane-1,6-diamine				
Oral	LD50	900 mg/kg (rat)		
61788-46-3 Amines, coco alkyl				
1 1		500 mg/kg (ATE)		
1	90-72-2 2,4,6-tris(dimethylaminomethyl)phenol			
Oral	LD50	500 mg/kg (ATE)		

#### · Primary irritant effect:

- on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· Sensitization: Sensitization possible through skin contact.

#### · Summary of effects and symptoms by route of exposure

· Eyes:

eye damage, pain redness, serious irritation burns

· Skin:

chemical burns blistering redness, irritation

rash, allergic contact dermatitis

· Inhalation: irritation of the respiratory tract

· Swallowed:

irritation

abdominal pain

burning sensation

nausea, vomiting

## Delayed and immediate effects as well as chronic effects from short and long-term exposure Prolonged and repeated exposure to uncured epoxy hardener may lead to skin sensitization.

#### Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

#### · Carcinogenic categories

#### · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

(Contd. on page 9)



according to WHMIS 2023 and HCS 2024

Date of issue 07/02/2025 Version number 6.02 Revision: 07/02/2025

Trade name: 832FX-B

(Contd. of page 8)

Page 9/13

· NTP (National Toxicology Program)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
  - Aquatic toxicity:

Very toxic to aquatic life with long lasting effect.

Avoid release to the environment.

Collect spillage.

- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Results of PBT and vPvB assessment
  - · PBT: Not applicable.
  - · vPvB: Not applicable.
- · Other adverse effects
  - Remark: Very toxic for fish

### 13 Disposal considerations

- Waste treatment methods
  - Recommendation: This material and its container must be disposed of as hazardous waste.
  - Uncleaned packagings:
    - Recommendation:

Containers may still present a chemical hazard/ danger when empty.

Dispose of contents in accordance with all local, regional, national, and international regulations.

Where possible retain label warnings and SDS and observe all notices pertaining to the product.

### 14 Transport information

· UN-Number

· DOT/TDG, IMDG, IATA UN2735

· UN proper shipping name

DOT/TDG, IATA Amines, liquid, corrosive, n.o.s. (trimethylhexane-1,6-

diamine, polyoxypropylene diamine)

(Contd. on page 10)



according to WHMIS 2023 and HCS 2024

Date of issue 07/02/2025 Version number 6.02 Revision: 07/02/2025

Trade name: 832FX-B

(Contd. of page 9)

Page 10/13

·IMDG

AMINES, LIQUID, CORROSIVE, N.O.S. (trimethylhexane-1,6-diamine, polyoxypropylene diamine)

- · Transport hazard class(es)
  - · DOT/TDG (Transport dangerous goods):



· Class

8 Corrosive substances

· Label

8

· IMDG, IATA



· Class · Label 8 Corrosive substances

8

- · Packing group
  - · DOT/TDG, IMDG, IATA

Ш

· Environmental hazards:

Product contains environmentally hazardous substances:

Amines, coco alkyl

· Marine pollutant:

MARINE POLLUTANT

• Special marking (IATA):

**ENVIRONMENTALLY HAZARDOUS** 

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:



Limited Quantity

832FX-450ML, 832FX-1.7L

· DOT/TDG

· Quantity limitations

On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L

IMDG

· Limited quantities (LQ)

1L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 11)



according to WHMIS 2023 and HCS 2024

Date of issue 07/02/2025 Version number 6.02 Revision: 07/02/2025

Trade name: 832FX-B

(Contd. of page 10)

Page 11/13

· Special precautions for user

Not applicable.

Hazard identification number (Kemler code):

F-A,S-B

· EMS Number:

· Segregation groups

(SGG18) Alkalis

· Stowage Category · Segregation Code

SG35 Stow "separated from" SGG1-acids

UN "Model Regulation":

UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S.

(TRIMETHYLHEXANE-1,6-DIAMINE, POLYOXYPROPYLENE

DIAMINE), 8, II

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
  - · OSHA Hazard Communication Standard (29 CFR Part 1900)

The safety data sheet and label comply with HCS 2024.

· Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2023.

- · Sara
  - · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
  - · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 12)



according to WHMIS 2023 and HCS 2024

Date of issue 07/02/2025 Version number 6.02 Revision: 07/02/2025

Trade name: 832FX-B

(Contd. of page 11)

Page 12/13

#### · Carcinogenic categories

#### · TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

#### · Canadian substance listings:

#### · Canadian Domestic Substances List (DSL)

All ingredients are listed.

#### · Canadian Non-Domestic Substances List (NDSL)

None of the ingredients is listed.

#### · Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

#### · Canadian Ingredient Disclosure list (limit 1%)

25620-58-0 trimethylhexane-1,6-diamine

#### · HMIS-ratings (scale 0 - 4)

Health = \* 3 Fire = 1 Reactivity = 0

#### · Europe

#### · RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

#### · WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

### · Per- and polyfluoroalkyl substances (PFAS)

None of the ingredients is listed.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Regulatory department
- · Contact: sds@mgchemicals.com
- · Version number of previous version: 6.01
- Date of preparation 07/02/2025
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 13)



# Safety Data Sheet according to WHMIS 2023 and HCS 2024

Page 13/13

Date of issue 07/02/2025 Version number 6.02 Revision: 07/02/2025

Trade name: 832FX-B

(Contd. of page 12)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety

CA —