

SPE-T1-STSM-180 - SPE PCB connector



1163798

<https://www.phoenixcontact.com/de/produkte/1163798>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



SPE PCB connector, design: IEC 63171-2, degree of protection: IP20, number of positions: 2, 1 Gbps, CAT B (ISO/IEC 63171), material: Metal, connection method: THR solder connection, cable outlet: straight, Single Pair Ethernet

Your advantages

- Compact design for maximum space savings
- Connectors in accordance with IEC 63171-2
- THR solderable
- Robust industrial design
- 360° shielding
- Data transmission up to 600 MHz

Commercial data

Item number	1163798
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	D1 - Steckverbinder
Product key	ABNBBA
GTIN	4063151174095
Weight per piece (including packing)	4,02 g
Weight per piece (excluding packing)	4,02 g
Customs tariff number	85366990
Country of origin	DE

SPE-T1-STSM-180 - SPE PCB connector



1163798

<https://www.phoenixcontact.com/de/produkte/1163798>

Technical data

Product properties

Type	SPE
Product type	Data connector (device side)
Sensor type	Single Pair Ethernet
Number of positions	2
Type of packaging	Tape and Reel
Connection profile	SPE
Number of slots	1
Type	Socket
Shielded	yes
Cable outlet	straight

Insulation characteristics

Overvoltage category	I
Degree of pollution	2

Electrical properties

Rated voltage (III/2)	72 V DC
Rated surge voltage	2250 V DC
Rated surge voltage (III/2)	1500 V
Rated current	4 A
Frequency range	600 MHz
Insulation resistance	> 1 TΩ
Transmission medium	Copper
Transmission speed	1 Gbps
Power transmission	PoDL

Connection data

Connection technology

Connection method	THR solder connection
-------------------	-----------------------

Dimensions

Width	5 mm
Height	11.4 mm
Length	9.3 mm

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ni/Au
Contact carrier material	LCP
Housing material	Metal

SPE-T1-STSM-180 - SPE PCB connector



1163798

<https://www.phoenixcontact.com/de/produkte/1163798>

Cable/line

Test voltage Core/Core	1000 V DC
Test voltage Core/Shield	2250 V DC
Halogen-free	yes
Resistance to oil	yes
Flame resistance	UL 94 V0

Mechanical properties

Mechanical data

Insertion force per signal contact	< 1.50 N
Extraction force per signal contact	< 1.5 N

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Resistance to oil	yes

Standards and regulations

Flame resistance	UL 94 V0
Resistance to oil	yes

Mounting

Mounting type	THR soldering
Connection method	THR solder connection

Processing notes

Moisture Sensitive Level	MSL 1
--------------------------	-------

SPE-T1-STSM-180 - SPE PCB connector



1163798

<https://www.phoenixcontact.com/de/produkte/1163798>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/de/produkte/1163798>

 cULus Recognized Approval ID: E335024-20220331				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	60 V	1.4 A	-	-

SPE-T1-STSM-180 - SPE PCB connector



1163798

<https://www.phoenixcontact.com/de/produkte/1163798>

Classifications

ECLASS

ECLASS-11.0	27440390
ECLASS-13.0	27440390
ECLASS-12.0	27440390

ETIM

ETIM 8.0	EC001121
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SPE-T1-STSM-180 - SPE PCB connector



1163798

<https://www.phoenixcontact.com/de/produkte/1163798>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

SPE-T1-STSM-180 - SPE PCB connector



1163798

<https://www.phoenixcontact.com/de/produkte/1163798>

Accessories

SPE-T1-CCP-SF/1,0/AWG22/CCP-SF - Patch cable

1183807

<https://www.phoenixcontact.com/de/produkte/1183807>



Patch cable, design: IEC 63171-2, degree of protection: IP20, cable length: 1 m, number of positions: 2, 1 Gbps, CAT B, material: TPU, connection method: Crimp connection, connection cross section: AWG 22- 22, cable outlet: straight, Single Pair Ethernet

SPE-T1-CCP-SF/2,0/AWG22/CCP-SF - Patch cable

1183808

<https://www.phoenixcontact.com/de/produkte/1183808>



Patch cable, design: IEC 63171-2, degree of protection: IP20, cable length: 2 m, number of positions: 2, 1 Gbps, CAT B, material: TPU, connection method: Crimp connection, connection cross section: AWG 22- 22, cable outlet: straight, Single Pair Ethernet

SPE-T1-STSM-180 - SPE PCB connector



1163798

<https://www.phoenixcontact.com/de/produkte/1163798>

SPE-T1-CCP-SF/3,0/AWG22/CCP-SF - Patch cable

1183810

<https://www.phoenixcontact.com/de/produkte/1183810>



Patch cable, design: IEC 63171-2, degree of protection: IP20, cable length: 3 m, number of positions: 2, 1 Gbps, CAT B, material: TPU, connection method: Crimp connection, connection cross section: AWG 22- 22, cable outlet: straight, Single Pair Ethernet

SPE-T1-CCP-SF/5,0/AWG22/CCP-SF - Patch cable

1183811

<https://www.phoenixcontact.com/de/produkte/1183811>



Patch cable, design: IEC 63171-2, degree of protection: IP20, cable length: 5 m, number of positions: 2, 1 Gbps, CAT B, material: TPU, connection method: Crimp connection, connection cross section: AWG 22- 22, cable outlet: straight, Single Pair Ethernet

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstraße 8
D-32825 Blomberg
+49 52 35/3-1 20 00
info@phoenixcontact.de