

VS-SCRJ-GOF-KU - Fiber optic coupling



1654358

<https://www.phoenixcontact.com/pc/products/1654358>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



SC-RJ coupling insert, duplex, for VS-PP-19-1HE-16-F patch panel, VS-TO...F... terminal outlets, and VS-SI-FP-2F front plate, can be used for GOF (multi-mode and single mode), HCS, and polymer fiber types

Your advantages

- High reliability with comprehensive quality assurance measures
- Optimized precision (stability) with the use of ceramic sleeves
- Future-proof with RoHS 2 conformity
- Tailored for compatibility with the DIN rail adapters

Commercial Data

Item number	1654358
Packing unit	1 pc
Minimum order quantity	1 pc
Product Key	ABNACG
Catalog Page	Page 380 (C-2-2019)
GTIN	4017918970635
Weight per Piece (including packing)	8.7 g
Weight per Piece (excluding packing)	8.7 g
Customs tariff number	39269097
Country of origin	CH

VS-SCRJ-GOF-KU - Fiber optic coupling



1654358

<https://www.phoenixcontact.com/pc/products/1654358>

Technical Data

Product properties

Type	SCRJ
Product type	Female insert
Number of positions	2
Connection profile	SCRJ
Number of module slots	1
Number of slots	2
Type	Socket
Cable outlet	straight

Electrical properties

Transmission medium	FO
---------------------	----

Connection data

Connection technology

Connection method	Coupling
-------------------	----------

Dimensions

Mechanical characteristics

Ferrule diameter	2.50 mm
------------------	---------

Material specifications

Color	black
Color of the housing part	black
Flammability rating according to UL 94	V0
Ferrule material	Zirconia ceramics
Contact material	Copper alloy
Housing material	Plastic

Cable/line

Cable type	Fiberglass
External sheath, color	silver-colored
Tensile strength short-term/long-term	40 N
Resistance to oil	no

FO cable

Number of fibers	2
Fiber	POF, PCF, GOF
Fiber type	GOF, PCF, POF
Attenuation	≤ 0.2 dB
Transmission medium	FO

VS-SCRJ-GOF-KU - Fiber optic coupling



1654358

<https://www.phoenixcontact.com/pc/products/1654358>

Mechanical properties

Tensile strength short-term/long-term	40 N
---------------------------------------	------

Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
	IP20
Ambient temperature (operation)	-25 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Ambient temperature (assembly)	-5 °C ... 50 °C
Ambient temperature (installation)	-40 °C ... 85 °C
Resistance to UV radiation	no
Resistance to oil	no

Standards and regulations

Resistance to UV radiation	no
Resistance to oil	no

VS-SCRJ-GOF-KU - Fiber optic coupling

1654358

<https://www.phoenixcontact.com/pc/products/1654358>



Approvals



EAC

Approval ID: B.01687

VS-SCRJ-GOF-KU - Fiber optic coupling



1654358

<https://www.phoenixcontact.com/pc/products/1654358>

Classifications

ECLASS

ECLASS-9.0	19170122
ECLASS-10.0.1	19170122
ECLASS-11.0	19170122

ETIM

ETIM 8.0	EC001122
----------	----------

UNSPSC

UNSPSC 21.0	43223300
-------------	----------

VS-SCRJ-GOF-KU - Fiber optic coupling



1654358

<https://www.phoenixcontact.com/pc/products/1654358>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

VS-SCRJ-GOF-KU - Fiber optic coupling

1654358

<https://www.phoenixcontact.com/pc/products/1654358>



Accessories

VS-PP-19-1HE-16-F - Marshalling panel

1652994

<https://www.phoenixcontact.com/pc/products/1652994>

Patch panel, 19" assembly, IP20, with 16 slots for contact inserts with the Freenet system



VS-SI-FP-2F - Front plate

1658532

<https://www.phoenixcontact.com/pc/products/1658532>

Front plate, plastic, with two Freenet slots



Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com