

## Printed-circuit board connector - MSTB 2,5/ 3-ST (13) - 1756764

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB connector, nominal current: 12 A, number of positions: 3, pitch: 5 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Tin



The figure shows a 10-pos. version of the product in green

### Why buy this product

- ✓ Well-known connection principle allows worldwide use
- ✓ Low temperature rise, thanks to maximum contact force
- ✓ Allows connection of two conductors



### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 50 STK                                                                                                  |
| GTIN         | <br>4 017918 213862 |
| GTIN         | 4017918213862                                                                                           |

### Technical data

#### Dimensions

|             |       |
|-------------|-------|
| Pitch       | 5 mm  |
| Dimension a | 10 mm |

#### General

|                                  |                                      |
|----------------------------------|--------------------------------------|
| Range of articles                | MSTB 2,5/..-ST                       |
| Type of contact                  | Female connector                     |
| Number of positions              | 3                                    |
| Connection method                | Screw connection with tension sleeve |
| Rated voltage (III/3)            | 250 V                                |
| Connection in acc. with standard | EN-VDE                               |
| Nominal current $I_N$            | 12 A                                 |
| Nominal cross section            | 2.5 mm <sup>2</sup>                  |

# Printed-circuit board connector - MSTB 2,5/ 3-ST (13) - 1756764

## Technical data

### Connection data

|                                                                                         |                      |
|-----------------------------------------------------------------------------------------|----------------------|
| Conductor cross section solid min.                                                      | 0.2 mm <sup>2</sup>  |
| Conductor cross section solid max.                                                      | 2.5 mm <sup>2</sup>  |
| Conductor cross section flexible min.                                                   | 0.2 mm <sup>2</sup>  |
| Conductor cross section flexible max.                                                   | 2.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule without plastic sleeve min.              | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max.              | 2.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve min.                 | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.                 | 2.5 mm <sup>2</sup>  |
| Conductor cross section AWG min.                                                        | 24                   |
| Conductor cross section AWG max.                                                        | 12                   |
| 2 conductors with same cross section, solid min.                                        | 0.2 mm <sup>2</sup>  |
| 2 conductors with same cross section, solid max.                                        | 1 mm <sup>2</sup>    |
| 2 conductors with same cross section, stranded min.                                     | 0.2 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded max.                                     | 1.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.   | 0.25 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.   | 1 mm <sup>2</sup>    |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 1.5 mm <sup>2</sup>  |
| Minimum AWG according to UL/CUL                                                         | 30                   |
| Maximum AWG according to UL/CUL                                                         | 12                   |

### Standards and Regulations

|                                  |        |
|----------------------------------|--------|
| Connection in acc. with standard | EN-VDE |
|                                  | CSA    |

### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Approvals

### Approvals

#### Approvals

CSA / VDE Gutachten mit Fertigungsüberwachung / IECCEB Scheme / cULus Recognized / EAC

#### Ex Approvals

## Printed-circuit board connector - MSTB 2,5/ 3-ST (13) - 1756764

### Approvals

#### Approval details

|                                |                                                                                   |                                                                                                                                         |                 |
|--------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| CSA                            |  | <a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a> | LR13631-2585950 |
|                                | B                                                                                 | D                                                                                                                                       |                 |
| mm <sup>2</sup> /AWG/kcmil     | 28-12                                                                             | 28-12                                                                                                                                   |                 |
| Nominal current I <sub>N</sub> | 15 A                                                                              | 15 A                                                                                                                                    |                 |
| Nominal voltage U <sub>N</sub> | 300 V                                                                             | 300 V                                                                                                                                   |                 |

|                                            |                                                                                   |                                                                                                                                                                                                                |          |
|--------------------------------------------|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| VDE Gutachten mit<br>Fertigungsüberwachung |  | <a href="http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx">http://www2.vde.com/de/Institut/Online-Service/<br/>VDE-gepruefteProdukte/Seiten/Online-Suche.aspx</a> | 40004701 |
|                                            |                                                                                   |                                                                                                                                                                                                                |          |
| mm <sup>2</sup> /AWG/kcmil                 | 0.2-2.5                                                                           |                                                                                                                                                                                                                |          |
| Nominal current I <sub>N</sub>             | 12 A                                                                              |                                                                                                                                                                                                                |          |
| Nominal voltage U <sub>N</sub>             | 250 V                                                                             |                                                                                                                                                                                                                |          |

|                                |                                                                                     |                                                           |                |
|--------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|----------------|
| IECEE CB Scheme                |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | DE1-58978-B1B2 |
|                                |                                                                                     |                                                           |                |
| mm <sup>2</sup> /AWG/kcmil     | 0.2-2.5                                                                             |                                                           |                |
| Nominal current I <sub>N</sub> | 12 A                                                                                |                                                           |                |
| Nominal voltage U <sub>N</sub> | 250 V                                                                               |                                                           |                |

|                                |                                                                                     |                                                                                                                                                       |                 |
|--------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| cULus Recognized               |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-19931011 |
|                                | B                                                                                   | D                                                                                                                                                     |                 |
| mm <sup>2</sup> /AWG/kcmil     | 30-12                                                                               | 30-12                                                                                                                                                 |                 |
| Nominal current I <sub>N</sub> | 15 A                                                                                | 15 A                                                                                                                                                  |                 |
| Nominal voltage U <sub>N</sub> | 300 V                                                                               | 150 V                                                                                                                                                 |                 |

|     |                                                                                     |         |
|-----|-------------------------------------------------------------------------------------|---------|
| EAC |  | B.01742 |
|-----|-------------------------------------------------------------------------------------|---------|

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>