

Ferrule - A 50 -40

3241240

<https://www.phoenixcontact.com/pc/products/3241240>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Ferrule, length: 40 mm, color: silver

Commercial Data

Item number	3241240
Packing unit	100 pc
Minimum order quantity	1 pc
Product Key	BH3412
Catalog Page	Page 480 (C-3-2019)
GTIN	4046356908139
Weight per Piece (including packing)	3.63 g
Weight per Piece (excluding packing)	3.63 g
Customs tariff number	85369010
Country of origin	DE

Ferrule - A 50 -40

3241240

<https://www.phoenixcontact.com/pc/products/3241240>



Technical Data

Notes

General	These ferrules are not included in DIN 46228-1: 1992-08
---------	---

Product properties


Product type	Ferrule
Conductor category	stranded conductors, class 2, 5, 6 / B, C, K, M

Connection data

Conductor connection

Conductor cross section flexible max.	50 mm ²
Conductor cross section AWG max.	1/0
Stripping length	40 mm

Dimensions

Dimensional drawing	
Length	40 mm
Maximum stripping length	40 mm
Ferrule diameter	10.3 mm
Sleeve wall thickness	0.3 mm
Inner dimensions of the insulating collar	13 mm

Material specifications

Color	silver
Material	CU-DHP
Coating	tin-plated (galvanic)

Environmental and real-life conditions

Ambient conditions

Permanent temperature	105 °C
Short-term temperature	120 °C

Ferrule - A 50 -40


3241240

<https://www.phoenixcontact.com/pc/products/3241240>



Drawings

Dimensional drawing



Sleeve length (b), insulating collar inner dimension (d), sleeve diameter (k), sleeve wall thickness (j)

Ferrule - A 50 -40

3241240

<https://www.phoenixcontact.com/pc/products/3241240>



Classifications

ECLASS

ECLASS-9.0	27400201
ECLASS-10.0.1	27400201
ECLASS-11.0	27400201

ETIM

ETIM 8.0	EC000005
----------	----------

UNSPSC

UNSPSC 21.0	27121700
-------------	----------

Ferrule - A 50 -40

3241240
<https://www.phoenixcontact.com/pc/products/3241240>



Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Ferrule - A 50 -40

3241240

<https://www.phoenixcontact.com/pc/products/3241240>



Accessories

Crimping pliers

Crimping pliers - CRIMPFOX 50R - 1212041

<https://www.phoenixcontact.com/pc/products/1212041>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 35 mm² ... 50 mm², lateral entry, WM crimp

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com