



TELEPHONE/AUDIO/VIDEO **Pomona**[®]

ELECTRONICS



2014EDGE CATALOG

1166-36-2# – ALLIG CL; BANANA PLUG (RED)



ALLIG CL; BANANA PLUG (RED)

Pomona Electronics

ALLIG CL; BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
1166-36-2#	N-A	500



DBL BANANA; SHIELDED LINE

Pomona Electronics

Miniature Banana Plug, 20 AWG Wire Size, 41 x 36 Stranding, 3000 VDC Voltage Rating Rating: 1000 V RMS, +55°C (+131°F) max. Cable Type: Two conductor shielded twisted pair, 0.231" O.D. Features Cable Is Ideal in Audio Applications Where a Low Impedance Shielded Balance Line Is Desired

Part Number	Weight	Min. Quantity
1167-48	0.07	2



DBL BANANA; SHIELDED LINE

Pomona Electronics

Miniature Banana Plug, 20 AWG Wire Size, 41 x 36 Stranding, 3000 VDC Voltage Rating Rating: 1000 V RMS, +55°C (+131°F) max. Cable Type: Two conductor shielded twisted pair, 0.231" O.D. Features Cable Is Ideal in Audio Applications Where a Low Impedance Shielded Balance Line Is Desired

Part Number	Weight	Min. Quantity
1167-18	0.145	2



RET. B-PLUG; DIY; BLK

Pomona Electronics

Retractable Sheath Banana Plug, Lucel Acetal Polymer Insulation Ideal for creating a special patch cord length Retractable sheath banana plug use in sheathed and non-sheathed style of banana jacks.

Part Number	Weight	Min. Quantity
122505A	0.02	5



DBL BANANA; SHIELDED LINE

Pomona Electronics

Miniature Banana Plug, 20 AWG Wire Size, 41 x 36 Stranding, 3000 VDC Voltage Rating Rating: 1000 V RMS, +55°C (+131°F) max. Cable Type: Two conductor shielded twisted pair, 0.231" O.D. Features Cable Is Ideal in Audio Applications Where a Low Impedance Shielded Balance Line Is Desired

Part Number	Weight	Min. Quantity
1167-24	0.07	2



RET. B-PLUG; DIY; BLK

Pomona Electronics

RET. B-PLUG; DIY; BLK

Part Number	Weight	Min. Quantity
122505A#	N-A	500



DBL BANANA; SHIELDED LINE

Pomona Electronics

Miniature Banana Plug, 20 AWG Wire Size, 41 x 36 Stranding, 3000 VDC Voltage Rating Rating: 1000 V RMS, +55°C (+131°F) max. Cable Type: Two conductor shielded twisted pair, 0.231" O.D. Features Cable Is Ideal in Audio Applications Where a Low Impedance Shielded Balance Line Is Desired

Part Number	Weight	Min. Quantity
1167-30	0.175	2



RET. B-PLUG; DIY; RED

Pomona Electronics

Retractable Sheath Banana Plug, Lucel Acetal Polymer Insulation Ideal for creating a special patch cord length Retractable sheath banana plug use in sheathed and non-sheathed style of banana jacks.

Part Number	Weight	Min. Quantity
122506A	0.01	5



DBL BANANA; SHIELDED LINE

Pomona Electronics

Miniature Banana Plug, 20 AWG Wire Size, 41 x 36 Stranding, 3000 VDC Voltage Rating Rating: 1000 V RMS, +55°C (+131°F) max. Cable Type: Two conductor shielded twisted pair, 0.231" O.D. Features Cable Is Ideal in Audio Applications Where a Low Impedance Shielded Balance Line Is Desired

Part Number	Weight	Min. Quantity
1167-36	0.09	2



RET. B-PLUG; DIY; RED

Pomona Electronics

RET. B-PLUG; DIY; RED

Part Number	Weight	Min. Quantity
122506A#	N-A	500



JAN ELECTRONIC SUPPLIES, INC.

860-442-4386

1325-2 – BANANA PLUG; SOLDERLESS; 10 PCS; RE...

**DBL BANANA/BNC (F)**

Pomona Electronics

DBL BANANA/BNC (F)

Part Number	Weight	Min. Quantity
1269#	N-A	500

**ADAPTER;BNC(F);PHONO PLUG; BULK PAC...**

Pomona Electronics

ADAPTER;BNC(F);PHONO PLUG; BULK PACKAGED

Part Number	Weight	Min. Quantity
1297#	N-A	500

**ADAPTER;BNC(M);BANANA PLUG**

Pomona Electronics

ADAPTER;BNC(M);BANANA PLUG

Part Number	Weight	Min. Quantity
1270#	N-A	500

**BANANA PLUG; SOLDERLESS; 10 PCS; BL...**

Pomona Electronics

Standard Banana Jacks, Solderless and Stackable, 5000 VRMS, 15 A, +122 &deg;F Jack, Standard Banana Jack, Solderless and Stackable, 15 Amps, Black

Part Number	Weight	Min. Quantity
1325-0	0.145	1

**DBL BIND POST/BANANA PLUG**

Pomona Electronics

Double Banana Plug, 15 A (Max.) Current Rating, 2500 VDC Voltage Rating Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access p

Part Number	Weight	Min. Quantity
1286	0.02	5

**BANANA PLUG (BLACK)**

Pomona Electronics

BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
1325-0#	N-A	500

**DBL BIND POST/BANANA PLUG**

Pomona Electronics

DBL BIND POST/BANANA PLUG

Part Number	Weight	Min. Quantity
1286#_BULK	N-A	500

**BANANA PLUG (BROWN)**

Pomona Electronics

BANANA PLUG (BROWN)

Part Number	Weight	Min. Quantity
1325-1#	N-A	500

**ADAPTER;BNC(F);PHONO PLUG**

Pomona Electronics

500 V (RMS) Operating Voltage, BNC (Female) To Standard 1&frac4; Two Conductor Phone Plug Type 5319. Nickel-plated contact. Rating: 500 V RMS, +257&deg;F (+125&deg;C) Max. Convert 2 Conductor Audio Jacks to BNC

Part Number	Weight	Min. Quantity
1297	0.5	5

**BANANA PLUG; SOLDERLESS; 10 PCS; RE...**

Pomona Electronics

Standard Banana Jacks, Solderless and Stackable, 5000 VRMS, 15 A, +122 &deg;F Jack, Standard Banana Jack, Solderless and Stackable, 15 Amps, Red

Part Number	Weight	Min. Quantity
1325-2	0.145	1



1325-2# – BANANA PLUG (RED)

**BANANA PLUG (RED)**

Pomona Electronics

BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
1325-2#	N-A	500

**BANANA PLUG BULK PACK (VIOLET)**

Pomona Electronics

BANANA PLUG BULK PACK (VIOLET)

Part Number	Weight	Min. Quantity
1325-7#	N-A	500

**BANANA PLUG (ORANGE)**

Pomona Electronics

BANANA PLUG (ORANGE)

Part Number	Weight	Min. Quantity
1325-3#	N-A	500

**BANANA PLUG (GRAY)**

Pomona Electronics

BANANA PLUG (GRAY)

Part Number	Weight	Min. Quantity
1325-8#	N-A	500

**BANANA PLUG; MTO BULK; (YELLOW)**

Pomona Electronics

BANANA PLUG; MTO BULK; (YELLOW)

Part Number	Weight	Min. Quantity
1325-4#	N-A	500

**BANANA PLUG BULK PACK (WHITE)**

Pomona Electronics

BANANA PLUG BULK PACK (WHITE)

Part Number	Weight	Min. Quantity
1325-9#	N-A	500

**BANANA PLUG (GREEN) BULK PACK**

Pomona Electronics

BANANA PLUG (GREEN) BULK PACK

Part Number	Weight	Min. Quantity
1325-5#	N-A	500

**DOUBLE BANANA PLUG (BLACK)**

Pomona Electronics

Double banana jack — 4.22 mm (0.166) dia., brass, nickel-plated. Double banana plug, spring — One piece heat treated beryllium copper, nickel-plated. Fits standard 4.22 mm (0.166) dia. banana jack. Setscrews secure leads. Features recess for mounting small components. ABS Insulation.

Part Number	Weight	Min. Quantity
1330-0	0.035	5

**BANANA PLUG (BLUE)**

Pomona Electronics

BANANA PLUG (BLUE)

Part Number	Weight	Min. Quantity
1325-6#	N-A	500

**DOUBLE BANANA PLUG (BLACK)**

Pomona Electronics

DOUBLE BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
1330-0#	N-A	500



1442 – DBL BANANA/PHONO JACK

**DOUBLE BANANA PLUG (RED)****Pomona Electronics**

Double banana jack — 4.22 mm (0.166) dia., brass, nickel-plated. Double banana plug, spring — One piece heat treated beryllium copper, nickel-plated. Fits standard 4.22 mm (0.166) dia. banana jack. Setscrews secure leads. Features recess for mounting small components. ABS Insulation.

Part Number	Weight	Min. Quantity
1330-2	0.035	5

**DOUBLE BANANA PLUG WITH SOLDER TURR...****Pomona Electronics**

DOUBLE BANANA PLUG WITH SOLDER TURRETS; RED

Part Number	Weight	Min. Quantity
1330-ST-2	0.035	5

**DOUBLE BANANA PLUG WITH SOLDER TURR...****Pomona Electronics**

DOUBLE BANANA PLUG WITH SOLDER TURRETS; YELLOW

Part Number	Weight	Min. Quantity
1330-ST-4	N-A	100

**BANANA PLUG/JACK; ISOL (BLACK)****Pomona Electronics**

Part Number	Weight	Min. Quantity
1390-0	0.01	5

**BANANA PLUG/JACK; ISOL (RED)****Pomona Electronics**

BANANA PLUG/JACK; ISOL (RED)

Part Number	Weight	Min. Quantity
1390-2	0.03	5

**B-JACK/PIN TIP 10/PKG (BLACK)****Pomona Electronics**

Brass Rod Per ASTM B16-85, Temper H02 Body, Connector Banana Jack To Pin Tip Plug Permits standard banana plug patch cords to be used with equipment having tip jacks. Cross hole 4.22 mm (0.166) dia. provides side stackup connection. Upper: Banana jack. 4.22 mm (0.166) dia. brass, nickel-plated. Insu

Part Number	Weight	Min. Quantity
1432-0	0.115	1

**B-JACK/PIN TIP (BLACK)****Pomona Electronics**

B-JACK/PIN TIP (BLACK)

Part Number	Weight	Min. Quantity
1432-0#	N-A	500

**B-JACK/PIN TIP 10/PKG (RED)****Pomona Electronics**

Brass Rod Per ASTM B16-85, Temper H02 Body, Connector Banana Jack To Pin Tip Plug Permits standard banana plug patch cords to be used with equipment having tip jacks. Cross hole 4.22 mm (0.166) dia. provides side stackup connection. Upper: Banana jack. 4.22 mm (0.166) dia. brass, nickel-plated. Insu

Part Number	Weight	Min. Quantity
1432-2	0.114	1

**B-JACK/PIN TIP (RED)****Pomona Electronics**

B-JACK/PIN TIP (RED)

Part Number	Weight	Min. Quantity
1432-2#	N-A	500

**DBL BANANA/PHONO JACK****Pomona Electronics**

Phono Jack To Double Banana Plug, 500 VDC Operating Voltage, Adapter Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access pane

Part Number	Weight	Min. Quantity
1442	0.5	5

1581-0 – B-JACK; TIN PL 10/PKG (BLACK)

**B-JACK; TIN PL 10/PKG (BLACK)****Pomona Electronics**

+115°C (Max.) Operating Temperature, 30 VAC⁄60 VDC (Max.), Panel Mount Banana Jack Mounts in panels from 1.60 mm (0.063) to 9.53 mm (0.375) thick. Nickel plated lockwasher and 1⁄4-32 hex nut. Material: Brass. Rating: 2500 WVDC, 15 amps, +1

Part Number	Weight	Min. Quantity
1581-0	0.121	1

**B-JACK; TIN PL (BLACK)****Pomona Electronics**

B-JACK; TIN PL (BLACK)

Part Number	Weight	Min. Quantity
1581-0#	11.5	500

**B-JACK; TIN PL (RED)****Pomona Electronics**

B-JACK; TIN PL (RED)

Part Number	Weight	Min. Quantity
1581-2#	N-A	500

**B-JACK; TIN PL 10/PKG (ORANGE)****Pomona Electronics**

Connector, 15 A Current Rating, Brass Body Material, Polycarbonate Insulation Material Maximum operating temperature +115 °C Jack mounting type panel, polycarbonate insulation material.

Part Number	Weight	Min. Quantity
1581-3	0.125	1

**BANANA JACK; TIN PL (SET)****Pomona Electronics**

BANANA JACK; TIN PL (SET)

Part Number	Weight	Min. Quantity
1581-02	0.03	5

**B-JACK, TIN PLATED (ORANGE)****Pomona Electronics**

B-JACK, TIN PLATED (ORANGE)

Part Number	Weight	Min. Quantity
1581-3#_BULK	N-A	500

**B-JACK; TIN PL 10/PKG (BROWN)****Pomona Electronics**

Connector, 15 A Current Rating, Brass Body Material, Polycarbonate Insulation Material Maximum operating temperature +115 °C Jack mounting type panel, polycarbonate insulation material.

Part Number	Weight	Min. Quantity
1581-1	0.5	1

**B-JACK; TIN PL 10/PKG (YELLOW)****Pomona Electronics**

+115°C (Max.) Operating Temperature, 30 VAC⁄60 VDC (Max.), Panel Mount Banana Jack Mounts in panels from 1.60 mm (0.063) to 9.53 mm (0.375) thick. Nickel plated lockwasher and 1⁄4-32 hex nut. Material: Brass. Rating: 2500 WVDC, 15 amps, +1

Part Number	Weight	Min. Quantity
1581-4	0.123	1

**B-JACK; TIN PL 10/PKG (RED)****Pomona Electronics**

+115°C (Max.) Operating Temperature, 30 VAC⁄60 VDC (Max.), Panel Mount Banana Jack Mounts in panels from 1.60 mm (0.063) to 9.53 mm (0.375) thick. Nickel plated lockwasher and 1⁄4-32 hex nut. Material: Brass. Rating: 2500 WVDC, 15 amps, +1

Part Number	Weight	Min. Quantity
1581-2	0.125	1

**B-JACK; TIN PL 10/PKG (GREEN)****Pomona Electronics**

+115°C (Max.) Operating Temperature, 30 VAC⁄60 VDC (Max.), Panel Mount Banana Jack Mounts in panels from 1.60 mm (0.063) to 9.53 mm (0.375) thick. Nickel plated lockwasher and 1⁄4-32 hex nut. Material: Brass. Rating: 2500 WVDC, 15 amps, +1

Part Number	Weight	Min. Quantity
1581-5	0.121	1



1614A-2 – INSULATED SPADE LUG/JACK (RED)

**B-JACK; TIN PL (GREEN)**

Pomona Electronics

B-JACK; TIN PL (GREEN)

Part Number	Weight	Min. Quantity
1581-5#	N-A	500

**B-JACK; TIN PL (GRAY)**

Pomona Electronics

B-JACK; TIN PL (GRAY)

Part Number	Weight	Min. Quantity
1581-8#	N-A	500

**B-JACK; TIN PL 10/PKG (BLUE)**

Pomona Electronics

+115°C (Max.) Operating Temperature, 30 VAC⁄60 VDC (Max.), Panel Mount Banana Jack Mounts in panels from 1.60 mm (0.063) to 9.53 mm (0.375) thick. Nickel plated lockwasher and 1⁄4-32 hex nut. Material: Brass. Rating: 2500 WVDC, 15 amps, +1

Part Number	Weight	Min. Quantity
1581-6	N-A	1

**B-JACK; TIN PL 10/PKG (WHITE)**

Pomona Electronics

+115°C (Max.) Operating Temperature, 30 VAC⁄60 VDC (Max.), Panel Mount Banana Jack Mounts in panels from 1.60 mm (0.063) to 9.53 mm (0.375) thick. Nickel plated lockwasher and 1⁄4-32 hex nut. Material: Brass. Rating: 2500 WVDC, 15 amps, +1

Part Number	Weight	Min. Quantity
1581-9	0.125	1

**B-JACK; TIN PL (BLUE)**

Pomona Electronics

B-JACK; TIN PL (BLUE)

Part Number	Weight	Min. Quantity
1581-6#	N-A	500

**B-JACK; TIN PL (WHITE)**

Pomona Electronics

B-JACK; TIN PL (WHITE)

Part Number	Weight	Min. Quantity
1581-9#	N-A	500

**B-JACK; TIN PL 10/PKG (VIOLET)**

Pomona Electronics

Connector, 15 A Current Rating, Brass Body Material, Polycarbonate Insulation Material Maximum operating temperature +115 °C Jack mounting type panel, polycarbonate insulation material.

Part Number	Weight	Min. Quantity
1581-7	0.125	1

**INSULATED SPADE LUG/JACK (BLK)**

Pomona Electronics

Spade Lug to Insulated Banana Jack, 1.86 in. Length, Nylon Insulation Material Ideal for use with binding posts Compatible with any Pomona banana plug or equivalent Has a shrouded jack for use with any shrouded DMM plug Jack outer diameter 0.46 in.

Part Number	Weight	Min. Quantity
1614A-0	0.164	5

**B-JACK; TIN PL 10/PKG (GRAY)**

Pomona Electronics

Connector, 15 A Current Rating, Brass Body Material, Polycarbonate Insulation Material Maximum operating temperature +115 °C Jack mounting type panel, polycarbonate insulation material.

Part Number	Weight	Min. Quantity
1581-8	0.125	1

**INSULATED SPADE LUG/JACK (RED)**

Pomona Electronics

Spade Lug to Insulated Banana Jack, 1.86 in. Length, Nylon Insulation Material Ideal for use with binding posts Compatible with any Pomona banana plug or equivalent Has a shrouded jack for use with any shrouded DMM plug Jack outer diameter 0.46 in.

Part Number	Weight	Min. Quantity
1614A-2	0.016	5



1693-36-0 – MICROVOLT SPADE LUGS (BLACK)

**MICROVOLT SPADE LUGS (BLACK)****Pomona Electronics**

Spade Lug Patch Cord For Low Voltage Measurements, 12 AWG, 2000 VRMS⁄VDC, 20 A Special alloy plating and construction preserve the accuracy of micro-volt and nano-volt measurement equipment. Designed to greatly minimize the effect of Thermal Electric Voltage (Thermal EMF). Thermal EMF is gener

Part Number	Weight	Min. Quantity
1693-36-0	0.1	5

**MICROVOLT SPADE LUGS (RED)****Pomona Electronics**

Spade Lug Patch Cord For Low Voltage Measurements, 12 AWG, 2000 VRMS⁄VDC, 20 A Special alloy plating and construction preserve the accuracy of micro-volt and nano-volt measurement equipment. Designed to greatly minimize the effect of Thermal Electric Voltage (Thermal EMF). Thermal EMF is gener

Part Number	Weight	Min. Quantity
1693-36-2	0.092	5

**MICROVOLT SPADE LUGS ;RED****Pomona Electronics**

MICROVOLT SPADE LUGS ;RED

Part Number	Weight	Min. Quantity
1693-6-2	N-A	24

**MICROVOLT SPADE LUGS (BLACK)****Pomona Electronics**

Spade Lug Patch Cord For Low Voltage Measurements, 12 AWG, 2000 VRMS⁄VDC, 20 A Special alloy plating and construction preserve the accuracy of micro-volt and nano-volt measurement equipment. Designed to greatly minimize the effect of Thermal Electric Voltage (Thermal EMF). Thermal EMF is gener

Part Number	Weight	Min. Quantity
1693-60-0	0.155	5

**MICROVOLT SPADE LUGS (RED)****Pomona Electronics**

Spade Lug Patch Cord For Low Voltage Measurements, 12 AWG, 2000 VRMS⁄VDC, 20 A Special alloy plating and construction preserve the accuracy of micro-volt and nano-volt measurement equipment. Designed to greatly minimize the effect of Thermal Electric Voltage (Thermal EMF). Thermal EMF is gener

Part Number	Weight	Min. Quantity
1693-60-2	0.5	5

**MICROVOLT SPADE LUG; SHIELDED****Pomona Electronics**

Shielded Low Voltage Spade Lug Patch Cord, 12 AWG, 2000 VRMS⁄VDC, 20 A Special alloy plating and construction preserve the accuracy of micro-volt and nano-volt measurement equipment. Designed to greatly minimize the effect of Thermal Electric Voltage (Thermal EMF). Thermal EMF is generated at

Part Number	Weight	Min. Quantity
1756-24	0.15	5

**MICROVOLT SPADE LUG; SHIELDED****Pomona Electronics**

Shielded Low Voltage Spade Lug Patch Cord, 12 AWG, 2000 VRMS⁄VDC, 20 A Special alloy plating and construction preserve the accuracy of micro-volt and nano-volt measurement equipment. Designed to greatly minimize the effect of Thermal Electric Voltage (Thermal EMF). Thermal EMF is generated at

Part Number	Weight	Min. Quantity
1756-48	0.249	5

**PIN TIP JACK/BANANA PLUG 10/PK (BLA...****Pomona Electronics**

Pin Jack to Banana Plug Connector, 2500 WVDC Voltage Rating, Beryllium Copper Spring Material Permits pin tip cords to be used with equipment having banana jacks Brass plug body material. 5 A current rating.

Part Number	Weight	Min. Quantity
1809-0	0.155	1

**PIN TIP JACK/BANANA PLUG 10/PK (RED...****Pomona Electronics**

Pin Jack to Banana Plug Connector, 2500 WVDC Voltage Rating, Beryllium Copper Spring Material Permits pin tip cords to be used with equipment having banana jacks Brass plug body material. 5 A current rating.

Part Number	Weight	Min. Quantity
1809-2	0.155	1

**DBL BANANA SPLICE (BLACK)****Pomona Electronics**

Double Banana Plug Splice Connector, 15 A Current Rating Provides rapid method for splicing cables Reduces necessity of storing extra long cables The voltage rating is 5000 VDC.

Part Number	Weight	Min. Quantity
1823-0	0.035	5

1825-8# – BANANA PLUG (GRAY)

**DBL BANANA SPLICE (RED)**

Pomona Electronics

Part Number	Weight	Min. Quantity
1823-2	0.035	5

**BANANA PLUG (YELLOW)**

Pomona Electronics

BANANA PLUG (YELLOW)

Part Number	Weight	Min. Quantity
1825-4#	N-A	500

**BANANA PLUG (BLACK)**

Pomona Electronics

BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
1825-0#	N-A	500

**BANANA PLUG (GREEN)**

Pomona Electronics

BANANA PLUG (GREEN)

Part Number	Weight	Min. Quantity
1825-5#	N-A	500

**BANANA PLUG (BROWN)**

Pomona Electronics

BANANA PLUG (BROWN)

Part Number	Weight	Min. Quantity
1825-1#	N-A	500

**BANANA PLUG PKG (BLUE)**

Pomona Electronics

BANANA PLUG PKG (BLUE)

Part Number	Weight	Min. Quantity
1825-6#	N-A	500

**BANANA PLUG (RED)**

Pomona Electronics

BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
1825-2#	N-A	500

**BANANA PLUG (VIOLET)**

Pomona Electronics

BANANA PLUG (VIOLET)

Part Number	Weight	Min. Quantity
1825-7#	N-A	500

**BANANA PLUG (ORANGE)**

Pomona Electronics

BANANA PLUG (ORANGE)

Part Number	Weight	Min. Quantity
1825-3#	N-A	500

**BANANA PLUG (GRAY)**

Pomona Electronics

BANANA PLUG (GRAY)

Part Number	Weight	Min. Quantity
1825-8#	N-A	500

1825-9# – BANANA PLUG (WHITE)

**BANANA PLUG (WHITE)**

Pomona Electronics

BANANA PLUG (WHITE)

Part Number	Weight	Min. Quantity
1825-9#	N-A	500

**ALLIG CL/SPADE LUG (RED)**

Pomona Electronics

ALLIG CL/SPADE LUG (RED)

Part Number	Weight	Min. Quantity
1960-36-2	0.5	5

SGL B-PLUG SPLICE 10/PKG (BLACK)

Pomona Electronics

Single Banana Plug Splice, 15 A (Max.) Current Rating, Nickel Plated Brass Body Material Provides rapid method for splicing single banana plug patch cords. Reduces the necessity of storing extra long patch cords. Molded thermoplastic body provides protective insulation. 4.22 mm (0.166) dia. banana j

Part Number	Weight	Min. Quantity
1829-0	0.14	1

**MINIATURE SHORTED DBL BANANA PLUG; ...**

Pomona Electronics

Upper: Miniature double banana jack. Brass, gold plated. Insulation : ABS. Lower: Miniature double banana plug. Spring: One piece heat treated beryllium copper, gold plated. Fits miniature 2.64 mm (0.104) dia. banana jack. Rating: 2500 WVDC, 5 amps, +50°C (+122°F) max.

Part Number	Weight	Min. Quantity
2035-0	0.5	5

SGL B-PLUG SPLICE 10/PKG (RED)

Pomona Electronics

Single Banana Plug Splice, 15 A (Max.) Current Rating, Nickel Plated Brass Body Material Provides rapid method for splicing single banana plug patch cords. Reduces the necessity of storing extra long patch cords. Molded thermoplastic body provides protective insulation. 4.22 mm (0.166) dia. banana j

Part Number	Weight	Min. Quantity
1829-2	N-A	1

**MINI DBL BANANA; SHORTED (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
2035-0#	N-A	500

DBL BANANA; 3 TURRET ISOL

Pomona Electronics

DBL BANANA; 3 TURRET ISOL

Part Number	Weight	Min. Quantity
1837	0.05	5

**MINIATURE SHORTED DBL BANANA PLUG; ...**

Pomona Electronics

Upper: Miniature double banana jack. Brass, gold plated. Insulation : ABS. Lower: Miniature double banana plug. Spring: One piece heat treated beryllium copper, gold plated. Fits miniature 2.64 mm (0.104) dia. banana jack. Rating: 2500 WVDC, 5 amps, +50°C (+122°F) max.

Part Number	Weight	Min. Quantity
2035-2	0.5	5

ALLIG CL/SPADE LUG (BLACK)

Pomona Electronics

ALLIG CL/SPADE LUG (BLACK)

Part Number	Weight	Min. Quantity
1960-36-0	0.072	5

**PHENOLIC BOX WITH DOUBLE BANANA PLU...**

Pomona Electronics

Cover and Cover Screws Included

Part Number	Weight	Min. Quantity
2096	0.055	2

2142-0# – MINI B-JACK (BLACK)

**BOX; DBL BANANA/JACKS****Pomona Electronics**

Component Mounting Phenolic Boxes Electrical grade phenolic housing material Cover and Cover Screws Included

Part Number	Weight	Min. Quantity
2098	0.062	2

**BIND POST/PJ051****Pomona Electronics**

Pomona Binding Post to PJ051 Phone Plug Features Permits single or double banana plug to be used with equipment having three circuit phone jacks Tip connected to hot side of adapter and ring connected to ground side Sleeve. No connection Cross holes 4.2 (0.166) dia. in plug body provide side stackup

Part Number	Weight	Min. Quantity
2112	0.5	2

**PHENOLIC BOX****Pomona Electronics**

Pan Head Screws, Phenolic Box with Covers Black color Black Phenolic Housing Black XP Laminated Paper Base Phenolic Cover +150°C (+302°F) Max. Rating Two #2-56 Cover Screws Included

Part Number	Weight	Min. Quantity
2103	0.5	2

**B-JACK/MINI PLUG 10/PK (BLACK)****Pomona Electronics**

Part Number	Weight	Min. Quantity
-------------	--------	---------------

2138-0	0.12	1
--------	------	---

**BOX;PHENOLIC;BLK;2.38;1.53;1.53****Pomona Electronics**

Pan Head Screws, Phenolic Box with Covers Black color Black Phenolic Housing Black XP Laminated Paper Base Phenolic Cover +150°C (+302°F) Max. Rating Two #2-56 Cover Screws Included

Part Number	Weight	Min. Quantity
2104	0.5	2

**B-JACK/MINI PLUG 10/PK (RED)****Pomona Electronics**

Standard Banana Jack to Miniature Banana Plug Connector, 2500 VDC Operating Voltage Permits standard banana plug to be used with equipment having miniature banana jacks Jack insulation material acrylonitrile-butadiene-styrene.

Part Number	Weight	Min. Quantity
2138-2	0.12	1

**PHENOLIC BOX; BLACK****Pomona Electronics**

PHENOLIC BOX; BLACK

Part Number	Weight	Min. Quantity
2104#	N-A	500

**BANANA JACK; BLACK MINI; 10/PKG****Pomona Electronics**

Gold Plated Finish, 5 A, Brass Body, Insulated Miniature Banana Jack Closed entry 2.64 mm (0.104) dia. jack. Mounts in panels up to 6.35 mm (0.250) thick. Nickel plated 8-32 hex nut and lockwasher included. Material: Brass. Finish: Gold plated Insulation: Polycarbonate. Rating: 1500 WVDC, 5 amps, +

Part Number	Weight	Min. Quantity
2142-0	0.045	1

**PHENOLIC BOX****Pomona Electronics**

Pan Head Screws, Phenolic Box with Covers Black color Black Phenolic Housing Black XP Laminated Paper Base Phenolic Cover +150°C (+302°F) Max. Rating Two #2-56 Cover Screws Included

Part Number	Weight	Min. Quantity
2105	0.045	2

**MINI B-JACK (BLACK)****Pomona Electronics**

Part Number	Weight	Min. Quantity
2142-0#	N-A	500

2142-2 – BANANA JACK RED MINI; 10/PKG

**BANANA JACK RED MINI; 10/PKG****Pomona Electronics**

Gold Plated Finish, 5 A, Brass Body, Insulated Miniature Banana Jack Closed entry 2.64 mm (0.104) dia. jack. Mounts in panels up to 6.35 mm (0.250) thick. Nickel plated 8-32 hex nut and lockwasher included. Material: Brass. Finish: Gold plated Insulation: Polycarbonate. Rating: 1500 WVDC, 5 amps, +

Part Number	Weight	Min. Quantity
2142-2	0.045	1

**MINI B-JACK (RED)****Pomona Electronics**

Part Number	Weight	Min. Quantity
2142-2#	N-A	500

**MINI B-JACK 10/PKG (ORANGE)****Pomona Electronics**

Part Number	Weight	Min. Quantity
2142-3	0.045	1

**MINI B-JACK (ORANGE)****Pomona Electronics**

MINI B-JACK (ORANGE)

Part Number	Weight	Min. Quantity
2142-3#	N-A	500

**MINI B-JACK 10/PKG (YELLOW)****Pomona Electronics**

Insulated Miniature Banana Jack, #8-32 AWG Wire Size, 5 A Current Rating Accepts miniature banana plugs Mounts in panels up to 0.250 in. thick Banana jack with current rating of 5 A.

Part Number	Weight	Min. Quantity
2142-4	0.045	1

**MINI B-JACK (YELLOW)****Pomona Electronics**

Part Number	Weight	Min. Quantity
2142-4#	N-A	500

**MINI B-JACK 10/PKG (GREEN)****Pomona Electronics**

Gold Plated Finish, 5 A, Brass Body, Insulated Miniature Banana Jack Closed entry 2.64 mm (0.104) dia. jack. Mounts in panels up to 6.35 mm (0.250) thick. Nickel plated 8-32 hex nut and lockwasher included. Material: Brass. Finish: Gold plated Insulation: Polycarbonate. Rating: 1500 WVDC, 5 amps, +

Part Number	Weight	Min. Quantity
2142-5	0.045	1

**MINI B-JACK (GREEN)****Pomona Electronics**

MINI B-JACK (GREEN)

Part Number	Weight	Min. Quantity
2142-5#	N-A	500

**MINI B-JACK 10/PKG (BLUE)****Pomona Electronics**

Gold Plated Finish, 5 A, Brass Body, Insulated Miniature Banana Jack Closed entry 2.64 mm (0.104) dia. jack. Mounts in panels up to 6.35 mm (0.250) thick. Nickel plated 8-32 hex nut and lockwasher included. Material: Brass. Finish: Gold plated Insulation: Polycarbonate. Rating: 1500 WVDC, 5 amps, +

Part Number	Weight	Min. Quantity
2142-6	0.045	1

**MINI B-JACK (BLUE)****Pomona Electronics**

MINI B-JACK (BLUE)

Part Number	Weight	Min. Quantity
2142-6#	N-A	500



2240-0 – ALLIGATOR CLIP W/BANNANA JACK (BLAC...

**BANANA JACK WHITE MINI; 10/PKG****Pomona Electronics**

Gold Plated Finish, 5 A, Brass Body, Insulated Miniature Banana Jack Closed entry 2.64 mm (0.104) dia. jack. Mounts in panels up to 6.35 mm (0.250) thick. Nickel plated 8-32 hex nut and lockwasher included. Material: Brass. Finish: Gold plated Insulation: Polycarbonate. Rating: 1500 WVDC, 5 amps, +

Part Number	Weight	Min. Quantity
2142-9	0.5	1

**MINI B-JACK (WHITE)****Pomona Electronics**

MINI B-JACK (WHITE)

Part Number	Weight	Min. Quantity
2142-9#	N-A	500

**MINI DBL BANANA JACK (BLACK)****Pomona Electronics**

Panel Mount, Polycarbonate, 5 A, Double Miniature Banana Jack Mounts in panels up to 4.77 mm (0.188) thick. Nickel plated 8-32 hex nut and lockwasher included. Material: Brass. Finish: Gold plated. Insulation: Polycarbonate. One black and one red jack. Choice of black or red mounting base. Rating: 1

Part Number	Weight	Min. Quantity
2143-0	0.02	5

**MINI DBL BANANA JACK; (BLACK)****Pomona Electronics**

MINI DBL BANANA JACK; (BLACK)

Part Number	Weight	Min. Quantity
2143-0#	N-A	500

**MINI DBL BANANA JACK (RED)****Pomona Electronics**

MINI DBL BANANA JACK (RED)

Part Number	Weight	Min. Quantity
2143-2	0.015	5

**BOX; DBL BANANA****Pomona Electronics**

Component Mounting Box, Brass⁄Beryllium Copper Body Material Electrical grade phenolic⁄die cast aluminum alloy A380 or A384 housing material Cover and Cover Screws Included

Part Number	Weight	Min. Quantity
2224	0.105	2

**BANANA PLUG; RG58C/U****Pomona Electronics**

BANANA PLUG; RG58C/U

Part Number	Weight	Min. Quantity
2239-C-24	N-A	2

**BANANA PLUG; RG58C/U****Pomona Electronics**

BANANA PLUG; RG58C/U

Part Number	Weight	Min. Quantity
2239-C-36	0.15	2

**BANANA PLUG; RG58C/U****Pomona Electronics**

BANANA PLUG; RG58C/U

Part Number	Weight	Min. Quantity
2239-C-48	0.175	2

**ALLIGATOR CLIP W/BANNANA JACK (BLAC...****Pomona Electronics**

5 A, 150 V (RMS), Alligator Clip To Banana Jack with Flex Boot Alligator clip has 0.300" max. jaw opening. Overall Length: 2.16"; Rating: 150 V, 5 amps, +50°C (+122°F) max. Sold unassembled. #13; 3289. Gold plated. One Clip and insulator. #13; 2240: Nickel plated. Package of 10 cli

Part Number	Weight	Min. Quantity
2240-0	N-A	1



2240-0# – ALLIGATOR CLIP W/BANNANA JACK (BLAC...

**ALLIGATOR CLIP W/BANNANA JACK (BLAC...**

Pomona Electronics

ALLIGATOR CLIP W/BANNANA JACK (BLACK)

Part Number	Weight	Min. Quantity
2240-0#	N-A	500

**MINI BANANA PLUG/JACK (RED)**

Pomona Electronics

Internal setscrews to secure cable or component leads. Upper: Miniature double banana jack. Brass, gold-plated. Insulation: ABS. Lower: Miniature double banana plug. Spring: One piece heat treated beryllium copper, gold plated. Fits miniature 2.64 mm (0.104) dia. banana jack. Setscrew: Steel, blue z

Part Number	Weight	Min. Quantity
2244-2	0.0146	5

**ALLIG CL/B-JACK 10/PKG (RED)**

Pomona Electronics

5 A, 150 V (RMS), Alligator Clip To Banana Jack with Flex Boot Alligator clip has 0.300" max. jaw opening. Overall Length: 2.16". Rating: 150 V, 5 amps, +50°C (+122°F) max. Sold unassembled. #13; 3289. Gold plated. One Clip and insulator. #13; 2240: Nickel plated. Package of 10 cli

Part Number	Weight	Min. Quantity
2240-2	0.145	1

**MINI BANANA PLUG/JACK (RED)**

Pomona Electronics

MINI BANANA PLUG/JACK (RED)

Part Number	Weight	Min. Quantity
2244-2#	N-A	500

**BANANA PLUG/BNC (M); RG58C**

Pomona Electronics

BANANA PLUG/BNC (M); RG58C

Part Number	Weight	Min. Quantity
2241-C-36	0.16	16

**MINI BANANA PLUG; RG174/U**

Pomona Electronics

Double Banana Plug Both End Cable Assembly, 18 AWG Wire Size, 65 x 36 Stranding RG174/U. Rating: 1000 V RMS, +55°C (+131°F) max. Cable Type: 0.100" O.D.

Part Number	Weight	Min. Quantity
2247-K-24	N-A	2

**MINI BANANA PLUG/JACK (BLACK)**

Pomona Electronics

Internal setscrews to secure cable or component leads. Upper: Miniature double banana jack. Brass, gold-plated. Insulation: ABS. Lower: Miniature double banana plug. Spring: One piece heat treated beryllium copper, gold plated. Fits miniature 2.64 mm (0.104) dia. banana jack. Setscrew: Steel, blue z

Part Number	Weight	Min. Quantity
2244-0	0.015	5

**MINI BANANA PLUG; RG174/U**

Pomona Electronics

MINI BANANA PLUG; RG174/U

Part Number	Weight	Min. Quantity
2247-K-24#	N-A	500

**MINI BANANA PLUG/JACK (BLACK)**

Pomona Electronics

MINI BANANA PLUG/JACK (BLACK)

Part Number	Weight	Min. Quantity
2244-0#	N-A	500

**PHENOLIC BOX WITH BINDING POSTS & B...**

Pomona Electronics

Component Mounting Phenolic Boxes Electrical grade phenolic housing material Cover and Cover Screws Included

Part Number	Weight	Min. Quantity
2259	0.085	2

2390 – SHIELDED BOX WITH TWO BNC (F)

**DBL BANANA JACK (BLACK)****Pomona Electronics**

Panel Mount, +115 °C (Max.) Operating Temperature, Insulated Double Banana Jack Jack, Insulated Double Banana Jack, Black Base, 15 Amp

Part Number	Weight	Min. Quantity
2269-0	0.03	5

**DBL BANANA JACK (BLACK)****Pomona Electronics**

DBL BANANA JACK (BLACK)

Part Number	Weight	Min. Quantity
2269-0#	N-A	500

**DBL BANANA JACK (RED)****Pomona Electronics**

Panel Mount, +115 °C (Max.) Operating Temperature, Insulated Double Banana Jack Mounts in panels from 1.60 mm (0.063) to 9.53 mm (0.375) thick. Nickel plated lockwasher and 1¼-32 hex nut. One black and one red jack. Choice of black or red mounting base. Material: Brass. Finish: Bright tin

Part Number	Weight	Min. Quantity
2269-2	0.035	5

MICROVOLT SPADE LUG**Pomona Electronics**

Part Number	Weight	Min. Quantity
2305	0.025	5

**BINDING POST; MINI INSULATED NYLON;...****Pomona Electronics**

5 A, 1500 V (RMS) (Max.), Single Insulated Miniature Binding Posts Accepts miniature banana plug. #8-32 hex nut and lockwasher included. 2.2 (0.086) dia. cross hole is perpendicular with flat on insulator. Mounts in panels up to 4.8 (0.188) thick. Material: Binding post body, captive thumb nut and h

Part Number	Weight	Min. Quantity
2382-0	0.5	5

**BINDING POST; MINI INSULATED NYLON;...****Pomona Electronics**

5 A, 1500 V (RMS) (Max.), Single Insulated Miniature Binding Posts Accepts miniature banana plug. #8-32 hex nut and lockwasher included. 2.2 (0.086) dia. cross hole is perpendicular with flat on insulator. Mounts in panels up to 4.8 (0.188) thick. Material: Binding post body, captive thumb nut and h

Part Number	Weight	Min. Quantity
2382-2	0.02	5

**MINI BIND POST; GOLD PL (GREEN)****Pomona Electronics**

MINI BIND POST; GOLD PL (GREEN)

Part Number	Weight	Min. Quantity
2382-5	N-A	5

**MINI BIND POST; GOLD PL (BLUE)****Pomona Electronics**

MINI BIND POST; GOLD PL (BLUE)

Part Number	Weight	Min. Quantity
2382-6	0.02	5

**MINI BIND POST; GOLD PL (BLACK)****Pomona Electronics**

Miniature Double Binding Post Assembly, Gold Plated (Black)

Part Number	Weight	Min. Quantity
2383-0	0.035	5


**SHIELDED BOX WITH TWO BNC (F)****Pomona Electronics**

Aluminum Box with Cover BNC Female¼Female Connectors 50 Ohms nominal impedance Coax Connectors Are 50 Ohm Nominal Impedance Boxes with Connectors Are Rated at 500 VRMS Max., +150°C (+302°F) Max. Except for Model 2399 Which Is Rated at 335 VRMS Max. and Model 2411 Which Is Rated at 1000

Part Number	Weight	Min. Quantity
2390	0.135	2



2391 – SHIELDED BOX; BNC (M) TO BNC (F)

**SHIELDED BOX; BNC (M) TO BNC (F)****Pomona Electronics**

Size B Aluminum Box with Cover 50 Ohms nominal impedance Pan head self-tapping steel screws Coax Connectors Are 50 Ohm Nominal Impedance Boxes with Connectors Are Rated at 500 VRMS Max., +150°C (+302°F) Max. Except for Model 2399 Which Is Rated at 335 VRMS Max. and Model 2411 Which Is Rated

Part Number	Weight	Min. Quantity
2391	0.5	2

**SHIELDED BOX; BNC (F-F-F)****Pomona Electronics**

Aluminum Box with Cover BNC Female Tee Connectors 50 Ohms nominal impedance Coax Connectors Are 50 Ohm Nominal Impedance Boxes with Connectors Are Rated at 500 VRMS Max., +150°C (+302°F) Max. Except for Model 2399 Which Is Rated at 335 VRMS Max. and Model 2411 Which Is Rated at 1000 VRMS

Part Number	Weight	Min. Quantity
2392	N-A	2

**BOX; BNC/BIND POST****Pomona Electronics**

BOX; BNC/BIND POST

Part Number	Weight	Min. Quantity
2393	N-A	2

**SHIELDED BOX****Pomona Electronics**

Nylon Shoulder Washer&fras;Bushing Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are aluminum 1100-H14 with clear anodize finish per MIL

Part Number	Weight	Min. Quantity
2397	0.08	2

**SHIELDED BOX****Pomona Electronics**

SHIELDED BOX

Part Number	Weight	Min. Quantity
2397#	N-A	500

**SHIELDED BOX****Pomona Electronics**

Aluminum Box With Cover, Pan Head Self Tapping Steel Screw Type, Die Cast Aluminum Alloy Housing Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. C

Part Number	Weight	Min. Quantity
2400	0.08	2

**SHIELDED BOX; BNC (F-F-M)****Pomona Electronics**

Aluminum Box with Cover BNC Tee F-F-M Connectors 50 Ohms nominal impedance Coax Connectors Are 50 Ohm Nominal Impedance Boxes with Connectors Are Rated at 500 VRMS Max., +150°C (+302°F) Max. Except for Model 2399 Which Is Rated at 335 VRMS Max. and Model 2411 Which Is Rated at 1000 VRMS

Part Number	Weight	Min. Quantity
2401	N-A	2

**SHIELDED BOX****Pomona Electronics**

Size B Aluminum Box With Cover, 2.25 in. Width, 1.38 in. Height Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are aluminum 1100-H14 with

Part Number	Weight	Min. Quantity
2417	0.5	2

**SHIELDED BOX****Pomona Electronics**

SHIELDED BOX

Part Number	Weight	Min. Quantity
2417#	N-A	500

**SHIELDED BOX****Pomona Electronics**

Size B Aluminum Box With Cover, 2.25 in. Width, 1.13 in. Depth Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are aluminum 1100-H14 with c

Part Number	Weight	Min. Quantity
2428	0.105	2



2447A – PANEL MT.; .500 CENTER

**SHIELDED BOX**

Pomona Electronics

SHIELDED BOX

Part Number	Weight	Min. Quantity
2428#	N-A	500

**BINDING POST;BRASS;8-32;POLYCA;GRN**

Pomona Electronics

BINDING POST;BRASS;8-32;POLYCA;GRN

Part Number	Weight	Min. Quantity
2439-5	0.5	5

MINI BIND POST; TIN PL (BLACK)

Pomona Electronics

5 A, 1500 V (RMS) (Max.), Single Insulated Miniature Binding Posts Accepts miniature banana plug. #8-32 hex nut and lockwasher included. 2.2 (0.086) dia. cross hole is perpendicular with flat on insulator. Mounts in panels up to 4.8 (0.188) thick. Material: Binding post body, captive thumb nut and h

Part Number	Weight	Min. Quantity
2439-0	0.02	5

MINI BIND POST; TIN PL (GREEN)

Pomona Electronics

MINI BIND POST; TIN PL (GREEN)

Part Number	Weight	Min. Quantity
2439-5#	N-A	500

MINI BIND POST; TIN PL (BLACK)

Pomona Electronics

MINI BIND POST; TIN PL (BLACK)

Part Number	Weight	Min. Quantity
2439-0#	N-A	500

MINI BIND POST; TIN PL (BLUE)

Pomona Electronics

MINI BIND POST; TIN PL (BLUE)

Part Number	Weight	Min. Quantity
2439-6	0.02	5

MINI BIND POST; TIN PL (BROWN)

Pomona Electronics

MINI BIND POST; TIN PL (BROWN)

Part Number	Weight	Min. Quantity
2439-1	N-A	5

MINI BIND POST; TIN PL (BLACK)

Pomona Electronics

Miniature Double Binding Post Assembly, Tin Plated (Black)

Part Number	Weight	Min. Quantity
2440-0	N-A	5

MINI BIND POST; TIN PL (RED)

Pomona Electronics

5 A, 1500 V (RMS) (Max.), Single Insulated Miniature Binding Posts Accepts miniature banana plug. #8-32 hex nut and lockwasher included. 2.2 (0.086) dia. cross hole is perpendicular with flat on insulator. Mounts in panels up to 4.8 (0.188) thick. Material: Binding post body, captive thumb nut and h

Part Number	Weight	Min. Quantity
2439-2	0.02	5

PANEL MT.; .500 CENTER

Pomona Electronics

BNC Connectors, 50 Ohms (Nom.) Impedance, Gold Contact Plating Brass body material Brass contact material.

Part Number	Weight	Min. Quantity
2447A	0.05	5



2451A – BNC(F) PANEL MT.; .500 CENTER

**BNC(F) PANEL MT.; .500 CENTER****Pomona Electronics**

Panel Mount Female BNC Connector, 50 Ohms Impedance, Nickel Plated Brass Body, PTFE Insulation 1.07" overall length Tarnish resistant plating.

Part Number	Weight	Min. Quantity
2451A	0.025	5

**B-PL/MINI JACK 10/PK (BLACK)****Pomona Electronics**

B-PL/MINI JACK 10/PK (BLACK)

Part Number	Weight	Min. Quantity
2477-0	0.15	1

**B-PLG/MINI JACK 10/PK (RED)****Pomona Electronics**

B-PLG/MINI JACK 10/PK (RED)

Part Number	Weight	Min. Quantity
2477-2	0.154	1

**ALLIG CL/BNC (F)****Pomona Electronics**

ALLIG CL/BNC (F)

Part Number	Weight	Min. Quantity
2630#	N-A	500

**MINI CL/BNC (F)****Pomona Electronics**

MINI CL/BNC (F)

Part Number	Weight	Min. Quantity
2631#	N-A	500

**PJ051/BNC (F)****Pomona Electronics**

Brass With Tarnish Resistant Plating, 500 V, Phone Plug (WE 310) To BNC Female Adapter Type 5319. Nickel-plated contact.

Part Number	Weight	Min. Quantity
2798	0.04	2

**BANANA JACK; BLACK STD; 10/PKG****Pomona Electronics**

+115°C (Max.) Operating Temperature, 30 VAC & 60 VDC (Max.), Panel Mount Banana Jack Mounts in panels from 1.60 mm (0.063) to 9.53 mm (0.375) thick. Nickel plated lockwasher and 1/4-32 hex nut. Material: Brass. Rating: 2500 WVDC, 15 amps, +1

Part Number	Weight	Min. Quantity
2854-0	0.125	1

**B-JACK GOLD PL (BLACK)****Pomona Electronics**

B-JACK GOLD PL (BLACK)

Part Number	Weight	Min. Quantity
2854-0#	N-A	500

**B-JACK GOLD PL 10/PKG (BROWN)****Pomona Electronics**

B-JACK GOLD PL 10/PKG (BROWN)

Part Number	Weight	Min. Quantity
2854-1	0.5	1

**BANANA JACK; RED STD; 10/PKG****Pomona Electronics**

+115°C (Max.) Operating Temperature, 30 VAC & 60 VDC (Max.), Panel Mount Banana Jack Mounts in panels from 1.60 mm (0.063) to 9.53 mm (0.375) thick. Nickel plated lockwasher and 1/4-32 hex nut. Material: Brass. Rating: 2500 WVDC, 15 amps, +1

Part Number	Weight	Min. Quantity
2854-2	0.12	1

2882-C-60 – PIN TIP/BNC (M); RG58C/U

**BANANA JACK; GOLD PLATED MTO BULK (...)**

Pomona Electronics

BANANA JACK; GOLD PLATED MTO BULK (RED)

Part Number	Weight	Min. Quantity
2854-2#	N-A	500

**BANANA JACK; PANEL (GRAY) 10/PKG**

Pomona Electronics

BANANA JACK; PANEL (GRAY) 10/PKG

Part Number	Weight	Min. Quantity
2854-8	0.5	1

B-JACK GOLD PL 10/PKG (YELLOW)

Pomona Electronics

+115°C (Max.) Operating Temperature, 30 VAC⁄60 VDC (Max.), Panel Mount Banana Jack Mounts in panels from 1.60 mm (0.063) to 9.53 mm (0.375) thick. Nickel plated lockwasher and 1⁄4-32 hex nut. Material: Brass. Rating: 2500 WVDC, 15 amps, +1

Part Number	Weight	Min. Quantity
2854-4	0.5	1

BANANA JACK WHITE STD; 10/PKG

Pomona Electronics

+115°C (Max.) Operating Temperature, 30 VAC⁄60 VDC (Max.), Panel Mount Banana Jack Mounts in panels from 1.60 mm (0.063) to 9.53 mm (0.375) thick. Nickel plated lockwasher and 1⁄4-32 hex nut. Material: Brass. Rating: 2500 WVDC, 15 amps, +1

Part Number	Weight	Min. Quantity
2854-9	0.125	1

B-JACK GOLD PL 10/PKG (GREEN)

Pomona Electronics

+115°C (Max.) Operating Temperature, 30 VAC⁄60 VDC (Max.), Panel Mount Banana Jack Mounts in panels from 1.60 mm (0.063) to 9.53 mm (0.375) thick. Nickel plated lockwasher and 1⁄4-32 hex nut. Material: Brass. Rating: 2500 WVDC, 15 amps, +1

Part Number	Weight	Min. Quantity
2854-5	0.5	1

BANANA JACK; GOLD PLATED (WHITE)

Pomona Electronics

BANANA JACK; GOLD PLATED (WHITE)

Part Number	Weight	Min. Quantity
2854-9#	N-A	500

BANANA JACK; GOLD PLATED (GREEN)

Pomona Electronics

BANANA JACK; GOLD PLATED (GREEN)

Part Number	Weight	Min. Quantity
2854-5#	N-A	500

PIN TIP/BNC (M); RG58C/U

Pomona Electronics

PIN TIP/BNC (M); RG58C/U

Part Number	Weight	Min. Quantity
2882-C-244#	N-A	500

B-JACK GOLD PL 10/PKG (BLUE)

Pomona Electronics

+115°C (Max.) Operating Temperature, 30 VAC⁄60 VDC (Max.), Panel Mount Banana Jack Mounts in panels from 1.60 mm (0.063) to 9.53 mm (0.375) thick. Nickel plated lockwasher and 1⁄4-32 hex nut. Material: Brass. Rating: 2500 WVDC, 15 amps, +1

Part Number	Weight	Min. Quantity
2854-6	0.125	1

**PIN TIP/BNC (M); RG58C/U**

Pomona Electronics

Part Number	Weight	Min. Quantity
2882-C-60	N-A	2



2901 – SHIELDED BOX

**SHIELDED BOX****Pomona Electronics**


Size C Aluminum Box With Cover, 2.64 in. Height, 5.25 in. Width Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are aluminum 1100-H14 with

Part Number	Weight	Min. Quantity
2901	0.5	2

**SHIELDED BOX****Pomona Electronics**

SHIELDED BOX

Part Number	Weight	Min. Quantity
2901#	N-A	500

**SHIELDED BOX****Pomona Electronics**

Size C Aluminum Box With Cover, 2.64 in. Height, 5.25 in. Width Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are aluminum 1100-H14 with

Part Number	Weight	Min. Quantity
2906	0.5	2

**SHIELDED BOX****Pomona Electronics**

SHIELDED BOX

Part Number	Weight	Min. Quantity
2906#	N-A	500

**MINI BANANA PLUG (BLACK)****Pomona Electronics**

MINI BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
2944-0	0.0112	5

**MINI BANANA PLUG (BLACK)****Pomona Electronics**

MINI BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
2944-0#	N-A	500

**MINI BANANA PLUG (RED)****Pomona Electronics**

MINI BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
2944-2	0.011	5

**MINI BANANA PLUG (BLACK)****Pomona Electronics**

Miniature Solderless Stackup Banana Plug With Safety Collar, 2500 Vrms (Max.), + 50deg;C (Max.) Wire firmly held in place with setscrew. The integral collar insulates leads and acts as a strain relief by preventing the flexing of lead at setscrew. Upper: Miniature banana jack — 2.64 mm (0.104

Part Number	Weight	Min. Quantity
2945-0	0.011	5

**MINI BANANA PLUG (BLACK)****Pomona Electronics**

MINI BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
2945-0#_BULK	N-A	500

**MINI BANANA PLUG (RED)****Pomona Electronics**

Miniature Solderless Stackup Banana Plug With Safety Collar, 2500 Vrms (Max.), + 50deg;C (Max.) Wire firmly held in place with setscrew. The integral collar insulates leads and acts as a strain relief by preventing the flexing of lead at setscrew. Upper: Miniature banana jack — 2.64 mm (0.104

Part Number	Weight	Min. Quantity
2945-2	0.012	5



2BA-60 – DBL BANANA PLUG; 2 COND

**MINI PLUG/BANANA JACK**

Pomona Electronics

Part Number	Weight	Min. Quantity
2952	0.028	5

**TRIPLE BANANA PLUG (BLACK)**

Pomona Electronics

Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access panel or need a simple banana plug for a monitor. In the shop, lab, studi

Part Number	Weight	Min. Quantity
2970-0	0.5	5

**TRIPLE BANANA PLUG (BLACK)**

Pomona Electronics

TRIPLE BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
2970-0#	N-A	500

**TRIPLE BANANA PLUG (RED)**

Pomona Electronics

Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access panel or need a simple banana plug for a monitor. In the shop, lab, studi

Part Number	Weight	Min. Quantity
2970-2	0.055	5

**DBL BANANA PLUG; 2 COND**

Pomona Electronics

Retractable Sheath Stacking Banana Plug Patch Cord, 18 AWG Wire Size, 65 x 36 Stranding Materials: Plug Bodies: Brass, Nickel Plated Springs: Beryllium Copper, Nickel Plated Ratings Operating Temperature: +55°C Max. Operating Voltage: 2BA — 300 V RMS, 2BB — 1900 V RMS, 2BC —

Part Number	Weight	Min. Quantity
2BA-18	0.5	5

**DBL BANANA PLUG; 2 COND**

Pomona Electronics

Retractable Sheath Stacking Banana Plug Patch Cord, 18 AWG Wire Size, 65 x 36 Stranding Materials: Plug Bodies: Brass, Nickel Plated Springs: Beryllium Copper, Nickel Plated Ratings Operating Temperature: +55°C Max. Operating Voltage: 2BA — 300 V RMS, 2BB — 1900 V RMS, 2BC —

Part Number	Weight	Min. Quantity
2BA-24	0.5	5

**DBL BANANA PLUG; 2 COND**

Pomona Electronics

Retractable Sheath Stacking Banana Plug Patch Cord, 18 AWG Wire Size, 65 x 36 Stranding Materials: Plug Bodies: Brass, Nickel Plated Springs: Beryllium Copper, Nickel Plated Ratings Operating Temperature: +55°C Max. Operating Voltage: 2BA — 300 V RMS, 2BB — 1900 V RMS, 2BC —

Part Number	Weight	Min. Quantity
2BA-36	0.5	5

**DBL BANANA PLUG; 2 COND**

Pomona Electronics

DBL BANANA PLUG; 2 COND

Part Number	Weight	Min. Quantity
2BA-36#	N-A	500

**DBL BANANA PLUG; 2 COND**

Pomona Electronics

Retractable Sheath Stacking Banana Plug Patch Cord, 18 AWG Wire Size, 65 x 36 Stranding Materials: Plug Bodies: Brass, Nickel Plated Springs: Beryllium Copper, Nickel Plated Ratings Operating Temperature: +55°C Max. Operating Voltage: 2BA — 300 V RMS, 2BB — 1900 V RMS, 2BC —

Part Number	Weight	Min. Quantity
2BA-48	0.5	5

**DBL BANANA PLUG; 2 COND**

Pomona Electronics

Part Number	Weight	Min. Quantity
2BA-60	0.5	2



2BA-AL-36 – ALLIG CL/DBL BANANA; 2 COND

**ALLIG CL/DBL BANANA; 2 COND****Pomona Electronics**

PVC Insulated Black Color Alligator Clip Cable Type Two conductor Twisted pair Ratings Operating Temperature: +50°C Max. Operating Voltage: 2BA: 150 V RMS /VDC Current: 5 Amps Beryllium copper, nickel plated springs.

Part Number	Weight	Min. Quantity
2BA-AL-36	0.5	2

**ALLIG CL/DBL BANANA; 2 COND****Pomona Electronics**

PVC Insulated Black Color Alligator Clip Cable Type Two conductor Twisted pair Ratings Operating Temperature: +50°C Max. Operating Voltage: 2BA: 150 V RMS /VDC Current: 5 Amps Beryllium copper, nickel plated springs.

Part Number	Weight	Min. Quantity
2BA-AL-48	0.5	2

**DBL BANANA; RG58C/U****Pomona Electronics**

Retractable Sheath Stacking Banana Plug Patch Cord, 18 AWG Wire Size, 65 x 36 Stranding Materials: Plug Bodies: Brass, Nickel Plated Springs: Beryllium Copper, Nickel Plated Ratings Operating Temperature: +55°C Max. Operating Voltage: 2BA — 300 V RMS, 2BB — 1900 V RMS, 2BC —

Part Number	Weight	Min. Quantity
2BC-24	0.5	5

**DBL BANANA; RG58C/U****Pomona Electronics**

Retractable Sheath Stacking Banana Plug Patch Cord, 18 AWG Wire Size, 65 x 36 Stranding Materials: Plug Bodies: Brass, Nickel Plated Springs: Beryllium Copper, Nickel Plated Ratings Operating Temperature: +55°C Max. Operating Voltage: 2BA — 300 V RMS, 2BB — 1900 V RMS, 2BC —

Part Number	Weight	Min. Quantity
2BC-36	0.5	5

**CABLE ASSY;COAX;DBLE BANANA PLUG****Pomona Electronics**

Retractable Sheath Stacking Banana Plug Patch Cord, 18 AWG Wire Size, 65 x 36 Stranding Materials: Plug Bodies: Brass, Nickel Plated Springs: Beryllium Copper, Nickel Plated Ratings Operating Temperature: +55°C Max. Operating Voltage: 2BA — 300 V RMS, 2BB — 1900 V RMS, 2BC —

Part Number	Weight	Min. Quantity
2BC-48	N-A	5

**CABLE ASSY;COAX;DBLE BANANA PLUGS****Pomona Electronics**

Retractable Sheath Stacking Banana Plug Patch Cord, 18 AWG Wire Size, 65 x 36 Stranding Materials: Plug Bodies: Brass, Nickel Plated Springs: Beryllium Copper, Nickel Plated Ratings Operating Temperature: +55°C Max. Operating Voltage: 2BA — 300 V RMS, 2BB — 1900 V RMS, 2BC —

Part Number	Weight	Min. Quantity
2BC-60	N-A	5

**DBL BANANA/ALLIG CL;RG58C/U****Pomona Electronics**

DBL BANANA/ALLIG CL;RG58C/U

Part Number	Weight	Min. Quantity
2BC-AL-36	0.5	2

**DBL BANANA/ALLIG CL;RG58C/U****Pomona Electronics**

DBL BANANA/ALLIG CL;RG58C/U

Part Number	Weight	Min. Quantity
2BC-AL-60	0.5	2

**DBL BAN/BNC (M); RG58C/U****Pomona Electronics**

DBL BAN/BNC (M); RG58C/U

Part Number	Weight	Min. Quantity
2BC-BNC-5#	N-A	16

**DBL BANANA/MINI CL; RG58C/U****Pomona Electronics**

DBL BANANA/MINI CL; RG58C/U

Part Number	Weight	Min. Quantity
2BC-MG-36	0.5	2

3221# – PIN TIP/BNC (F)

**DBL BANANA/PIN TIP; RG58C/U**

Pomona Electronics

Part Number	Weight	Min. Quantity
2BC-PP-36	0.5	2

**MINI BANANA PLUG; SHORTED**

Pomona Electronics

Miniature Double Banana Plug Shorting Bar, 5 A Current Rating Low profile 1.6 mm thick brass shorting bar Center hole accepts #4-40 screw, for easy removal. It mates to Model # 2143 or any miniature double banana jack.

Part Number	Weight	Min. Quantity
3030	0.5	5

**DBL BANANA/PIN TIP; RG58C/U**

Pomona Electronics

DBL BANANA/PIN TIP; RG58C/U

Part Number	Weight	Min. Quantity
2BC-PP-48	0.17	2

**MINI BANANA PLUG; SHORTED**

Pomona Electronics

MINI BANANA PLUG; SHORTED

Part Number	Weight	Min. Quantity
3030#	N-A	500

**DBL BANANA/PIN TIP; RG58C/U**

Pomona Electronics

DBL BANANA/PIN TIP; RG58C/U

Part Number	Weight	Min. Quantity
2BC-PP-60	0.5	2

**BANANA PLUG/BNC (F)**

Pomona Electronics

BANANA PLUG/BNC (F)

Part Number	Weight	Min. Quantity
3073#	N-A	500

**MINI CL/MINI PLUG; RG174/U**

Pomona Electronics

Part Number	Weight	Min. Quantity
3027-K-24	0.055	2

**MINI CL/BANANA PLUG (RED)**

Pomona Electronics

MINI CL/BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
3220-12-2	0.5	5

**MINI CL/MINI PLUG;RG174/U**

Pomona Electronics

MINI CL/MINI PLUG;RG174/U

Part Number	Weight	Min. Quantity
3027-K-24#	N-A	500

**PIN TIP/BNC (F)**

Pomona Electronics

PIN TIP/BNC (F)

Part Number	Weight	Min. Quantity
3221#	N-A	500

3230 – SHIELDED BOX; 2.25IN X 1.38IN X 1.1...

**SHIELDED BOX; 2.25IN X 1.38IN X 1.1...****Pomona Electronics**

Component Mounting Box, Brass⁄Beryllium Copper Body Material Electrical grade phenolic⁄die cast aluminum alloy A380 or A384 housing material Coax Connectors Are 50 Ohm Nominal Impedance Boxes with Connectors Are Rated at 500 VRMS Max., +150°C (+302°F) Max. Except for Model 2399 W

Part Number	Weight	Min. Quantity
3230	0.5	2

**SHIELDED BOX; 2.25IN X 1.38IN X 1.1...****Pomona Electronics**

SHIELDED BOX; 2.25IN X 1.38IN X 1.13IN WITH TWO BNC (F);BULK

Part Number	Weight	Min. Quantity
3230#	N-A	500

**SHIELDED BOX; 2.25IN X 1.38IN X 1.1...****Pomona Electronics**

Aluminum Box with Cover BNC Male⁄Female Connectors 50 Ohms nominal impedance Coax Connectors Are 50 Ohm Nominal Impedance Boxes with Connectors Are Rated at 500 VRMS Max., +150°C (+302°F) Max. Except for Model 2399 Which Is Rated at 335 VRMS Max. and Model 2411 Which Is Rated at 1000 V

Part Number	Weight	Min. Quantity
3231	0.5	2

**SHIELDED BOX; BNC (F-F-F)****Pomona Electronics**

Aluminum Box with Cover BNC Female Tee Connectors 50 Ohms nominal impedance Coax Connectors Are 50 Ohm Nominal Impedance Boxes with Connectors Are Rated at 500 VRMS Max., +150°C (+302°F) Max. Except for Model 2399 Which Is Rated at 335 VRMS Max. and Model 2411 Which Is Rated at 1000 VRMS

Part Number	Weight	Min. Quantity
3232	N-A	2

**BOX; BNC (F-F-F-F)****Pomona Electronics**

Part Number	Weight	Min. Quantity
3234	N-A	2

**SHIELDED BOX; BNC (F) ISOL.****Pomona Electronics**

Component Mounting Phenolic Boxes Electrical grade phenolic housing material Coax Connectors Are 50 Ohm Nominal Impedance Boxes with Connectors Are Rated at 500 VRMS Max., +150°C (+302°F) Max. Except for Model 2399 Which Is Rated at 335 VRMS Max. and Model 2411 Which Is Rated at 1000 VRMS

Part Number	Weight	Min. Quantity
3239	0.5	2

**PLG/RIVET.062 PANEL 10/PKG****Pomona Electronics**

Connector Type Standard Rivet Banana Plug, Current Rating 15 A, 5000 VDC, 0.094 " Depth Fits Standard (0.166) dia. banana jack. Material: Banana plug body; brass spring; beryllium copper; Finish: Nickel plating.

Part Number	Weight	Min. Quantity
3257	0.5	1

**PLG/RIVET.062 PANEL****Pomona Electronics**

PLG/RIVET.062 PANEL

Part Number	Weight	Min. Quantity
3257#	N-A	500

**PLG/RIVET.093 PANEL 10/PKG****Pomona Electronics**

Connector Type Standard Rivet Banana Plug, Current Rating 15 A, 5000 VDC, 0.094 " Depth Fits Standard (0.166) dia. banana jack. Material: Banana plug body; brass spring; beryllium copper; Finish: Nickel plating.

Part Number	Weight	Min. Quantity
3258	0.051	1

**PLG/RIVET.093 PANEL****Pomona Electronics**

PLG/RIVET.093 PANEL

Part Number	Weight	Min. Quantity
3258#_BULK	N-A	500

3268# – MINI PLG/RIVET.062

**PLG/RIVET .093 PANEL 10/PKG****Pomona Electronics**

Standard Rivet Type Banana Plug with Turret For 3/32" Thick Panel, Voltage Rating 5000 VDC Fits Standard (0.166) dia. banana jack. Material: Banana plug body; brass spring; beryllium copper; Finish: Nickel plating.

Part Number	Weight	Min. Quantity
3261	0.5	1

**PLG/RIVET .093 PANEL****Pomona Electronics**

PLG/RIVET .093 PANEL

Part Number	Weight	Min. Quantity
3261#	N-A	500

**B-PLUG; 6-32 X 1/2 10/PKG****Pomona Electronics**

Standard Banana Plug With Threaded Stud and Solder Lug, Voltage Rating 5000 Vrms Material: Banana plug body & Brass; Spring & One piece heat treated beryllium copper. Fits standard 4.22 mm (0.166) dia. banana jack. Finish: Nickel plated. Rating: 5000 WVDC, 15 amps. Furnished with hex nut

Part Number	Weight	Min. Quantity
3263	0.085	1

**B-PLUG; 6-32 X 1/2****Pomona Electronics**

B-PLUG; 6-32 X 1/2

Part Number	Weight	Min. Quantity
3263#	N-A	500

**B-PLUG; 8-32 X 1/2; 10/PKG****Pomona Electronics**

Connector Type Standard Banana Plug, Current Ratings 15 A, Voltage Rating 5000 Vrms Material: Banana plug body & Brass; Spring & One piece heat treated beryllium copper. Fits standard 4.22 mm (0.166) dia. banana jack. Finish: Nickel plated. Rating: 5000 WVDC, 15 amps. Furnished with hex

Part Number	Weight	Min. Quantity
3264	0.5	1

**B-PLUG; 8-32 X 1/2****Pomona Electronics**

B-PLUG; 8-32 X 1/2

Part Number	Weight	Min. Quantity
3264#	N-A	500

**B-JACK 1/4-32 THREAD 10/PKG****Pomona Electronics**

Operating Voltage 30 VAC & 60 VDC (Max.), Standard Uninsulated - Banana Jack Threaded for rapid mounting. Used with standard banana plugs. Furnished with hex nut and solder lug. Material: Banana jack and hex nut & Brass; Solder lug & copper. Finish: Banana jack and hex nut & Ni

Part Number	Weight	Min. Quantity
3267	0.5	1

**B-JACK 1/4-32 THREAD****Pomona Electronics**

Part Number	Weight	Min. Quantity
3267#	N-A	500

**BANANA PLUG; MINIATURE; RIVET TYPE 1...****Pomona Electronics**

Connector Type Miniature Rivet Banana Plug, Voltage Rating 2500 VDC, Current Rating 5 A (Max.) Excellent for riveting to panels or boards. Material: Miniature banana plug body & Brass; Spring & One piece heat treated beryllium copper. Fits miniature 2.64 mm (0.104) dia. banana jack. Fini

Part Number	Weight	Min. Quantity
3268	N-A	1

**MINI PLG/RIVET.062****Pomona Electronics**

MINI PLG/RIVET.062

Part Number	Weight	Min. Quantity
3268#	N-A	500



3269 – MINI BANANA PLUG/BNC (F)

**MINI BANANA PLUG/BNC (F)****Pomona Electronics**

30 VAC&frac;60 VDC (Max.) Operating Voltage, Adapter - BNC Female To Miniature Double Banana Plug Type 3269 BNC female to miniature double banana plug fits miniature 0.104" diameter banana jacks. Rating. Operating Voltage: 500 V RMS max., +50°C (+122°F) max. Type 3296 miniature binding

Part Number	Weight	Min. Quantity
3269	0.026	5

**BANANA PLUG; RIVET TYPE MODEL 3271;...****Pomona Electronics**

BANANA PLUG; RIVET TYPE MODEL 3271; 10/PKG

Part Number	Weight	Min. Quantity
3271	0.015	1

**MINI B-PLUG 4-40X.230 10/PKG****Pomona Electronics**

Miniature Banana Plug With Threaded Stud, Voltage Rating 2500 VDC Threaded stud for rapid mounting. Solder turret for attachment of wires. Furnished with nickel-plated 4-40 hex nut, unassembled. Material: Miniature banana plug body — Brass; Spring — one-piece heat-treated beryllium copper

Part Number	Weight	Min. Quantity
3276	0.03	1

**MINI B-PLG4-40X.230****Pomona Electronics**

MINI B-PLG4-40X.230

Part Number	Weight	Min. Quantity
3276#	N-A	500

**MINI PLG/RIVET.093****Pomona Electronics**

MINI PLG/RIVET.093

Part Number	Weight	Min. Quantity
3271#	N-A	500

**MINI JACK/RIVET.062 10/PKG****Pomona Electronics**

MINI JACK/RIVET.062 10/PKG

Part Number	Weight	Min. Quantity
3277	0.3	1

**MINI PLG/RIVET .125 10/PKG****Pomona Electronics**

Connector Type Miniature Rivet Banana Plug, Voltage Rating 2500 VDC, Current Rating 5 A (Max.) Excellent for riveting to panels or boards. Material: Miniature banana plug body — Brass; Spring — One piece heat treated beryllium copper. Fits miniature 2.64 mm (0.104) dia. banana jack. Fini

Part Number	Weight	Min. Quantity
3272	0.5	1

**MINI JACK/RIVET.062****Pomona Electronics**

MINI JACK/RIVET.062

Part Number	Weight	Min. Quantity
3277#	N-A	500

**MINI PLG/RIVET .125****Pomona Electronics**

MINI PLG/RIVET .125

Part Number	Weight	Min. Quantity
3272#	N-A	500

**ADAPTER;BNC T;3 RECEPT****Pomona Electronics**

BNC T Adapter, 50 Ohms Nominal Impedance, PTFE Dielectric Material Nominal impedance 50 Ohms Brass body The connector have dielectric material PTFE.

Part Number	Weight	Min. Quantity
3284	0.5	5

3316 – SHIELDED BOX

**ADAPTER;BNC T;RECEP-PLUG-RECEP****Pomona Electronics**

BNC T Female-Male-Female Adapter, Brass Body Material, Gold Center Contact Material Adapter, BNC Female-Male-Female, Gold Plated Brass, 50 Ohms Dielectric: PTFE Operating Voltage: Shield/Earth: 30VAC/60VDC Max. Inner Conductor/Shield: 500VRMS Max. Operating Temperature: -65°C to +16

Part Number	Weight	Min. Quantity
3285	0.5	5

**UHF (F)/BNC (M)****Pomona Electronics**

UHF Female to BNC Male Adapter PTFE dielectric material Brass with tarnish resistant shell material. Gold plated phosphor bronze center contact material.

Part Number	Weight	Min. Quantity
3287	0.05	5

**ADAPTER;BNC(F);N(M)****Pomona Electronics**

Adapter N (Male) to BNC (Female), Brass Body, Contact Material Gold Plated Beryllium Copper Connector meets the interface requirements of MIL-STD-348 Adapter N (Male) to BNC (Female) with brass body, gold plated beryllium copper contact material.

Part Number	Weight	Min. Quantity
3288	0.5	5

**ALLIG CL/BANANA JACK (BLACK)****Pomona Electronics**

5 A, 150 V (RMS), Alligator Clip To Banana Jack with Flex Boot Alligator clip has 0.300" max. jaw opening. Overall Length: 2.16". Rating: 150 V, 5 amps, +50°C (+122°F) max. Sold unassembled. 3289. Gold plated. One Clip and insulator. 2240: Nickel plated. Package of 10 cli

Part Number	Weight	Min. Quantity
3289-0	N-A	5

**ALLIG CL/BANANA JACK (RED)****Pomona Electronics**

ALLIG CL/BANANA JACK (RED)

Part Number	Weight	Min. Quantity
3289-2#	N-A	500

**SHIELDED BOX****Pomona Electronics**

Size F Extruded Aluminum Box With Cover, Flat Head with Clear Iridite Dip Screw Type Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are a

Part Number	Weight	Min. Quantity
3301	0.5	2

**SHIELDED BOX****Pomona Electronics**

Shielded Aluminum Box Size F Unfinished, Flat Head Screw, Extruded Aluminum Alloy Housing Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers a

Part Number	Weight	Min. Quantity
3306	0.8	2

**SHIELDED BOX****Pomona Electronics**


Fiber Flat Washers Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are aluminum 1100-H14 with clear anodize finish per MIL-A-8625. Material

Part Number	Weight	Min. Quantity
3311	0.5	2

**SHIELDED BOX****Pomona Electronics**

SHIELDED BOX

Part Number	Weight	Min. Quantity
3311#	N-A	500

**SHIELDED BOX****Pomona Electronics**

SHIELDED BOX

Part Number	Weight	Min. Quantity
3316	1	2

3352-A-60 – PJ051/ALLIG CL; 2 COND

**PJ051/ALLIG CL; 2 COND****Pomona Electronics**

Body Brass, 18 AWG, Phone Plug To Alligator Clips Rating: 150 V RMS, +50°C (+122°F) max. Cable Type: 2 cond. twisted pair, 0.250" O.D.

Part Number	Weight	Min. Quantity
3352-A-60	0.5	1

**WE310/2 ALLIGS; CABLE 60 INCHES****Pomona Electronics**

WE310/2 ALLIGS; CABLE 60 INCHES

Part Number	Weight	Min. Quantity
3352N-A-60	N-A	1

**BANANA PLUG (BLACK)****Pomona Electronics**

BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
3364-0	0.5	5

**BANANA PLUG (RED)****Pomona Electronics**

BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
3364-2	0.035	5

**BIND POST/BNC (M) (BLACK)****Pomona Electronics**

Brass Per QQ-B-626, Allow 360, 1½ Hard Body, Adapter - Binding Post To BNC Male Permits single banana plug to be used with equipment having a BNC female. Upper: Binding post with captive thumb nut. Brass, nickel plated. Accepts standard banana plugs. Insulation: Polycarbonate. Lower: BNC Male

Part Number	Weight	Min. Quantity
3430-0	0.031	5

**BIND POST/BNC (M) (BLACK)****Pomona Electronics**

BIND POST/BNC (M) (BLACK)

Part Number	Weight	Min. Quantity
3430-0#	N-A	500

**BIND POST/BNC (M) (RED)****Pomona Electronics**

Brass Per QQ-B-626, Allow 360, 1½ Hard Body, Adapter - Binding Post To BNC Male Permits single banana plug to be used with equipment having a BNC female. Upper: Binding post with captive thumb nut. Brass, nickel plated. Accepts standard banana plugs. Insulation: Polycarbonate. Lower: BNC Male

Part Number	Weight	Min. Quantity
3430-2	0.03	5

**PIN TIP PLUG; SHORTED (BLACK)****Pomona Electronics**

Shorting Bar Pin Tip Plug, Black Color, 5 A Current Rating, 1.2 in. Height Ideal as a connecting link for use with 12.70 mm (0.500) spaced pin jacks. 2.03 mm (0.500) spaced pin jacks. 2.03 mm (0.080) double pin tip plug internally solder-bonded with #20 AWG wire. “Shorting bar” stamped on

Part Number	Weight	Min. Quantity
3452-0	0.0138	5

**PIN TIP PLUG; SHORTED (BLACK)****Pomona Electronics**

Part Number	Weight	Min. Quantity
3452-0#	N-A	500

**PIN TIP PLUG; SHORTED (RED)****Pomona Electronics**

Part Number	Weight	Min. Quantity
3452-2	0.0142	5

3542-5 – PIN TIP JACK GOLD PL 10/PKG (GREE...

**PIN TIP PLUG; SHORTED (RED) MTO BUL...**

Pomona Electronics

PIN TIP PLUG; SHORTED (RED) MTO BULK

Part Number	Weight	Min. Quantity
3452-2#	N-A	500

**PIN TIP JACK GOLD PL 10/PKG (RED)**

Pomona Electronics

Insulated Panel Mount Pin Tip Jacks, Gold plated Brass Contact Pin jack for 0.080" pin plug. Mounts in panels to 6.35 mm (0.250) thick. Nickel-plated 8-32 hex nut and lockwasher included. Material: Pin jack body, brass. Spring: Beryllium copper. Finish: Pin jack, gold plated, Insulation: Polycarbonate

Part Number	Weight	Min. Quantity
3542-2	0.049	1

MINI CL/PIN TIP JACK (BLACK)

Pomona Electronics

5 A, 45 V (RMS) & DC, Insulated Minigator Clip to Pin Tip Jack Alligator clip has 0.187" max. jaw opening. Overall Length: 2.05". Rating: 45 V, 5 amps, +50°C (+122°F) max.

Part Number	Weight	Min. Quantity
3491-0	0.014	5

**PIN TIP JACK GOLD PL (RED)**

Pomona Electronics

PIN TIP JACK GOLD PL (RED)

Part Number	Weight	Min. Quantity
3542-2#	N-A	500

MINI CL/PIN TIP JACK (RED)

Pomona Electronics

5 A, 45 V (RMS) & DC, Insulated Minigator Clip to Pin Tip Jack Alligator clip has 0.187" max. jaw opening. Overall Length: 2.05". Rating: 45 V, 5 amps, +50°C (+122°F) max.

Part Number	Weight	Min. Quantity
3491-2	0.014	5

**PIN TIP JACK GOLD PL 10/PKG (ORANG...**

Pomona Electronics

Part Number	Weight	Min. Quantity
3542-3	0.048	1

PIN TIP JACK GOLD PL 10/PKG (BLA...

Pomona Electronics

Insulated Panel Mount Pin Tip Jacks, Gold plated Brass Contact Pin jack for 0.080" pin plug. Mounts in panels to 6.35 mm (0.250) thick. Nickel-plated 8-32 hex nut and lockwasher included. Material: Pin jack body, brass. Spring: Beryllium copper. Finish: Pin jack, gold plated, Insulation: Polycarbonate

Part Number	Weight	Min. Quantity
3542-0	0.05	1

**PIN TIP JACK GOLD PL 10/PKG (YEL...**

Pomona Electronics

Part Number	Weight	Min. Quantity
3542-4	0.5	1

PIN TIP JACK GOLD PL (BLACK)

Pomona Electronics

PIN TIP JACK GOLD PL (BLACK)

Part Number	Weight	Min. Quantity
3542-0#	N-A	500

**PIN TIP JACK GOLD PL 10/PKG (GREE...**

Pomona Electronics

Insulated Panel Mount Pin Tip Jacks, Gold plated Brass Contact Pin jack for 0.080" pin plug. Mounts in panels to 6.35 mm (0.250) thick. Nickel-plated 8-32 hex nut and lockwasher included. Material: Pin jack body, brass. Spring: Beryllium copper. Finish: Pin jack, gold plated, Insulation: Polycarbonate

Part Number	Weight	Min. Quantity
3542-5	0.5	1



3542-5# – PIN TIP JACK GOLD PL (GREEN)

**PIN TIP JACK GOLD PL (GREEN)**

Pomona Electronics
PIN TIP JACK GOLD PL (GREEN)

Part Number	Weight	Min. Quantity
3542-5#	N-A	500

**PIN TIP PLUG (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
3548-0	0.5	5

PIN TIP JACK GOLD PL 10/PKG (BLUE)

Pomona Electronics

Part Number	Weight	Min. Quantity
3542-6	0.05	1

**PIN TIP PLUG (RED)**

Pomona Electronics

Part Number	Weight	Min. Quantity
3548-2	0.012	5

PIN TIP JACK GOLD PL (BLUE)

Pomona Electronics
PIN TIP JACK GOLD PL (BLUE)

Part Number	Weight	Min. Quantity
3542-6#	N-A	500

**TRIAxIAL BULKHEAD (F)**

Pomona Electronics

Connector Triaxial Bulkhead Receptacle, Brass per QQ-B-626, Alloy 360, Â½ Hard Material Body Brass body material PTFE dielectric material.

Part Number	Weight	Min. Quantity
3580	0.0234	1

PIN TIP JACK GOLD PL 10/PKG (WHIT...

Pomona Electronics

Insulated Panel Mount Pin Tip Jacks, Gold plated Brass Contact Pin jack for 0.080" pin plug. Mounts in panels to 6.35 mm (0.250) thick. Nickel-plated 8-32 hex nut and lockwasher included. Material: Pin jack body, brass. Spring: Beryllium copper. Finish: Pin jack, gold plated, Insulation: Polycarbonate

Part Number	Weight	Min. Quantity
3542-9	0.5	1

**TRIAx (M) FOR BELDEN 9272**

Pomona Electronics


Assembly Instructions Triaxial Cable Plug, PTFE Dielectric Material Brass body material PTFE dielectric material.

Part Number	Weight	Min. Quantity
3600	0.055	1

PIN TIP JACK GOLD PL (WHITE)

Pomona Electronics
PIN TIP JACK GOLD PL (WHITE)

Part Number	Weight	Min. Quantity
3542-9#	N-A	500

**SHIELDED BOX**

Pomona Electronics

Die Cast Aluminum Box, Clear Anodized Cover Finish, Phillips Pan Head Screw Type Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are aluminum

Part Number	Weight	Min. Quantity
3601	0.4	2




3744A-0 – BANANA JACK/SPADE LUG #4-6 (BLACK...

**SHIELDED BOX; SIZE D WITH TWO BNC (...)****Pomona Electronics**

Shielded Housing BNC Female Connectors 50 Ohms nominal impedance Coax Connectors Are 50 Ohm Nominal Impedance Boxes with Connectors Are Rated at 500 VRMS Max., +150°C (+302°F) Max. Except for Model 2399 Which Is Rated at 335 VRMS Max. and Model 2411 Which Is Rated at 1000 VRMS

Part Number	Weight	Min. Quantity
3602	0.5	2

**SHIELDED BOX****Pomona Electronics**

Die Cast Aluminum Box, Clear Anodized Cover Finish, Phillips Pan Head Screw Type Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are alumin

Part Number	Weight	Min. Quantity
3606	0.324	2

**MINI B-PLUG 10/PKG (BLACK)****Pomona Electronics**

Miniature Banana Plug Solder Type, 2500 VDC, 5 A, Operating Temperature + 80 °C, Nylon Insulation Miniature in-line plug for use with miniature binding posts or banana jacks. Wire is soldered directly to threaded plug. Material: Miniature banana plug body — Brass; Spring — One piece

Part Number	Weight	Min. Quantity
3690-0	0.0238	1

**MINI B-PLUG 10/PKG (RED)****Pomona Electronics**

Miniature Banana Plug Solder Type, 2500 VDC, 5 A, Operating Temperature + 80 °C, Nylon Insulation Miniature in-line plug for use with miniature binding posts or banana jacks. Wire is soldered directly to threaded plug. Material: Miniature banana plug body — Brass; Spring — One piece

Part Number	Weight	Min. Quantity
3690-2	0.0238	1

**COVER****Pomona Electronics**

COVER

Part Number	Weight	Min. Quantity
3719	0.45	5

**COVER****Pomona Electronics**

COVER

Part Number	Weight	Min. Quantity
3719#_BULK	N-A	500

**FLANGE MTG COVER****Pomona Electronics**

Part Number	Weight	Min. Quantity
3728	N-A	5

**SHIELDED BOX****Pomona Electronics**

Die Cast Aluminum Enclosure, Blue Baked Enamel Finish, Flat Head Screw Type Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are aluminum 11

Part Number	Weight	Min. Quantity
3742	1.485	2

**SHIELDED BOX****Pomona Electronics**

SHIELDED BOX

Part Number	Weight	Min. Quantity
3743	1.5	2

**BANANA JACK/SPADE LUG #4-6 (BLACK...****Pomona Electronics**

Banana Jack/Spade Lug #4-6 (Black)

Part Number	Weight	Min. Quantity
3744A-0	0.0096	5

3744A-02 – BANANA JACK/SPADE LUG #4-6 SET

**BANANA JACK/SPADE LUG #4-6 SET**

Pomona Electronics

BANANA JACK/SPADE LUG #4-6 SET

Part Number	Weight	Min. Quantity
3744A-02	0.015	5

**BANANA JACK/SPADE LUG #4-6 (RED)**

Pomona Electronics

Banana Jack/Spade Lug #4-6 (Red)

Part Number	Weight	Min. Quantity
3744A-2	0.0098	5

**BINDING POST; GOLD PLT (BLACK)**

Pomona Electronics

8-32 Thread Post, 1 $\frac{1}{4}$ in. Mounting Hole Size, Thread Size 8-32, Standard Binding Posts Accepts standard banana plug. Thin line design for high-density packaging. Nickel plated 8-32 hex nut and lockwasher included. 2.54 mm (0.100) dia. cross hole is perpendicular with flat on insulator. Mounts

Part Number	Weight	Min. Quantity
3750-0	0.025	5

**BINDING POST; GOLD PLT. (BROWN)**

Pomona Electronics

BINDING POST; GOLD PLT. (BROWN)

Part Number	Weight	Min. Quantity
3750-1	N-A	5

**BINDING POST; GOLD PLT (RED)**

Pomona Electronics

8-32 Thread Post, 1 $\frac{1}{4}$ in. Mounting Hole Size, Thread Size 8-32, Standard Binding Posts Accepts standard banana plug. Thin line design for high-density packaging. Nickel plated 8-32 hex nut and lockwasher included. 2.54 mm (0.100) dia. cross hole is perpendicular with flat on insulator. Mounts

Part Number	Weight	Min. Quantity
3750-2	0.025	5

**BINDING POST; GOLD PLT. (ORANGE)**

Pomona Electronics

Standard Binding Post, 15 A Rated Current, 2500 V (RMS) Rated Voltage, Brass Body Material Accepts standard banana plug, wire or spade lug Mounts in panels from 0.070 in. to 0.250 in. thick. Nickel plated steel lockwasher. Polycarbonate insulation material.

Part Number	Weight	Min. Quantity
3750-3	0.025	5

**BINDING POST; GOLD PLT. (YELLOW)**

Pomona Electronics

Model 3750 Standard Binding Post Accepts standard banana plug, wire or spade lug Mounts in panels from 0.070 in. to 0.250 in. thick (1.77mm to 6.35 mm) thick Hands free usage in controlled voltage environments: 2500 V (RMS) maximum.

Part Number	Weight	Min. Quantity
3750-4	0.025	5

**BINDING POST; GOLD PLT. (GREEN)**

Pomona Electronics

Model 3750 Standard Binding Post Accepts standard banana plug, wire or spade lug Mounts in panels from 0.070 in. to 0.250 in. thick (1.77mm to 6.35 mm) thick Hands free usage in controlled voltage environments: 2500 V (RMS) maximum.

Part Number	Weight	Min. Quantity
3750-5	0.025	5

**BINDING POST; GOLD PLT. (BLUE)**

Pomona Electronics

Model 3750 Standard Binding Post Accepts standard banana plug, wire or spade lug Mounts in panels from 0.070 in. to 0.250 in. thick (1.77mm to 6.35 mm) thick Hands free usage in controlled voltage environments: 2500 V (RMS) maximum.

Part Number	Weight	Min. Quantity
3750-6	0.025	5

**BINDING POST; GOLD PLT. (VIOLET)**

Pomona Electronics

Part Number	Weight	Min. Quantity
3750-7	0.025	5

3760-1 – BINDING POST; TIN PLT.(BROWN)

**BINDING POST; GOLD PLT. (GRAY)****Pomona Electronics**

BINDING POST; GOLD PLT. (GRAY)

Part Number	Weight	Min. Quantity
3750-8	0.0246	5

**BINDING POST; GOLD PLT. (WHITE)****Pomona Electronics**

Model 3750 Standard Binding Post Accepts standard banana plug, wire or spade lug Mounts in panels from .070" to .250" (1.77mm to 6.35 mm) thick Hands free usage in controlled voltage environments: 2500 V (RMS) maximum.

Part Number	Weight	Min. Quantity
3750-9	N-A	5

**SHIELDED BOX; MINIATURE WITH TWO BNC...****Pomona Electronics**

Aluminum Box with Cover BNC Female to BNC Male Connectors 50 Ohms nominal impedance Coax Connectors Are 50 Ohm Nominal Impedance Boxes with Connectors Are Rated at 500 VRMS Max., +150°C (+302°F) Max. Except for Model 2399 Which Is Rated at 335 VRMS Max. and Model 2411 Which Is Rated at 1000

Part Number	Weight	Min. Quantity
3751	0.5	2

**SHIELDED BOX; MINIATURE WITH BNC (M...****Pomona Electronics**

Aluminum Box with Cover BNC Female to BNC Male Connectors 50 Ohms nominal impedance Pan head self-tapping steel screws Coax Connectors Are 50 Ohm Nominal Impedance Boxes with Connectors Are Rated at 500 VRMS Max., +150°C (+302°F) Max. Except for Model 2399 Which Is Rated at 335 VRMS Max. and

Part Number	Weight	Min. Quantity
3752	0.05	2

**SHIELDED BOX****Pomona Electronics**

Miniature Size Aluminum Box with Cover, Blue Baked Enamel Finish Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are aluminum 1100-H14 with

Part Number	Weight	Min. Quantity
3753	0.06	2

**SHIELDED BOX****Pomona Electronics**

SHIELDED BOX

Part Number	Weight	Min. Quantity
3753#	N-A	500

**SHIELDED BOX****Pomona Electronics**

Miniature Size Aluminum Box with Cover, Tarnish Resistant Plating Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are aluminum 1100-H14 with

Part Number	Weight	Min. Quantity
3754	0.06	2

**BINDING POST; TIN PLT.(BLACK)****Pomona Electronics**

8-32 Thread Post, 1/4 in. Mounting Hole Size, Thread Size 8-32, Standard Binding Posts Accepts standard banana plug. Thin line design for high-density packaging. Nickel plated 8-32 hex nut and lockwasher included. 2.54 mm (0.100) dia. cross hole is perpendicular with flat on insulator. Mounts

Part Number	Weight	Min. Quantity
3760-0	0.025	5

**BINDING POST; TIN PLT (BLACK)****Pomona Electronics**

BINDING POST; TIN PLT (BLACK)

Part Number	Weight	Min. Quantity
3760-0#	N-A	500

**BINDING POST; TIN PLT.(BROWN)****Pomona Electronics**

BINDING POST; TIN PLT.(BROWN)

Part Number	Weight	Min. Quantity
3760-1	N-A	5



3760-2 – BINDING POST; TIN PLT. (RED)

**BINDING POST; TIN PLT. (RED)****Pomona Electronics**

8-32 Thread Post, 1¼ in. Mounting Hole Size, Thread Size 8-32, Standard Binding Posts Accepts standard banana plug. Thin line design for high-density packaging. Nickel plated 8-32 hex nut and lockwasher included. 2.54 mm (0.100) dia. cross hole is perpendicular with flat on insulator. Mounts

Part Number	Weight	Min. Quantity
3760-2	0.025	5

**BINDING POST; TIN PLT; (RED)****Pomona Electronics**

BINDING POST; TIN PLT; (RED)

Part Number	Weight	Min. Quantity
3760-2#	N-A	500

**BINDING POST; TIN PLT; (GREEN)****Pomona Electronics**

BINDING POST; TIN PLT; (GREEN)

Part Number	Weight	Min. Quantity
3760-5#	N-A	500

**BINDING POST; TIN PLT. (BLUE)****Pomona Electronics**

Part Number	Weight	Min. Quantity
3760-6	0.025	5

**BINDING POST; TIN PLT. (ORANGE)****Pomona Electronics**

BINDING POST; TIN PLT. (ORANGE)

Part Number	Weight	Min. Quantity
3760-3	0.025	5

**BINDING POST; TIN PLT. (VIOLET)****Pomona Electronics**

Part Number	Weight	Min. Quantity
3760-7	0.025	5

**BINDING POST; TIN PLT.(YELLOW)****Pomona Electronics**

Part Number	Weight	Min. Quantity
3760-4	0.025	5

**BINDING POST; TIN PLT. (GRAY)****Pomona Electronics**

BINDING POST; TIN PLT. (GRAY)

Part Number	Weight	Min. Quantity
3760-8	N-A	5

**BINDING POST; TIN PLT. (GREEN)****Pomona Electronics**

8-32 Thread Post, 1¼ in. Mounting Hole Size, Thread Size 8-32, Standard Binding Posts Accepts standard banana plug. Thin line design for high-density packaging. Nickel plated 8-32 hex nut and lockwasher included. 2.54 mm (0.100) dia. cross hole is perpendicular with flat on insulator. Mounts

Part Number	Weight	Min. Quantity
3760-5	0.025	5

**BINDING POST; TIN PLT. (WHITE)****Pomona Electronics**

BINDING POST; TIN PLT. (WHITE)

Part Number	Weight	Min. Quantity
3760-9	0.025	5



3782-12-5 – MINIGRABBER/BANANA PLUG (GREEN)

BINDING POST; MICROVOLT (BLACK)**Pomona Electronics**

8-32 Thread Post, 1¼ in. Mounting Hole Size, Thread Size 8-32, Standard Binding Posts Accepts standard banana plug. Thin line design for high-density packaging. Nickel plated 8-32 hex nut and lockwasher included. 2.54 mm (0.100) dia. cross hole is perpendicular with flat on insulator. Mounts

Part Number	Weight	Min. Quantity
3770-0	0.02	5

BINDING POST; MICROVOLT (BLACK)**Pomona Electronics**

BINDING POST; MICROVOLT (BLACK)

Part Number	Weight	Min. Quantity
3770-0#	N-A	500

BINDING POST; MICROVOLT (RED)**Pomona Electronics**

8-32 Thread Post, 1¼ in. Mounting Hole Size, Thread Size 8-32, Standard Binding Posts Accepts standard banana plug. Thin line design for high-density packaging. Nickel plated 8-32 hex nut and lockwasher included. 2.54 mm (0.100) dia. cross hole is perpendicular with flat on insulator. Mounts

Part Number	Weight	Min. Quantity
3770-2	0.025	5

BINDING POST; MICROVOLT (RED)**Pomona Electronics**

BINDING POST; MICROVOLT (RED)

Part Number	Weight	Min. Quantity
3770-2#	N-A	500

BANANA JACK/SPADE LUG #8-10 (BLAC...**Pomona Electronics**

Brass per QQ-B-626, Alloy 360, 1¼2 Hard Body, Adapter Spade Lug To Banana Jack Permits single banana plug to be used with equipment having barrier strips. Lugs fit a no. 8 or 10 screw. Banana jack — 4.2 (0.166) dia., brass, nickel plated. Insulation: ABS. 0.8 (0.03) thick spade lug. Copp

Part Number	Weight	Min. Quantity
3777A-0	0.0062	5

BANA JACK/SPADE LUG #8-10 SET (1BLK...**Pomona Electronics**

BANA JACK/SPADE LUG #8-10 SET (1BLK; 1RED)

Part Number	Weight	Min. Quantity
3777A-02	0.0154	5

BANANA JACK/SPADE LUG #8-10 (RED)**Pomona Electronics**

Brass per QQ-B-626, Alloy 360, 1¼2 Hard Body, Adapter Spade Lug To Banana Jack Permits single banana plug to be used with equipment having barrier strips. Lugs fit a no. 8 or 10 screw. Banana jack — 4.2 (0.166) dia., brass, nickel plated. Insulation: ABS. 0.8 (0.03) thick spade lug. Copp

Part Number	Weight	Min. Quantity
3777A-2	0.0098	5

MINIGRABBER/BANANA PLUG (RED)**Pomona Electronics**

MINIGRABBER/BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
3782-12-2	0.5	5

MINIGRABBER/BANANA PLUG (YELLOW)**Pomona Electronics**

MINIGRABBER/BANANA PLUG (YELLOW)

Part Number	Weight	Min. Quantity
3782-12-4	0.5	5

MINIGRABBER/BANANA PLUG (GREEN)**Pomona Electronics**

MINIGRABBER/BANANA PLUG (GREEN)

Part Number	Weight	Min. Quantity
3782-12-5	0.5	5

3782-12-6 – MINIGRABBER/BANANA PLUG (BLUE)

**MINIGRABBER/BANANA PLUG (BLUE)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (BLUE)

Part Number	Weight	Min. Quantity
3782-12-6	0.5	5

**MINIGRABBER/BANANA PLUG (BLACK)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
3782-36-0#	N-A	500

**MINIGRABBER/BANANA PLUG (SET)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (SET)

Part Number	Weight	Min. Quantity
3782-24-02	0.5	5

**MINIGRABBER/BANANA PLUG (SET)**

Pomona Electronics

Part Number	Weight	Min. Quantity
3782-36-02	0.5	5

**MINIGRABBER/BANANA PLUG (YELLOW)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (YELLOW)

Part Number	Weight	Min. Quantity
3782-24-4	0.5	5

**MINIGRABBER/BANANA PLUG (RED)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
3782-36-2#	N-A	500

**MINIGRABBER/BANANA PLUG (GREEN)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (GREEN)

Part Number	Weight	Min. Quantity
3782-24-5	0.5	5

**MINIGRABBER/BANANA PLUG (YELLOW)**

Pomona Electronics

Part Number	Weight	Min. Quantity
3782-36-4	0.044	5

**MINIGRABBER/BANANA PLUG (BLUE)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (BLUE)

Part Number	Weight	Min. Quantity
3782-24-6	0.5	5

**MINIGRABBER/BANANA PLUG (GREEN)**

Pomona Electronics

Part Number	Weight	Min. Quantity
3782-36-5	0.5	5

3839 – DUST CAP; BNC (F)

**MINIGRABBER/BANANA PLUG (BLUE)**

Pomona Electronics

Part Number	Weight	Min. Quantity
3782-36-6	0.5	5

**MINIGRABBER/BANANA PLUG (GREEN)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (GREEN)

Part Number	Weight	Min. Quantity
3782-60-5	0.0564	5

**MINIGRABBER/BANANA PLUG (YELLOW)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (YELLOW)

Part Number	Weight	Min. Quantity
3782-48-4	0.5	5

**MINIGRABBER/BANANA PLUG (BLUE)**

Pomona Electronics

Part Number	Weight	Min. Quantity
3782-60-6	0.05	5

**MINIGRABBER/BANANA PLUG (GREEN)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (GREEN)

Part Number	Weight	Min. Quantity
3782-48-5	0.5	5

**SPLICE; PIN TIP PLUG/BANANA (BLACK...**

Pomona Electronics

SPLICE; PIN TIP PLUG/BANANA (BLACK)

Part Number	Weight	Min. Quantity
3834-0	0.5	5

**MINIGRABBER/BANANA PLUG (BLUE)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (BLUE)

Part Number	Weight	Min. Quantity
3782-48-6	0.055	5

**SPLICE; PIN TIP PLUG TO BANANA PLUG...**

Pomona Electronics

SPLICE; PIN TIP PLUG TO BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
3834-0#	N-A	500

**MINIGRABBER/BANANA PLUG (YELLOW)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (YELLOW)

Part Number	Weight	Min. Quantity
3782-60-4	0.5	5

**DUST CAP; BNC (F)**

Pomona Electronics

BNC Cap for Female with Bead Chain Protect sensitive instrument inputs Non-shorting Tarnish resistant plating Brass body material.

Part Number	Weight	Min. Quantity
3839	0.5	5

3842 – ADAPTER;N(M);N(M)

**ADAPTER;N(M);N(M)****Pomona Electronics**

N (Male) to N (Male) Adapter, 1000 V (RMS) Operating Voltage, Brass Body Material The nominal length of the adapter is 1.59 in. The contact material of the adapter is gold plated brass.

Part Number	Weight	Min. Quantity
3842	0.5	5

**TRPL BNDPOST MTG BASE 10/PKG (BL...****Pomona Electronics**

TRPL BNDPOST MTG BASE 10/PKG (BLACK)

Part Number	Weight	Min. Quantity
3863-0	N-A	1

**PLASTIC BOX (BLACK)****Pomona Electronics**

Part Number	Weight	Min. Quantity
3850-0	0.5	2

**DBL BANANA; COILED MIC CBL****Pomona Electronics**

Part Number	Weight	Min. Quantity
3864-48	0.18	2

**PLASTIC BOX (BLUE)****Pomona Electronics**

Part Number	Weight	Min. Quantity
3850-6	0.5	2

**DBL BANANA; COILED MIC CBL****Pomona Electronics**

Part Number	Weight	Min. Quantity
3864-72	0.17	2

**DBL BNDPOST MTG BASE 10/PKG (BLAC...****Pomona Electronics**

Part Number	Weight	Min. Quantity
3862-0	0.05	1

**PIN TIP PLUGS TO BNC (M)****Pomona Electronics**

PIN TIP PLUGS TO BNC (M)

Part Number	Weight	Min. Quantity
3901	0.5	5

**DBL BNDPOST MTG BASE (BLACK)****Pomona Electronics**

DBL BNDPOST MTG BASE (BLACK)

Part Number	Weight	Min. Quantity
3862-0#	N-A	500

**MINIGRABBER (BLACK)****Pomona Electronics**

MINIGRABBER (BLACK)

Part Number	Weight	Min. Quantity
3925-0#_BULK	N-A	500

4022-0 – MINI B-JACK 10/PKG (BLACK)

**MINIGRABBER 10/PKG (BROWN)**

Pomona Electronics

MINIGRABBER 10/PKG (BROWN)

Part Number	Weight	Min. Quantity
3925-1	0.075	1

**MINIGRABBER 10/PKG (WHITE)**

Pomona Electronics

Part Number	Weight	Min. Quantity
3925-9	0.5	1

**MINIGRABBER; (BROWN)**

Pomona Electronics

MINIGRABBER; (BROWN)

Part Number	Weight	Min. Quantity
3925-1#	N-A	500

**BANANA JACK; .025 SQ PIN 10/PK (BL...**

Pomona Electronics

BANANA JACK; .025 SQ PIN 10/PK (BLACK)

Part Number	Weight	Min. Quantity
4005-0	0.12	1

**MINIGRABBER 10/PKG (BLUE)**

Pomona Electronics

MINIGRABBER 10/PKG (BLUE)

Part Number	Weight	Min. Quantity
3925-6	0.5	1

**BANANA JACK; .025 SQ PIN (BLACK)**

Pomona Electronics

BANANA JACK; .025 SQ PIN (BLACK)

Part Number	Weight	Min. Quantity
4005-0#	N-A	500

**MINIGRABBER 10/PKG (VIOLET)**

Pomona Electronics

MINIGRABBER 10/PKG (VIOLET)

Part Number	Weight	Min. Quantity
3925-7	0.075	1

**BANANA JACK; .025 SQ PIN (RED) 10/...**

Pomona Electronics

BANANA JACK; .025 SQ PIN (RED) 10/PKG

Part Number	Weight	Min. Quantity
4005-2	0.5	1

**MINIGRABBER 10/PKG (GRAY)**

Pomona Electronics

MINIGRABBER 10/PKG (GRAY)

Part Number	Weight	Min. Quantity
3925-8	N-A	1

**MINI B-JACK 10/PKG (BLACK)**

Pomona Electronics

MINI B-JACK 10/PKG (BLACK)

Part Number	Weight	Min. Quantity
4022-0	0.5	1

4022-2 – MINI B-JACK (RED) 10/PKG

**MINI B-JACK (RED) 10/PKG****Pomona Electronics**

MINI B-JACK (RED) 10/PKG

Part Number	Weight	Min. Quantity
4022-2	N-A	1

**ADAPTER;BNC(M);PHONO JACK****Pomona Electronics**

BNC Male to 2 Conductor Standard Phone Jack Adapter, 500 V (RMS) Operating Voltage Permits a standard 2 conductor 0.250" Dia. phone plug to be used with equipment having BNC female All metal construction to insure proper shielding Rating: 500 V RMS, +257deg;F (+125deg;C) Max. Convert 2 Cond

Part Number	Weight	Min. Quantity
4043	0.5	2

**PHONE JACK/DBL BANANA****Pomona Electronics**

Brass Per QQ-B-626, Alloy 360, 1½ Hard Body, Adapter - Phone Jack To Double Banana Plug Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line include

Part Number	Weight	Min. Quantity
4044	0.5	2

**PHONE JACK/DBL BANANA****Pomona Electronics**

PHONE JACK/DBL BANANA

Part Number	Weight	Min. Quantity
4044#	N-A	500

**PHONO JACK/BNC (M)****Pomona Electronics**

PHONO JACK/BNC (M)

Part Number	Weight	Min. Quantity
4054#	N-A	500

**ATTEN;COAX;BNC(M);BNC(F);50 OHM;14D...****Pomona Electronics**

Attenuator, Operating Temperature -55 to +102 deg;C, Nominal Impedance 50 Ohms, Beryllium Copper

Part Number	Weight	Min. Quantity
4108-14DB	N-A	1

**ATTEN;COAX;BNC(M);BNC(F);50 OHM;20D...****Pomona Electronics**

Brass Body, 2 W @ +70deg;C, BNC 50 Ohms Attenuator & Kits Use to attenuate signals in coaxial lines

Part Number	Weight	Min. Quantity
4108-20DB	N-A	1

**ATTEN;COAX;BNC(M);BNC(F);50 OHM;6DB****Pomona Electronics**

Attenuator, Operating Temperature -55 to +102 deg;C, Nominal Impedance 50 Ohms, Beryllium Copper

Part Number	Weight	Min. Quantity
4108-6DB	0.5	1

**SHORTING LINK 10/PKG****Pomona Electronics**

Part Number	Weight	Min. Quantity
4115	0.5	1

**D-I-Y MINIGRABBER (2 PCS OF 3925 - ...****Pomona Electronics**

Part Number	Weight	Min. Quantity
4176-02	0.5	5

4274-36-2 – BANANA PLUG/FUSE HOLDER (RED)

**SHIELDED BOX****Pomona Electronics**

Enclosure, Binding Head Screw Type, Die Cast Aluminum Body Material Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are aluminum 1100-H14 w

Part Number	Weight	Min. Quantity
4226	1.5	2

**BINDING POST; BLACK****Pomona Electronics**

30 VAC&frac{1}{2};60 VDC (Max.) Voltage Rating, 15 A, Double Binding Post Assemblys Nickel-plated 8-32 hex nut and lockwasher included. One red and one black tin plated binding post (type 3760) with double mounting base. Material: Double binding post with captive thumb nut — Brass. Accepts standard

Part Number	Weight	Min. Quantity
4243-0	0.5	5

**BINDING POST (BLACK)****Pomona Electronics**

BINDING POST (BLACK)

Part Number	Weight	Min. Quantity
4243-0#	N-A	500

**BINDING POST; RED****Pomona Electronics**

30 VAC&frac{1}{2};60 VDC (Max.) Voltage Rating, 15 A, Double Binding Post Assemblys Nickel-plated 8-32 hex nut and lockwasher included. One red and one black tin plated binding post (type 3760) with double mounting base. Material: Double binding post with captive thumb nut — Brass. Accepts standard

Part Number	Weight	Min. Quantity
4243-2	0.5	5

**COVER****Pomona Electronics**

COVER

Part Number	Weight	Min. Quantity
4245	N-A	5

**COVER****Pomona Electronics**

COVER

Part Number	Weight	Min. Quantity
4246	N-A	5

**COVER****Pomona Electronics**

Part Number	Weight	Min. Quantity
4247	N-A	5

**COVER****Pomona Electronics**

COVER

Part Number	Weight	Min. Quantity
4248	N-A	5

**BANANA PLUG/FUSE HOLDER (BLACK)****Pomona Electronics**

Part Number	Weight	Min. Quantity
4274-36-0	0.08	5

**BANANA PLUG/FUSE HOLDER (RED)****Pomona Electronics**

Part Number	Weight	Min. Quantity
4274-36-2	0.4	5

4279-12 – BANTAM PHONE PLUGS

**BANTAM PHONE PLUGS****Pomona Electronics**

PVC Insulation, 22 AWG, 7 x 30 Stranding, 300 VRMS, Bantam Plug Cable Assembly Rating: 300 V RMS, +50°C (+122°F) max. Cable Type: 2 cond. shielded twisted pair, 0.180" O.D.

Part Number	Weight	Min. Quantity
4279-12	N-A	2

**BANTAM PHONE PLUGS****Pomona Electronics**

PVC Insulation, 22 AWG, 7 x 30 Stranding, 300 VRMS, Bantam Plug Cable Assembly Rating: 300 V RMS, +50°C (+122°F) max. Cable Type: 2 cond. shielded twisted pair, 0.180" O.D.

Part Number	Weight	Min. Quantity
4279-24	0.07	2

**BANTAM PHONE PLUGS****Pomona Electronics**

PVC Insulation, 22 AWG, 7 x 30 Stranding, 300 VRMS, Bantam Plug Cable Assembly Rating: 300 V RMS, +50°C (+122°F) max. Cable Type: 2 cond. shielded twisted pair, 0.180" O.D.

Part Number	Weight	Min. Quantity
4279-36	N-A	2

**BANTAM PHONE PLUGS****Pomona Electronics**

PVC Insulation, 22 AWG, 7 x 30 Stranding, 300 VRMS, Bantam Plug Cable Assembly Rating: 300 V RMS, +50°C (+122°F) max. Cable Type: 2 cond. shielded twisted pair, 0.180" O.D.

Part Number	Weight	Min. Quantity
4279-48	0.5	2

**BANTAM PHONE PLUGS****Pomona Electronics**

PVC Insulation, 22 AWG, 7 x 30 Stranding, 300 VRMS, Bantam Plug Cable Assembly Rating: 300 V RMS, +50°C (+122°F) max. Cable Type: 2 cond. shielded twisted pair, 0.180" O.D.

Part Number	Weight	Min. Quantity
4279-60	0.5	2

**BANTAM PHONE PLUGS****Pomona Electronics**

PVC Insulation, 22 AWG, 7 x 30 Stranding, 300 VRMS, Bantam Plug Cable Assembly Bantam plugs are molded directly to the cable for optimum durability

Part Number	Weight	Min. Quantity
4279-72	0.5	2

**PJ051/BANTAM PHONE PLUGS****Pomona Electronics****PJ051/BANTAM PHONE PLUGS**

Part Number	Weight	Min. Quantity
4280-48	N-A	1

**PJ051/BANTAM PHONE PLUGS****Pomona Electronics**

Bantam Miniature Phone Plug, PVC Insulation Material, 0.18 in. Outer Diameter Shielded cable to reduce noise WE-310 and bantam plugs molded to the cable for optimum durability Plug operating voltage 300 V (RMS) (Max.).

Part Number	Weight	Min. Quantity
4280-60	N-A	1

**PJ051/BANTAM PHONE PLUGS****Pomona Electronics****PJ051/BANTAM PHONE PLUGS**

Part Number	Weight	Min. Quantity
4280-60#	N-A	500

**BANTAM/310 CABLE****Pomona Electronics****BANTAM/310 CABLE**

Part Number	Weight	Min. Quantity
4280N-36	0.5	1

4513# – MINI B-PLUG 4-40X.480

**BANTAM/DBL BANANA SHIELDED****Pomona Electronics**

Features Shielded cable to reduce noise Provides quick access from Bantam Jack to Terminals Bantam Plus is molded to the cable to provide optimum durability

Part Number	Weight	Min. Quantity
4281-60	N-A	1

**ECO/PSMA (F)/BNC (F)****Pomona Electronics**

Adapter, SMA Female To BNC Female, Gold Plated Beryllium Copper Body, 50 Ohms Impedance SMA female adapter for use with BNC female, gold plated beryllium copper body with 50 Ohms Impedance.

Part Number	Weight	Min. Quantity
4291	0.065	5

**PLASTIC BOX (BLACK)****Pomona Electronics**

Part Number	Weight	Min. Quantity
4384-0	N-A	2

**PLASTIC BOX; (BLUE)****Pomona Electronics**

PLASTIC BOX; (BLUE)

Part Number	Weight	Min. Quantity
4384-6	N-A	2

**TRIAx (F); HERMETIC****Pomona Electronics**

Triaxial BNC Connector, 50 Ohms Impedance, Brass Body Material, Gold Contact Plating Mounts in panels up to 0.25 in. Hermetic seal-50 PSI differential pressure Leakage rate less than 10^{-7} cc/frac{sec} of tracer gas at one atmosphere

Part Number	Weight	Min. Quantity
4388	0.03	2

**TRIAx (F); HERMETIC; BULK****Pomona Electronics**

TRIAx (F); HERMETIC; BULK

Part Number	Weight	Min. Quantity
4388#	N-A	500

**COVER****Pomona Electronics**

COVER

Part Number	Weight	Min. Quantity
4416	N-A	2

**B-PLUG 8-32 X 5/8 10/PKG****Pomona Electronics**

B-PLUG 8-32 X 5/8 10/PKG

Part Number	Weight	Min. Quantity
4512	N-A	1

**MINI B-PLUG 4-40X.480 10/PKG****Pomona Electronics**

Miniature Banana Plug With Threaded Stud, Voltage Rating 2500 VDC Threaded stud for rapid mounting. Solder turret for attachment of wires. Furnished with nickel-plated 4-40 hex nut, unassembled. Material: Miniature banana plug body — Brass; Spring — one-piece heat-treated beryllium copper

Part Number	Weight	Min. Quantity
4513	0.027	1

**MINI B-PLUG 4-40X.480****Pomona Electronics**

MINI B-PLUG 4-40X.480

Part Number	Weight	Min. Quantity
4513#	N-A	500



4521-0#_BULK – CLIP,HOOK,W/0.025 PIN INTERFACE, (B...

**CLIP,HOOK,W/0.025 PIN INTERFACE, (B...**

Pomona Electronics

CLIP,HOOK,W/0.025 PIN INTERFACE, (BLACK)

Part Number	Weight	Min. Quantity
4521-0#_BULK	N-A	500

**MINIGRABBER PACK (BLACK)**

Pomona Electronics

MINIGRABBER PACK (BLACK)

Part Number	Weight	Min. Quantity
4555-0#	N-A	500

**CLIP,HOOK,W/0.025 PIN INTERFACE, (R...**

Pomona Electronics

CLIP,HOOK,W/0.025 PIN INTERFACE, (RED)

Part Number	Weight	Min. Quantity
4521-2#_BULK	N-A	500

**MINIGRABBER PACK (RED)**

Pomona Electronics

MINIGRABBER PACK (RED)

Part Number	Weight	Min. Quantity
4555-2#	N-A	500

**PIN TIP JACK (BLACK)**

Pomona Electronics

Pin Tip, Double; Black; 5 A; 1500 VDC; Gold Plated Brass H.H., Alloy 360

Part Number	Weight	Min. Quantity
4543-0	0.01	5

**ADAPTER;BNC(F);PWB PINS**

Pomona Electronics

BNC Connector, 50 Ohms (Nom.) Impedance, Gold Contact Plating
Brass body material Beryllium copper contact material.

Part Number	Weight	Min. Quantity
4578	0.8	5

**PIN TIP JACK (BLACK)**

Pomona Electronics

PIN TIP JACK (BLACK)

Part Number	Weight	Min. Quantity
4543-0#	N-A	500

**ADAPTER,BNC(F),PWB PINS**

Pomona Electronics

ADAPTER,BNC(F),PWB PINS

Part Number	Weight	Min. Quantity
4578#_BULK	N-A	500

**PIN TIP JACK (RED)**

Pomona Electronics

Pin Tip, Double; Red; 5 A; 1500 VDC; Gold Plated Brass H.H., Alloy 360

Part Number	Weight	Min. Quantity
4543-2	0.01	5

**TRPL B-JACK MNTNG BASE 10/PKG (BLA...**

Pomona Electronics

Part Number	Weight	Min. Quantity
4590-0	N-A	1

4619-0 – DBL MIN B-JACK MTG BASE 10/PKG (BL...

**TRPL B-JACK MNTNG BASE (BLACK)**

Pomona Electronics

TRPL B-JACK MNTNG BASE (BLACK)

Part Number	Weight	Min. Quantity
4590-0#	N-A	500

**MINI B-PLUG (BLACK)**

Pomona Electronics

MINI B-PLUG (BLACK)

Part Number	Weight	Min. Quantity
4617-0	0.007	5

**TRIPLE BANANA JACK (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
4601-0	0.05	5

**MINI B-PLUG (BLACK)**

Pomona Electronics

MINI B-PLUG (BLACK)

Part Number	Weight	Min. Quantity
4617-0#	N-A	500

**TRIPLE BANANA JACK (RED)**

Pomona Electronics

TRIPLE BANANA JACK (RED)

Part Number	Weight	Min. Quantity
4601-2	0.05	5

**MINI B-PLUG (RED)**

Pomona Electronics

MINI B-PLUG (RED)

Part Number	Weight	Min. Quantity
4617-2	0.007	5

**TRPL MIN B-JACK MNT BASE 10/PKG (BL...**

Pomona Electronics

TRPL MIN B-JACK MNT BASE 10/PKG (BLACK)

Part Number	Weight	Min. Quantity
4614-0	0.01	1

**MINI B-PLUG (RED)**

Pomona Electronics

MINI B-PLUG (RED)

Part Number	Weight	Min. Quantity
4617-2#	N-A	500

**TRPL MIN B-JACK MNT BASE (BLACK)**

Pomona Electronics

TRPL MIN B-JACK MNT BASE (BLACK)

Part Number	Weight	Min. Quantity
4614-0#	N-A	500

**DBL MIN B-JACK MTG BASE 10/PKG (BL...**

Pomona Electronics

DBL MIN B-JACK MTG BASE 10/PKG (BLACK)

Part Number	Weight	Min. Quantity
4619-0	0.001	1

4653-0 – MINI BANANA PLUG (BLACK)

**MINI BANANA PLUG (BLACK)**

Pomona Electronics

MINI BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
4653-0	0.025	5

**TRIAx BULKHEAD (F)**

Pomona Electronics

TRIAx BULKHEAD (F)

Part Number	Weight	Min. Quantity
4661	N-A	1

**DBL B-JACK MTG BASE 10/PKG (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
4654-0	0.5	1

**BANANA PLUG/BANANA JACK (BLACK)**

Pomona Electronics

Stack-Up Banana Plug, 18 AWG Wire Size, 65 x 36 Stranding, 15 A (Continuous) Current Rating Dual purpose. Insulates all hot leads when used as an extension cord. Endless extension couplings possible with any banana plug patch cord. 1st End: Banana plug. Brass body, beryllium copper spring, nickel pl

Part Number	Weight	Min. Quantity
4702-24-0	0.035	5

**SHIELDED BOX**

Pomona Electronics

Enclosure, Pan Head Self Tapping Screw Type, Die Cast Aluminum Material Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are aluminum 1100-H

Part Number	Weight	Min. Quantity
4655	0.235	2

**BANANA PLUG/BANANA JACK (BLACK)**

Pomona Electronics

BANANA PLUG/BANANA JACK (BLACK)

Part Number	Weight	Min. Quantity
4702-24-0#	N-A	500

**SHIELDED BOX; BNC (F)**

Pomona Electronics

Coax Connectors Are 50 Ohm Nominal Impedance Boxes with Connectors Are Rated at 500 VRMS Max., +150°C (+302°F) Max. Except for Model 2399 Which Is Rated at 335 VRMS Max. and Model 2411 Which Is Rated at 1000 VRMS

Part Number	Weight	Min. Quantity
4656	0.315	2

**BANANA PLUG/BANANA JACK (RED)**

Pomona Electronics

Stack-Up Banana Plug, 18 AWG Wire Size, 65 x 36 Stranding, 15 A (Continuous) Current Rating Dual purpose. Insulates all hot leads when used as an extension cord. Endless extension couplings possible with any banana plug patch cord. 1st End: Banana plug. Brass body, beryllium copper spring, nickel pl

Part Number	Weight	Min. Quantity
4702-24-2	0.06	5

**COVER**

Pomona Electronics

COVER

Part Number	Weight	Min. Quantity
4658	N-A	2

**BANANA PLUG/BANANA JACK (RED)**

Pomona Electronics

BANANA PLUG/BANANA JACK (RED)

Part Number	Weight	Min. Quantity
4702-24-2#	N-A	500

4741-24-0 – .025 SQ RECEPTACLE (BLACK)

**BANANA PLUG/BANANA JACK (BLACK)****Pomona Electronics**

Stack-Up Banana Plug, 18 AWG Wire Size, 65 x 36 Stranding, 15 A (Continuous) Current Rating Dual purpose. Insulates all hot leads when used as an extension cord. Endless extension couplings possible with any banana plug patch cord. 1st End: Banana plug. Brass body, beryllium copper spring, nickel pl

Part Number	Weight	Min. Quantity
4702-36-0	0.075	5

**BANANA PLUG/BANANA JACK (RED)****Pomona Electronics**

Stack-Up Banana Plug, 18 AWG Wire Size, 65 x 36 Stranding, 15 A (Continuous) Current Rating Dual purpose. Insulates all hot leads when used as an extension cord. Endless extension couplings possible with any banana plug patch cord. 1st End: Banana plug. Brass body, beryllium copper spring, nickel pl

Part Number	Weight	Min. Quantity
4702-36-2	0.075	5

**BANANA PLUG/BANANA JACK (BLACK)****Pomona Electronics**

Stack-Up Banana Plug, 18 AWG Wire Size, 65 x 36 Stranding, 15 A (Continuous) Current Rating Dual purpose. Insulates all hot leads when used as an extension cord. Endless extension couplings possible with any banana plug patch cord. 1st End: Banana plug. Brass body, beryllium copper spring, nickel pl

Part Number	Weight	Min. Quantity
4702-48-0	0.085	5

**BANANA PLUG/BANANA JACK (RED)****Pomona Electronics**

Stack-Up Banana Plug, 18 AWG Wire Size, 65 x 36 Stranding, 15 A (Continuous) Current Rating Dual purpose. Insulates all hot leads when used as an extension cord. Endless extension couplings possible with any banana plug patch cord. 1st End: Banana plug. Brass body, beryllium copper spring, nickel pl

Part Number	Weight	Min. Quantity
4702-48-2	0.085	5

**MINIGRABBER W/BAN JACK (BLACK)****Pomona Electronics**

MINIGRABBER W/BAN JACK (BLACK)

Part Number	Weight	Min. Quantity
4723-0#	N-A	500

**TRIAx; 2-LUG/ALLIG CL****Pomona Electronics**

Part Number	Weight	Min. Quantity
4725	0.25	1

**COVER****Pomona Electronics**

COVER

Part Number	Weight	Min. Quantity
4726	N-A	2

**.025 SQ RECEPTACLE (BLACK)****Pomona Electronics**

Square Pin Receptacle Patch Cord, Phosphor Bronze Body, 22 AWG Wire Size Wire: 22 AWG, 0.064" O.D. Rating: 45 VAC/60 VDC; 3 amps; +50°C max.

Part Number	Weight	Min. Quantity
4741-12-0	0.5	5

**.025 SQ RECEPTACLE (RED)****Pomona Electronics**

.025 SQ RECEPTACLE (RED)

Part Number	Weight	Min. Quantity
4741-12-2	0.01	5

**.025 SQ RECEPTACLE (BLACK)****Pomona Electronics**

Square Pin Receptacle Patch Cord, Phosphor Bronze Body, 22 AWG Wire Size Wire: 22 AWG, 0.064" O.D. Rating: 45 VAC/60 VDC; 3 amps; +50°C max.

Part Number	Weight	Min. Quantity
4741-24-0	0.014	5



4741-24-2 – .025 SQ RECEPTACLE (RED)

**.025 SQ RECEPTACLE (RED)****Pomona Electronics**

Square Pin Receptacle Patch Cord, Phosphor Bronze Body, 22 AWG Wire Size Wire: 22 AWG, 0.064" O.D. Rating: 45 VAC/60 VDC; 3 amps; +50°C max.

Part Number	Weight	Min. Quantity
4741-24-2	0.014	5

**.025 SQ RECEPTACLE (BLACK)****Pomona Electronics**

Square Pin Receptacle Patch Cord, Phosphor Bronze Body, 22 AWG Wire Size Wire: 22 AWG, 0.064" O.D. Rating: 45 VAC/60 VDC; 3 amps; +50°C max.

Part Number	Weight	Min. Quantity
4741-6-0	0.5	5

**.025 SQ RECEPTACLE (RED)****Pomona Electronics**

.025 SQ RECEPTACLE (RED)

Part Number	Weight	Min. Quantity
4741-6-2	0.5	5

**.025 SQ RECEPTACLE (RED)****Pomona Electronics**

.025 SQ RECEPTACLE (RED)

Part Number	Weight	Min. Quantity
4741-6-2#	N-A	500

**COVER****Pomona Electronics**

COVER

Part Number	Weight	Min. Quantity
4742	N-A	5

**DBL BANANA/GRABBER; RG174/U****Pomona Electronics**

DBL BANANA/GRABBER; RG174/U

Part Number	Weight	Min. Quantity
4768-K-24	0.5	2

**DBL BANANA/GRABBER; RG174/U****Pomona Electronics**

DBL BANANA/GRABBER; RG174/U

Part Number	Weight	Min. Quantity
4768-K-36	0.5	2

**DBL BANANA/GRABBER; RG174/U****Pomona Electronics**

Part Number	Weight	Min. Quantity
4768-K-48	0.085	2

**DBL BANANA/GRABBER; RG174/U****Pomona Electronics**

DBL BANANA/GRABBER; RG174/U

Part Number	Weight	Min. Quantity
4768-K-60	0.5	2

**SPRING LOADED BIND POST (BLACK)****Pomona Electronics**

SPRING LOADED BIND POST (BLACK)

Part Number	Weight	Min. Quantity
4770-0	N-A	2

4773-2# – PIN TIP JACK (RED)



SPRING LOADED BIND POST (RED)

Pomona Electronics
SPRING LOADED BIND POST (RED)

Part Number	Weight	Min. Quantity
4770-2	N-A	2



BANANA PLUG/.025 SQ RECEPT (BLACK)

Pomona Electronics
BANANA PLUG/.025 SQ RECEPT (BLACK)

Part Number	Weight	Min. Quantity
4771-84-0#	N-A	24



BANANA PLUG/.025 SQ RECEPT (BLACK)

Pomona Electronics
BANANA PLUG/.025 SQ RECEPT (BLACK)

Part Number	Weight	Min. Quantity
4771-24-0	0.0248	5



PIN TIP PLUG/.025 SQ RECEPT (BLACK...

Pomona Electronics
PIN TIP PLUG/.025 SQ RECEPT (BLACK)

Part Number	Weight	Min. Quantity
4772-24-0	0.5	5



BANANA PLUG/.025 SQ RECEPT (RED)

Pomona Electronics
BANANA PLUG/.025 SQ RECEPT (RED)

Part Number	Weight	Min. Quantity
4771-24-2	0.022	5



PIN TIP PLUG/.025 SQ RECEPT (RED)

Pomona Electronics
PIN TIP PLUG/.025 SQ RECEPT (RED)

Part Number	Weight	Min. Quantity
4772-24-2	0.016	5



BANANA PLUG/.025 SQ RECEPT (BLACK...

Pomona Electronics

Part Number	Weight	Min. Quantity
4771-36-0	0.5	5



PIN TIP JACK (BLACK)

Pomona Electronics
PIN TIP JACK (BLACK)

Part Number	Weight	Min. Quantity
4773-0#	N-A	500



BANANA PLUG/.025 SQ RECEPT (RED)

Pomona Electronics

Part Number	Weight	Min. Quantity
4771-36-2	0.5	5



PIN TIP JACK (RED)

Pomona Electronics
PIN TIP JACK (RED)

Part Number	Weight	Min. Quantity
4773-2#	N-A	500

4773-6# – PIN TIP JACK (BLUE)

**PIN TIP JACK (BLUE)**

Pomona Electronics

PIN TIP JACK (BLUE)

Part Number	Weight	Min. Quantity
4773-6#	N-A	500

**DBL BANANA PLUG HIGH TEMP (BLACK...**

Pomona Electronics

Stackable Double Banana Plug with Cable Guide, 15 A Current Rating
Simplified attachment of cables or small components by means of set screws
Banana plug spring is beryllium copper for long insertion life.

Part Number	Weight	Min. Quantity
4898-0	0.04	5

PIN TIP JACK (WHITE)

Pomona Electronics

PIN TIP JACK (WHITE)

Part Number	Weight	Min. Quantity
4773-9	0.5	5

**DBL BANANA PLUG HIGH TEMP (BLUE)**

Pomona Electronics

DBL BANANA PLUG HIGH TEMP (BLUE)

Part Number	Weight	Min. Quantity
4898-6	0.5	5

GRABBER/BNC (M); RG174/U

Pomona Electronics

GRABBER/BNC (M); RG174/U

Part Number	Weight	Min. Quantity
4777-K-48	N-A	2

**B-PLUG HIGH TEMP 10/PKG (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
4899-0	0.175	1

DBL BANANA PLUG; GOLD PL (BLACK)

Pomona Electronics

Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access panel or need a simple banana plug for a monitor. In the shop, lab, studi

Part Number	Weight	Min. Quantity
4892-0	0.5	5

**B-PLUG HIGH TEMP 10/PKG (BLUE)**

Pomona Electronics

B-PLUG HIGH TEMP 10/PKG (BLUE)

Part Number	Weight	Min. Quantity
4899-6	0.5	1

DBL BANANA PLUG; GOLD PL (RED)

Pomona Electronics

Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access panel or need a simple banana plug for a monitor. In the shop, lab, studi

Part Number	Weight	Min. Quantity
4892-2	0.035	5

**B-JACK HIGH TEMP 10/PKG (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
4900-0	0.14	1



JAN ELECTRONIC SUPPLIES, INC.

860-442-4386

4911A-48-0 – RETR. SHEATH BANANA PLUG (BLACK)

**B-JACK HIGH TEMP 10/PKG (BLUE)**

Pomona Electronics

Part Number	Weight	Min. Quantity
4900-6	0.14	1

**SHIELDED BOX**

Pomona Electronics

Enclosure, Die Cast Aluminum Material, Phillips Pan Head, Self-Tapping, Steel Screw Type Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers ar

Part Number	Weight	Min. Quantity
4903	0.5	2

**RETR. SHEATH BANANA PLUG (BLACK)**

Pomona Electronics

Stack-Up Banana Plug, 18 AWG Wire Size, 65 x 36 Stranding, 15 A (Continuous) Current Rating Wire: 18 AWG, 3.7 (0.144) O.D. Rating: 1000 V per IEC1010-2-031, 10 amps, +80°C (+176°F) max.

Part Number	Weight	Min. Quantity
4911A-12-0	0.06	5

**RETR. SHEATH BANANA PLUG (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
4911A-120-0	N-A	24

**RETR. SHEATH BANANA PLUG (RED)**

Pomona Electronics

Part Number	Weight	Min. Quantity
4911A-120-2	N-A	24

**RETR. SHEATH BANANA PLUG (BLACK)**

Pomona Electronics

Wire: 18 AWG, 3.7 mm (0.144") O.D. Rating: 1000 V per IEC1010-2-031, 10 amps, +80°C (+176°F) max.

Part Number	Weight	Min. Quantity
4911A-24-0	N-A	5

**RETR. SHEATH BANANA PLUG (RED)**

Pomona Electronics

Wire: 18 AWG, 3.7 mm (0.144") O.D. Rating: 1000 V per IEC1010-2-031, 10 amps, +80°C (+176°F) max.

Part Number	Weight	Min. Quantity
4911A-24-2	N-A	5

**RETR. SHEATH BANANA PLUG (BLACK)**

Pomona Electronics

Wire: 18 AWG, 3.7 mm (0.144") O.D. Rating: 1000 V per IEC1010-2-031, 10 amps, +80°C (+176°F) max.

Part Number	Weight	Min. Quantity
4911A-36-0	0.075	5

**RETR. SHEATH BANANA PLUG (RED)**

Pomona Electronics

Wire: 18 AWG, 3.7 mm (0.144") O.D. Rating: 1000 V per IEC1010-2-031, 10 amps, +80°C (+176°F) max.

Part Number	Weight	Min. Quantity
4911A-36-2	0.5	5

**RETR. SHEATH BANANA PLUG (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
4911A-48-0	0.097	5

4911A-48-2 – RETR. SHEATH BANANA PLUG (RED)

**RETR. SHEATH BANANA PLUG (RED)**

Pomona Electronics

Part Number	Weight	Min. Quantity
4911A-48-2	0.5	5

**RETR. SHEATH BANANA PLUG (BLACK)**

Pomona Electronics

Wire: 18 AWG, 3.7 mm (0.144") O.D. Rating: 1000 V per IEC1010-2-031, 10 amps, +80&deg;C (+176&deg;F) max.

Part Number	Weight	Min. Quantity
4911A-60-0	0.5	5

**RETR. SHEATH BANANA PLUG (RED)**

Pomona Electronics

Wire: 18 AWG, 3.7 mm (0.144") O.D. Rating: 1000 V per IEC1010-2-031, 10 amps, +80&deg;C (+176&deg;F) max.

Part Number	Weight	Min. Quantity
4911A-60-2	0.5	5

**SHEATHED BANANA 18;20;22AWG (BLACK)**

Pomona Electronics

Sheathed Banana Plug, 15 A Current Rating, Brass, Nickel Plated Body Heavy-duty plastic body withstands cracking if accidentally dropped Sheathed banana plug with threaded two piece design allows wires to be soldered or crimped to the banana plug.

Part Number	Weight	Min. Quantity
4933-0	0.012	5

**SHEATHED BAN 18;20;22AWG (BLACK)**

Pomona Electronics

SHEATHED BAN 18;20;22AWG (BLACK)

Part Number	Weight	Min. Quantity
4933-0#	N-A	500

**SHEATHED BANANA 18;20;22AWG (RED)**

Pomona Electronics

Sheathed Banana Plug, 15 A Current Rating, Brass, Nickel Plated Body Heavy-duty plastic body withstands cracking if accidentally dropped Sheathed banana plug with threaded two piece design allows wires to be soldered or crimped to the banana plug.

Part Number	Weight	Min. Quantity
4933-2	0.014	5

**SHEATHED JACK 18;20;22AWG (BLACK)**

Pomona Electronics

SHEATHED JACK 18;20;22AWG (BLACK)

Part Number	Weight	Min. Quantity
4934-0	0.013	5

**SHEATHED JACK 18;20;22AWG (BLACK)**

Pomona Electronics

SHEATHED JACK 18;20;22AWG (BLACK)

Part Number	Weight	Min. Quantity
4934-0#	N-A	500

**SHEATHED JACK 18;20;22AWG (RED)**

Pomona Electronics

SHEATHED JACK 18;20;22AWG (RED)

Part Number	Weight	Min. Quantity
4934-2	0.5	5

**SHEATHED JACK 18;20;22AWG (RED)**

Pomona Electronics

SHEATHED JACK 18;20;22AWG (RED)

Part Number	Weight	Min. Quantity
4934-2#	N-A	500

4997 – FIELD PLUG; BNC (M);RG58C/U

**TWINAX (M); RG108**

Pomona Electronics

TWINAX (M); RG108

Part Number	Weight	Min. Quantity
4957	N-A	2

**TWINAX BULKHEAD (F)**

Pomona Electronics

TWINAX BULKHEAD (F)

Part Number	Weight	Min. Quantity
4958	0.5	1

**SHEATHED BANANA; 14-16AWG (BLACK)**

Pomona Electronics

SHEATHED BANANA; 14-16AWG (BLACK)

Part Number	Weight	Min. Quantity
4986-0	0.5	5

**SHEATHED BANANA; 14-16AWG (RED)**

Pomona Electronics

SHEATHED BANANA; 14-16AWG (RED)

Part Number	Weight	Min. Quantity
4986-2	N-A	5

**PJ051/BANTAM JACK**

Pomona Electronics

Pomona Bantam Female to WE310 Male Adapter allows use of miniature phone plug patch cords to be used in equipment fitted with PJ-051 Jacks.

Part Number	Weight	Min. Quantity
4993	0.045	2

**BINDING POST; MIL-P-55149/8 (BLACK)**

Pomona Electronics

Overall Length 2 in., 5⅙in., Insulating Nylon, spring Loaded Binding Post Hex Shapes Meets MIL-P-55149/8. Silicone rubber O-rings provide water resistant seal when mounted in panels from 0.062" to 0.125" (15.75 mm to 3.18 mm) thick. Made of nickel-plated brass.

Part Number	Weight	Min. Quantity
4995-0	0.5	5

**BIND POST; MIL-P-55149/8 (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
4995-0#	N-A	500

**BINDING POST; MIL-P-55149/8 (RED)**

Pomona Electronics

Overall Length 2 in., 5⅙in., Insulating Nylon, spring Loaded Binding Post Hex Shapes Meets MIL-P-55149/8. Silicone rubber O-rings provide water resistant seal when mounted in panels from 0.062" to 0.125" (15.75 mm to 3.18 mm) thick. Made of nickel-plated brass.

Part Number	Weight	Min. Quantity
4995-2	0.5	5

**BINDING POST; MIL-P-55149/8 (RED)**

Pomona Electronics

Part Number	Weight	Min. Quantity
4995-2#	N-A	500

**FIELD PLUG; BNC (M);RG58C/U**

Pomona Electronics

FIELD PLUG; BNC (M);RG58C/U

Part Number	Weight	Min. Quantity
4997	0.04	5

5001_POM – BIND POST/BANTAM PLUG

**BIND POST/BANTAM PLUG****Pomona Electronics**

Binding Posts To Miniature (Bantam) Plug, Brass Per QQ-B-626, Alloy 360, 1½ Hard, Adapter Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're sett

Part Number	Weight	Min. Quantity
5001_POM	N-A	2

**HEX HEAD BIND POST (BLUE)****Pomona Electronics**

HEX HEAD BIND POST (BLUE)

Part Number	Weight	Min. Quantity
5018-6	0.041	5

**HEX HEAD BIND POST (BLACK)****Pomona Electronics**

Overall Length 2.07 in. (Open Max.), Gold Plated Brass, Hex Head Binding Posts Material: Binding post body, nuts, lockwasher — Gold plated. Meets MIL-P-55149/1A. Rating: 1500 V RMS, 30 amps, +80°C (+176°F) max.

Part Number	Weight	Min. Quantity
5018-0	0.042	5

**HEX HEAD BIND POST (WHITE)****Pomona Electronics**

Part Number	Weight	Min. Quantity
5018-9	0.5	5

**HEX HEAD BIND POST (RED)****Pomona Electronics**

Overall Length 2.07 in. (Open Max.), Gold Plated Brass, Hex Head Binding Posts Material: Binding post body, nuts, lockwasher — Gold plated. Meets MIL-P-55149/1A. Rating: 1500 V RMS, 30 amps, +80°C (+176°F) max.

Part Number	Weight	Min. Quantity
5018-2	0.04	5

**BANTAM/2 MINI GRABBERS; 60 INCHES****Pomona Electronics**

BANTAM/2 MINI GRABBERS; 60 INCHES

Part Number	Weight	Min. Quantity
5019N-60	0.145	2

**HEX HEAD BIND POST (YELLOW)****Pomona Electronics**

HEX HEAD BIND POST (YELLOW)

Part Number	Weight	Min. Quantity
5018-4	0.5	5

**DIP REMOVER; SIZE 24****Pomona Electronics**

DIP REMOVER; SIZE 24

Part Number	Weight	Min. Quantity
5024	N-A	5

**HEX HEAD BIND POST (GREEN)****Pomona Electronics**

HEX HEAD BIND POST (GREEN)

Part Number	Weight	Min. Quantity
5018-5	0.5	5

**BANTAM/2 ALLIGS; CABLE 60 INCHES****Pomona Electronics**

BANTAM/2 ALLIGS; CABLE 60 INCHES

Part Number	Weight	Min. Quantity
5026N-60	0.16	2

5113A – XLR (F) PANEL RECEPTACLE; 3 CONTACT...

**TRIAxIAL (M); BELDEN 9222****Pomona Electronics**

Triaxial Cable Assembly Triaxial 2 Lug Male Each End, On Belden 9222 Triaxial Cable 20 AWG wire size It is triaxial cable male connector.

Part Number	Weight	Min. Quantity
5054-36	0.5	1

**TERMINATION; COAX; BNC (M); SHORT****Pomona Electronics**

BNC Shorting Cap Used to provide protection and supply a short across an input 3 in. long chain Brass tarnish resistant plating body material.

Part Number	Weight	Min. Quantity
5085	0.5	5

**TRIAxIAL (M); BELDEN 9222****Pomona Electronics**

TRIAxIAL (M); BELDEN 9222

Part Number	Weight	Min. Quantity
5054-60	0.5	1

**BNC (F)/TRIAxIAL (M)****Pomona Electronics**

BNC Male to 2 Lug Triaxial Male Adapter, Gold Plated Brass Body, Gold Plated Contacts DC to 500 MHz frequency Tarnish resistant outer contact - BNC male to 2 lug triaxial male adapter.

Part Number	Weight	Min. Quantity
5090	0.5	2

**2 LUG TRIAX; BELDEN 9222****Pomona Electronics**

Triaxial Male 2 Lug Connector to Cable, Brass, Tarnish Resistant Plating Body Material Brass body material PTFE dielectric material.

Part Number	Weight	Min. Quantity
5056	0.056	2

**BNC (F)/TRIAxIAL (M)****Pomona Electronics**

Part Number	Weight	Min. Quantity
5090#	N-A	500

**STRESS BOOT W/NUT; RG58 (BLACK)****Pomona Electronics**

Connector, Strain Relief Boot with Clamp Nut, RG58 and RG141 Cable Type Rating. Operating Voltage: 500 V RMS max., +50°C (+122°F) max. Make your own cable with strain relief. Boot with nut only. For use with connectors using a 7/16-28 clamp nut. Simply replace supplied nut with the one on th

Part Number	Weight	Min. Quantity
5076-0	0.03	5

**DIP CLIP; 8 PIN****Pomona Electronics**

Part Number	Weight	Min. Quantity
5108	0.5	5

**STRESS BOOT W/NUT; RG58 (BLACK)****Pomona Electronics**

STRESS BOOT W/NUT; RG58 (BLACK)

Part Number	Weight	Min. Quantity
5076-0#	N-A	500

**XLR (F) PANEL RECEPTACLE; 3 CONTACT...****Pomona Electronics**

3 Conductor, Bronze with a Tin Finish Contacts, Wall Mount Female Connectors Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged cab

Part Number	Weight	Min. Quantity
5113A	0.11	5



5117A – XLR (M) PANEL RECEPTACLE; 3 CONTACT...

**XLR (M) PANEL RECEPTACLE; 3 CONTACT...****Pomona Electronics**

3 Conductor, Bronze with a Tin Finish Contacts, Wall Mount Male Connectors Audio experts can afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged cable

Part Number	Weight	Min. Quantity
5117A	0.075	5

**STRESS BOOT; RG58 (BLACK)****Pomona Electronics**

STRESS BOOT; RG58 (BLACK)

Part Number	Weight	Min. Quantity
5155-0#	N-A	500

**XLR (F); 5 SILVER-PLATED PINS; NICK...****Pomona Electronics**

XLR (F); 5 SILVER-PLATED PINS; NICKEL-PLATED SHELL (100 PER PKG)

Part Number	Weight	Min. Quantity
5125ABULK	N-A	1

**STRESS BOOT; RG58 10/PKG (RED)****Pomona Electronics**

STRESS BOOT; RG58 10/PKG (RED)

Part Number	Weight	Min. Quantity
5155-2	N-A	1

**XLR (M); 5 SILVER-PLATED PINS; NICK...****Pomona Electronics**

XLR (M); 5 SILVER-PLATED PINS; NICKEL-PLATED SHELL (100 PER PKG)

Part Number	Weight	Min. Quantity
5126ABULK	N-A	1

**STRESS BOOT; RG59 10/PKG (BLACK)****Pomona Electronics**

Part Number	Weight	Min. Quantity
5156-0	0.125	1

**DOUBLE BANANA PLUG SHORTING BAR; IN...****Pomona Electronics**

Fits Standard (0.166) dia. banana jack. Material: Banana plug body; brass spring; beryllium copper; Finish: Nickel plating.

Part Number	Weight	Min. Quantity
5145	0.5	5

**STRESS BOOT; RG59 (BLACK)****Pomona Electronics**

STRESS BOOT; RG59 (BLACK)

Part Number	Weight	Min. Quantity
5156-0#	N-A	500

**STRESS BOOT; RG58 10/PKG (BLACK)****Pomona Electronics**

Stress Relief Boot, Black Color PVC material

Part Number	Weight	Min. Quantity
5155-0	0.15	1

**STRESS BOOT; RG59 10/PKG (RED)****Pomona Electronics**

Part Number	Weight	Min. Quantity
5156-2	0.5	1

5168-0 – BANANA JACK; 14 AWG (BLACK)

**STRESS BOOT; RG58 (RED)**

Pomona Electronics

STRESS BOOT; RG58 (RED)

Part Number	Weight	Min. Quantity
5156-2#	N-A	500

**SHORTED BANANA W/BIND POST (RED)**

Pomona Electronics

Mates to Model #2269 or Any Standard Double Banana Jack Binding Post Cross Hole Allows Attachment of Pin Tip Plugs Shorting Bar is Completely Encapsulated in Clear Polypropylene Operating Voltage: 2500 V for Hands Free Use Operating Temperature: +50 C. (+122 F.) Max. Current: 15 Amperes Resistance:

Part Number	Weight	Min. Quantity
5165-2	0.04	5

STRESS BOOT;R RG174 10/PKG (BLACK...

Pomona Electronics

STRESS BOOT;R RG174 10/PKG (BLACK)

Part Number	Weight	Min. Quantity
5157-0	0.5	1

**BANANA JACK; 20 AWG 10/PK (BLACK)**

Pomona Electronics

15 A, 30 VAC⁄60 VDC (Max.), +50 °C (Max.) Operating Temperature, Banana Jack With Flexible Boot Material: Nickel plated brass.

Part Number	Weight	Min. Quantity
5167-0	0.11	1

STRESS BOOT;R RG174 (BLACK)

Pomona Electronics

STRESS BOOT;R RG174 (BLACK)

Part Number	Weight	Min. Quantity
5157-0#	N-A	500

**BANANA JACK, 20 AWG (BLACK)**

Pomona Electronics

BANANA JACK, 20 AWG (BLACK)

Part Number	Weight	Min. Quantity
5167-0#_BULK	N-A	500

SHORTED BANANA W/BIND POST (BLACK)

Pomona Electronics

Mates to Model #2269 or Any Standard Double Banana Jack Binding Post Cross Hole Allows Attachment of Pin Tip Plugs Shorting Bar is Completely Encapsulated in Clear Polypropylene Operating Voltage: 2500 V for Hands Free Use Operating Temperature: +50 C. (+122 F.) Max. Current: 15 Amperes Resistance:

Part Number	Weight	Min. Quantity
5165-0	0.04	5

**BANANA JACK; 20 AWG 10/PK (RED)**

Pomona Electronics

15 A, 30 VAC⁄60 VDC (Max.), +50 °C (Max.) Operating Temperature, Banana Jack With Flexible Boot Material: Nickel plated brass.

Part Number	Weight	Min. Quantity
5167-2	0.11	1

SHORTED BANANA W/BIND POST (BLACK)

Pomona Electronics

SHORTED BANANA W/BIND POST (BLACK)

Part Number	Weight	Min. Quantity
5165-0#	N-A	500

**BANANA JACK; 14 AWG (BLACK)**

Pomona Electronics

Operating Voltage 30 VAC⁄60 VDC (Max.), Do-It-Yourself In-Line Banana Jack With Flexible Boot Material: Nickel plated brass.

Part Number	Weight	Min. Quantity
5168-0	0.0154	5



5168-0# – BANANA JACK; 14 AWG (BLACK)

**BANANA JACK; 14 AWG (BLACK)**

Pomona Electronics

BANANA JACK; 14 AWG (BLACK)

Part Number	Weight	Min. Quantity
5168-0#	N-A	500

**BANANA JACK; 14 AWG (RED)**

Pomona Electronics

Operating Voltage 30 VAC⁄60 VDC (Max.), Do-It-Yourself In-Line Banana Jack With Flexible Boot Material: Nickel plated brass.

Part Number	Weight	Min. Quantity
5168-2	0.015	5

**BANANA PLUG FOR 18 - 20 AWG WIRE; B...**

Pomona Electronics

Banana Plug with Flexible Boot, 5000 VDC, 15 A, Operating Temperature +50 °C (Max.) Fits Standard (0.166) dia. banana jack. Material: Banana plug body; brass spring; beryllium copper; Finish: Nickel plating.

Part Number	Weight	Min. Quantity
5169-0	0.025	5

**BANANA PLUG FOR 18 - 20 AWG WIRE; R...**

Pomona Electronics

Banana Plug with Flexible Boot, 5000 VDC, 15 A, Operating Temperature +50 °C (Max.) Fits Standard (0.166) dia. banana jack. Material: Banana plug body; brass spring; beryllium copper; Finish: Nickel plating.

Part Number	Weight	Min. Quantity
5169-2	0.025	5

**BANANA PLUG; 14 AWG (BLACK)**

Pomona Electronics

Banana Plug with Flexible Boot, 30 VAC⁄60 VDC (Max.), 15 A, Operating Temperature +50 °C Fits Standard (0.166) dia. banana jack. Material: Banana plug body; brass spring; beryllium copper; Finish: Nickel plating.

Part Number	Weight	Min. Quantity
5170-0	0.5	5

**BANANA PLUG; 14 AWG (BLACK)**

Pomona Electronics

BANANA PLUG; 14 AWG (BLACK)

Part Number	Weight	Min. Quantity
5170-0#	N-A	500

**BANANA PLUG; 14 AWG (RED)**

Pomona Electronics

Banana Plug with Flexible Boot, 30 VAC⁄60 VDC (Max.), 15 A, Operating Temperature +50 °C Fits Standard (0.166) dia. banana jack. Material: Banana plug body; brass spring; beryllium copper; Finish: Nickel plating.

Part Number	Weight	Min. Quantity
5170-2	0.025	5

**PIN TIP PLUG; 20 AWG (BLACK)**

Pomona Electronics

PIN TIP PLUG; 20 AWG (BLACK)

Part Number	Weight	Min. Quantity
5173-0	0.0212	5

**PIN TIP PLUG; 20AWG (BLACK)**

Pomona Electronics

PIN TIP PLUG; 20AWG (BLACK)

Part Number	Weight	Min. Quantity
5173-0#	N-A	500

**PIN TIP PLUG; 20 AWG (RED)**

Pomona Electronics

Part Number	Weight	Min. Quantity
5173-2	0.0226	5



5223-48 – 3 LUG TRIAX; BELDEN 9222

**PIN TIP PLUG; 20 AWG (RED)**

Pomona Electronics

PIN TIP PLUG; 20 AWG (RED)

Part Number	Weight	Min. Quantity
5173-2#	N-A	500

**TRIAxIAL (F-F) BULKHEAD**

Pomona Electronics

Gold Plated Beryllium Copper Contact Center, Connector Female To Female Triaxial Bulkhead Feed Thru

Part Number	Weight	Min. Quantity
5178	0.045	1

**SHIELDED BOX**

Pomona Electronics

Enclosure, Binding Head Screw Type, Die Cast Aluminum Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are aluminum 1100-H14 with clear anod

Part Number	Weight	Min. Quantity
5186	0.5	2

**COVER**

Pomona Electronics

COVER

Part Number	Weight	Min. Quantity
5198	N-A	2

**SHIELDED BOX**

Pomona Electronics

Enclosure, Pan Head Self Tapping Steel Screw Type, Die Cast Aluminum Material Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are aluminum

Part Number	Weight	Min. Quantity
5203	N-A	2

**DIP CLIP; 8 PIN HI DENSITY**

Pomona Electronics

Part Number	Weight	Min. Quantity
5208	0.035	5

**3 LUG TRIAX; BELDEN 9222**

Pomona Electronics

Triaxial Male 3 Lung Connector To Cable, Brass, Tarnish Resistant Plating Body Material Brass body material PTFE dielectric material.

Part Number	Weight	Min. Quantity
5218	0.057	2

**3 LUG TRIAX; BULKHEAD**

Pomona Electronics

Connector 3 Lug Bayonet BNC Triaxial, Teflon Insulation Material, Teflon Per MIL-P-19468 Dielectric Brass body material TEFLON dielectric material.

Part Number	Weight	Min. Quantity
5219	0.0268	1

**3 LUG TRIAX; BELDEN 9222**

Pomona Electronics

Triaxial Cable Assembly Male Both Ends, 3 Lug, Yellow Color, Triaxial Conductors Cable Type, 20 AWG Ratings Operating Voltage: 500 VRMS/DC. Nominal Impedance of Cable: 50 Ohms. Features Mates to Model #5219 2 Shields Provided for Use in High Interference Areas Lengths Other Than Those Specified Avail

Part Number	Weight	Min. Quantity
5223-36	0.24	1

**3 LUG TRIAX; BELDEN 9222**

Pomona Electronics

3 LUG TRIAX; BELDEN 9222

Part Number	Weight	Min. Quantity
5223-48	N-A	3



5223-60 – 3 LUG TRIAX; BELDEN 9222

**3 LUG TRIAX; BELDEN 9222****Pomona Electronics**

Triaxial Cable Assembly Male Both Ends, 3 Lug, Yellow Color, Triaxial Conductors Cable Type, 20 AWG Ratings Operating Voltage: 500 VRMS/DC. Nominal Impedance of Cable: 50 Ohms. Features Mates to Model #5219 2 Shields Provided for Use in High Interference Areas Lengths Other Than Those Specified Avail

Part Number	Weight	Min. Quantity
5223-60	0.32	1

**BANANA JACK; HIGH TEMP (BLACK)****Pomona Electronics**

BANANA JACK; HIGH TEMP (BLACK)

Part Number	Weight	Min. Quantity
5233-0	0.0388	5

**B-PLUG HIGH TEMP 10/PKG (BLACK)****Pomona Electronics**

B-PLUG HIGH TEMP 10/PKG (BLACK)

Part Number	Weight	Min. Quantity
5230-0	0.165	1

**SMD GRABBER; 10/PKG (WHITE)****Pomona Electronics**

SMD GRABBER; 10/PKG (WHITE)

Part Number	Weight	Min. Quantity
5243-9	0.023	1

**B-PLUG HIGH TEMP (BLACK)****Pomona Electronics**

B-PLUG HIGH TEMP (BLACK)

Part Number	Weight	Min. Quantity
5230-0#	N-A	500

**SOIC CLIP; 24 PIN****Pomona Electronics**

Part Number	Weight	Min. Quantity
5254	N-A	2

**B-PLUG HIGH TEMP 10/PKG (BLUE)****Pomona Electronics**

B-PLUG HIGH TEMP 10/PKG (BLUE)

Part Number	Weight	Min. Quantity
5230-6	0.165	1

**SHIELDED BOX****Pomona Electronics**

Enclosure Die Cast Aluminum Material, Pan Head, Slotted, Self-Tapping Steel Screw Type Provide excellent RFI/EMI protection when used with the included cover and cover screws. Available with no finish or blue baked enamel per Federal Standard 595 #295109 over primer wash per DOD-P-15328. Covers are

Part Number	Weight	Min. Quantity
5255	0.23	2

**B-PLUG HIGH TEMP (BLUE)****Pomona Electronics**

B-PLUG HIGH TEMP (BLUE)

Part Number	Weight	Min. Quantity
5230-6#	N-A	500

**TRIAxIAL (F-F) 2 LUG****Pomona Electronics**

PTFE Dielectric, 1.35 in. Length, 0.38 in. Dia., Connector Triaxial Adapter 2 Lug Female to Female

Part Number	Weight	Min. Quantity
5290	0.03	2

5302-12-2 – SMD GRABBER/BANANA PLUG (RED)

**MICROVOLT/BANANA PLUG CORD (BLACK)**

Pomona Electronics

MICROVOLT/BANANA PLUG CORD (BLACK)

Part Number	Weight	Min. Quantity
5291A-24-0	N-A	24

**MICROVOLT/BANANA PLUG CORD (RED)**

Pomona Electronics

MICROVOLT/BANANA PLUG CORD (RED)

Part Number	Weight	Min. Quantity
5291A-60-2	0.5	5

**MICROVOLT/BANANA PLUG CORD (RED)**

Pomona Electronics

MICROVOLT/BANANA PLUG CORD (RED)

Part Number	Weight	Min. Quantity
5291A-24-2	N-A	24

**2 LUG BNC (M)/TRIAxIAL (F)**

Pomona Electronics

Part Number	Weight	Min. Quantity
5298	0.045	2

**MICROVOLT/BANANA PLUG CORD (BLACK)**

Pomona Electronics

MICROVOLT/BANANA PLUG CORD (BLACK)

Part Number	Weight	Min. Quantity
5291A-36-0	0.12	5

**3 LUG TRIAXIAL (F)/BNC (M)**

Pomona Electronics

3 Lug Triaxial Female to BNC Male Adapter, Gold Plated Brass Body, Teflon Insulation DC to 500 MHz frequency Tarnish resistant outer contact.

Part Number	Weight	Min. Quantity
5299	0.5	5

**MICROVOLT/BANANA PLUG CORD (RED)**

Pomona Electronics

MICROVOLT/BANANA PLUG CORD (RED)

Part Number	Weight	Min. Quantity
5291A-36-2	0.125	5

**BNC (F)/3 LUG TRIAXIAL (M)**

Pomona Electronics

BNC Female to Triaxial 3 Lug Male Adapter, Nickel Plated Brass Body, Teflon Insulation Provides an easy interface between a BNC (M) and a 3 lug triax (F) DC to 500 MHz frequency Tarnish resistant outer contact.

Part Number	Weight	Min. Quantity
5300	0.5	2

**MICROVOLT/BANANA PLUG CORD (BLACK)**

Pomona Electronics

MICROVOLT/BANANA PLUG CORD (BLACK)

Part Number	Weight	Min. Quantity
5291A-60-0	0.175	5

**SMD GRABBER/BANANA PLUG (RED)**

Pomona Electronics

SMD GRABBER/BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
5302-12-2	0.025	5

5302-48-0# – SMD GRABBER/BANANA PLUG; MTO BULK; ...

**SMD GRABBER/BANANA PLUG; MTO BULK; ...**

Pomona Electronics

Part Number	Weight	Min. Quantity
5302-48-0#	N-A	24

**STACKING SNAP JACK**

Pomona Electronics

Part Number	Weight	Min. Quantity
5532	0.022	5

**SMD GRABBER/BANANA PLUG; MTO BULK; ...**

Pomona Electronics

Part Number	Weight	Min. Quantity
5302-48-2#	N-A	24

**ANTISTATIC GRND. CORD**

Pomona Electronics

ANTISTATIC GRND. CORD

Part Number	Weight	Min. Quantity
5534	0.06	2

**SMD GRABBER (BLACK)**

Pomona Electronics

SMD GRABBER (BLACK)

Part Number	Weight	Min. Quantity
5360-0#	N-A	500

**IN-LINE B-PLUG/RT ANGLE BANANA (BLA...**

Pomona Electronics

IN-LINE B-PLUG/RT ANGLE BANANA (BLACK)

Part Number	Weight	Min. Quantity
5547-48-0	0.5	5

**ADAPTER;DUAL;BINDING POST;BANANA PL...**

Pomona Electronics

ABS Insulating, Dual Banana Plug with Binding Posts Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access panel or need a simpl

Part Number	Weight	Min. Quantity
5405	0.5	5

**IN-LINE B-PLUG/RT ANGLE BANANA (RED...**

Pomona Electronics

IN-LINE B-PLUG/RT ANGLE BANANA (RED)

Part Number	Weight	Min. Quantity
5547-48-2	0.1	5

**RING TERMINAL**

Pomona Electronics

RING TERMINAL

Part Number	Weight	Min. Quantity
5531	0.016	5

**EXTENDED TIP ADAPTER (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
5682-0	0.014	5

5749-36 – UNIVERSAL ADAPTER CABLE

EXTENDED TIP ADAPTER (RED)

Pomona Electronics

Part Number	Weight	Min. Quantity
5682-2	0.013	5

INTERFACE; TNC (F)

Pomona Electronics

Part Number	Weight	Min. Quantity
5740	N-A	5

INTERFACE; BNC (M)

Pomona Electronics

INTERFACE; BNC (M)

Part Number	Weight	Min. Quantity
5735	N-A	5

INTERFACE; SMA (F)

Pomona Electronics

INTERFACE; SMA (F)

Part Number	Weight	Min. Quantity
5741	N-A	5

INTERFACE; TNC (M)

Pomona Electronics

INTERFACE; TNC (M)

Part Number	Weight	Min. Quantity
5736	N-A	5

INTERFACE; DBL BINDING POST

Pomona Electronics

Part Number	Weight	Min. Quantity
5744	N-A	2

INTERFACE; SMA (M)

Pomona Electronics

INTERFACE; SMA (M)

Part Number	Weight	Min. Quantity
5737	N-A	5

**UNIVERSAL ADAPTER CABLE**

Pomona Electronics

UNIVERSAL ADAPTER CABLE

Part Number	Weight	Min. Quantity
5749-24	0.5	5

INTERFACE; BNC (F)

Pomona Electronics

INTERFACE; BNC (F)

Part Number	Weight	Min. Quantity
5739	N-A	5

**UNIVERSAL ADAPTER CABLE**

Pomona Electronics

Part Number	Weight	Min. Quantity
5749-36	0.2	5

5749-48 – UNIVERSAL ADAPTER CABLE

**UNIVERSAL ADAPTER CABLE**

Pomona Electronics

UNIVERSAL ADAPTER CABLE

Part Number	Weight	Min. Quantity
5749-48	0.5	5

**INTERFACE; RCA PHONO (M)**

Pomona Electronics

INTERFACE; RCA PHONO (M)

Part Number	Weight	Min. Quantity
5754	N-A	5

**UNIVERSAL ADAPTER CABLE**

Pomona Electronics

UNIVERSAL ADAPTER CABLE

Part Number	Weight	Min. Quantity
5749-60	0.5	5

**INTERFACE; TYPE F (F)**

Pomona Electronics

Part Number	Weight	Min. Quantity
5755	N-A	5

**UNIVERSAL ADAPTER CABLE; 50 OHM; 6 ...**

Pomona Electronics

Part Number	Weight	Min. Quantity
5749-72	2	5

**INTERFACE; UHF (F)**

Pomona Electronics

INTERFACE; UHF (F)

Part Number	Weight	Min. Quantity
5756	N-A	5

**INTERFACE; UHF (M)**

Pomona Electronics

INTERFACE; UHF (M)

Part Number	Weight	Min. Quantity
5752	N-A	5

**INTERFACE; MINI UHF (F)**

Pomona Electronics

INTERFACE; MINI UHF (F)

Part Number	Weight	Min. Quantity
5757	N-A	5

**INTERFACE; MINI UHF (M)**

Pomona Electronics

INTERFACE; MINI UHF (M)

Part Number	Weight	Min. Quantity
5753	N-A	5

**INTERFACE; RCA PHONO (F)**

Pomona Electronics

INTERFACE; RCA PHONO (F)

Part Number	Weight	Min. Quantity
5758	N-A	5

5916A# – MEDIUM ALLIGATOR CLIP

**INTERFACE; TYPE F (M)**

Pomona Electronics

INTERFACE; TYPE F (M)

Part Number	Weight	Min. Quantity
5759	N-A	5

**SIGNAL SAMPLER**

Pomona Electronics

SIGNAL SAMPLER

Part Number	Weight	Min. Quantity
5760	N-A	2

**ALLIGATOR CLIP; BLACK**

Pomona Electronics

ALLIGATOR CLIP; BLACK

Part Number	Weight	Min. Quantity
5787A-0	0.015	5

**ALLIGATOR CLIP; RED**

Pomona Electronics

ALLIGATOR CLIP; RED

Part Number	Weight	Min. Quantity
5787A-2	0.5	5

**ALLIGATOR CLIP (BLACK) 10/PKG**

Pomona Electronics

Alligator clip has 0.240" max. jaw opening. Overall Length: 1.57". Rating: 45 V, +80°C (+176°F) max.

Part Number	Weight	Min. Quantity
5788-0	0.5	1

**ALLIGATOR CLIP (BLACK)**

Pomona Electronics

ALLIGATOR CLIP (BLACK)

Part Number	Weight	Min. Quantity
5788-0#	N-A	500

**ALLIGATOR CLIP (RED)**

Pomona Electronics

ALLIGATOR CLIP (RED)

Part Number	Weight	Min. Quantity
5788-2#	N-A	500

**FLEX MAXIPINCER SET; 1000V**

Pomona Electronics

Maxigrabber has pincer type contact.

Part Number	Weight	Min. Quantity
5910B	N-A	2

**1KV;INSULATION PIERCING GRABBER (RE...**

Pomona Electronics

1KV;INSULATION PIERCING GRABBER (RED)

Part Number	Weight	Min. Quantity
5913-2#	N-A	100

**MEDIUM ALLIGATOR CLIP**

Pomona Electronics

MEDIUM ALLIGATOR CLIP

Part Number	Weight	Min. Quantity
5916A#	N-A	500

5916A_POM – MEDIUM ALLIGATOR CLIP

**MEDIUM ALLIGATOR CLIP****Pomona Electronics**

Steel, 0.40 in. Width, IEC 1010 Compliant IEC 1010 Complaints Each clip has sheathed 4 mm (0.16") receptacle to accept Pomona flexible leads. One black and one red clip. Fully insulated clip with 0.30" jaw opening.

Part Number	Weight	Min. Quantity
5916A_POM	N-A	5

**SHEATHED BANANA JACK;10/PK (GREEN)****Pomona Electronics**

SHEATHED BANANA JACK;10/PK (GREEN)

Part Number	Weight	Min. Quantity
5931-5	N-A	1

SHEATHED BANANA JACK; 10/PK (BLAC...**Pomona Electronics**

Part Number	Weight	Min. Quantity
5931-0	0.5	1

**SHEATHED BANANA JACK; 10/PK (BLUE)****Pomona Electronics**

SHEATHED BANANA JACK; 10/PK (BLUE)

Part Number	Weight	Min. Quantity
5931-6	N-A	1

**SHEATHED BANANA JACK (SET)****Pomona Electronics**

SHEATHED BANANA JACK (SET)

Part Number	Weight	Min. Quantity
5931-02	N-A	5

**SHEATHED BANANA JACK; 10/PK (WHITE)****Pomona Electronics**

SHEATHED BANANA JACK; 10/PK (WHITE)

Part Number	Weight	Min. Quantity
5931-9	0.125	1

**SHEATHED BANANA JACK;10/PK (RED)****Pomona Electronics**

Banana Jack, 36 A Current Rating, Panel Mounting Type, Brass Body Material Ring threads onto the insulated body to firmly secure jack to panel Banana jack is gold plated for superb electrical connection Jack mounting type panel, red color.

Part Number	Weight	Min. Quantity
5931-2	0.12	1

**BANANA PLUG; D-I-Y;4MM 10/PK (BLACK...****Pomona Electronics**

Part Number	Weight	Min. Quantity
5934-0	N-A	1

**SHEATHED BANANA JACK;10/PK (YELLOW)****Pomona Electronics**

SHEATHED BANANA JACK;10/PK (YELLOW)

Part Number	Weight	Min. Quantity
5931-4	N-A	1

**BAN PLUG; D-I-Y; 4MM;10/PK (RED)****Pomona Electronics**

Part Number	Weight	Min. Quantity
5934-2	0.1	1



6042B-2 – ALLIG CLIP EX-LARGE IEC1010 (RED)

**BANANA JACK (BLACK) 10/PKG**

Pomona Electronics

BANANA JACK (BLACK) 10/PKG

Part Number	Weight	Min. Quantity
5935-0	0.001	1

**TRI-FOLD POUCH**

Pomona Electronics

TRI-FOLD POUCH

Part Number	Weight	Min. Quantity
5955	0.165	5

**BANANA PLUG; D-I-Y; 2MM; 10/PK (BLA...**

Pomona Electronics

BANANA PLUG; D-I-Y; 2MM; 10/PK (BLACK)

Part Number	Weight	Min. Quantity
5936-0	0.03	1

**TRI-FOLD POUCH**

Pomona Electronics

TRI-FOLD POUCH

Part Number	Weight	Min. Quantity
5955#	N-A	500

**BANANA PLUG; D-I-Y; 2MM; (BLACK)**

Pomona Electronics

BANANA PLUG; D-I-Y; 2MM; (BLACK)

Part Number	Weight	Min. Quantity
5936-0#	N-A	500

**ALL.CLIP; EX-LARGE IEC1010**

Pomona Electronics

ALL.CLIP; EX-LARGE IEC1010

Part Number	Weight	Min. Quantity
6041B#	N-A	500

**BANANA PLUG; D-I-Y; 2MM; 10/PK (RED...**

Pomona Electronics

BANANA PLUG; D-I-Y; 2MM; 10/PK (RED)

Part Number	Weight	Min. Quantity
5936-2	0.027	1

**ALLIG CLIP EX-LARGE IEC1010 (BLA...**

Pomona Electronics

Part Number	Weight	Min. Quantity
6042B-0	0.055	5

**JUMPERS; 45V; .025 SQ PIN RECEPTACLES...**

Pomona Electronics

Square Pin Receptacle Patch Cord, 3 A (Max.) Current Rating, +50 °C Operating Temperature Wire: 22 AWG, 0.064" O.D. Rating: 45 VRMS; 3 amps; +50°C. Phosphor bronze material, PVC insulation, gold plated.

Part Number	Weight	Min. Quantity
5948	N-A	1

**ALLIG CLIP EX-LARGE IEC1010 (RED)**

Pomona Electronics

ALLIG CLIP EX-LARGE IEC1010 (RED)

Part Number	Weight	Min. Quantity
6042B-2	0.055	5



6203 – INS SPADE LUG W/BAN JACK SET

**INS SPADE LUG W/BAN JACK SET**

Pomona Electronics

Part Number	Weight	Min. Quantity
6203	0.03	5

**COUPLER; IEC1010 SET**

Pomona Electronics

COUPLER; IEC1010 SET

Part Number	Weight	Min. Quantity
6252#	N-A	500

**INS SPADE LUG W/BAN JACK SET**

Pomona Electronics

INS SPADE LUG W/BAN JACK SET

Part Number	Weight	Min. Quantity
6203#	N-A	500

**CABLE PUSH ON BNC**

Pomona Electronics

CABLE PUSH ON BNC

Part Number	Weight	Min. Quantity
6253-C-36	0.175	2

**MINI GBR/BAN JACK IEC1010 (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
6248-12-0	0.045	5

**7/16 DIN MALE/N MALE**

Pomona Electronics

7/16 DIN MALE/N MALE

Part Number	Weight	Min. Quantity
6256	0.275	1

**MINI GBR/BAN JACK IEC1010 (RED)**

Pomona Electronics

MINI GBR/BAN JACK IEC1010 (RED)

Part Number	Weight	Min. Quantity
6248-12-2	N-A	5

**7/16 DIN MALE/N FEMALE**

Pomona Electronics

7/16 DIN MALE/N FEMALE

Part Number	Weight	Min. Quantity
6257	N-A	1

**MINIGBR W/MULTI-STACK B PLUG (RED)**

Pomona Electronics

MINIGBR W/MULTI-STACK B PLUG (RED)

Part Number	Weight	Min. Quantity
6249-12-2	0.042	5

**7/16 DIN FEMALE/N FEMALE**

Pomona Electronics

7/16 DIN FEMALE/N FEMALE

Part Number	Weight	Min. Quantity
6260	0.21	1

6324-96 – BANTAM/RJ48 CABLE

**EXTENDED FINE PT TIP ADAP (SET RED/...****Pomona Electronics**

EXTENDED FINE PT TIP ADAP (SET RED/BLACK)

Part Number	Weight	Min. Quantity
6262-02#	N-A	500

**INS SLEEVE FOR BNC; TEN COLORS****Pomona Electronics**

BNC Male Flexible Insulated Connector Resist removal after installation Perfect for use with any of the Pomona 2249 type cables Flexible insulators which help prevent inadvertent contact with the outer shell of the BNC.

Part Number	Weight	Min. Quantity
6291	N-A	1

EXTENDED FINE PT TIP ADAPTER (RED)**Pomona Electronics**

EXTENDED FINE PT TIP ADAPTER (RED)

Part Number	Weight	Min. Quantity
6262-2	0.5	5

**BANTAM (F) WE-310 (M) ADAPTER****Pomona Electronics**

Part Number	Weight	Min. Quantity
6315	N-A	2

DBL BANANA PLUG W/SAFETY SHROUD; 36...**Pomona Electronics**

Stack-Up Banana Plug, 18 AWG Wire Size, 65 x 36 Stranding, 15 A (Continuous) Current Rating Ratings IEC-1010-2-031, Category II, P2 Compliant. Operating Temperature: +55&deg;C (+131&deg;F) Max. Operating Voltage: 600 V RMS Features Cable Is Designed to Be Used with All Standard 0.166&quot; or 4 mm D

Part Number	Weight	Min. Quantity
6283-C-36	0.5	5

**310 Y/RJ48 CABLE****Pomona Electronics**

310 Y/RJ48 CABLE

Part Number	Weight	Min. Quantity
6316-96	N-A	1

DBL BANANA PLUG W/SAFETY SHROUD; 48...**Pomona Electronics**

Stack-Up Banana Plug, 18 AWG Wire Size, 65 x 36 Stranding, 15 A (Continuous) Current Rating Ratings IEC-1010-2-031, Category II, P2 Compliant. Operating Temperature: +55&deg;C (+131&deg;F) Max. Operating Voltage: 600 V RMS Features Cable Is Designed to Be Used with All Standard 0.166&quot; or 4 mm D

Part Number	Weight	Min. Quantity
6283-C-48	0.5	5

**BANTAM/RJ11 CABLE****Pomona Electronics**

BANTAM/RJ11 CABLE

Part Number	Weight	Min. Quantity
6323-96	N-A	1

DBL BANANA PLUG W/SAFETY SHROUD; 60...**Pomona Electronics**

Stack-Up Banana Plug, 18 AWG Wire Size, 65 x 36 Stranding, 15 A (Continuous) Current Rating Ratings IEC-1010-2-031, Category II, P2 Compliant. Operating Temperature: +55&deg;C (+131&deg;F) Max. Operating Voltage: 600 V RMS Features Cable Is Designed to Be Used with All Standard 0.166&quot; or 4 mm D

Part Number	Weight	Min. Quantity
6283-C-60	0.5	5

**BANTAM/RJ48 CABLE****Pomona Electronics**

BANTAM/RJ48 CABLE

Part Number	Weight	Min. Quantity
6324-96	N-A	1



JAN ELECTRONIC SUPPLIES, INC.

860-442-4386

6331-96 – DUAL BANTAM EA. END CABLE

**DUAL BANTAM EA. END CABLE****Pomona Electronics**

DUAL BANTAM EA. END CABLE

Part Number	Weight	Min. Quantity
6331-96	0.25	1

**JACK; BAN; USER INSTALLED SET****Pomona Electronics**

JACK; BAN; USER INSTALLED SET

Part Number	Weight	Min. Quantity
6384-02	0.036	5

**SHEATHED BANANA PLUG (BLACK) 10/PKG****Pomona Electronics**

Banana Plug User Installed (18-22 AWG), 1500 V (Max.), 15 A, Operating Temperature +135 °C (Max.) Fully insulated banana plug and jack attaches to insulated wire. Compatible with most safety shrouded banana jacks and all banana plugs. Easily installed with commonly available hand tools. Insulation: Thermoplastic elast

Part Number	Weight	Min. Quantity
6383-0	0.5	1

**JACK; BANANA 10/PKG (RED)****Pomona Electronics**

User Installed (18-22 AWG), Model 6384 & Assembly Instructions Banana Jack Fully insulated banana plug and jack attaches to insulated wire. Compatible with most safety shrouded banana jacks and all banana plugs. Easily installed with commonly available hand tools. Insulation: Thermoplastic elast

Part Number	Weight	Min. Quantity
6384-2	0.04	1

**PLUG; BAN; USER INSTALLED SET****Pomona Electronics**

PLUG; BAN; USER INSTALLED SET

Part Number	Weight	Min. Quantity
6383-02	0.035	5

**BANANA JACK; PANEL TIN; 10/PKG (BL...****Pomona Electronics**

1000 V (RMS), 15 A, Brass Body, Nylon Insulation, Panel Mount, Banana Jack Plug Accepts shrouded banana plugs used in multimeters. Mounts in 1/8" diameter hole with included hex nut and washer. ST designates solder turret. Other terminals are available. T designates tin plating. Nickel an

Part Number	Weight	Min. Quantity
6387-ST-T-0	0.5	1

**SHEATHED BANANA PLUG (RED) 10/PKG****Pomona Electronics**

Banana Plug User Installed (18-22 AWG), 1500 V (Max.), 15 A, Operating Temperature +135 °C (Max.) Fully insulated banana plug and jack attaches to insulated wire. Compatible with most safety shrouded banana jacks and all banana plugs. Easily installed with commonly available hand tools. Insulation: Thermoplastic elast

Part Number	Weight	Min. Quantity
6383-2	1	1

**BANANA JACK; PANEL TIN; 10/PKG (R...****Pomona Electronics**

1000 V (RMS), 15 A, Brass Body, Nylon Insulation, Panel Mount, Banana Jack Plug Accepts shrouded banana plugs used in multimeters. Mounts in 1/8" diameter hole with included hex nut and washer. ST designates solder turret. Other terminals are available. T designates tin plating. Nickel an

Part Number	Weight	Min. Quantity
6387-ST-T-2	0.108	1

**JACK; BANANA 10/PKG (BLACK)****Pomona Electronics**

User Installed (18-22 AWG), Model 6384 & Assembly Instructions Banana Jack Fully insulated banana plug and jack attaches to insulated wire. Compatible with most safety shrouded banana jacks and all banana plugs. Easily installed with commonly available hand tools. Insulation: Thermoplastic elast

Part Number	Weight	Min. Quantity
6384-0	0.15	1

**INSULATION PIERCING CLIP SET****Pomona Electronics**

Part Number	Weight	Min. Quantity
6413	N-A	2



JAN ELECTRONIC SUPPLIES, INC.

860-442-4386

6516-96 – STD. WECO TO BNC (M) CABLE

**GBR; MICRO SMD OSC TIP ADAPTER****Pomona Electronics**

GBR; MICRO SMD OSC TIP ADAPTER

Part Number	Weight	Min. Quantity
6443	N-A	1

**MICRO SMD GBR; .025 INCH PITCH (BLA...****Pomona Electronics**

Use with PQFP and SOIC Packages with 0.05 mm or Greater Lead Pitch; Pincer and 0.030" Pin Plug Are Directly Connected; No Sliding Parts; Pincers Are Stationary; Housing Moves to Close Tips Together; Available in Ten Colors

Part Number	Weight	Min. Quantity
6490-0	0.025	2

**5 WAY ALL.TO SHEATHED RT ANGLE SET ...****Pomona Electronics**

Clip includes bed of nails and single needle tip for easy, versatile piercing of wire insulation to contact inner conductor for measurement. Pierces 19 to 26 AWG wire. Leads are 48 inch silicone with DMM plugs. Includes black and red.

Part Number	Weight	Min. Quantity
6483-48-02	N-A	5

**MICRO SMD GBR; .025 INCH PITCH RED****Pomona Electronics**

Use with PQFP and SOIC Packages with 0.05 mm or Greater Lead Pitch; Pincer and 0.030" Pin Plug Are Directly Connected; No Sliding Parts; Pincers Are Stationary; Housing Moves to Close Tips Together; Available in Ten Colors

Part Number	Weight	Min. Quantity
6490-2	0.025	2

**BED OF NAILS/SHEATH R/A BANANA BLA...****Pomona Electronics**

BED OF NAILS/SHEATH R/A BANANA BLACK

Part Number	Weight	Min. Quantity
6485-48-0	0.5	2

**MINIATURE WECO CABLE ASSEMBLY****Pomona Electronics**

MINIATURE WECO CABLE ASSEMBLY

Part Number	Weight	Min. Quantity
6502-96	0.1	2

**BED OF NAILS/SHEATH R/A BANANA RED****Pomona Electronics**

BED OF NAILS/SHEATH R/A BANANA RED

Part Number	Weight	Min. Quantity
6485-48-2	0.5	2

**MINI WECO TO BNC (M) CABLE****Pomona Electronics**

Patch Cord, Alligator Clips Both Ends, 18 AWG, Vinyl Insulation, 5 A Contact Resistance: 1.5 mW max. Insulation Resistance: 5000 M Ω ; Dielectric Withstand Voltage: 1500 V RMS. Voltage: 33 V RMS / 70 VDC. BNC cable RG59 type

Part Number	Weight	Min. Quantity
6515-96	N-A	2

**BED OF NAILS TO BANTAM PLUG****Pomona Electronics**

BED OF NAILS TO BANTAM PLUG

Part Number	Weight	Min. Quantity
6486-60	N-A	2

**STD. WECO TO BNC (M) CABLE****Pomona Electronics**

Patch Cord, Alligator Clips Both Ends, 18 AWG, Vinyl Insulation, 5 A Impedance: 75 Ω ; Dielectric Withstand Voltage: 1500 VRMS. Voltage: 33 VRMS/70 VDC. BNC cable RG59 type

Part Number	Weight	Min. Quantity
6516-96	N-A	2



6524-96 – WE-310/DBL BANANA PLUG CABLE

**WE-310/DBL BANANA PLUG CABLE**

Pomona Electronics

WE-310/DBL BANANA PLUG CABLE

Part Number	Weight	Min. Quantity
6524-96	N-A	1

**75 OHM BNC PLUG; 3 GHZ; 18 AWG**

Pomona Electronics

75 OHM BNC PLUG; 3 GHZ; 18 AWG

Part Number	Weight	Min. Quantity
6703ABULK	N-A	1

**MOD.OSC.ADAPTER TO SMD GRABBER**

Pomona Electronics

MOD.OSC.ADAPTER TO SMD GRABBER

Part Number	Weight	Min. Quantity
6553	N-A	1

**75 OHM BNC PLUG; 3 GHZ; 23 AWG**

Pomona Electronics

75 OHM BNC PLUG; 3 GHZ; 23 AWG

Part Number	Weight	Min. Quantity
6704ABULK	N-A	1

**ALL.W/BANANA JACK 10/PKG**

Pomona Electronics

Steel, 2 in. Body Length, 0.16 in. I.D., Alligator with Banana Jack Alligator clip has 0.300" max. jaw opening. Overall Length: 2.16"; Rating: 150 V, 5 amps, +50°C (+122°F) max. Sold unassembled. 3289. Gold plated. One Clip and insulator. 2240: Nickel plated. Package of 10

Part Number	Weight	Min. Quantity
6567	0.08	1

**DO-IT-YOURSELF 4MM STACKABLE BANANA...**

Pomona Electronics

Multi-Stacking Sheath Banana Plug, 1000 Vrms, 20 A, Temperature +55°C (Max.) Can be vertically stacked on top of each other Fits standard banana safety-style jacks Fits DMM with safety-style banana jacks Simple assembly

Part Number	Weight	Min. Quantity
6721-0	0.025	5

**1010 FLEX BOOT ALLIG/2MM TIP 10 PCS...**

Pomona Electronics

1010 FLEX BOOT ALLIG/2MM TIP 10 PCS (BLACK)

Part Number	Weight	Min. Quantity
6574-0_10PK	N-A	10

**DO-IT-YOURSELF 4MM STACKABLE BANANA...**

Pomona Electronics

Multi-Stacking Sheath Banana Plug, 1000 Vrms, 20 A, Temperature +55°C (Max.) Can be vertically stacked on top of each other Fits standard banana safety-style jacks Fits DMM with safety-style banana jacks Simple assembly

Part Number	Weight	Min. Quantity
6721-2	0.025	5

**75 OHM BNC PLUG; 3 GHZ; 20 AWG**

Pomona Electronics

75 OHM BNC PLUG; 3 GHZ; 20 AWG

Part Number	Weight	Min. Quantity
6702ABULK	N-A	1

**4MM SAFETY BANANA JACK TO BANANA PL...**

Pomona Electronics

Standard Sheath Banana Jack to Non-Sheath Banana Plug, 600 V (RMS) Voltage Operating, Adapter Accepts safety-sheathed 4 mm banana plug and adapts to standard banana plug.

Part Number	Weight	Min. Quantity
6728-0	0.015	5

6854 – XLR (F) PANEL RECEPTACLE; 5 CONTACT...



4MM SAFETY BANANA JACK TO BANANA PL...

Pomona Electronics

Standard Sheath Banana Jack to Non-Sheath Banana Plug, 600 V (RMS) Voltage Operating, Adapter Accepts safety-sheathed 4 mm banana plug and adapts to standard banana plug.

Part Number	Weight	Min. Quantity
6728-2	0.012	5



DO-IT-YOURSELF 4MM RIGHT ANGLE BANA...

Pomona Electronics

Right Angle Sheath Banana Plug, 1000 Vrms, 20 A, Temperature Maximum +55 °C Fits standard banana safety-style jacks Fits DMM with safety-style banana jacks Simple assembly

Part Number	Weight	Min. Quantity
6729-0	0.025	5



DO-IT-YOURSELF 4MM RIGHT ANGLE BANA...

Pomona Electronics

Right Angle Sheath Banana Plug, 1000 Vrms, 20 A, Temperature Maximum +55 °C Fits standard banana safety-style jacks Fits DMM with safety-style banana jacks Simple assembly

Part Number	Weight	Min. Quantity
6729-2	0.025	5



75 OHM BNC (M) PANEL MOUNT; 0.50 SP...

Pomona Electronics

75 OHM BNC (M) PANEL MOUNT; 0.50 SPACING

Part Number	Weight	Min. Quantity
6735BULK	N-A	1



75 OHM BNC (F) PANEL MOUNT; 0.50 SP...

Pomona Electronics

75 OHM BNC (F) PANEL MOUNT; 0.50 SPACING

Part Number	Weight	Min. Quantity
6736BULK	N-A	1



75 OHM BNC (F) PCB MOUNT; VERTICAL

Pomona Electronics

75 OHM BNC (F) PCB MOUNT; VERTICAL

Part Number	Weight	Min. Quantity
6747BULK	N-A	1



F (F) PCB MOUNT

Pomona Electronics

Part Number	Weight	Min. Quantity
6803	0.01	5



F (F) PCB MOUNT; BULK

Pomona Electronics

F (F) PCB MOUNT; BULK

Part Number	Weight	Min. Quantity
6803#	N-A	500



XLR (M); 3 GOLD-PLATED PINS; BLACK ...

Pomona Electronics

XLR (M); 3 GOLD-PLATED PINS; BLACK NICKEL-PLATED SHELL

Part Number	Weight	Min. Quantity
6851BULK	N-A	1



XLR (F) PANEL RECEPTACLE; 5 CONTACT...

Pomona Electronics

5 Contacts, XLR (F) 5-pin Rectangular Flanged Panel Mount Connectors Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged cable assem

Part Number	Weight	Min. Quantity
6854	0.1	5



6855 – XLR (M) PANEL RECEPTACLE; 5 CONTACT...

**XLR (M) PANEL RECEPTACLE; 5 CONTACT...****Pomona Electronics**

5 Contacts, XLR (M) 5-pin Rectangular Flanged Panel Mount Connectors Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged cable assem

Part Number	Weight	Min. Quantity
6855	0.05	5

**XLR (F) / XLR (F) ADAPTER****Pomona Electronics**

Die Cast Zinc Alloy with Tarnish Resistant Body, Adapters Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged cable assemblies and d

Part Number	Weight	Min. Quantity
6856	0.15	5

**XLR (M) / XLR (M) ADAPTER****Pomona Electronics**

Die Cast Zinc Alloy with Tarnish Resistant Body, Adapters Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged cable assemblies and d

Part Number	Weight	Min. Quantity
6857	0.15	5

**XLR (F) / 1/4 INCH PLUG (STEREO) AD...****Pomona Electronics**

Die Cast Zinc Alloy with Tarnish Resistant Nickel-Plating Body, XLR & 1/4 inch & 2 & 1/4 inch Adapters Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line i

Part Number	Weight	Min. Quantity
6863	0.15	5

**XLR (M) / 1/4 INCH PLUG (STEREO) AD...****Pomona Electronics**

Die Cast Zinc Alloy with Tarnish Resistant Nickel-Plating Body, XLR & 1/4 inch & 2 & 1/4 inch Adapters Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line i

Part Number	Weight	Min. Quantity
6864	0.15	5

**XLR PLUG / JACK; 15 FOOT LOW NOISE ...****Pomona Electronics**

XLR Plug & Jack Cable 180 in., Cable Type Soft PVC Low Noise Microphone Cable Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugge

Part Number	Weight	Min. Quantity
6869-180	0.65	5

**XLR PLUG / JACK; 25 FOOT LOW NOISE ...****Pomona Electronics**

XLR Plug-Jack Cable, 25 ft. Length Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged cable assemblies and delivers a wide variety

Part Number	Weight	Min. Quantity
6869-300	0.5	5

**1/4 PHONE PLUG; 2 POLE (MONO)****Pomona Electronics**

45 lbs. (Typ.) Pull Strength, Black-Nickel Plating, Length 3.55 in., Phone Plug Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged

Part Number	Weight	Min. Quantity
6873	0.5	5

**1/4 PHONE PLUG; 3 POLE (STEREO)****Pomona Electronics**

45 lbs. (Typ.) Pull Strength, Black-Nickel Plating, Length 3.55 in., Phone Plug Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged

Part Number	Weight	Min. Quantity
6874	0.05	5

**1/4 PLUG / RCA JACK ADAPTER****Pomona Electronics**

1/4 & 1/4 Jack (mono) & RCA Plug Adapters, Nickel-Plated Brass Contact Center, 1/4 & 1/4 Plug (mono) & RCA Jack Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they ca

Part Number	Weight	Min. Quantity
6878	0.05	5



JAN ELECTRONIC SUPPLIES, INC.

860-442-4386

7151 – RIGHT ANGLE 2-CONDUCTOR 1/4 PLUG

1/4 JACK / RCA PLUG ADAPTER

Pomona Electronics

1/4" Jack (mono) RCA Plug Adapters, Nickel-Plated Brass Contact Center, 1/4" Plug (mono) RCA Jack Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can.

Part Number	Weight	Min. Quantity
6879	0.1	5

RCA JACK

Pomona Electronics

RCA Jack Connector, Die Cast Zinc Alloy Body, Gold Plated Brass Contact Get high-quality connections that are fast and easy to install. With the advent of HDTV, broadband cable, and sophisticated home entertainment systems, connecting today's CATV systems calls for high-performance parts. The connector

Part Number	Weight	Min. Quantity
6880	0.05	5

RCA PLUG

Pomona Electronics

RCA Plug Connector with Nickel Plated Die Cast Alloy Body Get high-quality connections that are fast and easy to install. With the advent of HDTV, broadband cable, and sophisticated home entertainment systems, connecting today's CATV systems calls for high-performance parts. The connectors you once

Part Number	Weight	Min. Quantity
6881	0.5	5

RCA ADAPTER (F/M/F)

Pomona Electronics

Gold Plated Brass Body, Black, RCA Adapter Get high-quality connections that are fast and easy to install. With the advent of HDTV, broadband cable, and sophisticated home entertainment systems, connecting today's CATV systems calls for high-performance parts. The connectors you once installed for a

Part Number	Weight	Min. Quantity
6882	0.05	5

DUAL BINDING POSTS

Pomona Electronics

30 A, 500 VAC Voltage Rating, Dual Binding Posts with Base (Raised Base) Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access

Part Number	Weight	Min. Quantity
6883	0.5	5

DUAL BINDING POSTS; RAISED BASE

Pomona Electronics

30 A, 500 VAC Voltage Rating, Dual Binding Posts with Base (Raised Base) Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access

Part Number	Weight	Min. Quantity
6884	0.1	5

CRIMP; 55A; 142; 142A; 223; 400

Pomona Electronics

BNC Connector, 50 Ohms (Nom.) Impedance, Gold Contact Plating Brass body material Brass contact material.

Part Number	Weight	Min. Quantity
7035	N-A	5

D SERIES SQ FLANGED PANEL RECEPT SO...

Pomona Electronics

D SERIES SQ FLANGED PANEL RECEPT SOLDER CUPS 3 PIN (F); BLACK

Part Number	Weight	Min. Quantity
7115	0.05	5

SHIELDED 2-CONDUCTOR PHONE PLUG- LO...

Pomona Electronics

Cable Mounted Phone Plug Type 5319. Nickel-plated contact. Stereo version. Nickel-plated brass plug.

Part Number	Weight	Min. Quantity
7150	0.05	5

RIGHT ANGLE 2-CONDUCTOR 1/4 PLUG

Pomona Electronics

Type 5319. Nickel-plated contact.

Part Number	Weight	Min. Quantity
7151	0.1	5

7152 – SHIELDED 3-CONDUCTOR PHONE PLUG

**SHIELDED 3-CONDUCTOR PHONE PLUG****Pomona Electronics**

Cable Mounted Phone Plug Type 5319. Nickel-plated contact. Stereo version. Nickel-plated brass plug.

Part Number	Weight	Min. Quantity
7152	0.05	5

**HORIZONTAL 3-CONDUCTOR JACK; SOLDER...****Pomona Electronics**

HORIZONTAL 3-CONDUCTOR JACK; SOLDER TABS

Part Number	Weight	Min. Quantity
7160	0.05	5

**2-CONDUCTOR JACK WITH INSULATED WAS...****Pomona Electronics**

1¼ in. Phone Jacks with Insulated Washer & Solder Lugs Type 5319. Nickel-plated contact. Body is diecast zinc alloy with tarnish resistant nickel plating. Mounting bushing is nickel-plated copper alloy. Hardware includes one copper alloy nickel-plated hex nut, and one steel nickel-plated

Part Number	Weight	Min. Quantity
7156	N-A	5

**XLR (F) / RCA (M)****Pomona Electronics**

&le≥ 3 Milliohms Contact Resistance, 3 (XLR)¼1 (RCA) Adapters Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged cable as

Part Number	Weight	Min. Quantity
7269	0.5	5

**3-CONDUCTOR JACK WITH INSULATED WAS...****Pomona Electronics**

1¼ in. Phone Jacks with Insulated Washer & Solder Lugs Type 5319. Nickel-plated contact. Body is diecast zinc alloy with tarnish resistant nickel plating. Mounting bushing is nickel-plated copper alloy. Hardware includes one copper alloy nickel-plated hex nut, and one steel nickel-plated

Part Number	Weight	Min. Quantity
7157	0.05	5

**XLR (M) / RCA (M)****Pomona Electronics**

&le≥ 3 Milliohms Contact Resistance, 3 (XLR)¼1 (RCA) Adapters Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged cable as

Part Number	Weight	Min. Quantity
7270	0.1	5

**HORIZONTAL 3-CONDUCTOR JACK; PC BOA...****Pomona Electronics**

HORIZONTAL 3-CONDUCTOR JACK; PC BOARD MOUNT

Part Number	Weight	Min. Quantity
7158	0.5	5

**XLR (F) / RCA (F)****Pomona Electronics**

&le≥ 3 Milliohms Contact Resistance, 3 (XLR)¼1 (RCA) Adapters Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged cable as

Part Number	Weight	Min. Quantity
7271	0.1	5

**HORIZONTAL 2-CONDUCTOR JACK; PC BOA...****Pomona Electronics**

HORIZONTAL 2-CONDUCTOR JACK; PC BOARD MOUNT

Part Number	Weight	Min. Quantity
7159	0.05	5

**XLR (M) / RCA (F)****Pomona Electronics**

&le≥ 3 Milliohms Contact Resistance, 3 (XLR)¼1 (RCA) Adapters Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged cable as

Part Number	Weight	Min. Quantity
7272	0.1	5

72910 – IEC INSULATED BNC (M) TO 2 MALE BAN...

**3 POLE (M) IN LINE XLR; SILVER CONT...****Pomona Electronics**

Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged cable assemblies and delivers a wide variety of audio interconnects and adapters

Part Number	Weight	Min. Quantity
7283	0.1	5

**3 POLE (F) IN LINE XLR; SILVER CONT...****Pomona Electronics**

Audio experts can't afford a connection to fail mid-stream. They prevent on-the-job emergencies by using the most rugged cable assemblies and connectors they can find. Pomona's new XLR line includes extra-rugged cable assemblies and delivers a wide variety of audio interconnects and adapters

Part Number	Weight	Min. Quantity
7284	0.1	5

**3 POLE (F) IN LINE XLR; SILVER CONT...****Pomona Electronics**

3 POLE (F) IN LINE XLR; SILVER CONTACTS; NICKEL

Part Number	Weight	Min. Quantity
7284BULK	N-A	1

**LUMAVOLT****Pomona Electronics**

AC Voltage Detector — Detects voltages from 40VAC to 300VAC from 1 to 15 inches away from the source. Flashlight feature includes ultra-bright white LED with 100,000 hour bulb. Offers long battery life with standard alkaline AAA battery. No lithium battery needed. Features: AC Voltage Detector

Part Number	Weight	Min. Quantity
7290	0.5	5

**HOLDING RODS FOR MICRO SMD CLIPS 10...****Pomona Electronics**

HOLDING RODS FOR MICRO SMD CLIPS 10/PKG

Part Number	Weight	Min. Quantity
72903	N-A	1

**CLIP LEAD FOR MICRO SMD GRABBER - 0...****Pomona Electronics**

CLIP LEAD FOR MICRO SMD GRABBER - 0.8MM FEMALE/2 MM FEMALE; (BLACK)

Part Number	Weight	Min. Quantity
72904-0	N-A	5

**CLIP LEAD FOR MICRO SMD GRABBER - 0...****Pomona Electronics**

CLIP LEAD FOR MICRO SMD GRABBER - 0.8MM FEMALE/2MM FEMALE; (RED)

Part Number	Weight	Min. Quantity
72904-2	N-A	5

**IEC INSULATED BNC (M) TO STACKABLE/...****Pomona Electronics**

Ratings Voltage: 33 V RMS 70 VDC, 6 A Impedance : 50Ω; Features Insulated BNC Connector and Sheathed, Stackable/Retractable Plugs for Added Safety

Part Number	Weight	Min. Quantity
72908	N-A	5

**IEC INSULATED BNC (F) TO STACKABLE/...****Pomona Electronics**

Ratings Voltage: 33 V RMS 70 VDC, 6 A Impedance : 50Ω; Features Insulated BNC Connector and Sheathed, Stackable/Retractable Plugs for Added Safety

Part Number	Weight	Min. Quantity
72909	N-A	5

**IEC INSULATED BNC (M) TO 2 MALE BAN...****Pomona Electronics**

Insulated BNCs and Sheathed Banana Jacks and Plugs Provide Added Safety Meets IEC Rating of 500 V CAT I, 150 V CAT II

Part Number	Weight	Min. Quantity
72910	N-A	5

72911 – IEC INSULATED BNC (F) TO 2 MALE BAN...



IEC INSULATED BNC (F) TO 2 MALE BAN...

Pomona Electronics

Insulated BNCs and Sheathed Banana Jacks and Plugs Provide Added Safety Meets IEC Rating of 500 V CAT I, 150 V CAT II

Part Number	Weight	Min. Quantity
72911	N-A	5



PANEL MT IEC1010 4MM(0.16IN) JACK F...

Pomona Electronics

Material : Gold-plated nickel (72912 and 72913). Rating : 1000 V Cat. III, 36 A Max.

Part Number	Weight	Min. Quantity
72913-2	N-A	1



PANEL MT IEC1010 4MM (0.16IN) JACK ...

Pomona Electronics

Material : Gold-plated nickel (72912 and 72913). Rating : 1000 V Cat. III, 36 A Max.

Part Number	Weight	Min. Quantity
72912-0	N-A	1



PANEL MT IEC1010 4MM(0.16IN) JACK F...

Pomona Electronics

PANEL MT IEC1010 4MM(0.16IN) JACK FOR SHEATHED PLUGS;TAB (RED)

Part Number	Weight	Min. Quantity
72913-2#	N-A	500



PANEL MT IEC1010 4MM (0.16IN) JACK ...

Pomona Electronics

Material : Gold-plated nickel (72912 and 72913). Rating : 1000 V Cat. III, 36 A Max.

Part Number	Weight	Min. Quantity
72912-2	N-A	1



4MM BANANA JACK TO 2MM BANANA PLUG ...

Pomona Electronics

4MM BANANA JACK TO 2MM BANANA PLUG ADAPTER;10/PKG (BLACK)

Part Number	Weight	Min. Quantity
72914-0	N-A	1



PANEL MT IEC1010 4MM(0.16IN) JACK F...

Pomona Electronics

Material : Gold-plated nickel (72912 and 72913). Rating : 1000 V Cat. III, 36 A Max.

Part Number	Weight	Min. Quantity
72913-0	N-A	1



4MM BANANA JACK TO 2MM BANANA PLUG ...

Pomona Electronics

Part Number	Weight	Min. Quantity
72914-02	N-A	5



PANEL MT IEC1010 4MM(0.16IN) JACK F...

Pomona Electronics

PANEL MT IEC1010 4MM(0.16IN) JACK FOR SHEATHED PLUGS; TAB (BLACK)

Part Number	Weight	Min. Quantity
72913-0#	N-A	500



4MM BANANA JACK TO 2MM BANANA PLUG ...

Pomona Electronics

Part Number	Weight	Min. Quantity
72914-2	N-A	1

72922-0 – 2MM SAFETY SHEATHED JACK WITH SOLDE...

**2MM SHEATHED JACK TO 2MM UNSHEATHED...****Pomona Electronics**

2MM SHEATHED JACK TO 2MM UNSHEATHED PLUG ADAPTER;10/PKG (BLACK)

Part Number	Weight	Min. Quantity
72915-0	N-A	1

**4MM BANANA PLUG TO 2MM SHEATHED BAN...****Pomona Electronics**

4MM BANANA PLUG TO 2MM SHEATHED BANANA JACK ADAPTER;10/PKG (RED)

Part Number	Weight	Min. Quantity
72917-2	N-A	1

**2MM SHEATHED JACK TO 2MM UNSHEATHED...****Pomona Electronics**

2MM SHEATHED JACK TO 2MM UNSHEATHED PLUG ADAPTER;10/PKG (RED)

Part Number	Weight	Min. Quantity
72915-2	N-A	1

**4MM PLUG W/ THREADED M3 STUD; 2 NUT...****Pomona Electronics**

4MM PLUG W/ THREADED M3 STUD; 2 NUTS; 12MM (0.5IN) STUD LENGTH;10/PKG

Part Number	Weight	Min. Quantity
72918	N-A	1

**4MM BANANA JACK TO 2MM BANANA JACK ...****Pomona Electronics**

4MM BANANA JACK TO 2MM BANANA JACK ADAPTER;10/PKG (BLACK)

Part Number	Weight	Min. Quantity
72916-0	N-A	1

**2MM SAFETY SHEATHED JACK WITH 1.9MM...****Pomona Electronics**

2MM SAFETY SHEATHED JACK WITH 1.9MM CONNECTING PIN; (BLACK)

Part Number	Weight	Min. Quantity
72921-0	N-A	5

**4MM BANANA JACK TO 2MM BANANA JACK ...****Pomona Electronics**

4MM BANANA JACK TO 2MM BANANA JACK ADAPTER;10/PKG (RED)

Part Number	Weight	Min. Quantity
72916-2	N-A	1

**2MM SAFETY SHEATHED JACK WITH 1.9MM...****Pomona Electronics**

2MM SAFETY SHEATHED JACK WITH 1.9MM CONNECTING PIN; (RED)

Part Number	Weight	Min. Quantity
72921-2	N-A	5

**4MM BANANA PLUG TO 2MM SHEATHED BAN...****Pomona Electronics**

4MM BANANA PLUG TO 2MM SHEATHED BANANA JACK ADAPTER;10/PKG (BLACK)

Part Number	Weight	Min. Quantity
72917-0	N-A	1

**2MM SAFETY SHEATHED JACK WITH SOLDE...****Pomona Electronics**

2MM SAFETY SHEATHED JACK WITH SOLDER TAB; (BLACK)

Part Number	Weight	Min. Quantity
72922-0	N-A	5

72922-2 – 2MM SAFETY SHEATHED JACK WITH SOLDE...

**2MM SAFETY SHEATHED JACK WITH SOLDE...****Pomona Electronics**

2MM SAFETY SHEATHED JACK WITH SOLDER TAB; (RED)

Part Number	Weight	Min. Quantity
72922-2	N-A	5

**IEC INSULATED BNC MALE TO BNC MALE ...****Pomona Electronics**

Features Insulated BNC connectors for added safety Meets IEC requirements for 500V CAT I, 150V CAT II

Part Number	Weight	Min. Quantity
72926-C-40	N-A	5

**MINI-ALLIGATOR CLIP WITH 2MM JACK; ...****Pomona Electronics**

Rating: 600 V Cat II, 10 A.

Part Number	Weight	Min. Quantity
72924-0	N-A	5

**IEC INSULATED BNC MALE TO BNC MALE ...****Pomona Electronics**

Features Insulated BNC connectors for added safety Meets IEC requirements for 500V CAT I, 150V CAT II

Part Number	Weight	Min. Quantity
72926-C-80	N-A	5

**MINI-ALLIGATOR CLIP WITH 2MM JACK; ...****Pomona Electronics**

Rating: 600 V Cat II, 10 A.

Part Number	Weight	Min. Quantity
72924-2	N-A	5

**INSULATED BNC (M) / 4MM PLUGS; 50 O...****Pomona Electronics**

Ratings Voltage: 500 V Cat I, 150 V Cat II, 3 A. Impedance : 50 &Omega; Color : Black Features Insulated BNC Connector and Sheathed, Stackable Plugs for Added Safety Thin RG58 Cable for Shielded, Yet Flexible Connections

Part Number	Weight	Min. Quantity
72927-C-40	N-A	5

**DO-IT-YOURSELF 2MM STACKABLE SAFETY...****Pomona Electronics**

DO-IT-YOURSELF 2MM STACKABLE SAFETY SHEATHED PLUG; (BLACK)

Part Number	Weight	Min. Quantity
72925-0	N-A	5

**INSULATED BNC (M) / 4MM PLUGS; 50 O...****Pomona Electronics**

Ratings Voltage: 500 V Cat I, 150 V Cat II, 3 A. Impedance : 50 &Omega; Color : Black Features Insulated BNC Connector and Sheathed, Stackable Plugs for Added Safety Thin RG58 Cable for Shielded, Yet Flexible Connections

Part Number	Weight	Min. Quantity
72927-C-80	N-A	5

**DO-IT-YOURSELF 2MM STACKABLE SAFETY...****Pomona Electronics**

DO-IT-YOURSELF 2MM STACKABLE SAFETY SHEATHED PLUG; (RED)

Part Number	Weight	Min. Quantity
72925-2	N-A	5

**IEC INSULATED BNC (M) TO 2 MALE BAN...****Pomona Electronics**

IEC INSULATED BNC (M) TO 2 MALE BANANA 4MM JACKS

Part Number	Weight	Min. Quantity
72937	N-A	5

73010 – MCX JACK STRAIGHT CRIMP; RG174; 316

**IEC INSULATED BNC (M) TO 2 MALE BAN...**

Pomona Electronics

IEC INSULATED BNC (M) TO 2 MALE BANANA 4MM JACKS

Part Number	Weight	Min. Quantity
72937#	N-A	500

**MCX PLUG R/A CRIMP; RG174; 316**

Pomona Electronics

Part Number	Weight	Min. Quantity
73005	N-A	5

IEC INSULATED BNC (F) TO 2 MALE BAN...

Pomona Electronics



Part Number	Weight	Min. Quantity
72938	N-A	5

**MCX PLUG R/A CRIMP; RG178**

Pomona Electronics

Part Number	Weight	Min. Quantity
73006	N-A	5

MCX PLUG STRAIGHT CRIMP; RG174; 316

Pomona Electronics



Part Number	Weight	Min. Quantity
73002	N-A	5

**MCX JACK STRAIGHT PCB RECEPTACLE**

Pomona Electronics

Part Number	Weight	Min. Quantity
73007	N-A	5

MCX PLUG STRAIGHT CRIMP; RG178

Pomona Electronics



Part Number	Weight	Min. Quantity
73003	N-A	5

**MCX JACK R/A PCB RECEPTACLE**

Pomona Electronics

Part Number	Weight	Min. Quantity
73008	N-A	5

MCX PLUG STRAIGHT CRIMP; RG179

Pomona Electronics



Part Number	Weight	Min. Quantity
73004	N-A	5

**MCX JACK STRAIGHT CRIMP; RG174; 316**

Pomona Electronics

MCX JACK STRAIGHT CRIMP; RG174; 316

Part Number	Weight	Min. Quantity
73010	N-A	5

73011 – MCX JACK STRAIGHT CRIMP; RG178

**MCX JACK STRAIGHT CRIMP; RG178**

Pomona Electronics

MCX JACK STRAIGHT CRIMP; RG178

Part Number	Weight	Min. Quantity
73011	N-A	5

**MCX PLUG R/A SEMI-RIGID; RG405**

Pomona Electronics

Part Number	Weight	Min. Quantity
73017	N-A	5

**MCX JACK STRAIGHT CRIMP; RG179**

Pomona Electronics

Part Number	Weight	Min. Quantity
73012	N-A	5

**MCX JACK STRAIGHT SURFACE MOUNT REC...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73018	N-A	5

**MCX PLUG STRAIGHT SEMI-RIGID; RG402**

Pomona Electronics

Part Number	Weight	Min. Quantity
73014	N-A	5

**MMCX PLUG STRAIGHT CRIMP; RG174; 31...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73023	N-A	5

**MCX PLUG STRAIGHT SEMI-RIGID; RG405**

Pomona Electronics

Part Number	Weight	Min. Quantity
73015	N-A	5

**MMCX PLUG STRAIGHT CRIMP; RG178**

Pomona Electronics

Part Number	Weight	Min. Quantity
73024	N-A	5

**MCX PLUG R/A SEMI-RIGID; RG402**

Pomona Electronics

Part Number	Weight	Min. Quantity
73016	N-A	5

**MMCX PLUG R/A CRIMP; RG174; 316**

Pomona Electronics

Part Number	Weight	Min. Quantity
73025	N-A	5

73038 – MMCX PLUG STRAIGHT EDGECARD

**MMCX PLUG R/A CRIMP; RG178**

Pomona Electronics

Part Number	Weight	Min. Quantity
73026	N-A	5

**MMCX PLUG R/A SEMI-RIGID; RG405**

Pomona Electronics

Part Number	Weight	Min. Quantity
73033	N-A	5

**MMCX JACK R/A PCB RECEPTACLE**

Pomona Electronics

Part Number	Weight	Min. Quantity
73028	N-A	5

**MMCX PLUG STRAIGHT SEMI-RIGID; RG405**

Pomona Electronics

Part Number	Weight	Min. Quantity
73034	N-A	5

**MMCX JACK STRAIGHT CRIMP; RG174; 31...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73029	N-A	5

**MMCX PLUG STRAIGHT SEMI-RIGID; RG405**

Pomona Electronics

Part Number	Weight	Min. Quantity
73035	N-A	5

**MMCX JACK STRAIGHT CRIMP; RG178**

Pomona Electronics

Part Number	Weight	Min. Quantity
73030	N-A	5

**MMCX JACK STRAIGHT SEMI-RIGID; RG405**

Pomona Electronics

Part Number	Weight	Min. Quantity
73037	N-A	5

**MMCX PLUG R/A SEMI-RIGID; RG402**

Pomona Electronics

Part Number	Weight	Min. Quantity
73032	N-A	5

**MMCX PLUG STRAIGHT EDGECARD**

Pomona Electronics

Part Number	Weight	Min. Quantity
73038	N-A	5

73039 – MMCX JACK STRAIGHT EDGECARD

**MMCX JACK STRAIGHT EDGECARD**

Pomona Electronics

Part Number	Weight	Min. Quantity
73039	N-A	5

**N ADAPTER; T TYPE; JACK-PLUG-JACK**

Pomona Electronics

Materials: Center Conductor: - Male: Brass, Gold Plated - Female: Phosphor Bronze, Gold Plated Connector Body: Brass, Nickel Plated Insulators: PTFE Specifications: Impedance: 50 Ω ; Frequency Range: DC to 4 GHz Contact Resistance: - Center Conductor: ≤ 1.0 m Ω ; Outer Conductor: ≤ 0.2 m Ω ; Insulation Resistance: ≥ 1000 M Ω

Part Number	Weight	Min. Quantity
73044	N-A	2

**N BULKHEAD ADAPTER; JACK TO JACK; P...**

Pomona Electronics

Materials: Center Conductor, Female: Phosphor Bronze, Gold Plated Connector Body: Brass, Nickel Plated Insulators: PTFE Specifications: Impedance: 50 Ω ; Frequency Range: DC to 11 GHz Contact Resistance: - Center Conductor: ≤ 1.0 m Ω ; - Outer Conductor: ≤ 0.2 m Ω ; Insulation Resistance: ≥ 1000 M Ω

Part Number	Weight	Min. Quantity
73045	N-A	5

**N JACK TO TNC PLUG**

Pomona Electronics

Pomona RF Between Series Adapter. DC 11 GHz bandwidth Connectors are precision machined Center Conductor: Phosphor Bronze, Gold Plated Connector Body: Brass, Nickel Plated Insulators: PTFE

Part Number	Weight	Min. Quantity
73046	N-A	2

**N JACK TO UHF PLUG**

Pomona Electronics

Pomona RF Between Series Adapters. DC 300 MHz bandwidth Connectors are precision machined Center Conductor: Phosphor Bronze, Gold Plated Connector Body: Brass, Nickel Plated Insulators: PTFE

Part Number	Weight	Min. Quantity
73047	N-A	2

**N RIGHT-ANGLE PLUG; 50 OHM; CLAMP/S...**

Pomona Electronics

N RIGHT-ANGLE PLUG; 50 OHM; CLAMP/SOLDER TYPE; RG214; 225; 393

Part Number	Weight	Min. Quantity
73048	N-A	5

**N RIGHT-ANGLE PLUG; 50 OHM; CRIMP T...**

Pomona Electronics

Materials: Center Conductor, Male: Brass, Gold Plated Connector Body: Brass, Nickel Plated Crimp Ferrule: Copper, Nickel Plated Insulators: PTFE Gasket: Silicone Rubber Specifications: Impedance: 50 Ω ; Frequency Range: DC to 6 GHz Contact Resistance: - Center Conductor: ≤ 1.0 m Ω ; - Outer Conductor: ≤ 0.2 m Ω ; Insulation Resistance: ≥ 1000 M Ω

Part Number	Weight	Min. Quantity
73049	N-A	5

**N STRAIGHT PLUG; 50 OHM; CRIMP TYPE...**

Pomona Electronics

Materials: Center Conductor, Male: Brass, Gold Plated Connector Body: Brass, Nickel Plated Crimp Ferrule: Copper, Nickel Plated Insulators: PTFE Gasket: Silicone Rubber Specifications: Impedance: 50 Ω ; Frequency Range: DC to 6 GHz Contact Resistance: - Center Conductor: ≤ 1.0 m Ω ; - Outer Conductor: ≤ 0.2 m Ω ; Insulation Resistance: ≥ 1000 M Ω

Part Number	Weight	Min. Quantity
73050	N-A	5

**N STRAIGHT PLUG; 50 OHM; CLAMP/SOLD...**

Pomona Electronics

Materials: Center Conductor, Male: Brass, Gold Plated Connector Body: Brass, Nickel Plated Insulators: PTFE Specifications: Impedance: 50 Ω ; Frequency Range: DC to 11 GHz Contact Resistance: - Center Conductor: ≤ 1.0 m Ω ; - Outer Conductor: ≤ 0.2 m Ω ; Insulation Resistance: ≥ 1000 M Ω

Part Number	Weight	Min. Quantity
73051	N-A	5

**N STRAIGHT PLUG; CRIMP TYPE; SEMI-R...**

Pomona Electronics

Materials: Center Conductor, Male: Brass, Gold Plated Connector Body: Brass, Nickel Plated and Silver Plated Insulators: PTFE Gasket: Silicone Rubber Specifications: Impedance: 50 Ω ; Frequency Range: DC to 11 GHz Contact Resistance: - Center Conductor: ≤ 1.0 m Ω ; - Outer Conductor: ≤ 0.2 m Ω ; Insulation Resistance: ≥ 1000 M Ω

Part Number	Weight	Min. Quantity
73052	N-A	5

73063-BB-36 – MMCX PLUG TO MMCX PLUG; RG316/U; 36...

**TNC RIGHT-ANGLE JACK TO PLUG ADAPTE...****Pomona Electronics**

Pomona TNC Connector. DC 4 GHz bandwidth Connectors are precision machined Center Conductor: Male: Brass, Gold Plated, Female: Phosphor Bronze, Gold Plated Connector Body: Brass, Nickel Plated Insulators: PTFE

Part Number	Weight	Min. Quantity
73053	N-A	2

**TNC RIGHT-ANGLE PLUG; 50 OHM; CRIMP...****Pomona Electronics**

Pomona TNC Right-Angle Plug. DC 6 GHz bandwidth Connectors are precision machined Meets interface requirements MIL-C-39012 Connector accepts cable types RG/U: 55, 142, 223, 400 Center Conductor, Male: Brass, Gold Plated Connector Body: Brass, Nickel Plated Crimp Ferrule: Copper, Nickel Plated Insula

Part Number	Weight	Min. Quantity
73054	N-A	5

**TNC STRAIGHT PLUG; 50 OHM; CRIMP TY...****Pomona Electronics**

TNC STRAIGHT PLUG; 50 OHM; CRIMP TYPE; RG58; 141

Part Number	Weight	Min. Quantity
73056	N-A	5

**TNC STRAIGHT PLUG; 50 OHM; CRIMP TY...****Pomona Electronics**

TNC STRAIGHT PLUG; 50 OHM; CRIMP TYPE; RG59; 62

Part Number	Weight	Min. Quantity
73057	N-A	5

**UHF JACK TO JACK ADAPTER****Pomona Electronics**

UHF JACK TO JACK ADAPTER

Part Number	Weight	Min. Quantity
73058	N-A	5

**UHF STRAIGHT PLUG; SOLDER TYPE; RG8...****Pomona Electronics**

UHF STRAIGHT PLUG; SOLDER TYPE; RG8; 9; 11; 63; 87A; 213; 214; 225

Part Number	Weight	Min. Quantity
73059	N-A	5

**N ST PLUG; 50 OHM; CLAMP/SOLDER TYP...****Pomona Electronics**

Materials: Center Conductor, Male: Brass, Gold Plated Connector Body: Brass, Nickel Plated Insulator: PTFE Specifications: Impedance: 50 Ω ; Frequency Range: DC to 11 GHz Contact Resistance: - Center Conductor: ≤ 1.0 m Ω ; - Outer Conductor: ≤ 0.2 m Ω ; Insulation R

Part Number	Weight	Min. Quantity
73062	N-A	2

**MMCX PLUG TO MMCX PLUG; RG316/U; 12...****Pomona Electronics**

Part Number	Weight	Min. Quantity
73063-BB-12	N-A	1

**MMCX PLUG TO MMCX PLUG; RG316/U; 24...****Pomona Electronics**

Part Number	Weight	Min. Quantity
73063-BB-24	N-A	1

**MMCX PLUG TO MMCX PLUG; RG316/U; 36...****Pomona Electronics**

Part Number	Weight	Min. Quantity
73063-BB-36	N-A	1

73063-BB-6 – MMCX PLUG TO MMCX PLUG; RG316/U; 6 ...

**MMCX PLUG TO MMCX PLUG; RG316/U; 6 INCH**

Pomona Electronics

MMCX PLUG TO MMCX PLUG; RG316/U; 6 INCH

Part Number	Weight	Min. Quantity
73063-BB-6	N-A	1

**MMCX PLUG TO SMA BULKHEAD JACK; RG316/U; 6 INCH**

Pomona Electronics

Part Number	Weight	Min. Quantity
73065-BB-12	N-A	1

**MMCX PLUG TO MMCX RIGHT-ANGLE PLUG; RG316/U; 6 INCH**

Pomona Electronics

Part Number	Weight	Min. Quantity
73064-BB-12	N-A	1

**MMCX PLUG TO SMA BULKHEAD JACK; RG316/U; 6 INCH**

Pomona Electronics

Part Number	Weight	Min. Quantity
73065-BB-24	N-A	1

**MMCX PLUG TO MMCX RIGHT-ANGLE PLUG; RG316/U; 24 INCH**

Pomona Electronics

MMCX PLUG TO MMCX RIGHT-ANGLE PLUG; RG316/U; 24 INCH

Part Number	Weight	Min. Quantity
73064-BB-24	N-A	1

**MMCX PLUG TO SMA BULKHEAD JACK; RG316/U; 24 INCH**

Pomona Electronics

Part Number	Weight	Min. Quantity
73065-BB-36	N-A	1

**MMCX PLUG TO MMCX RIGHT-ANGLE PLUG; RG316/U; 36 INCH**

Pomona Electronics

Part Number	Weight	Min. Quantity
73064-BB-36	N-A	1

**MMCX PLUG TO SMA BULKHEAD JACK; RG316/U; 36 INCH**

Pomona Electronics

Part Number	Weight	Min. Quantity
73065-BB-48	N-A	1

**MMCX PLUG TO MMCX RIGHT-ANGLE PLUG; RG316/U; 6 INCH**

Pomona Electronics

MMCX PLUG TO MMCX RIGHT-ANGLE PLUG; RG316/U; 6 INCH

Part Number	Weight	Min. Quantity
73064-BB-6	N-A	1

**MMCX RIGHT-ANGLE PLUG TO SMA BULKHEAD JACK; RG316/U; 6 INCH**

Pomona Electronics

Part Number	Weight	Min. Quantity
73066-BB-12	N-A	1

73068-BB-36 – MCX RIGHT-ANGLE PLUG TO MCX RIGHT-A...

**MMCX RIGHT-ANGLE PLUG TO SMA BULKHE...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73066-BB-24	N-A	1

**MCX PLUG TO MCX PLUG; RG316/U; 36 I...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73067-BB-36	N-A	1

**MMCX RIGHT-ANGLE PLUG TO SMA BULKHE...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73066-BB-36	N-A	1

**MCX PLUG TO MCX PLUG; RG316/U; 6 IN...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73067-BB-6	N-A	1

**MMCX RIGHT-ANGLE PLUG TO SMA BULKHE...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73066-BB-48	N-A	1

**MCX RIGHT-ANGLE PLUG TO MCX RIGHT-A...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73068-BB-12	N-A	1

**MCX PLUG TO MCX PLUG; RG316/U; 12 I...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73067-BB-12	N-A	1

**MCX RIGHT-ANGLE PLUG TO MCX RIGHT-A...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73068-BB-24	N-A	1

**MCX PLUG TO MCX PLUG; RG316/U; 24 I...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73067-BB-24	N-A	1

**MCX RIGHT-ANGLE PLUG TO MCX RIGHT-A...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73068-BB-36	N-A	1

73068-BB-6 – MCX RIGHT-ANGLE PLUG TO MCX RIGHT-A...

**MCX RIGHT-ANGLE PLUG TO MCX RIGHT-A...**

Pomona Electronics

MCX RIGHT-ANGLE PLUG TO MCX RIGHT-ANGLE PLUG; RG316/U; 6 INCH

Part Number	Weight	Min. Quantity
73068-BB-6	N-A	1

**MCX PLUG TO MCX PLUG; RG179/U; 75 O...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73075-VV-12	N-A	1

**MCX PLUG TO MCX PLUG; RG178/U; 12 I...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73075-UU-12	N-A	1

**MCX PLUG TO MCX PLUG; RG179/U; 75 O...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73075-VV-24	N-A	1

**MCX PLUG TO MCX PLUG; RG178/U; 24 I...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73075-UU-24	N-A	1

**MCX PLUG TO MCX PLUG; RG179/U; 75 O...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73075-VV-36	N-A	1

**MCX PLUG TO MCX PLUG; RG178/U; 36 I...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73075-UU-36	N-A	1

**MCX PLUG TO MCX PLUG; RG179/U; 75 O...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73075-VV-48	N-A	1

**MCX PLUG TO MCX PLUG; RG178/U; 48 I...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73075-UU-48	N-A	1

**MMCX PLUG TO MMCX PLUG; RG178/U; 12...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73077-UU-12	N-A	1

73085-4 – TERMINAL JACK; MALE 10-32 (YELLOW)

**MMCX PLUG TO MMCX PLUG; RG178/U; 24...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73077-UU-24	N-A	1

**MMCX PLUG TO SMA BULKHEAD JACK; RG1...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73078-UU-36	N-A	1

**MMCX PLUG TO MMCX PLUG; RG178/U; 36...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73077-UU-36	N-A	1

**MMCX PLUG TO SMA BULKHEAD JACK; RG1...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73078-UU-48	N-A	1

**MMCX PLUG TO MMCX PLUG; RG178/U; 48...**

Pomona Electronics

MMCX PLUG TO MMCX PLUG; RG178/U; 48 INCH

Part Number	Weight	Min. Quantity
73077-UU-48	N-A	1

**TERMINAL JACK; MALE 6-32 (YELLOW)**

Pomona Electronics

TERMINAL JACK; MALE 6-32 (YELLOW)

Part Number	Weight	Min. Quantity
73084-4	N-A	5

**MMCX PLUG TO SMA BULKHEAD JACK; RG1...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73078-UU-12	N-A	1

**TERMINAL JACK; MALE 6-32 (BLUE)**

Pomona Electronics

TERMINAL JACK; MALE 6-32 (BLUE)

Part Number	Weight	Min. Quantity
73084-6	N-A	5

**MMCX PLUG TO SMA BULKHEAD JACK; RG1...**

Pomona Electronics

Part Number	Weight	Min. Quantity
73078-UU-24	N-A	1

**TERMINAL JACK; MALE 10-32 (YELLOW)**

Pomona Electronics

TERMINAL JACK; MALE 10-32 (YELLOW)

Part Number	Weight	Min. Quantity
73085-4	N-A	5

73085-6 – TERMINAL JACK; MALE 10-32 (BLUE)

**TERMINAL JACK; MALE 10-32 (BLUE)**

Pomona Electronics

TERMINAL JACK; MALE 10-32 (BLUE)

Part Number	Weight	Min. Quantity
73085-6	N-A	5

**CABLE ASSY;COAX;BNC(M);BNC(M);18IN**

Pomona Electronics

Ratings Operating Voltage. Shield-Earth: 30 VAC/60 VDC Max. Inner Conductor/Shield: 500 V Max. +80&deg;C (+176&deg;F) Max. 50 Ohms

Part Number	Weight	Min. Quantity
BNC-C-18	N-A	5

**TERMINAL JACK; FEMALE 10-32 (YELLOW)**

Pomona Electronics

TERMINAL JACK; FEMALE 10-32 (YELLOW)

Part Number	Weight	Min. Quantity
73086-4	N-A	5

**CABLE ASSY;COAX;BNC(M);BNC(M);24IN**

Pomona Electronics

Ratings Operating Voltage. Shield-Earth: 30 VAC/60 VDC Max. Inner Conductor/Shield: 500 V Max. +80&deg;C (+176&deg;F) Max. 50 Ohms

Part Number	Weight	Min. Quantity
BNC-C-24	0.5	5

**TERMINAL JACK; FEMALE 10-32 (BLUE)**

Pomona Electronics

TERMINAL JACK; FEMALE 10-32 (BLUE)

Part Number	Weight	Min. Quantity
73086-6	N-A	5

**CABLE ASSY;COAX; BNC(M); BNC(M); 36...**

Pomona Electronics

Ratings Operating Voltage. Shield-Earth: 30 VAC/60 VDC Max. Inner Conductor/Shield: 500 V Max. +80&deg;C (+176&deg;F) Max. 50 Ohms

Part Number	Weight	Min. Quantity
BNC-C-36	0.5	5

**TERMINAL JACK; MALE 8-32; (YELLOW)**

Pomona Electronics

TERMINAL JACK; MALE 8-32; (YELLOW)

Part Number	Weight	Min. Quantity
73088-4	N-A	5

**CABLE ASSY;COAX;BNC(M); BNC(M); 72I...**

Pomona Electronics

Ratings Operating Voltage. Shield-Earth: 30 VAC/60 VDC Max. Inner Conductor/Shield: 500 V Max. +80&deg;C (+176&deg;F) Max. 50 Ohms

Part Number	Weight	Min. Quantity
BNC-C-72	0.5	5

**TERMINAL JACK; MALE 8-32; (BLUE)**

Pomona Electronics

TERMINAL JACK; MALE 8-32; (BLUE)

Part Number	Weight	Min. Quantity
73088-6	N-A	5

**BANANA PLUG/PIN TIP PLUG (BLACK)**

Pomona Electronics

BANANA PLUG/PIN TIP PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM1126-12-0#	N-A	24

EM1126-48-5# – ;BANANA PLUG/PIN TIP PLUG (GREEN)

**BANANA PLUG/PIN TIP PLUG (RED)**

Pomona Electronics

BANANA PLUG/PIN TIP PLUG (RED)

Part Number	Weight	Min. Quantity
EM1126-12-2#	N-A	24

**BANANA PLUG/PIN TIP PLUG (RED)**

Pomona Electronics

BANANA PLUG/PIN TIP PLUG (RED)

Part Number	Weight	Min. Quantity
EM1126-36-2#	N-A	24

**BANANA PLUG/PIN TIP PLUG (WHITE)**

Pomona Electronics

BANANA PLUG/PIN TIP PLUG (WHITE)

Part Number	Weight	Min. Quantity
EM1126-12-9#	N-A	24

**BANANA PLUG/PIN TIP PLUG (GREEN)**

Pomona Electronics

BANANA PLUG/PIN TIP PLUG (GREEN)

Part Number	Weight	Min. Quantity
EM1126-36-5#	N-A	24

**BANANA PLUG/PIN TIP PLUG (BLACK)**

Pomona Electronics

BANANA PLUG/PIN TIP PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM1126-24-0#	N-A	24

**BANANA PLUG/PIN TIP PLUG (BLACK)**

Pomona Electronics

BANANA PLUG/PIN TIP PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM1126-48-0#	N-A	24

**BANANA PLUG/PIN TIP PLUG (RED)**

Pomona Electronics

BANANA PLUG/PIN TIP PLUG (RED)

Part Number	Weight	Min. Quantity
EM1126-24-2#	N-A	24

**BANANA PLUG/PIN TIP PLUG (RED)**

Pomona Electronics

BANANA PLUG/PIN TIP PLUG (RED)

Part Number	Weight	Min. Quantity
EM1126-48-2#	N-A	24

**BANANA PLUG/PIN TIP PLUG (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
EM1126-36-0#	N-A	24

**;BANANA PLUG/PIN TIP PLUG (GREEN)**

Pomona Electronics

;BANANA PLUG/PIN TIP PLUG (GREEN)

Part Number	Weight	Min. Quantity
EM1126-48-5#	N-A	24

EM1126-60-0# – BANANA PLUG/PIN TIP PLUG (BLACK)

**BANANA PLUG/PIN TIP PLUG (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
EM1126-60-0#	N-A	24

**ALLIG CL; BANANA PLUG (GREEN)**

Pomona Electronics

ALLIG CL; BANANA PLUG (GREEN)

Part Number	Weight	Min. Quantity
EM1166-12-5#	N-A	24

**BANANA PLUG/PIN TIP PLUG (RED)**

Pomona Electronics

Part Number	Weight	Min. Quantity
EM1126-60-2#	N-A	24

**ALLIG CL; BANANA PLUG (BLACK)**

Pomona Electronics

ALLIG CL; BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM1166-120-0#	N-A	24

**BANANA PLUG/PIN TIP PLUG (WHITE)**

Pomona Electronics

BANANA PLUG/PIN TIP PLUG (WHITE)

Part Number	Weight	Min. Quantity
EM1126-60-9#	N-A	24

**ALLIG CL; BANANA PLUG (RED)**

Pomona Electronics

ALLIG CL; BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
EM1166-120-2#	N-A	24

**BANANA PLUG/PIN TIP PLUG (BLACK)**

Pomona Electronics

BANANA PLUG/PIN TIP PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM1126-96-0#	N-A	24

**ALLIG CL; BANANA PLUG (BLACK)**

Pomona Electronics

ALLIG CL; BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM1166-144-0#	N-A	24

**BANANA PLUG/PIN TIP PLUG (RED)**

Pomona Electronics

BANANA PLUG/PIN TIP PLUG (RED)

Part Number	Weight	Min. Quantity
EM1126-96-2#	N-A	24

**ALLIG CL; BANANA PLUG (RED)**

Pomona Electronics

ALLIG CL; BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
EM1166-144-2#	N-A	24



EM1166-36-5# – ALLIG CL; BANANA PLUG (GREEN)

**ALLIG CL; BANANA PLUG (BROWN)**

Pomona Electronics
ALLIG CL; BANANA PLUG (BROWN)

Part Number	Weight	Min. Quantity
EM1166-24-1#	N-A	24

**ALLIG CL; BANANA PLUG (VIOLET)**

Pomona Electronics
ALLIG CL; BANANA PLUG (VIOLET)

Part Number	Weight	Min. Quantity
EM1166-24-7#	N-A	24

**ALLIG CL; BANANA PLUG (ORANGE)**

Pomona Electronics
ALLIG CL; BANANA PLUG (ORANGE)

Part Number	Weight	Min. Quantity
EM1166-24-3#	N-A	24

**ALLIG CL; BANANA PLUG (GRAY)**

Pomona Electronics
ALLIG CL; BANANA PLUG (GRAY)

Part Number	Weight	Min. Quantity
EM1166-24-8#	N-A	24

**ALLIG CL; BANANA PLUG (YELLOW)**

Pomona Electronics
ALLIG CL; BANANA PLUG (YELLOW)

Part Number	Weight	Min. Quantity
EM1166-24-4#	N-A	24

**ALLIG CL; BANANA PLUG (BROWN)**

Pomona Electronics
ALLIG CL; BANANA PLUG (BROWN)

Part Number	Weight	Min. Quantity
EM1166-36-1#	N-A	24

**ALLIG CL; BANANA PLUG (GREEN)**

Pomona Electronics
ALLIG CL; BANANA PLUG (GREEN)

Part Number	Weight	Min. Quantity
EM1166-24-5#	N-A	24

**ALLIG CL; BANANA PLUG (YELLOW)**

Pomona Electronics
ALLIG CL; BANANA PLUG (YELLOW)

Part Number	Weight	Min. Quantity
EM1166-36-4#	N-A	24

**ALLIG CL; BANANA PLUG (BLUE)**

Pomona Electronics
ALLIG CL; BANANA PLUG (BLUE)

Part Number	Weight	Min. Quantity
EM1166-24-6#	N-A	24

**ALLIG CL; BANANA PLUG (GREEN)**

Pomona Electronics
ALLIG CL; BANANA PLUG (GREEN)

Part Number	Weight	Min. Quantity
EM1166-36-5#	N-A	24



EM1166-36-6# – ALLIG CL; BANANA PLUG (BLUE)

**ALLIG CL; BANANA PLUG (BLUE)**

Pomona Electronics

ALLIG CL; BANANA PLUG (BLUE)

Part Number	Weight	Min. Quantity
EM1166-36-6#	N-A	24

**ALLIG CL; BANANA PLUG (GREEN)**

Pomona Electronics

ALLIG CL; BANANA PLUG (GREEN)

Part Number	Weight	Min. Quantity
EM1166-48-5#	N-A	24

**ALLIG CL; BANANA PLUG (WHITE)**

Pomona Electronics

ALLIG CL; BANANA PLUG (WHITE)

Part Number	Weight	Min. Quantity
EM1166-36-9#	N-A	24

**ALLIG CL; BANANA PLUG (BLUE)**

Pomona Electronics

ALLIG CL; BANANA PLUG (BLUE)

Part Number	Weight	Min. Quantity
EM1166-48-6#	N-A	24

**ALLIG CL; BANANA PLUG (BLACK)**

Pomona Electronics

ALLIG CL; BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM1166-360-0#	N-A	24

**ALLIG CL; BANANA PLUG (WHITE)**

Pomona Electronics

ALLIG CL; BANANA PLUG (WHITE)

Part Number	Weight	Min. Quantity
EM1166-48-9#	N-A	24

**ALLIG CL; BANANA PLUG (RED)**

Pomona Electronics

ALLIG CL; BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
EM1166-360-2#	N-A	24

**ALLIG CL; BANANA PLUG (ORANGE); MTO...**

Pomona Electronics

ALLIG CL; BANANA PLUG (ORANGE); MTO BULK

Part Number	Weight	Min. Quantity
EM1166-60-3#	N-A	24

**ALLIG CL; BANANA PLUG (YELLOW)**

Pomona Electronics

ALLIG CL; BANANA PLUG (YELLOW)

Part Number	Weight	Min. Quantity
EM1166-48-4#	N-A	24

**ALLIG CL; BANANA PLUG (YELLOW)**

Pomona Electronics

ALLIG CL; BANANA PLUG (YELLOW)

Part Number	Weight	Min. Quantity
EM1166-60-4#	N-A	24

EM1368-A-600# – BANANA/DBL BANANA PLUG CABLE ASSY; ...

**ALLIG CL; BANANA PLUG (GREEN)**

Pomona Electronics
ALLIG CL; BANANA PLUG (GREEN)

Part Number	Weight	Min. Quantity
EM1166-60-5#	N-A	24

**DBL BANANA; 2 COND**

Pomona Electronics
DBL BANANA; 2 COND

Part Number	Weight	Min. Quantity
EM1326-A-96#	N-A	16

**ALLIG CL; BANANA PLUG (BLACK)**

Pomona Electronics
ALLIG CL; BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM1166-96-0#	N-A	24

**BANANA/DBL BANANA PLUG CABLE ASSY; ...**

Pomona Electronics
BANANA/DBL BANANA PLUG CABLE ASSY; 120 INCHES

Part Number	Weight	Min. Quantity
EM1368-A-120#	N-A	16

**ALLIG CL; BANANA PLUG (RED)**

Pomona Electronics
ALLIG CL; BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
EM1166-96-2#	N-A	24

**BANANA/DBL BANANA PLUG CABLE ASSY; ...**

Pomona Electronics
BANANA/DBL BANANA PLUG CABLE ASSY; 240 INCHES

Part Number	Weight	Min. Quantity
EM1368-A-240#	N-A	12

**DBL BANANA; SHIELDED LINE**

Pomona Electronics
DBL BANANA; SHIELDED LINE

Part Number	Weight	Min. Quantity
EM1167-120#	N-A	16

**BANANA/DBL BANANA PLUG CABLE ASSY; ...**

Pomona Electronics
BANANA/DBL BANANA PLUG CABLE ASSY; 360 INCHES

Part Number	Weight	Min. Quantity
EM1368-A-360#	N-A	12

**DBL BANANA; 2 COND**

Pomona Electronics
DBL BANANA; 2 COND

Part Number	Weight	Min. Quantity
EM1326-A-72	N-A	24

**BANANA/DBL BANANA PLUG CABLE ASSY; ...**

Pomona Electronics
BANANA/DBL BANANA PLUG CABLE ASSY; 600 INCHES

Part Number	Weight	Min. Quantity
EM1368-A-600#	N-A	4



EM1368-A-72# – BANANA/DBL BANANA PLUG CABLE ASSY

**BANANA/DBL BANANA PLUG CABLE ASSY**

Pomona Electronics
BANANA/DBL BANANA PLUG CABLE ASSY

Part Number	Weight	Min. Quantity
EM1368-A-72#	N-A	16

**BANANA PLUG/JACK; ISOL (GREEN)**

Pomona Electronics
BANANA PLUG/JACK; ISOL (GREEN)

Part Number	Weight	Min. Quantity
EM1390-5#	N-A	100

**BANANA/DBL BANANA PLUG CABLE ASSY; ...**

Pomona Electronics
BANANA/DBL BANANA PLUG CABLE ASSY; 900 INCHES

Part Number	Weight	Min. Quantity
EM1368-A-900#	N-A	4

**BANANA PLUG/JACK; ISOL (BLUE)**

Pomona Electronics
BANANA PLUG/JACK; ISOL (BLUE)

Part Number	Weight	Min. Quantity
EM1390-6#	N-A	100

**BANANA PLUG/JACK; ISOL (BROWN)**

Pomona Electronics
BANANA PLUG/JACK; ISOL (BROWN)

Part Number	Weight	Min. Quantity
EM1390-1#	N-A	100

**BANANA PLUG/JACK; ISOL (VIOLET)**

Pomona Electronics
BANANA PLUG/JACK; ISOL (VIOLET)

Part Number	Weight	Min. Quantity
EM1390-7#	N-A	100

**BANANA PLUG/JACK; ISOL (ORANGE)**

Pomona Electronics
BANANA PLUG/JACK; ISOL (ORANGE)

Part Number	Weight	Min. Quantity
EM1390-3#	N-A	100

**BANANA PLUG/JACK; ISOL (GRAY)**

Pomona Electronics
BANANA PLUG/JACK; ISOL (GRAY)

Part Number	Weight	Min. Quantity
EM1390-8#	N-A	100

**BANANA PLUG/JACK; ISOL (YELLOW)**

Pomona Electronics
BANANA PLUG/JACK; ISOL (YELLOW)

Part Number	Weight	Min. Quantity
EM1390-4#	N-A	100

**BANANA PLUG/JACK; ISOL (WHITE)**

Pomona Electronics
BANANA PLUG/JACK; ISOL (WHITE)

Part Number	Weight	Min. Quantity
EM1390-9#	N-A	100



EM1693-12-0# – MICROVOLT SPADE LUGS (BLACK)

**B-JACK/PIN TIP; (BROWN)**

Pomona Electronics

B-JACK/PIN TIP; (BROWN)

Part Number	Weight	Min. Quantity
EM1432-1#	N-A	100

**B-JACK/PIN TIP; (VIOLET)**

Pomona Electronics

B-JACK/PIN TIP; (VIOLET)

Part Number	Weight	Min. Quantity
EM1432-7#	N-A	100

**B-JACK/PIN TIP; (ORANGE)**

Pomona Electronics

B-JACK/PIN TIP; (ORANGE)

Part Number	Weight	Min. Quantity
EM1432-3#	N-A	100

**B-JACK/PIN TIP; (GRAY)**

Pomona Electronics

B-JACK/PIN TIP; (GRAY)

Part Number	Weight	Min. Quantity
EM1432-8#	N-A	100

**B-JACK/PIN TIP; (YELLOW)**

Pomona Electronics

B-JACK/PIN TIP; (YELLOW)

Part Number	Weight	Min. Quantity
EM1432-4#	N-A	100

**B-JACK/PIN TIP; (WHITE)**

Pomona Electronics

B-JACK/PIN TIP; (WHITE)

Part Number	Weight	Min. Quantity
EM1432-9#	N-A	100

**B-JACK/PIN TIP; (GREEN)**

Pomona Electronics

B-JACK/PIN TIP; (GREEN)

Part Number	Weight	Min. Quantity
EM1432-5#	N-A	100

**TYNE N (M); RG214/U**

Pomona Electronics

TYNE N (M); RG214/U

Part Number	Weight	Min. Quantity
EM1658-T-240	N-A	2

**B-JACK/PIN TIP; (BLUE)**

Pomona Electronics

B-JACK/PIN TIP; (BLUE)

Part Number	Weight	Min. Quantity
EM1432-6#	N-A	100

**MICROVOLT SPADE LUGS (BLACK)**

Pomona Electronics

MICROVOLT SPADE LUGS (BLACK)

Part Number	Weight	Min. Quantity
EM1693-12-0#	N-A	24

EM1693-12-2# – MICROVOLT SPADE LUGS (RED)

**MICROVOLT SPADE LUGS (RED)**

Pomona Electronics

MICROVOLT SPADE LUGS (RED)

Part Number	Weight	Min. Quantity
EM1693-12-2#	N-A	24

**MICROVOLT SPADE LUG; SHIELDED**

Pomona Electronics

MICROVOLT SPADE LUG; SHIELDED

Part Number	Weight	Min. Quantity
EM1756-18#	N-A	24

**MICROVOLT SPADE LUGS; (BLACK)**

Pomona Electronics

MICROVOLT SPADE LUGS; (BLACK)

Part Number	Weight	Min. Quantity
EM1693-24-0#	N-A	24

**PIN TIP JACK/BANANA PLUG; (GREEN)**

Pomona Electronics

PIN TIP JACK/BANANA PLUG; (GREEN)

Part Number	Weight	Min. Quantity
EM1809-5#	N-A	100

**MICROVOLT SPADE LUGS (RED)**

Pomona Electronics

MICROVOLT SPADE LUGS (RED)

Part Number	Weight	Min. Quantity
EM1693-24-2#	N-A	24

**ALLIG CL/SPADE LUG (GREEN)**

Pomona Electronics

ALLIG CL/SPADE LUG (GREEN)

Part Number	Weight	Min. Quantity
EM1960-36-5#	N-A	24

**MICROVOLT SPADE LUGS (BLACK)**

Pomona Electronics

MICROVOLT SPADE LUGS (BLACK)

Part Number	Weight	Min. Quantity
EM1693-48-0#	N-A	24

**ALLIG/SPADE LUG (BLACK) MTO BULK**

Pomona Electronics

ALLIG/SPADE LUG (BLACK) MTO BULK

Part Number	Weight	Min. Quantity
EM1960-60-0#	N-A	24

**MICROVOLT SPADE LUGS (RED)**

Pomona Electronics

MICROVOLT SPADE LUGS (RED)

Part Number	Weight	Min. Quantity
EM1693-48-2#	N-A	24

**MINIATURE SHORTED DBL BANANA PLUG(W...**

Pomona Electronics

MINIATURE SHORTED DBL BANANA PLUG(WHITE)

Part Number	Weight	Min. Quantity
EM2035-9	N-A	100



EM2382-4# – MINI BIND POST; GOLD PL (YELLOW)

**MINI B-JACK (BROWN); MTO BULK**

Pomona Electronics
MINI B-JACK (BROWN); MTO BULK

Part Number	Weight	Min. Quantity
EM2142-1#	N-A	100

**BANANA PLUG/BNC (M); RG58C**

Pomona Electronics
BANANA PLUG/BNC (M); RG58C

Part Number	Weight	Min. Quantity
EM2241-C-48#	N-A	16

**MINI B-JACK (VIOLET); MTO BULK**

Pomona Electronics
MINI B-JACK (VIOLET); MTO BULK

Part Number	Weight	Min. Quantity
EM2142-7#	N-A	100

**MINI BANANA PLUG; RG174/U; MTO BULK**

Pomona Electronics
MINI BANANA PLUG; RG174/U; MTO BULK

Part Number	Weight	Min. Quantity
EM2247-K-180#	N-A	12

**MINI B-JACK (GRAY)**

Pomona Electronics
MINI B-JACK (GRAY)

Part Number	Weight	Min. Quantity
EM2142-8#	N-A	100

**MINI BANANA PLUG, RG174/U**

Pomona Electronics
MINI BANANA PLUG, RG174/U

Part Number	Weight	Min. Quantity
EM2247-K-36#	N-A	16

**BANANA PLUG; RG58C/U; MTO BULK**

Pomona Electronics
BANANA PLUG; RG58C/U; MTO BULK

Part Number	Weight	Min. Quantity
EM2239-C-120#	N-A	12

**MINI BANANA PLUG; RG174/U**

Pomona Electronics
MINI BANANA PLUG; RG174/U

Part Number	Weight	Min. Quantity
EM2247-K-48#	N-A	16

**BANANA PLUG/BNC(M) RG58C/U**

Pomona Electronics
BANANA PLUG/BNC(M) RG58C/U

Part Number	Weight	Min. Quantity
EM2241-C-24	N-A	16

**MINI BIND POST; GOLD PL (YELLOW)**

Pomona Electronics
MINI BIND POST; GOLD PL (YELLOW)

Part Number	Weight	Min. Quantity
EM2382-4#	N-A	100

EM2382-7# – MINI BIND POST; GOLD PL (VIOLET)



MINI BIND POST; GOLD PL (VIOLET)

Pomona Electronics
MINI BIND POST; GOLD PL (VIOLET)

Part Number	Weight	Min. Quantity
EM2382-7#	N-A	100



MINI BIND POST; TIN PL (BLACK)

Pomona Electronics
MINI BIND POST; TIN PL (BLACK)

Part Number	Weight	Min. Quantity
EM2440-0#	N-A	500



MINI BIND POST; GOLD PL (GRAY)

Pomona Electronics
MINI BIND POST; GOLD PL (GRAY)

Part Number	Weight	Min. Quantity
EM2382-8#	N-A	100



BANANA JACK; GOLD PLATED (ORANGE) MTO BULK

Pomona Electronics
BANANA JACK; GOLD PLATED (ORANGE) MTO BULK

Part Number	Weight	Min. Quantity
EM2854-3#	N-A	100



MINI BIND POST; GOLD PL (WHITE); MTO BULK

Pomona Electronics
MINI BIND POST; GOLD PL (WHITE); MTO BULK

Part Number	Weight	Min. Quantity
EM2382-9#	N-A	24



PIN TIP/BNC (M) RG58C/U

Pomona Electronics
PIN TIP/BNC (M) RG58C/U

Part Number	Weight	Min. Quantity
EM2882-C-18	N-A	16



MINI BIND POST; GOLD PL (RED)

Pomona Electronics
MINI BIND POST; GOLD PL (RED)

Part Number	Weight	Min. Quantity
EM2383-2#	N-A	100



PIN TIP/BNC (M); RG58C/U

Pomona Electronics
PIN TIP/BNC (M); RG58C/U

Part Number	Weight	Min. Quantity
EM2882-C-36#	N-A	16



MINI BIND POST; TIN PL BULK (WHITE)

Pomona Electronics
MINI BIND POST; TIN PL BULK (WHITE)

Part Number	Weight	Min. Quantity
EM2439-9#	N-A	100



PIN TIP/BNC (M); RG58C/U

Pomona Electronics
PIN TIP/BNC (M); RG58C/U

Part Number	Weight	Min. Quantity
EM2882-C-48	N-A	16



EM2945-5# – MINI BANANA PLUG (GREEN)

**PIN TIP/BNC (M); RG58C/U**

Pomona Electronics

PIN TIP/BNC (M); RG58C/U

Part Number	Weight	Min. Quantity
EM2882-C-84#	N-A	16

**MINI BANANA PLUG (GRAY)**

Pomona Electronics

MINI BANANA PLUG (GRAY)

Part Number	Weight	Min. Quantity
EM2944-8#	N-A	100

**PIN TIP/BNC (M); RG58C/U**

Pomona Electronics

PIN TIP/BNC (M); RG58C/U

Part Number	Weight	Min. Quantity
EM2882-C-96#	N-A	16

**MINI BANANA PLUG (BROWN)**

Pomona Electronics

MINI BANANA PLUG (BROWN)

Part Number	Weight	Min. Quantity
EM2945-1#	N-A	100

**MINI BANANA PLUG (RED)**

Pomona Electronics

MINI BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
EM2944-2#	N-A	500

**MINI BANANA PLUG (ORANGE)**

Pomona Electronics

MINI BANANA PLUG (ORANGE)

Part Number	Weight	Min. Quantity
EM2945-3#	N-A	100

**MINI BANANA PLUG (GREEN) MTO BULK**

Pomona Electronics

MINI BANANA PLUG (GREEN) MTO BULK

Part Number	Weight	Min. Quantity
EM2944-5#	N-A	100

**MINI BANANA PLUG (YELLOW)**

Pomona Electronics

MINI BANANA PLUG (YELLOW)

Part Number	Weight	Min. Quantity
EM2945-4#	N-A	100

**MINI BANANA PLUG (BLUE)**

Pomona Electronics

MINI BANANA PLUG (BLUE)

Part Number	Weight	Min. Quantity
EM2944-6#	N-A	100

**MINI BANANA PLUG (GREEN)**

Pomona Electronics

MINI BANANA PLUG (GREEN)

Part Number	Weight	Min. Quantity
EM2945-5#	N-A	100

EM2945-6# – MINI BANANA PLUG (BLUE)

**MINI BANANA PLUG (BLUE)**

Pomona Electronics

MINI BANANA PLUG (BLUE)

Part Number	Weight	Min. Quantity
EM2945-6#	N-A	100

**TRIPLE BANANA PLUG (VIOLET)**

Pomona Electronics

TRIPLE BANANA PLUG (VIOLET)

Part Number	Weight	Min. Quantity
EM2970-7#	N-A	100

**MINI BANANA PLUG (VIOLET)**

Pomona Electronics

MINI BANANA PLUG (VIOLET)

Part Number	Weight	Min. Quantity
EM2945-7#	N-A	100

**TRIPLE BANANA PLUG (WHITE)**

Pomona Electronics

TRIPLE BANANA PLUG (WHITE)

Part Number	Weight	Min. Quantity
EM2970-9#	N-A	100

**MINI BANANA PLUG (GRAY)**

Pomona Electronics

MINI BANANA PLUG (GRAY)

Part Number	Weight	Min. Quantity
EM2945-8#	N-A	100

**DBL BANANA PLUG; 2 COND**

Pomona Electronics

DBL BANANA PLUG; 2 COND

Part Number	Weight	Min. Quantity
EM2BA-120#	N-A	24

**MINI BANANA PLUG (WHITE)**

Pomona Electronics

MINI BANANA PLUG (WHITE)

Part Number	Weight	Min. Quantity
EM2945-9#	N-A	100

**DBL BANANA PLUG; 2 COND**

Pomona Electronics

DBL BANANA PLUG; 2 COND

Part Number	Weight	Min. Quantity
EM2BA-132#	N-A	12

**TRIPLE BANANA PLUG (BLUE)**

Pomona Electronics

TRIPLE BANANA PLUG (BLUE)

Part Number	Weight	Min. Quantity
EM2970-6#	N-A	100

**DBL BANANA PLUG; 2 COND MTO BULK**

Pomona Electronics

DBL BANANA PLUG; 2 COND MTO BULK

Part Number	Weight	Min. Quantity
EM2BA-1500#	N-A	4



EM2BC-BNC-48# – DBL BANANA/BNC (M); RG58C/U

**DBL BANANA PLUG; 2 COND**

Pomona Electronics

DBL BANANA PLUG; 2 COND

Part Number	Weight	Min. Quantity
EM2BA-240#	N-A	12

**DBL BANANA; RG58C/U**

Pomona Electronics

DBL BANANA; RG58C/U

Part Number	Weight	Min. Quantity
EM2BC-240#	N-A	16

**DBL BANANA PLUG; 2 COND MTO BULK**

Pomona Electronics

DBL BANANA PLUG; 2 COND MTO BULK

Part Number	Weight	Min. Quantity
EM2BA-288#	N-A	12

**DBL BANANA; RG58C/U**

Pomona Electronics

DBL BANANA; RG58C/U

Part Number	Weight	Min. Quantity
EM2BC-72#	N-A	16

**DBL BANANA PLUG; 2 COND MTO BULK**

Pomona Electronics

DBL BANANA PLUG; 2 COND MTO BULK

Part Number	Weight	Min. Quantity
EM2BA-360#	N-A	12

**DBL BANANA/ALLIG CL;RG58C/U**

Pomona Electronics

DBL BANANA/ALLIG CL;RG58C/U

Part Number	Weight	Min. Quantity
EM2BC-AL-48#	N-A	16

**ALLIG CL/DBL BANANA; 2 COND; MTO BU...**

Pomona Electronics

ALLIG CL/DBL BANANA; 2 COND; MTO BULK

Part Number	Weight	Min. Quantity
EM2BA-AL-60#	N-A	5

**DBL BANANA/BNC (M); RG58C/U**

Pomona Electronics

DBL BANANA/BNC (M); RG58C/U

Part Number	Weight	Min. Quantity
EM2BC-BNC-24#	N-A	12

**DBL BANANA; RG58C/U MTO BULK**

Pomona Electronics

DBL BANANA; RG58C/U MTO BULK

Part Number	Weight	Min. Quantity
EM2BC-12#	N-A	12

**DBL BANANA/BNC (M); RG58C/U**

Pomona Electronics

DBL BANANA/BNC (M); RG58C/U

Part Number	Weight	Min. Quantity
EM2BC-BNC-48#	N-A	16



EM2BC-BNC-60# – DBL BANANA/BNC (M); RG58C/U

**DBL BANANA/BNC (M); RG58C/U**

Pomona Electronics

DBL BANANA/BNC (M); RG58C/U

Part Number	Weight	Min. Quantity
EM2BC-BNC-60#	N-A	12

**DBL BANANA/PIN TIP; RG58C/U; MTO BU...**

Pomona Electronics

DBL BANANA/PIN TIP; RG58C/U; MTO BULK

Part Number	Weight	Min. Quantity
EM2BC-PP-240#	N-A	12

**DBL BAN/BNC (M); RG58C/U**

Pomona Electronics

DBL BAN/BNC (M); RG58C/U

Part Number	Weight	Min. Quantity
EM2BC-BNC-96#	N-A	16

**DBL BANANA/PIN TIP; RG58C/U**

Pomona Electronics

DBL BANANA/PIN TIP; RG58C/U

Part Number	Weight	Min. Quantity
EM2BC-PP-84#	N-A	12

**DBL BANANA TO MINI CLIP RG58C/U**

Pomona Electronics

DBL BANANA TO MINI CLIP RG58C/U

Part Number	Weight	Min. Quantity
EM2BC-MG-48#	N-A	16

**MINI CL/MINI PLUG;RG174/U - MTO BUL...**

Pomona Electronics

MINI CL/MINI PLUG;RG174/U - MTO BULK

Part Number	Weight	Min. Quantity
EM3027-K-60#	N-A	16

**DBL BANANA/MINI CL; RG58C/U**

Pomona Electronics

DBL BANANA/MINI CL; RG58C/U

Part Number	Weight	Min. Quantity
EM2BC-MG-60#	N-A	16

**MINI CL/MINI PLUG;RG174/U - MTO BUL...**

Pomona Electronics

MINI CL/MINI PLUG;RG174/U - MTO BULK

Part Number	Weight	Min. Quantity
EM3027-K-72#	N-A	16

**DBL BANANA/PIN TIP; RG58C/U; MTO BU...**

Pomona Electronics

DBL BANANA/PIN TIP; RG58C/U; MTO BULK

Part Number	Weight	Min. Quantity
EM2BC-PP-120#	N-A	12

**MINI CL/BANANA PLUG (BLACK)**

Pomona Electronics

MINI CL/BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM3220-180-0#	N-A	24



EM3782-12-1# – MINIGRABBER/BANANA PLUG (BROWN)

**MINI CL/BANANA PLUG (BLACK)**

Pomona Electronics
MINI CL/BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM3220-60-0#	N-A	24

**PIN TIP JACK GOLD PL (BROWN) MTO BU...**

Pomona Electronics
PIN TIP JACK GOLD PL (BROWN) MTO BULK

Part Number	Weight	Min. Quantity
EM3542-1#	N-A	100

**MINI CL/BANANA PLUG (RED)**

Pomona Electronics
MINI CL/BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
EM3220-60-2#	N-A	24

**PIN TIP JACK GOLD PL (VIOLET)**

Pomona Electronics
PIN TIP JACK GOLD PL (VIOLET)

Part Number	Weight	Min. Quantity
EM3542-7#	N-A	100

**MINI CL/BANANA PLUG (RED)**

Pomona Electronics
MINI CL/BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
EM3220-72-2	N-A	24

**PIN TIP JACK GOLD PL (GRAY) MTO BUL...**

Pomona Electronics
PIN TIP JACK GOLD PL (GRAY) MTO BULK

Part Number	Weight	Min. Quantity
EM3542-8#	N-A	100

**MINI CL/BANANA PLUG (RED)**

Pomona Electronics
MINI CL/BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
EM3220-84-2	N-A	24

**BINDING POST; MICROVOLT (GREEN); MT...**

Pomona Electronics
BINDING POST; MICROVOLT (GREEN); MTO BULK

Part Number	Weight	Min. Quantity
EM3770-5#	N-A	100

**WE310/2 ALLIGS; CABLE 60 INCHES MTO...**

Pomona Electronics
WE310/2 ALLIGS; CABLE 60 INCHES MTO BULK

Part Number	Weight	Min. Quantity
EM3352N-A-36#	N-A	12

**MINIGRABBER/BANANA PLUG (BROWN)**

Pomona Electronics
MINIGRABBER/BANANA PLUG (BROWN)

Part Number	Weight	Min. Quantity
EM3782-12-1#	N-A	24

EM3782-12-3# – MINIGRABBER/BANANA PLUG (ORANGE)

**MINIGRABBER/BANANA PLUG (ORANGE)**

Pomona Electronics
MINIGRABBER/BANANA PLUG (ORANGE)

Part Number	Weight	Min. Quantity
EM3782-12-3#	N-A	24

**MINIGRABBER/BANANA PLUG (BLUE)**

Pomona Electronics
MINIGRABBER/BANANA PLUG (BLUE)

Part Number	Weight	Min. Quantity
EM3782-18-6	N-A	24

**MINIGRABBER/BANANA PLUG (VIOLET)**

Pomona Electronics
MINIGRABBER/BANANA PLUG (VIOLET)

Part Number	Weight	Min. Quantity
EM3782-12-7#	N-A	24

**MINIGRABBER/BANANA PLUG (BROWN)**

Pomona Electronics
MINIGRABBER/BANANA PLUG (BROWN)

Part Number	Weight	Min. Quantity
EM3782-24-1#	N-A	24

**MINIGRABBER/BANANA PLUG (GRAY)**

Pomona Electronics
MINIGRABBER/BANANA PLUG (GRAY)

Part Number	Weight	Min. Quantity
EM3782-12-8#	N-A	24

**MINIGRABBER/BANANA PLUG (ORANGE)**

Pomona Electronics
MINIGRABBER/BANANA PLUG (ORANGE)

Part Number	Weight	Min. Quantity
EM3782-24-3#	N-A	24

**MINIGRABBER/BANANA PLUG (WHITE)**

Pomona Electronics
MINIGRABBER/BANANA PLUG (WHITE)

Part Number	Weight	Min. Quantity
EM3782-12-9#	N-A	24

**MINIGRABBER/BANANA PLUG (VIOLET)**

Pomona Electronics
MINIGRABBER/BANANA PLUG (VIOLET)

Part Number	Weight	Min. Quantity
EM3782-24-7#	N-A	24

**MINIGRABBER/BANANA PLUG (GREEN)**

Pomona Electronics
MINIGRABBER/BANANA PLUG (GREEN)

Part Number	Weight	Min. Quantity
EM3782-18-5	N-A	24

**MINIGRABBER/BANANA PLUG (GRAY)**

Pomona Electronics
MINIGRABBER/BANANA PLUG (GRAY)

Part Number	Weight	Min. Quantity
EM3782-24-8#	N-A	24



EM3782-72-0# – MINIGRABBER/BANANA PLUG MTO (BLACK)...

**MINIGRABBER/BANANA PLUG (WHITE)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (WHITE)

Part Number	Weight	Min. Quantity
EM3782-24-9#	N-A	24

**MINIGRABBER/BANANA PLUG (WHITE)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (WHITE)

Part Number	Weight	Min. Quantity
EM3782-36-9#	N-A	24

**MINIGRABBER/BANANA PLUG (BROWN)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (BROWN)

Part Number	Weight	Min. Quantity
EM3782-36-1#	N-A	24

**MINIGRABBER/BANANA PLUG (BROWN)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (BROWN)

Part Number	Weight	Min. Quantity
EM3782-48-1#	N-A	24

**MINIGRABBER/BANANA PLUG (ORANGE)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (ORANGE)

Part Number	Weight	Min. Quantity
EM3782-36-3#	N-A	24

**MINIGRABBER/BANANA PLUG (ORANGE)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (ORANGE)

Part Number	Weight	Min. Quantity
EM3782-48-3#	N-A	24

**MINIGRABBER/BANANA PLUG (VIOLET)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (VIOLET)

Part Number	Weight	Min. Quantity
EM3782-36-7#	N-A	24

**MINIGRABBER/BANANA PLUG (WHITE)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (WHITE)

Part Number	Weight	Min. Quantity
EM3782-48-9#	N-A	24

**MINIGRABBER/BANANA PLUG (GRAY)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (GRAY)

Part Number	Weight	Min. Quantity
EM3782-36-8#	N-A	24

**MINIGRABBER/BANANA PLUG MTO (BLACK)...**

Pomona Electronics

MINIGRABBER/BANANA PLUG MTO (BLACK) BULK

Part Number	Weight	Min. Quantity
EM3782-72-0#	N-A	24



EM3782-72-2# – MINIGRABBER/BANANA PLUG (RED) MTO B...

**MINIGRABBER/BANANA PLUG (RED) MTO B...**

Pomona Electronics

MINIGRABBER/BANANA PLUG (RED) MTO BULK

Part Number	Weight	Min. Quantity
EM3782-72-2#	N-A	24

**MINIGRABBER/BANANA PLUG (BLACK)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM3782-86-0	N-A	24

**MINIGRABBER/BANANA PLUG (BLACK)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM3782-96-0	N-A	24

**MINIGRABBER/BANANA PLUG (RED)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
EM3782-96-2	N-A	24

**MINIGRABBER/MINI BANANA (BLACK); MT...**

Pomona Electronics

MINIGRABBER/MINI BANANA (BLACK); MTO BULK

Part Number	Weight	Min. Quantity
EM3784-12-0#	N-A	24

**MINIGRABBER/MINI BANANA (BROWN)**

Pomona Electronics

MINIGRABBER/MINI BANANA (BROWN)

Part Number	Weight	Min. Quantity
EM3784-36-1#	N-A	24

**MINIGRABBER/MINI BANANA (ORANGE)**

Pomona Electronics

MINIGRABBER/MINI BANANA (ORANGE)

Part Number	Weight	Min. Quantity
EM3784-36-3#	N-A	24

**MINIGRABBER/MINI BANANA (YELLOW)**

Pomona Electronics

MINIGRABBER/MINI BANANA (YELLOW)

Part Number	Weight	Min. Quantity
EM3784-36-4#	N-A	24

**MINIGRABBER/MINI BANANA (GREEN)**

Pomona Electronics

MINIGRABBER/MINI BANANA (GREEN)

Part Number	Weight	Min. Quantity
EM3784-36-5#	N-A	24

**MINIGRABBER/MINI BANANA (BLUE)**

Pomona Electronics

MINIGRABBER/MINI BANANA (BLUE)

Part Number	Weight	Min. Quantity
EM3784-36-6#	N-A	24

EM4274-12-0# – BANANA PLUG/FUSE HOLDER (BLACK)

**MINIGRABBER/MINI BANANA (VIOLET)**

Pomona Electronics
MINIGRABBER/MINI BANANA (VIOLET)

Part Number	Weight	Min. Quantity
EM3784-36-7#	N-A	24

**DBL BANANA/GRABBER; RG58C/U MTO BUL...**

Pomona Electronics
DBL BANANA/GRABBER; RG58C/U MTO BULK

Part Number	Weight	Min. Quantity
EM3786-C-72#	N-A	12

**MINIGRABBER/MINI BANANA (GRAY)**

Pomona Electronics
MINIGRABBER/MINI BANANA (GRAY)

Part Number	Weight	Min. Quantity
EM3784-36-8#	N-A	24

**DBL BANANA/GRABBER; RG58C/U**

Pomona Electronics
DBL BANANA/GRABBER; RG58C/U

Part Number	Weight	Min. Quantity
EM3786-C-96#	N-A	16

**MINIGRABBER/MINI BANANA (WHITE)**

Pomona Electronics
MINIGRABBER/MINI BANANA (WHITE)

Part Number	Weight	Min. Quantity
EM3784-36-9#	N-A	24

**SPLICE; PIN TIP PLUG TO BANANA PLUG...**

Pomona Electronics
SPLICE; PIN TIP PLUG TO BANANA PLUG; (RED)

Part Number	Weight	Min. Quantity
EM3834-2#	N-A	100

**DBL BANANA/GRABBER; RG58C/U**

Pomona Electronics
DBL BANANA/GRABBER; RG58C/U

Part Number	Weight	Min. Quantity
EM3786-C-12#	N-A	16

**BANANA JACK; .025 SQ PIN (YELLOW)**

Pomona Electronics
BANANA JACK; .025 SQ PIN (YELLOW)

Part Number	Weight	Min. Quantity
EM4005-4#	N-A	100

**DBL BANANA/GRABBER; RG58C/U MTO BUL...**

Pomona Electronics
DBL BANANA/GRABBER; RG58C/U MTO BULK

Part Number	Weight	Min. Quantity
EM3786-C-120#	N-A	16

**BANANA PLUG/FUSE HOLDER (BLACK)**

Pomona Electronics
BANANA PLUG/FUSE HOLDER (BLACK)

Part Number	Weight	Min. Quantity
EM4274-12-0#	N-A	24

EM4274-24-0# – BANANA PLUG/FUSE HOLDER (BLACK) MTO...

**BANANA PLUG/FUSE HOLDER (BLACK) MTO...**

Pomona Electronics

BANANA PLUG/FUSE HOLDER (BLACK) MTO BULK

Part Number	Weight	Min. Quantity
EM4274-24-0#	N-A	24

**MINIGRABBER ORANGE MTO BULK**

Pomona Electronics

MINIGRABBER ORANGE MTO BULK

Part Number	Weight	Min. Quantity
EM4555-3#	N-A	100

**BANANA PLUG/FUSE HOLDER (RED) MTO B...**

Pomona Electronics

Part Number	Weight	Min. Quantity
EM4274-24-2#	N-A	24

**MINIGRABBER (YELLOW); MTO BULK**

Pomona Electronics

MINIGRABBER (YELLOW); MTO BULK

Part Number	Weight	Min. Quantity
EM4555-4#	N-A	100

**BNC(M); RG58 C/U**

Pomona Electronics

BNC(M); RG58 C/U

Part Number	Weight	Min. Quantity
EM4276-C-120#	N-A	12

**MINIGRABBER (GREEN); MTO BULK**

Pomona Electronics

MINIGRABBER (GREEN); MTO BULK

Part Number	Weight	Min. Quantity
EM4555-5#	N-A	100

**BANTAM PHONE PLUGS**

Pomona Electronics

BANTAM PHONE PLUGS

Part Number	Weight	Min. Quantity
EM4279-144#	N-A	16

**MINIGRABBER (BLUE)**

Pomona Electronics

Part Number	Weight	Min. Quantity
EM4555-6#	N-A	100

**MINIGRABBER (BROWN)**

Pomona Electronics

MINIGRABBER (BROWN)

Part Number	Weight	Min. Quantity
EM4555-1#	N-A	100

**MINIGRABBER VIOLET MTO BULK**

Pomona Electronics

MINIGRABBER VIOLET MTO BULK

Part Number	Weight	Min. Quantity
EM4555-7#	N-A	100



EM4650-24-5 – MINIGRABBER/BANANA PLUG (GREEN)

**MINIGRABBER (GRAY) MTO BULK**

Pomona Electronics

MINIGRABBER (GRAY) MTO BULK

Part Number	Weight	Min. Quantity
EM4555-8#	N-A	100

**GRABBER/BNC (M); RG58C/U; MTO BULK**

Pomona Electronics

GRABBER/BNC (M); RG58C/U; MTO BULK

Part Number	Weight	Min. Quantity
EM4648-C-48#	N-A	16

**MINIGRABBER (WHITE)**

Pomona Electronics

MINIGRABBER (WHITE)

Part Number	Weight	Min. Quantity
EM4555-9#	N-A	100

**MINIGRABBER/BANANA PLUG (BROWN)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (BROWN)

Part Number	Weight	Min. Quantity
EM4650-24-1	N-A	24

**DBL MIN B-JACK MTG BASE; (RED)**

Pomona Electronics

DBL MIN B-JACK MTG BASE; (RED)

Part Number	Weight	Min. Quantity
EM4619-2#	N-A	100

**MINIGRABBER/BANANA PLUG (ORANGE)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (ORANGE)

Part Number	Weight	Min. Quantity
EM4650-24-3	N-A	24

**GRABBER/BNC (M); RG58C/U**

Pomona Electronics

GRABBER/BNC (M); RG58C/U

Part Number	Weight	Min. Quantity
EM4648-C-24#	N-A	16

**MINIGRABBER/BANANA PLUG (YELLOW)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (YELLOW)

Part Number	Weight	Min. Quantity
EM4650-24-4	N-A	24

**GRABBER/BNC (M); RG58C/U**

Pomona Electronics

GRABBER/BNC (M); RG58C/U

Part Number	Weight	Min. Quantity
EM4648-C-36#	N-A	16

**MINIGRABBER/BANANA PLUG (GREEN)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (GREEN)

Part Number	Weight	Min. Quantity
EM4650-24-5	N-A	24



EM4650-24-6 – MINIGRABBER/BANANA PLUG (BLUE)

**MINIGRABBER/BANANA PLUG (BLUE)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (BLUE)

Part Number	Weight	Min. Quantity
EM4650-24-6	N-A	24

**MINIGRABBER/BANANA PLUG (RED)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
EM4650-60-2#	N-A	24

**MINIGRABBER/BANANA PLUG (VIOLET)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (VIOLET)

Part Number	Weight	Min. Quantity
EM4650-24-7	N-A	24

**DBL B-JACK MTG BASE (RED)**

Pomona Electronics

DBL B-JACK MTG BASE (RED)

Part Number	Weight	Min. Quantity
EM4654-2#	N-A	100

**MINIGRABBER/BANANA PLUG (GRAY)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (GRAY)

Part Number	Weight	Min. Quantity
EM4650-24-8	N-A	24

**BANANA PLUG/BANANA JACK (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
EM4702-12-0#	N-A	24

**MINIGRABBER/BANANA PLUG (WHITE)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (WHITE)

Part Number	Weight	Min. Quantity
EM4650-24-9	N-A	24

**BANANA PLUG/BANANA JACK (RED)**

Pomona Electronics

Part Number	Weight	Min. Quantity
EM4702-12-2#	N-A	24

**MINIGRABBER/BANANA PLUG (BLACK)**

Pomona Electronics

MINIGRABBER/BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM4650-60-0#	N-A	24

**BANANA PLUG/BANANA JACK; (BLACK)**

Pomona Electronics

BANANA PLUG/BANANA JACK; (BLACK)

Part Number	Weight	Min. Quantity
EM4702-18-0#	N-A	24

EM4741-36-2# – .025 SQ PIN RECEPTACLE (RED)

**BANANA PLUG/BANANA JACK; (RED)**

Pomona Electronics

BANANA PLUG/BANANA JACK; (RED)

Part Number	Weight	Min. Quantity
EM4702-18-2#	N-A	24

**;BANANA PLUG/BANANA JACK MTO BULK**

Pomona Electronics

;BANANA PLUG/BANANA JACK MTO BULK

Part Number	Weight	Min. Quantity
EM4702-60-2#	N-A	24

**BANANA PLUG/BANANA JACK (GREEN)**

Pomona Electronics

BANANA PLUG/BANANA JACK (GREEN)

Part Number	Weight	Min. Quantity
EM4702-24-5#	N-A	24

**TRIAx; 2-LUG/ALLIG MTO BULK**

Pomona Electronics

TRIAx; 2-LUG/ALLIG MTO BULK

Part Number	Weight	Min. Quantity
EM4725-360#	N-A	3

**BANANA PLUG/BANANA JACK (BLACK)**

Pomona Electronics

BANANA PLUG/BANANA JACK (BLACK)

Part Number	Weight	Min. Quantity
EM4702-360-0	N-A	24

**.025 SQ RECEPTACLE (WHITE)**

Pomona Electronics

.025 SQ RECEPTACLE (WHITE)

Part Number	Weight	Min. Quantity
EM4741-24-9#	N-A	24

**BANANA PLUG/BANANA JACK (RED)**

Pomona Electronics

BANANA PLUG/BANANA JACK (RED)

Part Number	Weight	Min. Quantity
EM4702-360-2	N-A	24

**.025 SQ PIN RECEPTACLE (BLACK)**

Pomona Electronics

.025 SQ PIN RECEPTACLE (BLACK)

Part Number	Weight	Min. Quantity
EM4741-36-0#	N-A	24

**BANANA PLUG/BANANA JACK (BLACK); MT...**

Pomona Electronics

BANANA PLUG/BANANA JACK (BLACK); MTO BULK

Part Number	Weight	Min. Quantity
EM4702-60-0#	N-A	24

**.025 SQ PIN RECEPTACLE (RED)**

Pomona Electronics

.025 SQ PIN RECEPTACLE (RED)

Part Number	Weight	Min. Quantity
EM4741-36-2#	N-A	24

EM4741-36-4# – .025 SQ PIN RECEPTACLE (YELLOW) MTO...

**.025 SQ PIN RECEPTACLE (YELLOW) MTO...**

Pomona Electronics

.025 SQ PIN RECEPTACLE (YELLOW) MTO BULK

Part Number	Weight	Min. Quantity
EM4741-36-4#	N-A	24

**BANANA PLUG/.025 SQ RECEPT (RED)**

Pomona Electronics

BANANA PLUG/.025 SQ RECEPT (RED)

Part Number	Weight	Min. Quantity
EM4771-12-2#	N-A	24

**.025 SQ PIN RECEPTACLE (GREEN)**

Pomona Electronics

.025 SQ PIN RECEPTACLE (GREEN)

Part Number	Weight	Min. Quantity
EM4741-36-5#	N-A	24

**BANANA PLUG/.025 SQ RECEPT; (BLUE)**

Pomona Electronics

BANANA PLUG/.025 SQ RECEPT; (BLUE)

Part Number	Weight	Min. Quantity
EM4771-24-6#	N-A	24

**.025 SQ RECEPTACLE (GRAY); MTO BULK**

Pomona Electronics

.025 SQ RECEPTACLE (GRAY); MTO BULK

Part Number	Weight	Min. Quantity
EM4741-6-8#	N-A	24

**BANANA PLUG/.025 SQ RECEPT (BLUE)**

Pomona Electronics

BANANA PLUG/.025 SQ RECEPT (BLUE)

Part Number	Weight	Min. Quantity
EM4771-36-6#	N-A	24

**.025 SQ RECEPTACLE (BLACK)**

Pomona Electronics

.025 SQ RECEPTACLE (BLACK)

Part Number	Weight	Min. Quantity
EM4741-96-0#	N-A	24

**BANANA PLUG/.025 SQ RECEPT (VIOLET)**

Pomona Electronics

BANANA PLUG/.025 SQ RECEPT (VIOLET)

Part Number	Weight	Min. Quantity
EM4771-36-7#	N-A	24

**BANANA PLUG/.025 SQ RECEPT (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
EM4771-12-0#	N-A	24

**BANANA PLUG/.025 SQ RECEPT (BLACK)**

Pomona Electronics

BANANA PLUG/.025 SQ RECEPT (BLACK)

Part Number	Weight	Min. Quantity
EM4771-48-0#	N-A	24



EM4911A-12-4# – RETR. SHEATH BANANA PLUG (YELLOW); ...

**BANANA PLUG/.025 SQ RECEPT (RED); M...**

Pomona Electronics

BANANA PLUG/.025 SQ RECEPT (RED); MTO BULK

Part Number	Weight	Min. Quantity
EM4771-48-2#	N-A	24

**DBL BANANA PLUG; GOLD PL; (YELLOW) ...**

Pomona Electronics

DBL BANANA PLUG; GOLD PL; (YELLOW) MTO BULK

Part Number	Weight	Min. Quantity
EM4892-4#	N-A	100

**PIN TIP JACK (GREEN)**

Pomona Electronics

PIN TIP JACK (GREEN)

Part Number	Weight	Min. Quantity
EM4773-5#	N-A	100

**BANANA PLUG GOLD PL (BROWN)**

Pomona Electronics

BANANA PLUG GOLD PL (BROWN)

Part Number	Weight	Min. Quantity
EM4897-1	N-A	100

**GRABBER/BNC (M); RG174/U**

Pomona Electronics

GRABBER/BNC (M); RG174/U

Part Number	Weight	Min. Quantity
EM4777-K-60#	N-A	16

**RETR. SHEATH BANANA PLUG (BLACK)**

Pomona Electronics

Part Number	Weight	Min. Quantity
EM4911A-108-0#	N-A	24

**GRABBER/PJ051; 2 COND SHLD**

Pomona Electronics

Part Number	Weight	Min. Quantity
EM4812-J-60#	N-A	24

**RETR. SHEATH BANANA PLUG (RED)**

Pomona Electronics

Part Number	Weight	Min. Quantity
EM4911A-108-2#	N-A	24

**DBL BANANA PLUG; GOLD PL; (BROWN)**

Pomona Electronics

DBL BANANA PLUG; GOLD PL; (BROWN)

Part Number	Weight	Min. Quantity
EM4892-1#	N-A	100

**RETR. SHEATH BANANA PLUG (YELLOW); ...**

Pomona Electronics

RETR. SHEATH BANANA PLUG (YELLOW); MTO BULK

Part Number	Weight	Min. Quantity
EM4911A-12-4#	N-A	100

EM4911A-24-4# – RETR. SHEATH BANANA PLUG (YELLOW); ...

**RETR. SHEATH BANANA PLUG (YELLOW); ...**

Pomona Electronics

RETR. SHEATH BANANA PLUG (YELLOW); MTO BULK

Part Number	Weight	Min. Quantity
EM4911A-24-4#	N-A	100

**RETR. SHEATH BANANA PLUG (BLACK)**

Pomona Electronics

RETR. SHEATH BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM4911A-80-0#	N-A	24

**RETR. SHEATH BANANA PLUG (BLACK); M...**

Pomona Electronics

RETR. SHEATH BANANA PLUG (BLACK); MTO BULK

Part Number	Weight	Min. Quantity
EM4911A-300-0#	N-A	24

**RETR. SHEATH BANANA PLUG (RED)**

Pomona Electronics

RETR. SHEATH BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
EM4911A-80-2#	N-A	24

**RETR. SHEATH BANANA PLUG (RED) MTO ...**

Pomona Electronics

RETR. SHEATH BANANA PLUG (RED) MTO BULK

Part Number	Weight	Min. Quantity
EM4911A-300-2#	N-A	24

**TRIAXIAL (M); BELDEN 9222**

Pomona Electronics

TRIAXIAL (M); BELDEN 9222

Part Number	Weight	Min. Quantity
EM5054-120	N-A	4

**RETR. SHEATH BANANA PLUG (YELLOW); ...**

Pomona Electronics

RETR. SHEATH BANANA PLUG (YELLOW); MTO BULK

Part Number	Weight	Min. Quantity
EM4911A-36-4#	N-A	100

**TRIAXIAL (M); BELDEN 9222**

Pomona Electronics

TRIAXIAL (M); BELDEN 9222

Part Number	Weight	Min. Quantity
EM5054-1200#	N-A	4

**RETR. SHEATH BANANA PLUG (YELLOW); ...**

Pomona Electronics

RETR. SHEATH BANANA PLUG (YELLOW); MTO BULK

Part Number	Weight	Min. Quantity
EM4911A-48-4#	N-A	100

**TRIAXIAL (M); BELDEN 9222; MTO; BUL...**

Pomona Electronics

TRIAXIAL (M); BELDEN 9222; MTO; BULK

Part Number	Weight	Min. Quantity
EM5054-144#	N-A	2



EM5155-4# – STRESS BOOT; RG58 (YELLOW)



TRIAXIAL (M); BELDEN 9222; MTO; BUL...

Pomona Electronics

TRIAXIAL (M); BELDEN 9222; MTO; BULK

Part Number	Weight	Min. Quantity
EMS054-204#	N-A	2



TRIAXIAL (M); BELDEN 9222; MTO; BUL...

Pomona Electronics

TRIAXIAL (M); BELDEN 9222; MTO; BULK

Part Number	Weight	Min. Quantity
EMS054-396#	N-A	2



TRIAXIAL (M); BELDEN 9222

Pomona Electronics

TRIAXIAL (M); BELDEN 9222

Part Number	Weight	Min. Quantity
EMS054-24#	N-A	4



TRIAXIAL (M); BELDEN 9222

Pomona Electronics

TRIAXIAL (M); BELDEN 9222

Part Number	Weight	Min. Quantity
EMS054-480#	N-A	2



TRIAXIAL (M); BELDEN 9222

Pomona Electronics

TRIAXIAL (M); BELDEN 9222

Part Number	Weight	Min. Quantity
EMS054-240	N-A	4



TRIAXIAL (M); BELDEN 9222

Pomona Electronics

TRIAXIAL (M); BELDEN 9222

Part Number	Weight	Min. Quantity
EMS054-720#	N-A	2



TRIAXIAL (M); BELDEN 9222; MTO; BUL...

Pomona Electronics

TRIAXIAL (M); BELDEN 9222; MTO; BULK

Part Number	Weight	Min. Quantity
EMS054-276#	N-A	2



STRESS BOOT; RG58 (BROWN); MTO BULK

Pomona Electronics

STRESS BOOT; RG58 (BROWN); MTO BULK

Part Number	Weight	Min. Quantity
EM5155-1#	N-A	100



TRIAXIAL (M); BELDEN 9222

Pomona Electronics

TRIAXIAL (M); BELDEN 9222

Part Number	Weight	Min. Quantity
EMS054-360#	N-A	2



STRESS BOOT; RG58 (YELLOW)

Pomona Electronics

STRESS BOOT; RG58 (YELLOW)

Part Number	Weight	Min. Quantity
EM5155-4#	N-A	100



EM5155-5# – STRESS BOOT; RG58 (GREEN); MTO BULK

**STRESS BOOT; RG58 (GREEN); MTO BULK**

Pomona Electronics
STRESS BOOT; RG58 (GREEN); MTO BULK

Part Number	Weight	Min. Quantity
EM5155-5#	N-A	100

**STRESS BOOT; RG59; (GREEN)**

Pomona Electronics
STRESS BOOT; RG59; (GREEN)

Part Number	Weight	Min. Quantity
EM5156-5#	N-A	100

**STRESS BOOT; RG58 (BLUE); MTO BULK**

Pomona Electronics
STRESS BOOT; RG58 (BLUE); MTO BULK

Part Number	Weight	Min. Quantity
EM5155-6#	N-A	100

**STRESS BOOT; RG59; (WHITE)**

Pomona Electronics
STRESS BOOT; RG59; (WHITE)

Part Number	Weight	Min. Quantity
EM5156-9#	N-A	100

**STRESS BOOT; RG58 (GRAY)**

Pomona Electronics
STRESS BOOT; RG58 (GRAY)

Part Number	Weight	Min. Quantity
EM5155-8#	N-A	100

**STRESS BOOT; RG174/U (RED)**

Pomona Electronics
STRESS BOOT; RG174/U (RED)

Part Number	Weight	Min. Quantity
EM5157-2#	N-A	100

**STRESS BOOT; RG58 (WHITE)**

Pomona Electronics
STRESS BOOT; RG58 (WHITE)

Part Number	Weight	Min. Quantity
EM5155-9#	N-A	100

**STRESS BOOT; RG174/U (ORANGE)**

Pomona Electronics
STRESS BOOT; RG174/U (ORANGE)

Part Number	Weight	Min. Quantity
EM5157-3#	N-A	100

**STRESS BOOT; RG59; (YELLOW)**

Pomona Electronics
STRESS BOOT; RG59; (YELLOW)

Part Number	Weight	Min. Quantity
EM5156-4#	N-A	100

**STRESS BOOT; RG174 (YELLOW) MTO BULK...**

Pomona Electronics
STRESS BOOT; RG174 (YELLOW) MTO BULK

Part Number	Weight	Min. Quantity
EM5157-4#	N-A	100



EM5173-7# – PIN TIP PLUG; 20AWG; (VIOLET)

**STRESS BOOT; RG174/U (GREEN)**

Pomona Electronics
STRESS BOOT; RG174/U (GREEN)

Part Number	Weight	Min. Quantity
EMS157-5#	N-A	100

**BANANA JACK; 20 AWG (WHITE)**

Pomona Electronics
BANANA JACK; 20 AWG (WHITE)

Part Number	Weight	Min. Quantity
EMS167-9#	N-A	100

**STRESS BOOT; RG174/U (BLUE)**

Pomona Electronics
STRESS BOOT; RG174/U (BLUE)

Part Number	Weight	Min. Quantity
EMS157-6#	N-A	100

**BANANA PLUG FOR 18-20 AWG WIRE; (BL...**

Pomona Electronics
BANANA PLUG FOR 18-20 AWG WIRE; (BLUE)

Part Number	Weight	Min. Quantity
EMS169-6#	N-A	100

**STRESS BOOT;RG174 (GRAY)**

Pomona Electronics
STRESS BOOT;RG174 (GRAY)

Part Number	Weight	Min. Quantity
EMS157-8#	N-A	100

**PIN TIP PLUG; 20AWG; (YELLOW)**

Pomona Electronics
PIN TIP PLUG; 20AWG; (YELLOW)

Part Number	Weight	Min. Quantity
EMS173-4#	N-A	100

**STRESS BOOT;RG174 (WHITE)**

Pomona Electronics
STRESS BOOT;RG174 (WHITE)

Part Number	Weight	Min. Quantity
EMS157-9#	N-A	100

**PIN TIP PLUG; 20AWG; (BLUE)**

Pomona Electronics
PIN TIP PLUG; 20AWG; (BLUE)

Part Number	Weight	Min. Quantity
EMS173-6#	N-A	100

**BANANA JACK; 20 AWG (GREEN)**

Pomona Electronics
BANANA JACK; 20 AWG (GREEN)

Part Number	Weight	Min. Quantity
EMS167-5#	N-A	100

**PIN TIP PLUG; 20AWG; (VIOLET)**

Pomona Electronics
PIN TIP PLUG; 20AWG; (VIOLET)

Part Number	Weight	Min. Quantity
EMS173-7#	N-A	100

EM5187-C-480# – BNC(M)/GRABBERS RG 58C/U

**BNC(M)/GRABBERS RG 58C/U**

Pomona Electronics

BNC(M)/GRABBERS RG 58C/U

Part Number	Weight	Min. Quantity
EM5187-C-480#	N-A	16

**BNC(M)/GRABBERS RG 174/U**

Pomona Electronics

BNC(M)/GRABBERS RG 174/U

Part Number	Weight	Min. Quantity
EM5187-K-480#	N-A	16

**LUG TRIAX; BELDEN 9222**

Pomona Electronics

LUG TRIAX; BELDEN 9222

Part Number	Weight	Min. Quantity
EM5223-120#	N-A	4

**3 LUG TRIAX; BELDEN 9222**

Pomona Electronics

Part Number	Weight	Min. Quantity
EM5223-168	N-A	3

**3 LUG TRIAX; BELDEN 9222**

Pomona Electronics

3 LUG TRIAX; BELDEN 9222

Part Number	Weight	Min. Quantity
EM5223-240#	N-A	2

**LUG TRIAX; BELDEN 9222**

Pomona Electronics

LUG TRIAX; BELDEN 9222

Part Number	Weight	Min. Quantity
EM5223-6#	N-A	4

**MICROVOLT/BANANA PLUG CORD (BLACK)...**

Pomona Electronics

MICROVOLT/BANANA PLUG CORD (BLACK); MTO BULK

Part Number	Weight	Min. Quantity
EM5291A-12-0#	N-A	24

**MICROVOLT/BANANA PLUG CORD (RED); ...**

Pomona Electronics

MICROVOLT/BANANA PLUG CORD (RED); MTO BULK

Part Number	Weight	Min. Quantity
EM5291A-12-2#	N-A	24

**MICROVOLT/BANANA PLUG CORD (BLK) MT...**

Pomona Electronics

MICROVOLT/BANANA PLUG CORD (BLK) MTO BULK

Part Number	Weight	Min. Quantity
EM5291A-120-0#	N-A	24

**MICROVOLT/BANANA PLUG CORD (RED) MT...**

Pomona Electronics

MICROVOLT/BANANA PLUG CORD (RED) MTO BULK

Part Number	Weight	Min. Quantity
EM5291A-120-2#	N-A	24

EM5406-7# – GOLD PLATED BANANA PLUG (VIOLET)

**SMD GRABBER/BANANA PLUG (BROWN)
MTO...**

Pomona Electronics

SMD GRABBER/BANANA PLUG (BROWN) MTO BULK

Part Number	Weight	Min. Quantity
EM5302-36-1#	N-A	24

**SMD GRABBER/BANANA PLUG (GRAY) MTO ...**

Pomona Electronics

SMD GRABBER/BANANA PLUG (GRAY) MTO BULK

Part Number	Weight	Min. Quantity
EM5302-36-8#	N-A	24

**SMD GRABBER/BANANA PLUG (ORANGE) MT...**

Pomona Electronics

SMD GRABBER/BANANA PLUG (ORANGE) MTO BULK

Part Number	Weight	Min. Quantity
EM5302-36-3#	N-A	24

**SMD GRABBER/BANANA PLUG (WHITE) MTO...**

Pomona Electronics

SMD GRABBER/BANANA PLUG (WHITE) MTO BULK

Part Number	Weight	Min. Quantity
EM5302-36-9#	N-A	24

**SMD GRABBER/BANANA PLUG (GREEN); MT...**

Pomona Electronics

SMD GRABBER/BANANA PLUG (GREEN); MTO BULK

Part Number	Weight	Min. Quantity
EM5302-36-5#	N-A	24

**GOLD PLATED BANANA PLUG (ORANGE)**

Pomona Electronics

GOLD PLATED BANANA PLUG (ORANGE)

Part Number	Weight	Min. Quantity
EM5406-3#	N-A	100

**SMD GRABBER/BANANA PLUG (BLUE); MTO...**

Pomona Electronics

SMD GRABBER/BANANA PLUG (BLUE); MTO BULK

Part Number	Weight	Min. Quantity
EM5302-36-6#	N-A	24

**GOLD PLATED BANANA PLUG (GREEN)**

Pomona Electronics

GOLD PLATED BANANA PLUG (GREEN)

Part Number	Weight	Min. Quantity
EM5406-5#	N-A	100

**SMD GRABBER/BANANA PLUG (VIOLET) MT...**

Pomona Electronics

SMD GRABBER/BANANA PLUG (VIOLET) MTO BULK

Part Number	Weight	Min. Quantity
EM5302-36-7#	N-A	24

**GOLD PLATED BANANA PLUG (VIOLET)**

Pomona Electronics

GOLD PLATED BANANA PLUG (VIOLET)

Part Number	Weight	Min. Quantity
EM5406-7#	N-A	100

EM5406-9# – GOLD PLATED BANANA PLUG (WHITE)

**GOLD PLATED BANANA PLUG (WHITE)**

Pomona Electronics
GOLD PLATED BANANA PLUG (WHITE)

Part Number	Weight	Min. Quantity
EM5406-9#	N-A	100

**MINIGBR W/MULTI-STACK - B PLUG (RED...**

Pomona Electronics
MINIGBR W/MULTI-STACK - B PLUG (RED)

Part Number	Weight	Min. Quantity
EM6249-48-2#	N-A	24

**D-I-Y MINIPINER (ORANGE)**

Pomona Electronics
D-I-Y MINIPINER (ORANGE)

Part Number	Weight	Min. Quantity
EM5418-3#	N-A	100

**MINIGRABBER W/RETR SHEATH B PLUG(BL...**

Pomona Electronics
MINIGRABBER W/RETR SHEATH B PLUG(BLACK)

Part Number	Weight	Min. Quantity
EM6250A-120-0#	N-A	24

**MINIGRABBER; ONE END (BLACK)**

Pomona Electronics
MINIGRABBER; ONE END (BLACK)

Part Number	Weight	Min. Quantity
EM6247-48-0#	N-A	24

**MINIGRABBER W/ RETR SHEATH B PLUG (...)**

Pomona Electronics
MINIGRABBER W/ RETR SHEATH B PLUG (RED)

Part Number	Weight	Min. Quantity
EM6250A-120-2#	N-A	24

**MINIGRABBER; ONE END (RED)**

Pomona Electronics
MINIGRABBER; ONE END (RED)

Part Number	Weight	Min. Quantity
EM6247-48-2#	N-A	24

**MINIGRABBER W/ ST BANANA PLUG (RED)**

Pomona Electronics
MINIGRABBER W/ ST BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
EM6251-48-2	N-A	24

**MINIGBR W/MULTI-STACK - B PLUG (BLA...**

Pomona Electronics
MINIGBR W/MULTI-STACK - B PLUG (BLACK)

Part Number	Weight	Min. Quantity
EM6249-48-0#	N-A	24

**CABLE PUSH ON BNC MTO BULK**

Pomona Electronics
CABLE PUSH ON BNC MTO BULK

Part Number	Weight	Min. Quantity
EM6253-C-96#	N-A	12



EM6291-7# – INS SLEEVE FOR BNC (VIOLET)

**DBL BANANA PLUG W/SAFETY SHROUD**

Pomona Electronics

DBL BANANA PLUG W/SAFETY SHROUD

Part Number	Weight	Min. Quantity
EM6283-C-120#	N-A	16

**INS SLEEVE FOR BNC; (ORANGE)**

Pomona Electronics

INS SLEEVE FOR BNC; (ORANGE)

Part Number	Weight	Min. Quantity
EM6291-3#	N-A	100

**DBL BANANA PLUG W/SAFETY SHROUD; 14...**

Pomona Electronics

DBL BANANA PLUG W/SAFETY SHROUD; 144 INCHES

Part Number	Weight	Min. Quantity
EM6283-C-144#	N-A	12

**INS SLEEVE FOR BNC (YELLOW)**

Pomona Electronics

INS SLEEVE FOR BNC (YELLOW)

Part Number	Weight	Min. Quantity
EM6291-4#	N-A	100

**DBL BANANA PLUG W/SAFETY SHROUD; 72...**

Pomona Electronics

DBL BANANA PLUG W/SAFETY SHROUD; 72 INCHES

Part Number	Weight	Min. Quantity
EM6283-C-72	N-A	16

**INS SLEEVE FOR BNC (GREEN)**

Pomona Electronics

INS SLEEVE FOR BNC (GREEN)

Part Number	Weight	Min. Quantity
EM6291-5#	N-A	100

**INS SLEEVE FOR BNC; (BLACK); MTO BU...**

Pomona Electronics

INS SLEEVE FOR BNC; (BLACK); MTO BULK

Part Number	Weight	Min. Quantity
EM6291-0#	N-A	500

**INS SLEEVE FOR BNC (BLUE)**

Pomona Electronics

INS SLEEVE FOR BNC (BLUE)

Part Number	Weight	Min. Quantity
EM6291-6#	N-A	100

**INS SLEEVE FOR BNC; (RED); MTO BULK**

Pomona Electronics

INS SLEEVE FOR BNC; (RED); MTO BULK

Part Number	Weight	Min. Quantity
EM6291-2#	N-A	500

**INS SLEEVE FOR BNC (VIOLET)**

Pomona Electronics

INS SLEEVE FOR BNC (VIOLET)

Part Number	Weight	Min. Quantity
EM6291-7#	N-A	100

EM6291-8# – INS SLEEVE FOR BNC; (GRAY); MTO BUL...



INS SLEEVE FOR BNC; (GRAY); MTO BUL...

Pomona Electronics

INS SLEEVE FOR BNC; (GRAY); MTO BULK

Part Number	Weight	Min. Quantity
EM6291-8#	N-A	100



INS SLEEVE FOR BNC; (WHITE); MTO BU...

Pomona Electronics

INS SLEEVE FOR BNC; (WHITE); MTO BULK

Part Number	Weight	Min. Quantity
EM6291-9#	N-A	100



BANANA JACK; PANEL TIN; (BROWN)

Pomona Electronics

Part Number	Weight	Min. Quantity
EM6387-ST-T-1#	N-A	100



BANANA JACK; PANEL TIN; (ORANGE)

Pomona Electronics

Part Number	Weight	Min. Quantity
EM6387-ST-T-3#	N-A	100



BANANA JACK; PANEL TIN; (YELLOW)

Pomona Electronics

Part Number	Weight	Min. Quantity
EM6387-ST-T-4#	N-A	100



BANANA JACK; PANEL TIN; (GREEN)

Pomona Electronics

Part Number	Weight	Min. Quantity
EM6387-ST-T-5#	N-A	100



BANANA JACK; PANEL TIN; (BLUE)

Pomona Electronics

Part Number	Weight	Min. Quantity
EM6387-ST-T-6#	N-A	100



BANANA JACK; PANEL TIN; (GRAY)

Pomona Electronics

BANANA JACK; PANEL TIN; (GRAY)

Part Number	Weight	Min. Quantity
EM6387-ST-T-8#	N-A	100



BANANA JACK; PANEL TIN; (WHITE)

Pomona Electronics

Part Number	Weight	Min. Quantity
EM6387-ST-T-9#	N-A	100



DOUBLE BANANA PLUG; SOLDERLESS; BLA...

Pomona Electronics

Stacking Double Banana Plug with Cable Guide, Gold Plated, Black, 15 Amps Rating: 5000 VDC, 15 A, +122&deg;F (+50&deg;C) (Model 4898, +302&deg;F (+150&deg;C) Max.)

Part Number	Weight	Min. Quantity
MDP-0	0.5	5



MDP-4# – DBL BANANA PLUG; (YELLOW)

**DBL BANANA PLUG (BLACK)**

Pomona Electronics

DBL BANANA PLUG (BLACK)

Part Number	Weight	Min. Quantity
MDP-0#	N-A	500

**DBL BANANA PLUG W/WIRE GUIDE (SET)**

Pomona Electronics

Part Number	Weight	Min. Quantity
MDP-02	0.65	5

**DBL BANANA PLUG (BROWN)**

Pomona Electronics

Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access panel or need a simple banana plug for a monitor. In the shop, lab, studi

Part Number	Weight	Min. Quantity
MDP-1	0.035	5

**DBL BANANA PLUG; (BROWN)**

Pomona Electronics

DBL BANANA PLUG; (BROWN)

Part Number	Weight	Min. Quantity
MDP-1#	N-A	500

**DOUBLE BANANA PLUG; SOLDERLESS; RED**

Pomona Electronics

Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access panel or need a simple banana plug for a monitor. In the shop, lab, studi

Part Number	Weight	Min. Quantity
MDP-2	0.13	5

**DBL BANANA PLUG (RED)**

Pomona Electronics

DBL BANANA PLUG (RED)

Part Number	Weight	Min. Quantity
MDP-2#	N-A	500

**DBL BANANA PLUG (ORANGE)**

Pomona Electronics

Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access panel or need a simple banana plug for a monitor. In the shop, lab, studi

Part Number	Weight	Min. Quantity
MDP-3	0.035	5

**DBL BANANA PLUG; (ORANGE)**

Pomona Electronics

DBL BANANA PLUG; (ORANGE)

Part Number	Weight	Min. Quantity
MDP-3#	N-A	500

**DOUBLE BANANA PLUG; SOLDERLESS; YELLOW**

Pomona Electronics

Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access panel or need a simple banana plug for a monitor. In the shop, lab, studi

Part Number	Weight	Min. Quantity
MDP-4	0.035	5

**DBL BANANA PLUG; (YELLOW)**

Pomona Electronics

DBL BANANA PLUG; (YELLOW)

Part Number	Weight	Min. Quantity
MDP-4#	N-A	500



MDP-5 – DBL BANANA PLUG (GREEN)

**DBL BANANA PLUG (GREEN)****Pomona Electronics**

Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access panel or need a simple banana plug for a monitor. In the shop, lab, studi

Part Number	Weight	Min. Quantity
MDP-5	0.035	5

**DBL BANANA PLUG; (GREEN)****Pomona Electronics**

DBL BANANA PLUG; (GREEN)

Part Number	Weight	Min. Quantity
MDP-5#	N-A	500

**DBL BANANA PLUG (BLUE)****Pomona Electronics**

Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access panel or need a simple banana plug for a monitor. In the shop, lab, studi

Part Number	Weight	Min. Quantity
MDP-6	0.035	5

**DBL BANANA PLUG; (BLUE)****Pomona Electronics**

DBL BANANA PLUG; (BLUE)

Part Number	Weight	Min. Quantity
MDP-6#	N-A	500

**DBL BANANA PLUG (VIOLET)****Pomona Electronics**

Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access panel or need a simple banana plug for a monitor. In the shop, lab, studi

Part Number	Weight	Min. Quantity
MDP-7	0.035	5

**DBL BANANA PLUG; (VIOLET)****Pomona Electronics**

DBL BANANA PLUG; (VIOLET)

Part Number	Weight	Min. Quantity
MDP-7#	N-A	500

**DBL BANANA PLUG (GRAY)****Pomona Electronics**

Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access panel or need a simple banana plug for a monitor. In the shop, lab, studi

Part Number	Weight	Min. Quantity
MDP-8	0.035	5

**DBL BANANA PLUG; (GRAY)****Pomona Electronics**

DBL BANANA PLUG; (GRAY)

Part Number	Weight	Min. Quantity
MDP-8#	N-A	500

**DBL BANANA PLUG (WHITE)****Pomona Electronics**

Regardless of the type of system you are designing or installing, you need a variety of connection aids. Pomona offers plugs, jacks and binding posts to fit a variety of applications. Whether you're setting up a complex access panel or need a simple banana plug for a monitor. In the shop, lab, studi

Part Number	Weight	Min. Quantity
MDP-9	0.035	5

**DBL BANANA PLUG; (WHITE)****Pomona Electronics**

DBL BANANA PLUG; (WHITE)

Part Number	Weight	Min. Quantity
MDP-9#	N-A	500



MDP-X# – DBL BANANA ISOLATION

**DOUBLE BANANA PLUG WITH SHORTING BA...****Pomona Electronics**

Double banana jack — 4.22 mm (0.166) dia., brass, nickel-plated. Double banana plug, spring — One piece heat treated beryllium copper, nickel-plated. Fits standard 4.22 mm (0.166) dia. banana jack. Banana plug internally shorted with #18 AWG wire. Banana jacks provide top stackup. Cross

Part Number	Weight	Min. Quantity
MDP-S-0	1	5

**DBL BANANA; SHORTED (BLACK)****Pomona Electronics**

DBL BANANA; SHORTED (BLACK)

Part Number	Weight	Min. Quantity
MDP-S-0#	N-A	500

**DBL BANANA; SHORTED (WHITE)****Pomona Electronics**

DBL BANANA; SHORTED (WHITE)

Part Number	Weight	Min. Quantity
MDP-S-9#	N-A	500

FULL SIZE BANANA PLUG; POMONA #MDP-...**Pomona Electronics**

Double banana jack — 4.22 mm (0.166) dia., brass, nickel-plated. Double banana plug, spring — One piece heat treated beryllium copper, nickel-plated. Fits standard 4.22 mm (0.166) dia. banana jack. MDP-ST standard double banana plug with solder tur-rets. Rating: 5000 WVDC, 15 amps, +55&de

Part Number	Weight	Min. Quantity
MDP-ST	0.035	5

**DOUBLE BANANA PLUG W/SHORTING BAR; ...****Pomona Electronics**

Double banana jack — 4.22 mm (0.166) dia., brass, nickel-plated. Double banana plug, spring — One piece heat treated beryllium copper, nickel-plated. Fits standard 4.22 mm (0.166) dia. banana jack. Banana plug internally shorted with #18 AWG wire. Banana jacks provide top stackup. Cross

Part Number	Weight	Min. Quantity
MDP-S-2	2	5

**DBL BANANA ISOLATION****Pomona Electronics**

Part Number	Weight	Min. Quantity
MDP-X	0.055	5

**DBL BANANA; SHORTED (RED)****Pomona Electronics**

DBL BANANA; SHORTED (RED)

Part Number	Weight	Min. Quantity
MDP-S-2#	N-A	500

**DBL BANANA ISOLATION****Pomona Electronics**

DBL BANANA ISOLATION

Part Number	Weight	Min. Quantity
MDP-X#	N-A	500

**DOUBLE BANANA PLUG WITH SHORTING BA...****Pomona Electronics**

Double banana jack — 4.22 mm (0.166) dia., brass, nickel-plated. Double banana plug, spring — One piece heat treated beryllium copper, nickel-plated. Fits standard 4.22 mm (0.166) dia. banana jack. Banana plug internally shorted with #18 AWG wire. Banana jacks provide top stackup. Cross

Part Number	Weight	Min. Quantity
MDP-S-9	0.03	5

