

Busbar system, accessories Busbar center-to-center spacing 60 mm
Busbar support 3-pole for busbars 12x 5 (10)-30x 5 (10) External
fixing Width: 20 mm



Model	
product brand name	SENTRON
Operating voltage / at AC / rated value	690 V
suitability for use	Flat bars
Type of connectable conductor cross-sections / for copper conductor / stranded	12 mm x 5 mm - 30 mm x 10 mm
Mechanical Design	
Width	20 mm
Busbar center-to-center spacing	60 mm
Certificates	

General Product Approval		Declaration of Conformity	Test Certificates	
				Special Test Certificate Miscellaneous
CSA	UR		EG-Konf.	

Shipping Approval	other
 	Miscellaneous
PRS	RINA

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1923-2AA01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1923-2AA01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1923-2AA01


CAX-Online-Generator

<http://www.siemens.com/cax>



Tender specifications

<http://www.siemens.com/specifications>

A



A



SCHNITT: A-A