



Liquidtight Flexible Cord & Cable Fittings

T&B Catalog Number:

2282

UPC Number:

78621002282

Status:

Active

Description:

Liquidtight Strain Relief Cord Connector, 1-1/2 Inch, 90 Degree Bend, Meets Coast Guard CG293, Cord Range 1.000 to 1.187 Inch, Malleable Iron

Application

Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).

Meets Coast Guard CG293

General

Material Malleable Iron

Dimension Information

Hub Size (inches)	1 1/2
Dimension A (inches)	2 11/32
Dimension B (inches)	2 7/8
Dimension C (inches)	13/16
Cord Range (inches)	1.000-1.187

Specifications

3dmodel Available on Website

Temperature Rating 105 C

Packaging

T&B Inner Pack	2
Package in Units	10
T&B Sold in UOM	Each
T&B Weight Per UOM	120 lbs. per 100

Application Support

Product Overview Available on Website

Specifications Available on Website

Portable Cord Selection Table Available on Website

Notes

Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).

Certifications

RoHS Compliance Yes

Certifications



File Nbr:

E 13938

For further technical assistance, please contact us...

8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com