




Liquidtight Flexible Cord & Cable Fittings

T&B Catalog Number:

2922SST

UPC Number:

78620987791

Status:

Active

Description:

1/2 in. stainless steel Ranger liquidtight cord connector, cord range - .500 - .750.

Features

	Type 304 stainless steel construction for your harshest environments
	Ranger liquidtight cord connectors offer twice the cord diameter range of similar connectors, so you can do more with fewer sizes to order and stock.
	Ranger connectors form a non-slip mechanical grip, providing a liquidtight seal and the strain relief required for flexible portable cord connections.
	Superior corrosion resistance in wash down areas and other corrosive environments.
	Stands up to heat and UV exposure better than non-metallic connectors.
	Beveled, moisture and oil-resistant synthetic rubber bushing system ensures superior compression and sealing of fitting to cord.
	Bushing marked with cord range for easy identification out of box.

Application

	Ideal for MRO and OEM applications in corrosive environments such as food & beverage and pharmaceutical processing wash down area.
	Pulp and paper mills, wastewater treatment, saltwater applications and petrochemical refining.

General

Material	Stainless Steel
Cord and Cable Types	SJ, SJE, SJEO, SJEOO, SJO, SJOW, SJOO, SJOOW, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SO, SOW, SOO, SOOW, SV, ST, STD, SVD.

Dimension Information

Hub Size (inches)	1/2
Dimension A (inches)	2.003
Dimension B (inches)	0.610
Dimension C (inches)	1.125
Cord Range (inches)	.500 - .750

Specifications

3dmodel	Available on Website
Temperature Rating	-20 C to 105 C

Packaging

T&B Order Multiple	25
T&B Inner Pack	25
Package in Units	100
T&B Sold in UOM	Each

T&B Weight Per UOM 0.25 lbs. Each

Application Support

304 Stainless Steel Corrosion Compatibility Chart - Available on Website

Product Overview Available on Website

Certifications



File Nbr:
E 13938

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com