

Actual



Representative

Catalog Number: 2942SST

 Product ID:
 7TAD105340R0009

 UPC Number:
 78620987802

 EAN Number:
 05415022259728

Status: Active

Liquidtight Strain Relief Connector, 1 Inch NPT Threads, Straight, Cord Range 0.700 to 0.950 Inch, 304 Stainless Steel Body with Rubber Bushing

- Type 304 stainless steel construction for your harshest environments
- Ranger liquidtight cord connectors offer twice the cord diameter range of similar connectors, so you can do more with fewer sizes to order and stock.
- Ranger connectors form a non-slip mechanical grip, providing a liquidtight seal and the strain relief required for flexible portable cord connections.
- Superior corrosion resistance in wash down areas and other corrosive environments.
- Stands up to heat and UV exposure better than non-metallic connectors.
- Beveled, moisture and oil-resistant synthetic rubber bushing system ensures superior compression and sealing of fitting to cord.
- Bushing marked with cord range for easy identification out of box.
- Ideal for MRO and OEM applications in corrosive environments such as food & Deverage and pharmaceutical processing wash down area.
- Pulp and paper mills, wastewater treatment, saltwater applications and petrochemical refining.

North American Specifications (UNSPSC)	
UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	T&B
Туре	Cord Connectors-Straight
Special Features	Type 304 Stainless Steel Construction for Your
	Harshest Environments
Application	Ideal for MRO and OEM Applications In Corrosive
	Environments Such As Food & Deverage and
	Pharmaceutical Processing Wash Down Area.
Standard	UL E13938, CSA
Size	1 Inch
Conductor Range	0.700 to 0.950 Inch
Material	Stainless Steel
Color	Metallic

European Specifications (ETIM)	
ETIM	EC000441 Cable screw gland
Thread type	NPT
Nominal thread size inch/gas pipe thread	1 inch
Suitable for cable diameter	17.78-24.13mm
Material	Metal
Material quality	Stainless steel V2A
Colour	Natural colour
Model	Straight

Packaging	
Inner Quantity	10
Inner Dimensions (inches)	6.3x3.2x4.69
Outer Quantity	50
Outer Dimensions (inches)	21x5x7



Weight Uom 39.5 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet WSD-000335

Header

3D Model Available on Website

For further technical assistance, please contact us...

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com ABB Installation Products Technical Support MS 3B-50

860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday

Phone: (888) 862-3289 Fax: (901) 252-1321

Email:techsupport@tnb.com